

<https://www.kaggle.com/datasets/bitext/training-dataset-for-chatbotvirtual-assistants>
<https://www.kaggle.com/datasets/kritanjali Jain/amazon-reviews>
<https://www.kaggle.com/datasets/thoughtvector/customer-support-on-twitter/data>
<https://rajpurkar.github.io/SQuAD-explorer/>

Dataset	Description	Use Case	Source
MultiWOZ	Complex, multi-turn goals (e.g., booking a hotel AND a taxi).	Useful for tasks with multiple objectives	GitHub/MultiWOZ
Ubuntu Dialogue	Technical support logs.	Great for "Solve" actions	Kaggle/Ubuntu
Twitter Airline	Sentiment-based dialogue data from Twitter.	Ideal for "Sentiment-based" rewards	Kaggle/Twitter Airline
Banking77	77 very specific banking intents.	Great for handling "Context" in conversations	HuggingFace/Banking77

IG we will use these:

MultiWOZ [clear Goal] : <https://truthless11.github.io/pdf/MultiWOZ23.pdf>

**Ubuntu[Great for solve flag/reward] : <https://dataset.cs.mcgill.ca/ubuntu-corpus-1.0/>

Bitext [popular]: <https://github.com/bitext/customer-support-ilm-chatbot-training-dataset>

**Twitter CS [Better than bitext?]: <https://github.com/naman-tiwari/Customer-Support-on-Twitter>

Easy to handle data gpt:

<https://www.kaggle.com/datasets/abhayayare/multi-turn-chatbot-conversation-dataset>

User rating also but not popular data : <https://www.kaggle.com/datasets/snehilsanyal/oasst1>

Github repos:

<https://github.com/maxbrenner-ai/GO-Bot-DRL>

<https://github.com/wasimusu/RL-Chatbot>

<https://github.com/pochih/RL-Chatbot>

<https://github.com/ldulcic/customer-support-chatbot>

<https://github.com/aadimangla/Customer-Service-Bot>

Field / Dataset	Twitter Customer Support	Ubuntu Dialogue Corpus	OpenAssistant Conversations
Purpose & Type	Short social media customer support tweets	Technical support chat logs	Human-annotated multi-turn chat with human ratings
Typical Use Case	Understand real complaints/responses	Long conversational support flows	Train reward models / RLHF / response quality evaluation
Primary Identifiers	<code>tweet_id</code> : unique tweet identifier <code>author_id</code> : who sent the tweet	<code>dialogueID</code> : unique conversation <code>folder</code> : source folder name	<code>message_id</code> : unique message ID <code>parent_id</code> : ID of parent message <code>user_id</code> : who posted the message
Conversation Structure	<code>inbound</code> : whether message is customer → company <code>response_tweet_id</code> : reply tweet IDs <code>in_response_to_tweet_id</code> : which tweet this replies to	<code>from</code> : speaker (implicitly) <code>to</code> : recipient (speaker) <code>date</code> : timestamp of the message	<code>parent_id</code> : conversation threading <code>message_tree_id</code> : dialogue tree structure <code>tree_state</code> : state in conversation <code>rank</code> : ordering or position in thread
Text Content	<code>text</code> : tweet body	<code>text</code> : chat message text	<code>text</code> : assistant or user message

Timing	<code>created_at</code> : when tweet was sent	<code>date</code> : timestamp	<code>created_date</code> : timestamp
Labels / Feedback	None labeled in dataset — no explicit satisfaction rating — but you can infer proxies (sentiment, escalation)	None labeled — no explicit quality score — can infer proxies (sentiment, continuation)	Human feedback present: <code>review_count</code>: how many humans rated <code>review_result</code>: boolean (accepted/rejected) by reviewers <code>labels</code>: object with human scores for quality, toxicity, etc.
Deleted Messages	Not present	Not present	<code>deleted</code> : whether message was deleted
Metadata	basic tweet fields	basic conversation fields	additional metadata like <code>lang</code> , <code>emojis</code>