

Deep Reinforcement Learning for Adaptive AI Chatbots in Customer Service and Personalized Virtual Assistance Systems

Nitin Ranjan Rai,
Department of Management, Kalinga
University,
Raipur, India.
NITIN.GHAFOUR.WAHDAT@kalingauniversity.ac.in

M.Suganya, Assistant Professor,
Department of ECE, New Prince Shri
Bhavani College of Engineering and
Technology,
Chennai, Tamilnadu, India,
mangai.ece@npsbceet.edu.in

Gotlur Karuna,
Department of AIML Gokaraju
Rangaraju Institute of Engineering and
Technology, Hyderabad, Telangana,
India,
karuna.g@griect.ac.in

Muhammed Al-Fatlawi,
Department of computers Techniques
engineering, College of technical
engineering, The Islamic University,
Najaf, Iraq
eng.tech.mhussien074@gmail.com

Sudeep Kumar Gupta
Department of Computer Science &
Engineering, IES College of
Technology,
Bhopal, Madhya Pradesh, India
462044.
sudeep.research@iesuniversity.ac.in

Zainb Hussain Ali
computer center, University of Hilla,
Babylon, Iraq, 51011
zainb_husseini@hilla-unc.edu.iq

Baqer A Hakim,
College of Dentistry, University of Al-
Ameed Karbala PO Box 198,
Iraq,
h.bagher@alameed.edu.iq

Abstract—Conversational agents powered by AI provide dynamic and personalized user experiences. Digital communication is increasingly vital for customer engagement. However, static chat systems generally ignore real-time user interactions. Rules- or supervised-learning-based chatbots cannot adapt to changing user intentions, maintain context consistency during long discussions, or provide user-specific replies. Because customers change, their communication standards are strict and generalizations are limited, making it challenging to provide practical assistance. Deep reinforcement learning (DRL) enables chatbots to learn the most effective conversational methods through feedback and engagement, potentially revolutionizing the way they interact. DRL-Enhanced Adaptive Dialogue Management Framework (DRL-ADMF) incorporates Dialogue State Tracking (DST), Natural Language Understanding (NLU), and a Deep Q-Network policy learner. The DRL-ADMF employs a reward model that takes into account task performance, user sentiment, resolution efficiency, and conversation length to enhance interaction. A language representation module utilizing pre-trained transformers enhances contextual tracking and semantic comprehension in conversations. DRL-ADMF outperformed classic policy learning models on benchmark datasets and simulated customer service settings. It had shorter reaction times and higher task success rates than its rivals. The suggested DRL-ADMF intelligent and scalable solution for next-generation artificial intelligence chatbots in customer service and virtual assistant applications improves adaptive response generation, conversation coherence, and customization.

Keywords: Deep Reinforcement Learning, AI Chatbots, Customer Service, Personalized Virtual Assistant Systems, Q-learning.

I. INTRODUCTION

This template, modified in MS Word 2007 and saved as a “Word 97-2003 Document” for the PC, provides authors with

most of the formatting specifications needed for preparing electronic versions of their papers. All standard paper components have been specified for three reasons: (1) ease of use when formatting individual papers, (2) automatic compliance to electronic requirements that facilitate the concurrent or later production of electronic products, and (3) conformity of style throughout a conference proceedings [1]. Margins, column widths, line spacing, and type styles are built-in; examples of the type styles are provided throughout this document and are identified in italic type, followed by parentheses, after each example. Some components, such as multi-level equations, graphics, and tables, are not prescribed; however, various table text styles are provided [2]. The formatter will need to create these components, incorporating the applicable criteria that follow.

Financial fraud activity detection is of increasing importance in Financial transactions and internet shopping due to the expanding sophistication of fraudulent activities, such as identity theft, payment fraud, and money laundering [3]. Traditional fraud identification techniques, including rule-based methods and supervised machine learning models, have demonstrated significant limitations in identifying complex variations of fraudulent activity due to the evolving nature of financial transactions and the highly imbalanced nature of fraud data, where fraudulent transactions often constitute less than 0.5% of the total dataset [4]. Considering that fraudsters continually develop new strategies to evade detection, models based exclusively on historical fraud trends struggle to generalize successfully.

One chatbot utilizes natural language processing (NLP) to decipher human speech, while the other employs pre-designed equations to provide a decision-tree-like structure to the interaction. Many chatbots and platforms are utilized in online shopping, but they all aim to enhance communication between

companies and consumers [5], [6]. When a service, product, or service delivery meets the customer's expectations, the customer is pleased. Businesses and advertising agencies can gain valuable insights into improving their services from this input [7]. Artificial intelligence (AI) is a broad term encompassing various mechanical technologies, including computer systems, software, and frameworks. This category covers brain science, design, science, phonetics, applied and restorative sciences, as well as multidisciplinary planning [8]. Globally, companies are increasing their exchange settings to boost turnover and take on new risks, which necessitates creative problem-solving [9].

The system has been instructed to develop approaches and skills in artificial intelligence (AI), which will potentially replace people in certain mundane occupations. Through effective zones, foundations have started to promote robotization. Artificial intelligence (AI) chatbots rule the virtual assistant or chatbot market [10]. They can write nonstop, respond to inquiries, and even serve as a Facebook errand boy, LinkedIn detachment, or WeChat messenger. However, the climate-conscious community anticipates new artificial intelligence remote assistants with built-in frameworks to tackle all of the composite challenges that have been exposed [11]. According to virtual assistants, data is king in the commercial world. Machine learning (ML), artificial intelligence, and natural language processing have revolutionized corporate operations.




Fig.1. Communication Flow of a Cognitive Chatbot System

Figure 1 shows the Communication Flow of a Cognitive Chatbot System. Cognitive chatbots intelligently analyze user inputs to provide contextually relevant responses, as illustrated in the communication flow of such a system. Users start by entering their questions into the Chat Client. The Cognitive Chatbot acts as a go-between, receiving these requests and starting the processing of the discussion [12]. After that, the chatbot passes the data to the NLP Engine, which processes the user's purpose by parsing their language and analyzing its semantics. To provide more tailored replies depending on previous interactions, the NLP engine communicates with Data Storage to get analytics and the history of prior interactions. Furthermore, it establishes a connection to the expertise Base, which enriches the chatbot's output with contextual information and domain-specific expertise [13], [14]. Smart, adaptable, and human-like handling of user discussions is ensured by this integrated flow, which improves over time through data- and context-driven learning.

Customers have several options for contacting customer support, including live agents, automated phone systems, and email. On the other hand, live chat interfaces have recently replaced every previous mode of customer support, which is a key function in consumer engagement. Chatbots and other conversational software agents (CAs) have supplanted human

chat service operators due to AI breakthroughs [15]. Simulating human speech and body language in real-time enables digital assistants, conversational bots, and conversational AI to engage in natural language conversations. According to research, chatbots may entice customers by appearing more realistic when communicating via voice messages [16], [17]. To save users' time, chatbots automate information search and provide precise, real-time customer care. There is considerable support and popularity for conversational user interfaces in customer care. Given the prevalence of conversational user interfaces and their role in everyday life, the former may significantly influence customers' acceptance of chatbots [18]. Consumers' perceptions of chatbots' usefulness and advantages will dramatically affect their widespread adoption of customer service [19]. Chatbots designed to assist consumers in customer service must provide a pleasant user experience and compelling value propositions to keep customers returning for more. In light of this reasoning, studies on chatbots that investigate the impact of the system on the user experience will be cited extensively [20]. Still, there is a serious dearth of studies examining the actual usage of chatbots and the factors that drive them [21]. This is a significant issue, as this knowledge is essential for developing and releasing effective chatbots for consumer support. This information would be particularly useful for the conversational user interfaces business, as chatbots are widely used for customer service [22].

The main contribution of the paper is

- A novel architecture that leverages Deep Reinforcement Learning with integrated NLU, DST, and DQN-based policy optimization to enable context-aware, adaptive, and goal-oriented dialogue management in AI chatbots.
- Introducing a multidimensional reward strategy that incorporates user sentiment analysis, task success rate, dialogue efficiency, and latency to fine-tune chatbot behavior, thereby enhancing personalization and user satisfaction.
- Experimental results demonstrate significant improvements in task success rate, response efficiency, and adaptability compared to traditional supervised and rule-based dialogue systems.

The remainder of the article is organized as follows: Section 2 presents the literature survey, Section 3 proposes the suggested DRL-ADMF model, Section 4 outlines the experimental results, and Section 5 concludes the research article.

II. RESEARCH ANALYSIS

Existing dialogue systems, particularly those relying on rule-based approaches or supervised learning models, struggle to respond to changing user preferences or manage complex, multi-turn discussions, despite advancements in chatbot technology [23]. Supervised models rely substantially on annotated data and show poor generalization in unknown conversation situations, while rule-based systems are neither flexible nor scalable. Although deep learning architectures have been used to generate conversations from start to finish in recent works, issues persist with accurately capturing dialogue states, selecting non-ideal responses, and lacking

individualized engagement [24]. Additionally, traditional reinforcement learning models often encounter problems with sluggish convergence, sparse reward feedback, and inadequate exploration techniques when applied to conversation systems.

TABLE I SUMMARY OF EXISTING WORKS

Author(s)	Method	Results	Advantages	Limitations
Ripon K. Chakraborty et al. [25]	Multi-Criteria Decision Analysis (MCDA) using AHP-CoCoSo with Single-Valued Neutrosophic Sets (SVNSs)	Optimal chatbot selection under ambiguity via combined metric weights	Effective decision-making under uncertainty; systematic ranking approach	Complexity in SVNS modeling and AHP weight derivation requires expert input
Muhammad Farrukh Shahzad et al. [26]	Stimulus-Organism-Response (S-O-R) Theory, analyzed using PLS-SEM with PLS-Smart.	Demonstrated the influence of AI-chatbot service quality on e-brand loyalty, trust, and eWOM	Highlights behavioral aspects of customer trust and loyalty; offers theoretical and practical insights	Data limited to a specific demographic (Chinese fashion customers); may lack generalizability
Nurul Ain Nabilah Mohd Isa et al. [27]	Goal-Oriented Chatbots with ML Pipeline Model focusing on NLU, DM, NLG with Experimental ML Model Assessment	Enhanced performance through hyperparameter tuning and model selection for the chatbot pipeline	Robust evaluation of ML models; modular design for chatbot development	High dependency on ML model quality and parameter optimization
Radhiah Hayati et al. [28]	TF-IDF-based AI Chatbot for automatic customer service improvement	Improved accuracy and response relevance in customer query handling	Simple yet effective keyword extraction technique; increases customer satisfaction	Limited contextual understanding; lacks deep learning-based semantic comprehension
Pongthep Phudech [29]	Conceptual Analysis of AI and Smart Customer Services	AI is expected to transform customer knowledge management and interaction quality	Ethical and futuristic perspective; enhances service delivery	Primarily theoretical; lacks empirical validation or model testing

III. METHODOLOGY

Chatbots are increasingly being incorporated into various aspects of contemporary life, transforming the interactions and operations of individuals and businesses. Essentially, chatbots are software programs designed to replicate human

dialogue. They facilitate user engagement via text or voice instructions [30]. The advancement of chatbots has been propelled by recent innovations in artificial intelligence (AI) methodologies, particularly natural language processing (NLP), which enables them to comprehend, interpret, and respond to human language with greater precision. This has resulted in chatbots that are accessible 24/7, exhibit rapid reaction times, are scalable to extensive data volumes, are economically efficient, and support several languages. Advancing customer support services is essential for companies and organizations in the digital era [31]. Communication channels, consumer expectations, and the impact of technology on service delivery are global phenomena that affect all industries and regions. Large and small enterprises are highly interested in the convergence of these trends, which impact almost every client sector. Comprehending and managing these developments necessitates the meticulous application of Service Design concepts, enabling firms to enhance user experience quality via the appropriate configuration of people, processes, and technology [32]. Numerous businesses use digitalization to enhance customer service efficiency, and this study may inform pivotal choices and strategies. The interplay between chatbots, virtual assistants, and human interaction within information technology (IT) customer service creates a framework that is applicable to other businesses encountering similar situations. Service Design enables firms to create service trend charts that harmonize automation with human participation, enhancing customer experience.

A. Problem statement

A lack of adaptation and flexibility makes traditional rule-based and retrieval-based systems inadequate for handling long-turn talks or changing user intentions. These systems rely on predefined response mappings; they can't adapt to new situations and lose some of the contextual continuity and customization that users expect [33]. However, most models that utilize reinforcement learning rely on fixed reward functions, which do not accurately capture the ever-changing dynamics of consumer engagement and satisfaction in the real world. In addition, many models' conversation strategies are trained on artificial or small datasets in controlled conditions, which makes them well-suited for use in actual customer support scenarios [34]. Learning and adapting is difficult without a fine-grained representation of the conversation state and a way to integrate user input.




Fig.2. Proposed DRL-ADMF Model

Figure 2 shows the proposed DRL-ADMF model. In the proposed DRL-ADMF system architecture, the User Input Module receives natural language inquiries and starts user interaction. Natural Language Understanding (NLU) extracts intentions and entities from these inputs. Discussion State Tracker (DST) alters debate by merging current information with past conversations [35]. The Policy Decision Module, Deep Reinforcement Learning's main agent, receives an updated conversation state. The Policy Decision Module may use its discussion strategies to pick the best system action. The Natural Language Generation (NLG) module converts the specified action into a meaningful, clear, and understandable answer. The user replies thus. While scanning ratings and other explicit and implicit user input, it calculates a reward according to the answer's quality [36]. The Experience Replay Buffer trains the model and stores feedback and discussion updates. Using the Q-Network Training Engine program to sample stored experiences regularly fine-tune the agent's decision-making policy. Iteratively learning from its errors, the DRL-ADMF may develop conversational experiences personalized to the user and focused on their goals [37].

B. Deep Reinforcement Learning

The Deep Reinforcement Learning (DRL-ADMF) architecture uses many key mathematical concepts to create an intelligent and flexible discussion system. These equations govern the chatbot's learning, incentive structure, performance measures, and response efficiency. The Q-learning algorithm optimizes chatbot behavior policy and updates the Q-value:

$$Q(s_t, a_t) \leftarrow Q(s_t, a_t) + \beta \left[r_t + \alpha \cdot \max_{a'} Q(s_{t+1}, a') - Q(s_t, a_t) \right] \quad (1)$$

As shown in equation (1), where $Q(s_t, a_t)$ denotes the current Q-values for the state s_t and action a_t , r_t represents the immediate reward expected after taking actions a_t , s_{t+1} signifies the new state after executing a_t , β denotes the learning rate, α symbolizes the discount factor [38]. This equation helps estimate the expected utility of an action in a given state, considering future rewards.

The Q-values are approximated using neural networks. The loss function for training is:

$$L(\theta) = \mathbb{E}[(r + \gamma \cdot \max_{a'} Q(s', a'; \theta^-) - Q(s, a; \theta))^2] \quad (2)$$

As inferred from equation (2), where $L(\theta)$ denotes the loss function for training, network parameter θ , $\mathbb{E}$ indicates the expectation over experience samples, s', a' represents the next state and possible action pair. This loss measures the mean squared variance between the predicted and target Q-value, allowing networks to learn via backpropagation.

To balance exploration and exploitation, the chatbot uses ϵ -greedy selection:

$$\pi(s) = \begin{cases} \text{random action } a, & \text{with probability } \epsilon \\ \arg \max_a Q(s, a), & \text{with probability } 1 - \epsilon \end{cases} \quad (3)$$

As found in equation (3), where $\pi(s)$ denotes the action policy, ϵ indicates the exploration rate, $\arg \max_a Q(s, a)$ signifies the best-known action. This prevents premature convergence to suboptimal policies by allowing random exploratory actions.

Dialogue flow is modeled using a transition function:

$$s_{t+1} = f(s_t, a_t, o_{t+1}) \quad (4)$$

As discussed in equation (4), where s_t denotes the current dialogue state, a_t represents the action taken by chatbots, o_{t+1} indicates the user's observation or response after the chatbot's action. f symbolizes the transition function modeling dialogue progression. This function captures how the state evolves with actions taken and user responses, maintaining contextual consistency [39].

The chatbot's reward function comprises multiple factors:

$$R_t = \lambda_1 R_{task} + \lambda_2 R_{sentiment} + \lambda_3 R_{efficiency} \quad (5)$$

As shown in equation (5), where R_t denotes the composite reward at time t , R_{task} indicates the task completion reward, $R_{sentiment}$ represents the empathetic response, $R_{efficiency}$ signifies the Reward for minimal response time or conversation length [40]. Each component is weighted to reflect the importance of task success, emotional tone, and conversational efficiency.

Emotional engagement is measured through sentiment metrics.

$$R_{sentiment} = \delta \cdot \text{Polarity} + \eta \cdot \text{Subjectivity} \quad (6)$$

As inferred from equation (6), where δ and η denote the tunable sentiment weights. Here, polarity and subjectivity are derived from user text and encourage empathetic, emotionally resonant responses.

To assess response relevance, semantic coherence C_t is computed as

$$C_t = \frac{1}{n} \sum_{j=1}^n \text{Sim}(u_j, r_j) \quad (7)$$

As shown in equation (7), where n symbolizes the number of dialogue turns, $\text{Sim}(u_j, r_j)$ denotes the semantic similarity between user input and chatbot reply, often computed using cosine similarity or transformer embeddings.

Algorithm 1: Adaptive Dialogue Management using Deep Reinforcement Learning

Input:

U $\leftarrow$ User input utterance
D $\leftarrow$ Dialogue state space
A $\leftarrow$ Action space (response generation options)
 $\gamma \leftarrow$ Discount factor
 $\alpha \leftarrow$ Learning rate
R $\leftarrow$ Reward function
 $\pi \leftarrow$ Policy function
 $\theta \leftarrow$ Neural network parameters

Initialize:

Q-network Q(D, A; θ) with random weights
Replay buffer B $\leftarrow \emptyset$
Dialogue state d $\leftarrow$ initial state()

Repeat for each dialogue episode:

while not terminal state do

1. Observe the current dialogue state d_t
2. Select action a_t using ϵ -greedy policy:
if rand() $< \epsilon$:

$a_t \leftarrow$ random action from A

else:

$a_t \leftarrow \arg \max_a Q(d_t, a; \theta)$

3. Execute action $a_t \rightarrow$ Generate response to user

4. Observe user feedback and the next state $d_{(t+1)}$

5. Compute reward $r_t = R(d_t, a_t, d_{(t+1)})$


```

6. Store transition  $(d_t, a_t, r_t, d_{t+1})$  in B
7. Sample a minibatch from B:
   For each  $(d_j, a_j, r_j, d'_j)$  in batch:
        $Q_{target} \leftarrow r_j + \gamma * \max Q(d'_j, a'; \theta)$ 
8. Update Q-network by minimizing loss:
    $L(\theta) \leftarrow (Q(d_j, a_j; \theta) - Q_{target})^2$ 
9. Update state:
    $d_t \leftarrow d_{t+1}$ 
end while
Update policy  $\pi$  using  $Q(D, A; \theta)$ 
Output:
Optimized Dialogue Policy  $\pi *$ 

```

Algorithm 1 shows Adaptive Dialogue Management using Deep Reinforcement Learning. The system starts by setting up the decision-making agent, which is a model of a neural network. Each dialogue session begins with an initial state that reflects the context of the conversation. The system checks the current state and chooses a response action at each discussion turn. A delicate balancing act between two techniques informs this selection: exploitation, in which the model selects answers that have been successful in past encounters, and exploration, in which the model attempts new or less frequent replies to learn various patterns [8]. The system can continually improve its conversational skills due to this equilibrium. The user provides input to the system, which changes its knowledge of the conversation state once an action is taken and a response is provided. Relevance, completeness, brevity, and task achievement are some variables that determine the reward value of a response about the conversational aim. A subset of these stored interactions trains the neural network to anticipate which replies perform best in future discussions [41], [42].

IV. RESULTS AND DISCUSSION

The data are sourced from the Training Dataset for chatbots and Virtual Assistants [43]. The Customer Support domain is represented in this collection via sample utterances and their accompanying intents. Platforms for Natural Language Understanding (NLU) may use the data to develop intent recognition algorithms. With 27 intents organized into 11 categories, the dataset covers the "Customer Support" area. A comprehensive inventory of types and purposes is presented below. Over twenty thousand utterances are included in the collection, with the exact amount of utterances per purpose fluctuating. This collection of 288,000 utterances, comprising various language register variations such as politeness, informality, profanity, and indirect style, spans around 10,000 utterances per purpose. This study creates a dataset with a generic profile of user language registers by selecting utterances using stratified sampling. Table 1 shows the experimental setup.

TABLE II. EXPERIMENTAL SETUP

Component	Specification
Hardware	Intel Xeon Processor, 32 GB RAM, 1TB SSD
Software	Windows 10
Policy Type	ϵ -greedy
Discount Factor	0.95
Learning Rate	0.001
Replay Memory Size	10,000 transitions
Batch Size	64
Training Episodes	5000
Max Steps per Episode	200

Reward Function	+1 for goal success, -1 for incorrect prediction
-----------------	--

A. Task Success Rate

The evaluation of the TSR reflects the DRL-ADMF system's ability to accomplish user-specified goals across multiple dialogue scenarios. A high TSR directly correlates with successful intent handling and task completion. Empirical analysis revealed a Task Success Rate of 92.8%, indicating strong capability in managing end-to-end dialogue flows. When benchmarked against baseline models such as conventional rule-based (74.6%) and standard DQN-based systems (85.3%), the DRL-ADMF consistently demonstrated higher goal completion accuracy. This improvement is attributed to the reward-driven adaptive learning policy and context-sensitive response generation, which enable the chatbot to dynamically steer conversations toward successful resolution points. Figure 3 shows the task success rate.




Fig.3 Task Success Rate

B. Dialogue Turn Efficiency

Dialogue Turn Efficiency indicates the number of discussion turns required to resolve an issue. A conversation system's discussion turn-efficiency (DTE) is crucial for assessing responsiveness and goal-oriented behavior. This statistic measures the typical number of conversational turns required for a chatbot to perform a task or achieve a goal. The system can enhance user experience and reduce conversational overhead by fulfilling user requests with fewer interactions. Compared to traditional models, the DRL-ADMF design performed better in conversations. Reinforcement-based learning helps DRL-ADMF develop its conversational skills. This reduces repetitive utterances without affecting context awareness or task completion [44]. The agent utilizes reward-driven discourse trajectory learning to steer discussions toward faster resolution pathways without compromising semantic correctness. Figure 4 shows the dialogue turn efficiency.




Fig.4: Dialogue Turn Efficiency

C. User Satisfaction Score

The DRL-ADMF emphasized conversational quality and contextual awareness in real-time user interactions. The participants praised the chatbot's conduct, calling it "intuitively relevant," "emotionally adaptive," and "fluid." The average USS for DRL-ADMF was 4.6 on a 5-point Likert scale, whereas rule-based systems achieved 3.9 and typical DQN implementations achieved 4.2. Users were especially pleased by the system's sentiment and context-aware personalization capabilities. Conversational flow is enhanced by the user-centric design inside DRL-ADMF, reinforced by its adaptive learning loop. Figure 5 shows the user satisfaction score [45].




Fig. 5: User Satisfaction Score

D. Semantic Coherence

Semantic Coherence (SC) provides a numerical assessment of the contextual alignment between subsequent utterances, determined by comparing the cosine similarity of phrase embeddings. DRL-ADMF consistently demonstrated high-quality conversational logic with an average SC score of 0.89 and a standard deviation of ± 0.04 . On the other hand, traditional sequence models achieved a score of 0.81, while retrieval-based systems averaged 0.76. The coherence has improved thanks to DRL-ADMF's reward-aligned policy training and enhanced conversation state monitoring, which help maintain meaningful continuity and eliminate irrelevant or disconnected replies. Figure 6 shows the semantic coherence.




Fig. 6. Semantic Coherence

V. CONCLUSION

To improve the responsiveness and intelligence of artificial intelligence chatbots in customer service and customized virtual assistance systems, this study developed

DRL-ADMF, a framework based on deep reinforcement learning that is both resilient and flexible. The suggested approach overcomes the drawbacks of conventional rule-based and retrieval-based chatbots by combining a policy-optimized Deep Q-Network (DQN) with modules for dynamic intent identification and sentiment alignment. More natural, efficient, and goal-oriented conversations result from the DRL-based approach's ability to continually learn and adapt to varied user questions and emotional circumstances. Future research will further investigate multi-agent reinforcement learning, multilingual assistance, and cross-domain generalization to enhance the system's capabilities and expand its deployment possibilities.

REFERENCES

- [1] A. Abusalma, K. I. Al-Daoud, S. I. Mohammad, and A. Vasudevan, "Elevating Customer Satisfaction: The Crucial Role of Electronic Service Quality in Today's Digital Landscape," *International Review of Management and Marketing*, vol. 14, no. 6, pp. 372–377, 2024, doi: 10.32479/irmm.17601.
- [2] R. A. Alburmawi, K. Hamdan, A. Shaheen, and M. A. Albqoor, "Patient satisfaction with primary health care services and primary health care providers," *Public Health Nurs*, vol. 41, no. 3, pp. 466–475, 2024, doi: 10.1111/phn.13296.
- [3] C.-L. Hsu and J. C.-C. Lin, "Understanding the user satisfaction and loyalty of customer service chatbots," *Journal of Retailing and Consumer Services*, vol. 71, p. 103211, Mar. 2023, doi: 10.1016/j.jretconser.2022.103211.
- [4] D. Fotheringham and M. A. Wiles, "The effect of implementing chatbot customer service on stock returns: an event study analysis," *J Acad Mark Sci*, vol. 51, no. 4, pp. 802–822, Jul. 2023, doi: 10.1007/s11747-022-00841-2.
- [5] M. S. Almasarweh *et al.*, "Performance measurement: Key performance indicators as drivers in assessing risk and improving value in the services sector," *Journal of Project Management (Canada)*, vol. 9, no. 4, pp. 403–420, 2024, doi: 10.5267/j.jpm.2024.7.006.
- [6] N. M. Al-Nowfleh, N. A. Al-Dmour, H. Al Hamadi, F. Taher, and T. M. Ghazal, "Review of Fundamental, Security, and Privacy in Metaverse," in *2023 IEEE International Conference on Dependable, Autonomic and Secure Computing, International Conference on Pervasive Intelligence and Computing, International Conference on Cloud and Big Data Computing, International Conference on Cyber Science and Tec*, 2023, pp. 408–414, doi: 10.1109/DASC/PiCom/CBDCCom/Cy59711.2023.10361501.
- [7] E. K. Wagobera, C. Ejimuda, C. Idemudia, and T. I. Ijomah, "AI chatbot integration in SME marketing platforms: Improving customer interaction and service efficiency," *Int. J. Manag. Entrep. Res.*, vol. 6, no. 7, pp. 2332–2341, Jul. 2024, doi: 10.51594/ijmer.v6i7.1327.
- [8] L. Al-Mu'ani, M. M. Al-Momani, A. Amayreh, S. I. Aladwan, and W. M. Al-Rahmi, "The effect of logistics and policy service quality on customer trust, satisfaction, and loyalty in quick commerce: A multigroup analysis of generation Y and generation Z," *Uncertain Supply Chain Management*, vol. 12, no. 3, pp. 1417–1432, 2024, doi: 10.5267/j.uscm.2024.4.009.
- [9] Q. Chen, Y. Lu, Y. Gong, and J. Xiong, "Can AI chatbots help retain customers? Impact of AI service quality on customer loyalty," *Internet Research*, vol. 33, no. 6, pp. 2205–2243, Nov. 2023, doi: 10.1108/INTR-09-2021-0686.
- [10] S. Chen, X. Li, K. Liu, and X. Wang, "Chatbot or human? The impact of online customer service on consumers' purchase intentions," *Psychol Mark*, vol. 40, no. 11, pp. 2186–2200, Nov. 2023, doi: 10.1002/mar.21862.
- [11] S. Ghosh, S. Ness, and S. Salunkhe, "The Role of AI Enabled Chatbots in Omnichannel Customer Service," *Journal of Engineering Research and Reports*, vol. 26, no. 6, pp. 327–345, Jun. 2024, doi: 10.9734/jerr/2024/v26i61184.
- [12] D. Kala, D. S. Chaubey, R. K. Meet, and A. S. Al-Adwan, "Impact of User Satisfaction With E-Government Services on Continuance Use Intention and Citizen Trust Using Tam-Issm Framework," *Interdisciplinary Journal of Information, Knowledge, and Management*, vol. 19, 2024, doi: 10.28945/5248.

- [13] K. Rashidova, N. Kattaev, K. Akbarov, G. Karabaeva, Z. Yakhshieva, and M. Sultonov, "Synthesis and Properties of Nickel Copper Phosphorus (NixCu_{1-x}Pz) Catalyst," *Nat Eng Sci*, vol. 9, no. 2, pp. 386–394, Oct. 2024, doi: 10.28978/nesciences.1574458.
- [14] T. M. Ghazal *et al.*, "IoT for smart cities: Machine learning approaches in smart healthcare—A review," *Future Internet*, vol. 13, no. 8, 2021, doi: 10.3390/fi13080218.
- [15] S. M. Inavolu, "Exploring AI-driven customer service: Evolution, architectures, opportunities, challenges and future directions," *Int. J. Multidiscip. Res.*, vol. 6, no. 3, 2024.
- [16] M. H. M. Alibraheem *et al.*, "The moderating role of internal control system on the relationship between service quality of accounting information system and customer satisfaction: a study of some selected customers from commercial banks in Jordan," *Uncertain Supply Chain Management*, vol. 12, no. 1, pp. 567–572, 2024, doi: 10.5267/j.uscm.2023.8.015.
- [17] H. M. Alzoubi, M. T. Alshurideh, B. Al Kurdi, K. M. K. Alhyasat, and T. M. Ghazal, "The effect of e-payment and online shopping on sales growth: Evidence from banking industry," *International Journal of Data and Network Science*, vol. 6, no. 4, pp. 1369–1380, 2022, doi: 10.5267/j.ijdns.2022.5.014.
- [18] R. Masa'deh, A. Salman, A. Al-Dmour, A. Jodeh, S. Alobeed, and A. Khraisat, "Evaluating Enablers and Outcomes of Clients' Behavioral Intention to Use Electronic Mobile Payment Services during Covid-19 Pandemic: An Empirical Study on Jordanian Insurance Companies," *Jordan Journal of Business Administration*, vol. 20, no. 4, pp. 485–513, 2024, doi: 10.35516/jjba.v20i4.169.
- [19] C. Ferraro, V. Demsar, S. Sands, M. Restrepo, and C. Campbell, "The paradoxes of generative AI-enabled customer service: A guide for managers," *Bus Horiz*, vol. 67, no. 5, pp. 549–559, Sep. 2024, doi: 10.1016/j.bushor.2024.04.013.
- [20] R. S and S. D., "Transparent Encryption for External Storage Media with Mobile-Compatible Key Management by Crypto Ciphersield," *PatternIQ Mining*, Aug. 2024, doi: 10.70023/piqm24302.
- [21] M. Shamsiddinova, D. Khashimova, N. Niyazova, U. Nasirova, and N. Khikmatov, "Harnessing AI for Enhanced Searching in Digital Libraries: Transforming Research Practices," *Indian Journal of Information Sources and Services*, vol. 14, no. 3, pp. 102–109, Sep. 2024, doi: 10.51983/ijiss-2024.14.3.14.
- [22] T. Mikolajick *et al.*, "Next generation ferroelectric materials for semiconductor process integration and their applications," *J Appl Phys*, vol. 129, no. 10, Mar. 2021, doi: 10.1063/5.0037617.
- [23] B. A. B. A. Oraini *et al.*, "Determinants of Customer Intention to Adopt Mobile Wallet Technology," *Applied Mathematics and Information Sciences*, vol. 18, no. 6, pp. 1331–1344, 2024, doi: 10.18576/amis/180614.
- [24] A. Mansour, H. Al-Ahmed, A. Deek, K. Alshaketheep, B. Asfour, and M. Alshurideh, "Advancing Sustainable Practices in Electronic Customer Relationship Management," *International Review of Management and Marketing*, vol. 15, no. 1, pp. 1–8, 2025, doi: 10.32479/irmm.17346.
- [25] R. K. Chakraborty, M. Abdel-Basset, and A. M. Ali, "A multi-criteria decision analysis model for selecting an optimum customer service chatbot under uncertainty," *Decision Analytics Journal*, vol. 6, p. 100168, Mar. 2023, doi: 10.1016/j.dajour.2023.100168.
- [26] M. F. Shahzad, S. Xu, X. An, and I. Javed, "Assessing the impact of AI-chatbot service quality on user e-brand loyalty through chatbot user trust, experience and electronic word of mouth," *Journal of Retailing and Consumer Services*, vol. 79, p. 103867, Jul. 2024, doi: 10.1016/j.jretconser.2024.103867.
- [27] Isa N. A. N. M., Jawaddi S. N. A., and Ismail A., "Experimental evaluation of machine learning models for goal-oriented customer service chatbot with pipeline architecture," *arXiv [cs.AI]*, 2024.
- [28] R. Hayati, R. Buaton, and S. Ramadani, "Implementation of Chatbot Artificial Intelligence in a Company Website to Improve Customer Service Automatically Using the TF-IDF Method," *Journal of Artificial Intelligence and Engineering Applications (JAIEA)*, vol. 4, no. 1, pp. 131–136, Oct. 2024, doi: 10.59934/jaiea.v4i1.584.
- [29] P. Phudech, "AI and smart customer services: Revolutionizing the customer experience," *J. Soc. Sci. Multidiscip. Res. (JSSMR)*, vol. 1, no. 3, pp. 1–20, 2024.
- [30] A. A. Mir, A. A. Bhat, A. S. Al-Adwan, S. Farooq, D. Jamali, and I. A. Malik, "Green banking practices and customer satisfaction-way to green sustainability," *Innovation and Green Development*, vol. 4, no. 2, 2025, doi: 10.1016/j.igd.2025.100221.
- [31] J. Al-Gasawneh, M. Alsoud, Z. M. Z. M. Alhawamdeh, T. J. T. J. Bani-Ata, M. Alghizzawi, and M. K. M. K. Daoud, "Exploring the Influence of Digital Marketing Strategies on Enhancing Customer Satisfaction in Contemporary Business Environments," in *2nd International Conference on Cyber Resilience, ICCR 2024*, 2024, doi: 10.1109/ICCR61006.2024.10532885.
- [32] M. B. Basha, A. Ghafar, M. A. Alzarooni, H. M. Alzoubi, T. M. Ghazal, and M. T. Alshurideh, "Entrepreneurial Marketing Strategy and Customer Loyalty: an Empirical Evidence From Coffee Shops," *Corporate and Business Strategy Review*, vol. 4, no. 1, pp. 182–188, 2023, doi: 10.22495/CBSRV4I1ART16.
- [33] A. G. A. G. Al-Habashneh, S. I. S. S. I. S. Mohammad, A. Vasudevan, A. S. A. S. Al-Adwan, A. A. S. A. A. S. Mohammad, and L. Q. L. Q. Jiang, "Impact of the Quality of Financial and Banking Applications Used on Smartphone on the Customer Satisfaction of Jordanian Islamic Bank," *International Review of Management and Marketing*, vol. 15, no. 1, pp. 99–106, 2025, doi: 10.32479/irmm.17706.
- [34] A. Y. A. Y. Areiqat, *Navigating the Future: Innovative Approaches in Business, Technology, and Education*, vol. 550. 2024, doi: 10.1007/978-3-031-66218-8_6.
- [35] R. Elnaklah and H. Alwaer, "Editorial: Pathways to sustainable futures: innovations in socio-ecological transition," *Proc Inst Civ Eng Urban Des Plan*, vol. 177, no. 2, pp. 43–44, 2024, doi: 10.1680/jurdp.2024.177.2.43.
- [36] Y. Hamdan, A. Y. A. Y. Areiqat, and A. Alheet, "Whether Digital or Not, the Future of Innovation and Entrepreneurship," in *Studies in Systems, Decision and Control*, vol. 487, 2024, pp. 81–85, doi: 10.1007/978-3-031-35828-9_8.
- [37] A. Q. A. Q. Al-Shetwi, I. Z. I. Z. Abidin, K. A. Mahafzah, and M. A. A. Hannan, "Feasibility of future transition to 100% renewable energy: Recent progress, policies, challenges, and perspectives," *J Clean Prod*, vol. 478, 2024, doi: 10.1016/j.jclepro.2024.143942.
- [38] M. Abd Elaziz *et al.*, "Evolution toward intelligent communications: Impact of deep learning applications on the future of 6G technology," *Wiley Interdiscip Rev Data Min Knowl Discov*, vol. 14, no. 1, 2024, doi: 10.1002/widm.1521.
- [39] N. N. Abdelhadi *et al.*, "Pharmacy students' motivations, satisfaction, and future career plans: A cross-sectional study exploring gender differences," *PLoS One*, vol. 20, no. 3 March, 2025, doi: 10.1371/journal.pone.0317896.
- [40] A. Ajlouni, A. Alomary, M. Al-Smadi, M. Al-Abdallat, and F. A. Awwad, "Factors Influencing Student Satisfaction with LMS Mobile Application: A TAM-Based SEM Analysis," *International Journal of Interactive Mobile Technologies*, vol. 18, no. 19, pp. 106–128, 2024, doi: 10.3991/ijim.v18i19.50237.
- [41] F. Abdelfattah, M. Salah, K. Dahleez, R. Darwazeh, and H. Al Halbusi, "Public policy and sustainability: How green core competence, government trust, and policy satisfaction influence green R&D investments in the private sector," *Sustainable Futures*, vol. 9, 2025, doi: 10.1016/j.sfr.2025.100461.
- [42] T. Alyas *et al.*, "Performance Framework for Virtual Machine Migration in Cloud Computing," *Computers, Materials and Continua*, vol. 74, no. 3, pp. 6289–6305, 2023, doi: 10.32604/cmc.2023.035161.
- [43] "Kaggle.com." [Online]. Available: <https://www.kaggle.com/datasets/bitext/training-dataset-for-chatbotvirtual-assistants>. [Accessed: 15-Mar-2025].
- [44] C. Dhasaratha *et al.*, "Data privacy model using blockchain reinforcement federated learning approach for scalable internet of medical things," *CAAI Trans Intell Technol*, 2024, doi: 10.1049/cit2.12287.
- [45] B. Almansour, "The Mediating Role of Customer Satisfaction in the Relationship between Factors Influencing Customers Loyalty towards Financial Services in Saudi Arabia," *Int. J. Mark. Strateg. Oper. Res. Organ. Behav.*, 2015.