

ROLL PULLER® XL

Unload van trucks and containers **up to 10× faster** — and keep your crew out from under the top tier.

PATENTS PENDING
MODELS RP3XL & RP4XL



RP3XL — fits 2.75"–3.25" ID cardboard cores

RP4XL — fits 3.75"–4.50" ID cardboard cores

16" BODY GRABS 4" DEEPER INTO THE CORE MINIMUM 0.5 CORE THICKNESS 1,000 LB MAX PULL EACH

WHY IT PAYS

- Eliminates most of the hand labor of carrying rolls from the rear of a van or container.
- Protects workers — and the employer — from injuries and claims.
- Pays for itself in just a few shipments.

A contractor pulled **75 rolls of paving fabric — 25 banded groups of three — in one pull** with three RP4XL pullers. Beyond the rated limit, but it happened.

We stock Grade 70 chain, slip and grab hooks, and 4" forged steel O-rings for complete multi-puller systems — cut and assembled to your set.

HOW TO USE IT

1. Attach a rope, strap, cable or 5/16" Grade 70 chain rated **4,700 lb WLL or greater** to the end ring.
2. Insert the puller into the core, leaving the red tape line — about 2" — exposed.
3. Pull the ring back to lock the teeth into the core, then tug to confirm the bite.
4. **Pull horizontally or with a slight upward lift.** Never pull downward on an angle — it drags the rolls beneath, can exceed 1,000 lb, and voids the warranty.
5. Push the ring in while holding the red taped end to release the teeth, then slide the puller out.

Multiple pullers: join them with short Grade 70 chains and hooks to a heavy steel O-ring, then pull from the center with 65 ft minimum of 1" rope. If a core starts to pull out, move up a row or add a puller per core.

THINK SAFETY

- Roll pullers do not break with proper use. Ropes, chains, cables and slings do.
- Hard hats, steel-toed shoes, eye protection and gloves at all times.
- **Never stand along the rope being pulled** or where rolls can fall — stand to the side of the truck.
- OSHA: never exceed the working load limit. Maximum 1,000 lb per puller.

CALL FOR PRICING & LEAD TIMES — +1 (440) 328-8200

gacco@outlook.com · www.gacco.com · www.rollpullers.com

Watch three pullers unload 18 banded rolls: [youtube.com/shorts/7I6ESZxjh4Y](https://www.youtube.com/shorts/7I6ESZxjh4Y)

90-day warranty against defects from date of purchase with proper use. © 1980–2026 Mounque Barazone & Geotextile Apparatus Company. All rights reserved.