HDFS (Cluster 1)

Actions

Filters

SCOPE

HDFS (Service-Wide)	122
Balancer	14
DataNode	76
Gateway	12
HttpFS	50
JournalNode	52
NFS Gateway	47
NameNode	103
SecondaryNameNode	52
Failover Controller	39

CATEGORY

Advanced	87
Checkpointing	2
High Availability	5
Logs	30
Main	38
Monitoring	96
Performance	20
Plugins	2
Ports and Addresses	26
Proxy	20
Replication	5
Resource Management	14
Security	51
Stacks Collection	5

STATUS

Error	0
Warning	0
Edited	0
Non-default	12
Has Overrides	0

Search

Show All Descriptions

ZooKeeper Service
HDFS (Service-Wide)
- (•) ZooKeeper
- ( ) none

KMS Service
HDFS (Service-Wide)
- (•) none

Object Store Service
HDFS (Service-Wide)
- (•) none

HDFS Block Size
dfs.block.size, dfs.blocksize
HDFS (Service-Wide)
128 MiB

Default Umask
dfs.umaskmode, fs.permissions.umask-mode
HDFS (Service-Wide)
022

Enable WebHDFS
dfs.webhdfs.enabled
[x] HDFS (Service-Wide)

Check HDFS Permissions
dfs.permissions
[x] HDFS (Service-Wide)

Compression Codecs
io.compression.codecs
HDFS (Service-Wide)
- org.apache.hadoop.io.compress.DefaultCodec
- org.apache.hadoop.io.compress.GzipCodec
- org.apache.hadoop.io.compress.BZip2Codec
- org.apache.hadoop.io.compress.DeflateCodec
- org.apache.hadoop.io.compress.SnappyCodec
- org.apache.hadoop.io.compress.Lz4Codec

Serve logs over HTTP
hadoop.http.logs.enabled
[x] HDFS (Service-Wide)

Rebalancing Threshold
Balancer Default Group
10

Save Changes

Feedback

Rebalancing Policy
Balancer Default Group
- (•) DataNode
- ( ) BlockPool

Excluded Hosts
Balancer Default Group

Included Hosts
Balancer Default Group

Source Hosts
Balancer Default Group

Maximum Concurrent Moves
dfs.datanode.balance.max.concurrent.moves
Balancer Default Group
50

Maximum Iteration Size
dfs.balancer.max-size-to-move
Balancer Default Group
10 GiB

Mover Threads
dfs.balancer.moverThreads
Balancer Default Group
1000

Dispatcher Threads
dfs.balancer.dispatcherThreads
Balancer Default Group
200

DataNode Failed Volumes Tolerated
dfs.datanode.failed.volumes.tolerated
DataNode Default Group
1

Reserved Space for Non DFS Use
dfs.datanode.du.reserved
DataNode Default Group
10 GiB

DataNode Data Directory
dfs.data.dir, dfs.datanode.data.dir
DataNode Default Group
/dfs/dn
/data/dfs/dn

Use Trash
[x] Gateway Default Group

Alternatives Priority
Gateway Default Group
90

HttpFS Load Balancer
HttpFS Default Group

Feedback

Save Changes

JournalNode Edits Directory
dfs.journalnode.edits.dir

JournalNode Default Group

Temporary Dump Directory
dfs.nfs3.dump.dir

NFS Gateway Default Group

/tmp/.hdfs-nfs

Allowed Hosts and Privileges
dfs.nfs.exports.allowed.hosts

NFS Gateway Default Group

* rw

Filesystem Trash Interval
fs.trash.interval

NameNode Default Group

1 day(s)

NameNode Data Directories
dfs.name.dir, dfs.namenode.name.dir

NameNode Default Group

/dfs/nn

/data/dfs/nn

NameNode Edits Directories
dfs.namenode.edits.dir

NameNode Default Group

Shared Edits Directory
dfs.namenode.shared.edits.dir

NameNode Default Group

Restore NameNode Directories at Checkpoint Time
dfs.name.dir.restore, dfs.namenode.name.dir.restore

NameNode Default Group

Filesystem Trash Checkpoint Interval
fs.trash.checkpoint.interval

NameNode Default Group

1 hour(s)

Topology Script File Name
net.topology.script.file.name

NameNode Default Group

Safemode Minimum DataNodes
dfs.safemode.min.datanodes, dfs.namenode.safemode.min.datanodes

NameNode Default Group

1

Safemode Extension
dfs.safemode.extension, dfs.namenode.safemode.extension

NameNode Default Group

30 second(s

Access Time Precision
dfs.access.time.precision

NameNode Default Group

1 hour(s)

Save Changes

Feedback

HDFS Checkpoint Directories
fs.checkpoint.dir, dfs.namenode.checkpoint.dir

SecondaryNameNode Default Group

/dfs/snn

Enable HDFS Block Metadata API
dfs.datanode.hdfs-blocks-metadata.enabled

☑ HDFS (Service-Wide)

System User

HDFS (Service-Wide)

hdfs

System Group

HDFS (Service-Wide)

hdfs

Shared Hadoop Group Name

HDFS (Service-Wide)

hadoop

System User's Home Directory

HDFS (Service-Wide)

/var/lib/hadoop-hdfs

HDFS Service Advanced Configuration Snippet (Safety Valve) for hdfs-site.xml

HDFS (Service-Wide)

View as XML

Feedback

Save Changes

Cluster-wide Advanced Configuration Snippet (Safety Valve) for core-site.xml

HDFS (Service-Wide)

View as XML

Name dfs.adls.oauth2.client.id

Value aa03a3a4-83d3-42ac-9507-393e172199d8

Description Description

Final

Name dfs.adls.oauth2.credential

Value pBwYpWUebxfVi3AHUNtDbI868sFLPL4UasclGv

Description Description

Final

Name dfs.adls.oauth2.refresh.url

Value https://login.microsoftonline.com/7575b092-fc!

Description Description

Final

Name dfs.adls.oauth2.access.token.provider.type

Value ClientCredential

Description Description

Final

HDFS Service Advanced Configuration Snippet (Safety Valve) for hadoop-policy.xml

HDFS (Service-Wide)

View as XML

HDFS Replication Environment Advanced Configuration Snippet (Safety Valve)

HDFS (Service-Wide)

HDFS Snapshot Shell Command Environment Advanced Configuration Snippet (Safety Valve)

HDFS (Service-Wide)

HDFS Advanced Configuration Snippet (Safety Valve) for ssl-client.xml

HDFS (Service-Wide)

View as XML

Feedback

Save Changes

HDFS Service Advanced Configuration Snippet (Safety Valve) for ssl-server.xml

HDFS (Service-Wide)

View as XML

HDFS Replication Environment Advanced Configuration Snippet (Safety Valve) for hadoop-env.sh

HDFS (Service-Wide)

HDFS Service Environment Advanced Configuration Snippet (Safety Valve)

HDFS (Service-Wide)

Java Configuration Options for Balancer

Balancer Default Group

Balancer Advanced Configuration Snippet (Safety Valve) for hdfs-site.xml

Balancer Default Group

View as XML

DataNode Volume Choosing Policy
dfs.datanode.fsdataset.volume.choosing.policy

DataNode Default Group

- (•) Round Robin
- ( ) Available Space

Available Space Policy Balanced Threshold
dfs.datanode.available-space-volume-choosing-policy.balanced-space-threshold

DataNode Default Group

10 GiB

Available Space Policy Balanced Preference
dfs.datanode.available-space-volume-choosing-policy.balanced-space-preference-fraction

DataNode Default Group

0.75

Hadoop Metrics2 Advanced Configuration Snippet (Safety Valve)
Edit Individual Values

DataNode Default Group ...and 2 others

Feedback

Save Changes

Java Configuration Options for DataNode

DataNode Default Group

```
-XX:+UseParNewGC -XX:+UseConcMarkSweepGC -
XX:CMSInitiatingOccupancyFraction=70 -
XX:+CMSParallelRemarkEnabled
```

DataNode Advanced Configuration Snippet (Safety Valve) for hdfs-site.xml

DataNode Default Group

View as XML

Automatically Restart Process
Edit Individual Values

- [x] DataNode Default Group ...and 1 other
- [ ] Failover Controller Default Group ...and 4 others

Enable Metric Collection
Edit Individual Values

- [x] DataNode Default Group ...and 6 others

Dump Heap When Out of Memory
Edit Individual Values

- [x] DataNode Default Group ...and 6 others

Heap Dump Directory
oom_heap_dump_dir
Edit Individual Values

DataNode Default Group ...and 6 others

/tmp

Kill When Out of Memory
Edit Individual Values

- [x] DataNode Default Group ...and 6 others

DataNode Environment Advanced Configuration Snippet (Safety Valve)

DataNode Default Group

DataNode Logging Advanced Configuration Snippet (Safety Valve)

DataNode Default Group

HA Health Monitor RPC Timeout
ha.health-monitor.rpc-timeout.ms

Failover Controller Default Group

45 second(s

Java Configuration Options for Failover Controller

Failover Controller Default Group

Feedback

Save Changes

Failover Controller Advanced Configuration Snippet (Safety Valve) for hdfs-site.xml

Failover Controller Default Group

View as XML

Failover Controller Environment Advanced Configuration Snippet (Safety Valve)

Failover Controller Default Group

Failover Controller Logging Advanced Configuration Snippet (Safety Valve)

Failover Controller Default Group

Gateway Logging Advanced Configuration Snippet (Safety Valve)

Gateway Default Group

Use Legacy Blockreader
dfs.client.use.legacy.blockreader

Gateway Default Group

Deploy Directory

Gateway Default Group

/etc/hadoop

Client Java Configuration Options

Gateway Default Group

-Djava.net.preferIPv4Stack=true

HDFS Client Environment Advanced Configuration Snippet (Safety Valve) for hadoop-env.sh

Gateway Default Group

HDFS Client Advanced Configuration Snippet (Safety Valve) for hdfs-site.xml

Gateway Default Group

View as XML

Feedback

Save Changes

Java Configuration Options for HttpFS

HttpFS Default Group

System User

HttpFS Default Group

httpfs

System Group

HttpFS Default Group

httpfs

HttpFS Advanced Configuration Snippet (Safety Valve) for httpfs-site.xml

HttpFS Default Group

View as XML

HttpFS Advanced Configuration Snippet (Safety Valve) for hdfs-site.xml

HttpFS Default Group

View as XML

HttpFS Environment Advanced Configuration Snippet (Safety Valve)

HttpFS Default Group

HttpFS Logging Advanced Configuration Snippet (Safety Valve)

HttpFS Default Group

Java Configuration Options for JournalNode

JournalNode Default Group

JournalNode Advanced Configuration Snippet (Safety Valve) for hdfs-site.xml

JournalNode Default Group

View as XML

JournalNode Environment Advanced Configuration Snippet (Safety Valve)

JournalNode Default Group

Feedback

Save Changes

JournalNode Logging Advanced Configuration Snippet (Safety Valve)

JournalNode Default Group

Java Configuration Options for NFS Gateway

NFS Gateway Default Group

NFS Gateway Advanced Configuration Snippet (Safety Valve) for hdfs-site.xml

NFS Gateway Default Group

View as XML

NFS Gateway Environment Advanced Configuration Snippet (Safety Valve)

NFS Gateway Default Group

NFS Gateway Logging Advanced Configuration Snippet (Safety Valve)

NFS Gateway Default Group

NameNode Nameservice

NameNode Default Group

Mount Points

NameNode Default Group

/

Quorum-based Storage Journal name

NameNode Default Group

Java Configuration Options for NameNode

NameNode Default Group

-XX:+UseParNewGC -XX:+UseConcMarkSweepGC -XX:CMSInitiatingOccupancyFraction=70 -XX:+CMSParallelRemarkEnabled

Enable Automatic Failover
dfs.ha.automatic-failover.enabled

☐ NameNode Default Group

Feedback

Save Changes

NameNode Advanced Configuration Snippet (Safety Valve) for hdfs-site.xml

NameNode Default Group

View as XML

NameNode Advanced Configuration Snippet (Safety Valve) for dfs_hosts_allow.txt

NameNode Default Group

NameNode Advanced Configuration Snippet (Safety Valve) for dfs_hosts_exclude.txt

NameNode Default Group

NameNode Advanced Configuration Snippet (Safety Valve) for dfs_all_hosts.txt

NameNode Default Group

Invalidate Work Percentage Per Iteration
dfs.namenode.invalidate.work.pct.per.iteration

NameNode Default Group

0.32

Replication Work Multiplier Per Iteration
dfs.namenode.replication.work.multiplier.per.iteration

NameNode Default Group

10

Maximum Number of Replication Threads on a DataNode
dfs.namenode.replication.max-streams

NameNode Default Group

20

Hard Limit on the Number of Replication Threads on a Datanode
dfs.namenode.replication.max-streams-hard-limit

NameNode Default Group

40

Avoid Reading Stale DataNode
dfs.namenode.avoid.read.stale.datanode

NameNode Default Group

Avoid Writing Stale DataNode
dfs.namenode.avoid.write.stale.datanode

NameNode Default Group

Stale DataNode Time Interval
dfs.namenode.stale.datanode.interval

NameNode Default Group

30 second(s

Feedback

Save Changes

Write Stale DataNode Ratio
dfs.namenode.write.stale.datanode.ratio

NameNode Default Group
0.5

JournalNode Write Transactions Timeout
dfs.qjournal.write-txns.timeout.ms

NameNode Default Group
20 second(s

JournalNode Start Segment Timeout
dfs.qjournal.start-segment.timeout.ms

NameNode Default Group
20 second(s

JournalNode Prepare Recovery Timeout
dfs.qjournal.prepare-recovery.timeout.ms

NameNode Default Group
2 minute(s

JournalNode Accept Recovery Timeout
dfs.qjournal.accept-recovery.timeout.ms

NameNode Default Group
2 minute(s

JournalNode Finalize Segment Timeout
dfs.qjournal.finalize-segment.timeout.ms

NameNode Default Group
2 minute(s

JournalNode Select Input Streams Timeout
dfs.qjournal.select-input-streams.timeout.ms

NameNode Default Group
20 second(s

JournalNode Get State Timeout
dfs.qjournal.get-journal-state.timeout.ms

NameNode Default Group
2 minute(s

JournalNode New Epoch Timeout
dfs.qjournal.new-epoch.timeout.ms

NameNode Default Group
2 minute(s

NameNode Environment Advanced Configuration Snippet (Safety Valve)

NameNode Default Group

NameNode Logging Advanced Configuration Snippet (Safety Valve)

NameNode Default Group

SecondaryNameNode Nameservice

SecondaryNameNode Default Group

Feedback

Save Changes

Java Configuration Options for Secondary NameNode

SecondaryNameNode Default Group

-XX:+UseParNewGC -XX:+UseConcMarkSweepGC -XX:CMSInitiatingOccupancyFraction=70 -XX:+CMSParallelRemarkEnabled

SecondaryNameNode Advanced Configuration Snippet (Safety Valve) for hdfs-site.xml

SecondaryNameNode Default Group

View as XML

SecondaryNameNode Environment Advanced Configuration Snippet (Safety Valve)

SecondaryNameNode Default Group

SecondaryNameNode Logging Advanced Configuration Snippet (Safety Valve)

SecondaryNameNode Default Group

Filesystem Checkpoint Transaction Threshold
dfs.namenode.checkpoint.txns
Edit Individual Values

NameNode Default Group ...and 1 other

1000000

Filesystem Checkpoint Period
dfs.namenode.checkpoint.period
Edit Individual Values

NameNode Default Group ...and 1 other

1 hour(s)

FailoverProxyProvider Class
dfs.client.failover.proxy.provider

HDFS (Service-Wide)

org.apache.hadoop.hdfs.server.namenode.ha.ConfiguredFailoverProxyI

HDFS High Availability Fencing Methods
dfs.ha.fencing.methods

HDFS (Service-Wide)

shell(true)

Timeout for Cloudera Manager Fencing Strategy
dfs.ha.fencing.cloudera_manager.timeout_millis

HDFS (Service-Wide)

10000

Timeout for SSH Fencing Strategy
dfs.ha.fencing.ssh.connect-timeout

HDFS (Service-Wide)

30 second(s

Private Keys for SSH Fencing Strategy
dfs.ha.fencing.ssh.private-key-files

HDFS (Service-Wide)

Feedback

Save Changes

DataNode Log Directory
hadoop.log.dir

DataNode Default Group
/var/log/hadoop-hdfs

DataNode Logging Threshold

DataNode Default Group
INFO

DataNode Max Log Size

DataNode Default Group
200 MiB

DataNode Maximum Log File Backups

DataNode Default Group
10

Failover Controller Log Directory

Failover Controller Default Group
/var/log/hadoop-hdfs

Failover Controller Logging Threshold

Failover Controller Default Group
INFO

Failover Controller Max Log Size

Failover Controller Default Group
200 MiB

Failover Controller Maximum Log File Backups

Failover Controller Default Group
10

Gateway Logging Threshold

Gateway Default Group
INFO

HttpFS Log Directory
hadoop.log.dir

HttpFS Default Group
/var/log/hadoop-httpfs

HttpFS Logging Threshold

HttpFS Default Group
INFO

HttpFS Max Log Size

HttpFS Default Group
200 MiB

HttpFS Maximum Log File Backups

HttpFS Default Group
10

JournalNode Log Directory

JournalNode Default Group
/var/log/hadoop-hdfs

JournalNode Logging Threshold

JournalNode Default Group
INFO

Save Changes

Feedback

JournalNode Max Log Size
JournalNode Default Group
200 MiB

JournalNode Maximum Log File Backups
JournalNode Default Group
10

NFS Gateway Log Directory
hadoop.log.dir
NFS Gateway Default Group
/var/log/hadoop-hdfs

NFS Gateway Logging Threshold
NFS Gateway Default Group
INFO

NFS Gateway Max Log Size
NFS Gateway Default Group
200 MiB

NFS Gateway Maximum Log File Backups
NFS Gateway Default Group
10

NameNode Log Directory
hadoop.log.dir
NameNode Default Group
/var/log/hadoop-hdfs

NameNode Block State Change Logging Threshold
log4j.logger.BlockStateChange
NameNode Default Group
INFO

NameNode Logging Threshold
NameNode Default Group
INFO

NameNode Max Log Size
NameNode Default Group
200 MiB

NameNode Maximum Log File Backups
NameNode Default Group
10

SecondaryNameNode Log Directory
hadoop.log.dir
SecondaryNameNode Default Group
/var/log/hadoop-hdfs

SecondaryNameNode Logging Threshold
SecondaryNameNode Default Group
INFO

SecondaryNameNode Max Log Size
SecondaryNameNode Default Group
200 MiB

Feedback

Save Changes

SecondaryNameNode Maximum Log File Backups
SecondaryNameNode Default Group
10

Enable Log Event Capture
☑ HDFS (Service-Wide)

Log Event Retry Frequency
HDFS (Service-Wide)
30

Active NameNode Role Health Check
☑ HDFS (Service-Wide)

Standby NameNode Health Check
☑ HDFS (Service-Wide)

Active NameNode Detection Window
HDFS (Service-Wide)
3 minute(s

NameNode Activation Startup Tolerance
HDFS (Service-Wide)
3 minute(s

HDFS Canary Health Check
☑ HDFS (Service-Wide)

Blocks With Corrupt Replicas Monitoring Thresholds
HDFS (Service-Wide)
Warning Specify 0.5
Critical Specify 1.0

Missing Block Monitoring Thresholds
HDFS (Service-Wide)
Warning Never
Critical Any

Under-replicated Block Monitoring Thresholds
HDFS (Service-Wide)
Warning Specify 10.0
Critical Specify 40.0

HDFS Free Space Monitoring Thresholds
HDFS (Service-Wide)
Warning Specify 20.0
Critical Specify 10.0

HDFS Health Canary Directory
HDFS (Service-Wide)
/tmp/.cloudera_health_monitoring_canary_files

HDFS Health Canary Directory Permissions
HDFS (Service-Wide)
-rwxrwxrwx

Feedback

Save Changes

Enable Configuration Change Alerts
Edit Individual Values

☐ HDFS (Service-Wide) ...and 9 others

Enable Service Level Health Alerts

☑ HDFS (Service-Wide)

Service Triggers

HDFS (Service-Wide)

```
[]
```

Service Monitor Client Config Overrides

HDFS (Service-Wide)

View as XML

Name	dfs.socket.timeout
Value	3000
Description	Description
	☐ Final
Name	dfs.datanode.socket.write.timeout
Value	3000
Description	Description
	☐ Final
Name	ipc.client.connect.max.retries
Value	1
Description	Description
	☐ Final
Name	fs.permissions.umask-mode
Value	000
Description	Description
	☐ Final

Service Monitor Derived Configs Advanced Configuration Snippet (Safety Valve)

HDFS (Service-Wide)

View as XML

Healthy DataNode Monitoring Thresholds

HDFS (Service-Wide)

Warning	Specify	95.0
Critical	Specify	90.0

Failover Controllers Healthy

☑ HDFS (Service-Wide)

Rules to Extract Events from Log Files

Balancer Default Group

Save Changes

View as JSON

Feedback

Edit Individual Values

Alert: false Rate: 1 Period: 1 Threshold: FATAL

Alert: false Rate: 0 Threshold: WARN Content: .* is deprecated. Instead, use .*

Alert: false Rate: 0 Threshold: WARN Content: .* is deprecated. Use .* instead

Alert: false Rate: 0 Exception Type: java.io.IOException

Alert: false Rate: 0 Exception Type: java.net.SocketException

Alert: false Rate: 0 Exception Type: java.net.SocketClosedException

Alert: false Rate: 0 Exception Type: java.io.EOFException

Alert: false Rate: 0 Exception Type: java.nio.channels.CancelledKeyException

Alert: false Rate: 1 Period: 2 Exception Type: .*

Alert: false Rate: 0 Threshold: WARN Content: Unknown job [^]+ being deleted.*

Alert: false Rate: 0 Threshold: WARN Content: Error executing shell command .+ No such process.+

Alert: false Rate: 0 Threshold: WARN Content: .*attempt to override final parameter.+

Alert: false Rate: 0 Threshold: WARN Content: [^]+ is a deprecated filesystem name. Use.*

Alert: false Rate: 1 Period: 1 Threshold: WARN

DataNode Default Group

View as JSON

Alert: false Rate: 1 Period: 1 Threshold: FATAL

Alert: false Rate: 0 Threshold: WARN Content: .* is deprecated. Instead, use .*

Alert: false Rate: 0 Threshold: WARN Content: .* is deprecated. Use .* instead

Alert: false Rate: 0 Exception Type: java.io.IOException

Alert: false Rate: 0 Exception Type: java.net.SocketException

Alert: false Rate: 0 Exception Type: java.net.SocketClosedException

Alert: false Rate: 0 Exception Type: java.io.EOFException

Alert: false Rate: 0 Exception Type: java.nio.channels.CancelledKeyException

Alert: false Rate: 1 Period: 5 Content: Datanode registration failed

Alert: false Rate: 1 Period: 2 Exception Type: .*

Alert: false Rate: 0 Threshold: WARN Content: Got a command from standby NN - ignoring command:.*

Alert: false Rate: 0 Threshold: WARN Content: Unknown job [^]+ being deleted.*

Alert: false Rate: 0 Threshold: WARN Content: Error executing shell command .+ No such process.+

Alert: false Rate: 0 Threshold: WARN Content: .*attempt to override final parameter.+

Alert: false Rate: 0 Threshold: WARN Content: [^]+ is a deprecated filesystem name. Use.*

Alert: false Rate: 1 Period: 1 Threshold: WARN

Failover Controller Default Group ...and 2 others

View as JSON

Alert: false Rate: 1 Period: 1 Threshold: FATAL

Alert: false Rate: 1 Period: 2 Exception Type: .*

Alert: false Rate: 1 Period: 1 Threshold: WARN

NameNode Default Group ...and 1 other

View as JSON

Alert: false Rate: 1 Period: 1 Threshold: FATAL

Alert: false Rate: 0 Threshold: WARN Content: .* is deprecated. Instead, use .*

Save Changes

Feedback

Alert: false Rate: 0 Threshold: WARN Content: .* is deprecated. Use .* instead

Alert: false Rate: 0 Exception Type: java.io.IOException

Alert: false Rate: 0 Exception Type: java.net.SocketException

Alert: false Rate: 0 Exception Type: java.net.SocketClosedException

Alert: false Rate: 0 Exception Type: java.io.EOFException

Alert: false Rate: 0 Exception Type: java.nio.channels.CancelledKeyException

Alert: false Rate: 1 Period: 2 Exception Type: .*

Alert: false Rate: 0 Threshold: WARN Content: Unknown job [^]+ being deleted.*

Alert: false Rate: 0 Threshold: WARN Content: Error executing shell command .+ No such process.+

Alert: false Rate: 0 Threshold: WARN Content: .*attempt to override final parameter.+

Alert: false Rate: 0 Threshold: WARN Content: [^]+ is a deprecated filesystem name. Use.*

Alert: false Rate: 1 Period: 1 Threshold: WARN

Alert: false Rate: 1 Threshold: INFO Content: Triggering checkpoint.*

DataNode Free Space Monitoring Thresholds

DataNode Default Group

Warning Specify 20.0

Critical Specify 10.0

DataNode Transceivers Usage Thresholds

DataNode Default Group

Warning Specify 75.0

Critical Specify 95.0

DataNode Connectivity Health Test

☑ DataNode Default Group

DataNode Connectivity Tolerance at Startup

DataNode Default Group

3 minute(s

DataNode Volume Failures Thresholds

DataNode Default Group

Warning Never

Critical Any

DataNode Block Count Thresholds

DataNode Default Group

Warning Specify 500000.0

Critical Never

Enable Health Alerts for this Role

Edit Individual Values

☐ DataNode Default Group

☑ Failover Controller Default Group ...and 5 others

Feedback

Save Changes

File Descriptor Monitoring Thresholds
DataNode Default Group
Warning Specify 50.0
Critical Specify 70.0

DataNode Process Health Test
☑ DataNode Default Group

DataNode Host Health Test
☑ DataNode Default Group

Log Directory Free Space Monitoring Absolute Thresholds
Edit Individual Values
DataNode Default Group ...and 6 others
Warning Specify 10 GiB
Critical Specify 5 GiB

Log Directory Free Space Monitoring Percentage Thresholds
Edit Individual Values
DataNode Default Group ...and 6 others
Warning Never
Critical Never

Heap Dump Directory Free Space Monitoring Absolute Thresholds
Edit Individual Values
DataNode Default Group ...and 6 others
Warning Specify 10 GiB
Critical Specify 5 GiB

Heap Dump Directory Free Space Monitoring Percentage Thresholds
Edit Individual Values
DataNode Default Group ...and 6 others
Warning Never
Critical Never

Unexpected Exits Thresholds
Edit Individual Values
DataNode Default Group ...and 6 others
Warning Never
Critical Any

Unexpected Exits Monitoring Period
Edit Individual Values
DataNode Default Group ...and 6 others
5 minute(s

Role Triggers
Edit Individual Values
DataNode Default Group ...and 6 others
[]

Process Swap Memory Thresholds
Edit Individual Values
DataNode Default Group ...and 6 others
Warning Any
Critical Never

Web Metric Collection
☑ DataNode Default Group

Save Changes

Feedback

Web Metric Collection Duration

DataNode Default Group

Warning Specify ▾ 10 second(s ▾

Critical Never ▾

Pause Duration Thresholds

DataNode Default Group

Warning Specify ▾ 30.0

Critical Specify ▾ 60.0

Pause Duration Monitoring Period

DataNode Default Group

5 minute(s ▾

DataNode Data Directory Free Space Monitoring Absolute Thresholds

DataNode Default Group

Warning Specify ▾ 10 GiB ▾

Critical Specify ▾ 5 GiB ▾

DataNode Data Directory Free Space Monitoring Percentage Thresholds

DataNode Default Group

Warning Never ▾

Critical Never ▾

File Descriptor Monitoring Thresholds

Failover Controller Default Group

Warning Specify ▾ 50.0

Critical Specify ▾ 70.0

Failover Controller Process Health Test

☑ Failover Controller Default Group

Failover Controller Host Health Test

☑ Failover Controller Default Group

File Descriptor Monitoring Thresholds

HttpFS Default Group

Warning Specify ▾ 50.0

Critical Specify ▾ 70.0

HttpFS Process Health Test

☑ HttpFS Default Group

HttpFS Host Health Test

☑ HttpFS Default Group

JournalNode Fsync Latency Thresholds

JournalNode Default Group

Warning Specify ▾ 1 second(s ▾

Critical Specify ▾ 3 second(s ▾

Active NameNode Sync Status Health Check

☑ JournalNode Default Group

Feedback

Save Changes

Active NameNode Sync Status Startup Tolerance
JournalNode Default Group
3 minute(s

File Descriptor Monitoring Thresholds
JournalNode Default Group
Warning Specify 50.0
Critical Specify 70.0

JournalNode Process Health Test
☑ JournalNode Default Group

JournalNode Host Health Test
☑ JournalNode Default Group

Web Metric Collection
☑ JournalNode Default Group

Web Metric Collection Duration
JournalNode Default Group
Warning Specify 10 second(s
Critical Never

Garbage Collection Duration Thresholds
JournalNode Default Group
Warning Specify 30.0
Critical Specify 60.0

Garbage Collection Duration Monitoring Period
JournalNode Default Group
5 minute(s

JournalNode Edits Directory Free Space Monitoring Absolute Thresholds
JournalNode Default Group
Warning Specify 10 GiB
Critical Specify 5 GiB

JournalNode Edits Directory Free Space Monitoring Percentage Thresholds
JournalNode Default Group
Warning Never
Critical Never

File Descriptor Monitoring Thresholds
NFS Gateway Default Group
Warning Specify 50.0
Critical Specify 70.0

NFS Gateway Process Health Test
☑ NFS Gateway Default Group

NFS Gateway Host Health Test
☑ NFS Gateway Default Group

Feedback

Save Changes

Temporary Dump Directory Free Space Monitoring Absolute Thresholds

NFS Gateway Default Group

Warning Specify ▾ 10 GiB ▾

Critical Specify ▾ 5 GiB ▾

Temporary Dump Directory Free Space Monitoring Percentage Thresholds

NFS Gateway Default Group

Warning Never ▾

Critical Never ▾

Filesystem Checkpoint Age Monitoring Thresholds

NameNode Default Group

Warning Specify ▾ 200.0

Critical Specify ▾ 400.0

Filesystem Checkpoint Transactions Monitoring Thresholds

NameNode Default Group

Warning Specify ▾ 200.0

Critical Specify ▾ 400.0

NameNode RPC Latency Thresholds

NameNode Default Group

Warning Specify ▾ 1 second(s ▾

Critical Specify ▾ 5 second(s ▾

NameNode RPC Latency Monitoring Window

NameNode Default Group

5 minute(s ▾

NameNode Directory Failures Thresholds

NameNode Default Group

Warning Never ▾

Critical Any ▾

NameNode Safemode Health Test

☑ NameNode Default Group

HDFS Metadata Upgrade Status Health Test

☑ NameNode Default Group

HDFS Rolling Metadata Upgrade Status Health Test

☑ NameNode Default Group

Health Test Startup Tolerance

NameNode Default Group

5 minute(s ▾

NameNode Out-Of-Sync JournalNodes Thresholds

NameNode Default Group

Warning Never ▾

Critical Any ▾

Feedback

Save Changes

File Descriptor Monitoring Thresholds
NameNode Default Group
Warning Specify ▾ 50.0
Critical Specify ▾ 70.0

NameNode Process Health Test
☑ NameNode Default Group

NameNode Host Health Test
☑ NameNode Default Group

Web Metric Collection
☑ NameNode Default Group

Web Metric Collection Duration
NameNode Default Group
Warning Specify ▾ 10 second(s ▾
Critical Never ▾

Pause Duration Thresholds
NameNode Default Group
Warning Specify ▾ 30.0
Critical Specify ▾ 60.0

Pause Duration Monitoring Period
NameNode Default Group
5 minute(s ▾

NameNode Data Directories Free Space Monitoring Absolute Thresholds
NameNode Default Group
Warning Specify ▾ 10 GiB ▾
Critical Specify ▾ 5 GiB ▾

NameNode Data Directories Free Space Monitoring Percentage Thresholds
NameNode Default Group
Warning Never ▾
Critical Never ▾

File Descriptor Monitoring Thresholds
SecondaryNameNode Default Group
Warning Specify ▾ 50.0
Critical Specify ▾ 70.0

SecondaryNameNode Process Health Test
☑ SecondaryNameNode Default Group

SecondaryNameNode Host Health Test
☑ SecondaryNameNode Default Group

Web Metric Collection
☑ SecondaryNameNode Default Group

Feedback

Save Changes

Web Metric Collection Duration

SecondaryNameNode Default Group

Warning Specify ▾ 10 second(s ▾

Critical Never ▾

Garbage Collection Duration Thresholds

SecondaryNameNode Default Group

Warning Specify ▾ 30.0

Critical Specify ▾ 60.0

Garbage Collection Duration Monitoring Period

SecondaryNameNode Default Group

5 minute(s ▾

HDFS Checkpoint Directories Free Space Monitoring Absolute Thresholds

SecondaryNameNode Default Group

Warning Specify ▾ 10 GiB ▾

Critical Specify ▾ 5 GiB ▾

HDFS Checkpoint Directories Free Space Monitoring Percentage Thresholds

SecondaryNameNode Default Group

Warning Never ▾

Critical Never ▾

FsImage Transfer Timeout
dfs.image.transfer.timeout

HDFS (Service-Wide)

1 minute(s ▾

FsImage Transfer Bandwidth
dfs.image.transfer.bandwidthPerSec

HDFS (Service-Wide)

0 GiB ▾

DataNode Local Path Access Users
dfs.block.local-path-access.user

HDFS (Service-Wide)

Enable HDFS Short-Circuit Read
dfs.client.read.shortcircuit

☑ HDFS (Service-Wide)

UNIX Domain Socket path
dfs.domain.socket.path

HDFS (Service-Wide)

/var/run/hdfs-sockets/dn

HDFS File Block Storage Location Timeout
dfs.client.file-block-storage-locations.timeout, dfs.client.file-block-storage-locations.timeout.millis

HDFS (Service-Wide)

10 second(s ▾

Handler Count
dfs.datanode.handler.count

DataNode Default Group

3

Feedback

Save Changes

Maximum Number of Transfer Threads
dfs.datanode.max.xcievers, dfs.datanode.max.transfer.threads

DataNode Default Group
4096

DataNode Balancing Bandwidth
dfs.balance.bandwidthPerSec, dfs.datanode.balance.bandwidthPerSec

DataNode Default Group
10 MiB

HDFS Thrift Server Max Threadcount
dfs.thrift.threads.max
Edit Individual Values

DataNode Default Group ...and 1 other
20

HDFS Thrift Server Min Threadcount
dfs.thrift.threads.min
Edit Individual Values

DataNode Default Group ...and 1 other
10

HDFS Thrift Server Timeout
dfs.thrift.timeout
Edit Individual Values

DataNode Default Group ...and 1 other
60

Enable purging cache after writes
dfs.datanode.drop.cache.behind.writes

☐ DataNode Default Group

Enable purging cache after reads
dfs.datanode.drop.cache.behind.reads

☐ DataNode Default Group

Enable immediate enqueuing of data to disk after writes
dfs.datanode.sync.behind.writes

☐ DataNode Default Group

Number of read ahead bytes
dfs.datanode.readahead.bytes

DataNode Default Group
4 MiB

Maximum Process File Descriptors
Edit Individual Values

DataNode Default Group ...and 6 others

Enable HDFS Short-Circuit Read
dfs.client.read.shortcircuit

☐ Gateway Default Group

NameNode Handler Count
dfs.namenode.handler.count

NameNode Default Group
30

NameNode Service Handler Count
dfs.namenode.service.handler.count

NameNode Default Group
30

Feedback

Save Changes

DateNode Plugins
dfs.datanode.plugins

DataNode Default Group

NameNode Plugins
dfs.namenode.plugins

NameNode Default Group

Use DataNode Hostname
dfs.client.use.datanode.hostname

☐ HDFS (Service-Wide)

Bind DataNode to Wildcard Address

☐ DataNode Default Group

Use DataNode Hostname
dfs.datanode.use.datanode.hostname

☐ DataNode Default Group

DataNode Protocol Port
dfs.datanode.ipc.address

DataNode Default Group
50020

DataNode Transceiver Port
dfs.datanode.address

DataNode Default Group
50010

DataNode HTTP Web UI Port
dfs.datanode.http.address

DataNode Default Group
50075

Secure DataNode Web UI Port (TLS/SSL)
dfs.datanode.https.address

DataNode Default Group
50475

REST Port
hdfs.httpfs.http.port

HttpFS Default Group
14000

Administration Port
hdfs.httpfs.admin.port

HttpFS Default Group
14001

JournalNode RPC Port
dfs.journalnode.rpc-address

JournalNode Default Group
8485

JournalNode HTTP Port
dfs.journalnode.http-address

JournalNode Default Group
8480

Secure JournalNode Web UI Port (TLS/SSL)
dfs.journalnode.https-address

JournalNode Default Group
8481

Bind JournalNode to Wildcard Address

☐ JournalNode Default Group

Feedback

Save Changes

NFS Gateway Server Port
nfs3.server.port

NFS Gateway Default Group
2049

NFS Gateway MountD Port
nfs3.mountd.port

NFS Gateway Default Group
4242

Portmap (or Rpcbind) Port

NFS Gateway Default Group
111

NFS Gateway Web UI Port
nfs.http.port

NFS Gateway Default Group
50079

Secure NFS Gateway Web UI Port (TLS/SSL)
nfs.https.port

NFS Gateway Default Group
50579

NameNode Port
fs.default.name,
fs.defaultFS

NameNode Default Group
8020

NameNode Service RPC Port
dfs.namenode.servicerpc-address

NameNode Default Group
8022

Bind NameNode to Wildcard Address

☐ NameNode Default Group

NameNode Web UI Port
dfs.http.address,
dfs.namenode.http-address

NameNode Default Group
50070

Secure NameNode Web UI Port (TLS/SSL)
dfs.https.port

NameNode Default Group
50470

SecondaryNameNode Web UI Port
dfs.secondary.http.address,
dfs.namenode.secondary.http-address

SecondaryNameNode Default Group
50090

Secure SecondaryNameNode Web UI Port (TLS/SSL)
dfs.secondary.https.port

SecondaryNameNode Default Group
50495

Bind SecondaryNameNode to Wildcard Address

☐ SecondaryNameNode Default Group

Oozie Proxy User Hosts
hadoop.proxyuser.oozie.hosts

HDFS (Service-Wide)
*

Feedback

Save Changes

Oozie Proxy User Groups
hadoop.proxyuser.oozie.groups
HDFS (Service-Wide)
*

Flume Proxy User Hosts
hadoop.proxyuser.flume.hosts
HDFS (Service-Wide)
*

Flume Proxy User Groups
hadoop.proxyuser.flume.groups
HDFS (Service-Wide)
*

HTTP Proxy User Groups
hadoop.proxyuser.HTTP.groups
HDFS (Service-Wide)
*

HTTP Proxy User Hosts
hadoop.proxyuser.HTTP.hosts
HDFS (Service-Wide)
*

HDFS Proxy User Groups
hadoop.proxyuser.hdfs.groups
HDFS (Service-Wide)
*

HDFS Proxy User Hosts
hadoop.proxyuser.hdfs.hosts
HDFS (Service-Wide)
*

Hive Proxy User Hosts
hadoop.proxyuser.hive.hosts
HDFS (Service-Wide)
*

Hive Proxy User Groups
hadoop.proxyuser.hive.groups
HDFS (Service-Wide)
*

Hue Proxy User Hosts
hadoop.proxyuser.hue.hosts
HDFS (Service-Wide)
*

Hue Proxy User Groups
hadoop.proxyuser.hue.groups
HDFS (Service-Wide)
*

HttpFS Proxy User Hosts
hadoop.proxyuser.httpfs.hosts
HDFS (Service-Wide)
*

HttpFS Proxy User Groups
hadoop.proxyuser.httpfs.groups
HDFS (Service-Wide)
*

Feedback

Save Changes

Mapred Proxy User Hosts
hadoop.proxyuser.mapred.hosts

HDFS (Service-Wide)
*

Mapred Proxy User Groups
hadoop.proxyuser.mapred.groups

HDFS (Service-Wide)
*

YARN Proxy User Hosts
hadoop.proxyuser.yarn.hosts

HDFS (Service-Wide)
*

YARN Proxy User Groups
hadoop.proxyuser.yarn.groups

HDFS (Service-Wide)
*

Service Monitor Proxy User Hosts
hadoop.proxyuser.smon.hosts

HDFS (Service-Wide)
*

Service Monitor Proxy User Groups
hadoop.proxyuser.smon.groups

HDFS (Service-Wide)
*

Replication Factor
dfs.replication

HDFS (Service-Wide)
3

Minimal Block Replication
dfs.replication.min, dfs.namenode.replication.min

HDFS (Service-Wide)
1

Maximal Block Replication
dfs.replication.max

HDFS (Service-Wide)
512

Maintenance State Minimal Block Replication
dfs.namenode.maintenance.replication.min

HDFS (Service-Wide)
1

Safemode Threshold Percentage
dfs.safemode.threshold.pct, dfs.namenode.safemode.threshold-pct

NameNode Default Group
0.999

Java Heap Size of Balancer in Bytes

Balancer Default Group
1 GiB

Java Heap Size of DataNode in Bytes

DataNode Default Group
1 GiB

Feedback

Save Changes

Maximum Memory Used for Caching
dfs.datanode.max.locked.memory

DataNode Default Group
4 GiB

Cgroup CPU Shares
cpu.shares
Edit Individual Values

DataNode Default Group ...and 6 others
1024

Cgroup I/O Weight
blkio.weight
Edit Individual Values

DataNode Default Group ...and 6 others
500

Cgroup Memory Soft Limit
memory.soft_limit_in_bytes
Edit Individual Values

DataNode Default Group ...and 6 others
-1 MiB

Cgroup Memory Hard Limit
memory.limit_in_bytes
Edit Individual Values

DataNode Default Group ...and 6 others
-1 MiB

Java Heap Size of Failover Controller in Bytes

Failover Controller Default Group
256 MiB

Client Java Heap Size in Bytes

Gateway Default Group
256 MiB

Java Heap Size of HttpFS in Bytes

HttpFS Default Group
256 MiB

Java Heap Size of JournalNode in Bytes

JournalNode Default Group
512 MiB

Java Heap Size of NFS Gateway in Bytes

NFS Gateway Default Group
256 MiB

Java Heap Size of NameNode in Bytes

NameNode Default Group
4 GiB

Java Heap Size of Secondary NameNode in Bytes

SecondaryNameNode Default Group
4 GiB

Superuser Group
dfs.permissions.supergroup, dfs.permissions.superuser group

HDFS (Service-Wide)
supergroup

Kerberos Principal

HDFS (Service-Wide)
hdfs

Feedback

Save Changes

HDFS User to Impersonate

HDFS (Service-Wide)

Hue's Kerberos Principal Short Name
hue.kerberos.principal.shortname

HDFS (Service-Wide)

DataNode Data Transfer Protection
dfs.data.transfer.protection

HDFS (Service-Wide)

- Authentication
- Integrity
- Privacy

Hadoop User Group Mapping Implementation
hadoop.security.group.mapping

HDFS (Service-Wide)

- org.apache.hadoop.security.JniBasedUnixGroupsMapping
- (•) org.apache.hadoop.security.ShellBasedUnixGroupsMapping
- org.apache.hadoop.security.LdapGroupsMapping

Hadoop User Group Mapping LDAP URL
hadoop.security.group.mapping.ldap.url

HDFS (Service-Wide)

Hadoop User Group Mapping LDAP TLS/SSL Enabled
hadoop.security.group.mapping.ldap.use.ssl

☐ HDFS (Service-Wide)

Hadoop User Group Mapping LDAP TLS/SSL Truststore
hadoop.security.group.mapping.ldap.ssl.keystore

HDFS (Service-Wide)

Hadoop User Group Mapping LDAP TLS/SSL Truststore Password
hadoop.security.group.mapping.ldap.ssl.keystore.password

HDFS (Service-Wide)

Hadoop User Group Mapping LDAP Bind User Distinguished Name
hadoop.security.group.mapping.ldap.bind.user

HDFS (Service-Wide)

Hadoop User Group Mapping LDAP Bind User Password
hadoop.security.group.mapping.ldap.bind.password

HDFS (Service-Wide)

Hadoop User Group Mapping Search Base
hadoop.security.group.mapping.ldap.base

HDFS (Service-Wide)

Feedback

Save Changes

Hadoop User Group Mapping LDAP User Search Filter
hadoop.security.group.mapping.ldap.search.filter.user

HDFS (Service-Wide)

(&(objectClass=user)(sAMAccountName={0}))

Hadoop User Group Mapping LDAP Group Search Filter
hadoop.security.group.mapping.ldap.search.filter.group

HDFS (Service-Wide)

(objectClass=group)

Hadoop User Group Mapping LDAP Group Membership Attribute
hadoop.security.group.mapping.ldap.search.attr.member

HDFS (Service-Wide)

member

Hadoop User Group Mapping LDAP Group Name Attribute
hadoop.security.group.mapping.ldap.search.attr.group.name

HDFS (Service-Wide)

cn

Hadoop Secure Authentication
hadoop.security.authentication

HDFS (Service-Wide)

- (•) simple
- ( ) kerberos

Hadoop Secure Authorization
hadoop.security.authorization

[ ] HDFS (Service-Wide)

Authorized Users

HDFS (Service-Wide)

*

Authorized Groups

HDFS (Service-Wide)

Authorized Admin Users

HDFS (Service-Wide)

*

Authorized Admin Groups

HDFS (Service-Wide)

Enable Access Control Lists
dfs.namenode.acls.enabled

[ ] HDFS (Service-Wide)

Enable Sentry Synchronization

[ ] HDFS (Service-Wide)

Feedback

Save Changes

Sentry Synchronization Path Prefixes
sentry.hdfs.integration.path.prefixes

HDFS (Service-Wide)

/user/hive/warehouse

Sentry Authorization Provider Group
sentry.authorization-provider.hdfs-group

HDFS (Service-Wide)

hive

Hadoop RPC Protection
hadoop.rpc.protection

HDFS (Service-Wide)

- (•) authentication
- ( ) integrity
- ( ) privacy

Enable Data Transfer Encryption
dfs.encrypt.data.transfer

[ ] HDFS (Service-Wide)

Data Transfer Encryption Algorithm
dfs.encrypt.data.transfer.algorithm

HDFS (Service-Wide)

- ( ) 3des
- (•) rc4
- ( ) AES/CTR/NoPadding

Data Transfer Cipher Suite Key Strength
dfs.encrypt.data.transfer.cipher.key.bitlength

HDFS (Service-Wide)

- ( ) 128
- ( ) 192
- (•) 256

Enable Kerberos Authentication for HTTP Web-Consoles

[ ] HDFS (Service-Wide)

Hadoop HTTP Authentication Cookie Domain

HDFS (Service-Wide)

Trusted Kerberos Realms

HDFS (Service-Wide)

Additional Rules to Map Kerberos Principals to Short Names

HDFS (Service-Wide)

Hadoop TLS/SSL Enabled
hadoop.ssl.enabled

[ ] HDFS (Service-Wide)

Hadoop TLS/SSL Server Keystore File Location
ssl.server.keystore.location

HDFS (Service-Wide)

Feedback

Save Changes

Hadoop TLS/SSL Server Keystore File Password
ssl.server.keystore.password

HDFS (Service-Wide)

Hadoop TLS/SSL Server Keystore Key Password
ssl.server.keystore.keypassword

HDFS (Service-Wide)

Cluster-Wide Default TLS/SSL Client Truststore Location
ssl.client.truststore.location

HDFS (Service-Wide)

Cluster-Wide Default TLS/SSL Client Truststore Password
ssl.client.truststore.password

HDFS (Service-Wide)

Enable Log and Query Redaction
redaction_policy_enabled

☐ HDFS (Service-Wide)

Log and Query Redaction Policy
redaction_policy

HDFS (Service-Wide)

View as JSON

No rules created

Test Redaction Rules

Input text to be redacted here

Test Redaction

DataNode Data Directory Permissions
dfs.datanode.data.dir.perm

DataNode Default Group

755

Signature Secret
hdfs.httpfs.signature.secret

HttpFS Default Group

••••••

Enable TLS/SSL for HttpFS

☐ HttpFS Default Group

HttpFS TLS/SSL Server JKS Keystore File Location

HttpFS Default Group

HttpFS TLS/SSL Server JKS Keystore File Password

HttpFS Default Group

HttpFS TLS/SSL Certificate Trust Store File

HttpFS Default Group

Feedback

Save Changes

HttpFS TLS/SSL Certificate Trust Store Password

HttpFS Default Group

Role-Specific Kerberos Principal

HttpFS Default Group

httpfs

Stacks Collection Enabled
stacks_collection_enabled
Edit Individual Values

DataNode Default Group ...and 6 others

Stacks Collection Directory
stacks_collection_directory
Edit Individual Values

DataNode Default Group ...and 6 others

Stacks Collection Frequency
stacks_collection_frequency
Edit Individual Values

DataNode Default Group ...and 6 others

5 second(s

Stacks Collection Data Retention
stacks_collection_data_retention
Edit Individual Values

DataNode Default Group ...and 6 others

100 MiB

Stacks Collection Method
stacks_collection_method
Edit Individual Values

DataNode Default Group ...and 6 others

- (•) jstack
- ( ) servlet

Display All **Per Page**

Feedback

Save Changes