

123456

power

File: power.kicad_sch

audio-codec

File: audio-codec.kicad_sch

usb

File: usb.kicad_sch

coreboard

File: coreboard.kicad_sch

audio-inputs

File: audio-inputs.kicad_sch

midi

File: midi.kicad_sch

mechanics

File: mechanics.kicad_sch

audio-outputs

File: audio-outputs.kicad_sch

control-chain

File: control-chain.kicad_sch

headphone

File: Headphone.kicad_sch

Notes

- All resistors named as RA* must have 1% tolerance

- All non-polarized capacitors named as CA* must use NP0 Temp. Coef.

- All other non-polarized capacitors should use X7R Temp. Coef.

- Decoupling caps must be placed as close as possible of the IC power pins

USB outp Power: 500mA

Inp Power: 12V 500mA

<https://github.com/moddevices/hw-mod-dwarf>

Dwarf Audio processing board

MOD Devices GmbH

Sheet: /

File: bottom-board.kicad_sch

Title: MOD Dwarf – Main Board

Size: A4


Date: 2021-09-06

Rev: 3.0



KiCad E.D.A. kicad 6.0.4-6f826c9f35-116-ubuntu20.04.1

Id: 1/11

123456




Use ferrite beads for EMI suppression and improved power supply decoupling



SPDIF is connected to always mirror the main outputs

Codec MCLK



The 0ohm resistor at I2S_MCLK must only be placed when the xtal is not placed, and vice versa.

USB outp Power: 500mA
Inp Power: 12V 500mA
<https://github.com/moddevices/hw-mod-dwarf>
Dwarf Audio processing board


MOD Devices GmbH

Sheet: /audio-codec/
File: audio-codec.kicad_sch

Title: MOD Dwarf – Main Board

Size: A4 Date: 2021-09-06
KiCad E.D.A. kicad 6.0.4-6f826c9f35-116-ubuntu20.04.1

Rev: 3.0
Id: 2/11



GC2, GC1: GAIN (dB)


1, 1	0.0
1, 0	6.0
0, 1	15.0
0, 0	20.4

The gain calculation includes the R_{DSon} value

J110: $R_{DSon} = 18R$

The CODEC only presents optimal dynamic range and THD+N for PGA setting: $-12dB$ to $+6dB$.

best achievable noise will be $-94dB$ since this is the Johnson noise with an impedance of $1M\Omega$



<https://github.com/moddevices/hw-mod-dwarf>

Dwarf Audio processing board

MOD Devices GmbH

Sheet: /audio-inputs/

File: audio-inputs.kicad_sch


Title: MOD Dwarf - Main Board


Size: A4 Date: 2021-09-06

KiCad E.D.A. kicad 6.0.4-6f826c9f35-116-ubuntu20.04.1


Rev: 3.0

Id: 3/11









This port is NOT used for ethernet, but for a serial protocol that includes power over the RJ-45 connector




USB outp Power: 500mA		
Inp Power: 12V 500mA		
https://github.com/moddevices/hw-mod-dwarf		
Dwarf Audio processing board		
MOD Devices GmbH		
Sheet: /control-chain/		
File: control-chain.kicad_sch		
Title: MOD Dwarf – Main Board		
Size: A4	Date: 2021-09-06	Rev: 3.0
KiCad E.D.A. kicad 6.0.4-6f826c9f35-116-ubuntu20.04.1		Id: 5/11



Size: A3	Date: 2021-09-06
KiCad E.D.A. kicad 6.0.4-6f826c9f35~116-ubuntu20.04.1	


Minimal load of 16 ohm with 0.1% THD+N
Max power 105mW





MOD Devices GmbH



Title: MOD Dwarf – Main Board

Rev: 3.0
Id: 7/11





USB outp Power: 500mA		
Inp Power: 12V 500mA		
https://github.com/moddevices/hw-mod-dwarf		
Dwarf Audio processing board		
MOD Devices GmbH		
Sheet: /midi/		
File: midi.kicad_sch		
Title: MOD Dwarf – Main Board		
Size: A4	Date: 2021-09-06	Rev: 3.0
KiCad E.D.A. kicad 6.0.4-6f826c9f35-116-ubuntu20.04.1		Id: 9/11



USB outp Power: 500mA		
Inp Power: 12V 500mA		
https://github.com/moddevices/hw-mod-dwarf		
Dwarf Audio processing board		
MOD Devices GmbH		
Sheet: /usb/		
File: usb.kicad_sch		
Title: MOD Dwarf – Main Board		
Size: A4	Date: 2021-09-06	Rev: 3.0
KiCad E.D.A. kicad 6.0.4-6f826c9f35-116-ubuntu20.04.1		Id: 11/11