

Plotting for Exploratory Data Analysis:-

→ Analyzing data using plotting tools, statistics, linear algebra etc.

→ column to be predicted = class label / dependant variable


Data already there = data points / vectors

→ n dimensional numerical array.

columns are called features / input variable / independent variable

→ 1D vector = scalar


$[a]$, $[1]$, $[8.1]$
↓ ↓ ↓
'a' 1 8.1



→ Balanced Dataset → each class has equal number of data points.

→ When reading a plot, always read axis labels & values. It doesn't always start at 0.

→ `iris.plot(kind='scatter', x='sepal_length', y='petal_width');`




(`sns.scatterplot()` only plots one plot.
`sns.FacetGrid()` can plot multiple plots.)

→ import Seaborn as sns

`sns.set_style('whitegrid')` → white grid structure

`sns.FacetGrid(iris, hue='species', size=4).map(plt.scatter, 'sepal_length', 'sepal_width').add_legend();`

dataset
by which
column should
the dataset be
colored



type of plot

x-axis

y-axis

legend

Can't separate as too many outliers.

line could separate setosa from versicolor & virginica (this is called linear separable)

Observations:-
① S-length & S-width can separate setosa flowers from others.
② separating versicolor & virginica is harder.

QUICK SEABORN INTRODUCTION:-

→ simpler way to plot attractive plots.


→ high level interface to matplotlib.

→ some features include:

- default aesthetic themes.
- custom color palettes
- ★ • Visualizing info from matrices & heatmaps.
- ★ • attractive statistical plots.
- ★ • easily displaying distributions

→ Seaborn is a complement, not a substitute of matplotlib

3D Scatter Plot :-



when 3D plot is plotted, we use a plane to separate instead of a line.

Plotting petal length helps notice that plotting a line can separate them which we were not able to do in a 2D plot.

Drawbacks:- \rightarrow while being interactive as a plot, it can't be viewed on 2D surfaces like paper or in an ipynb.


\rightarrow Since we can't visualize 4D datasets, we use pair plots.

there are 4 variable $\Rightarrow 4C_2$ pairs are possible.

$$6 \rightarrow \begin{cases} (SL, SW), (SW, PL) \\ (SL, PL), (PW, PL) \\ (SL, PW), (SW, PW) \end{cases}$$


Since we can't visualize 4D, we try to visualize these 6.

`< sns.pairplot(iris, hue="species", size=3)>`



(The diagonal plots are PDFs of each feature)

measure. As both are h/w PL, PW. Similarly there are 3 pairs in total. So we focus only on 6 plots.



\Rightarrow if $PL \leq 2$ & $PW \leq 1$
then flower type = setosa

if $(PW \leq 2 \& PW \geq 1) \& (PL \leq 5 \& PL \geq 2.5)$
then versicolor
 \rightarrow There will be some error but that's OK.

Drawback of pairplots:-


→ when dimensionality is 4, we get t_{c_2} plots

If the dimensionality is n , we will get n^2 plots which is not that useful.

So we use techniques like PCA, t-SNE that will help with this.

In real world, we limit pairplots to only important features & not apply it on all features.

1D Scatter Plots:-



→ harder to read.

→ green overlaps orange.


Number of points here is not clear.

To overcome this, instead of using a scatterplot, we can use a histogram.

```
sns.FacetGrid(iris, hue="species", size=5).  
map(sns.distplot, "petal_length").add_legend()
```

distribution
plot aka
histogram aka
density plot

y-axis:
count



Smoothed
histogram.
Smoothed using
kernel
Density
Estimation.
(KDE)

overlapping region

if petal length < 2
then setosa.

if petal length > 2 &

petal length < 4.7

then versicolor


if petal length > 4.7
then virginica.

≈


Univariate Analysis:-

→ Analysis of one variable (uni + variate)

→ The further the distributions are, the better.




✓




✗

PDF → probability of variable to be in the range of values. Ex:-



Cumulative Data Function:- (CDF)

→ What % of values are \leq the value at that point.



→ 100% of the values are ≤ 1.9

→ CDF

→ 60% of the values are ≤ 1.5


→ PDF

→ 0% of the values are ≤ 1.1

→ Differentiation of CDF = PDF
integration of PDF = CDF

The CDF value at this point = sum(values) till that point = cumulative sum.

→ Using CDF, we can make assumptions such as



→ 100% of setosa flowers petal length ≤ 2 .

→ 95% of virginica have petal length ≤ 5
⇒ error % = 5%

→ 15% of versicolosa have petal length ≤ 5
⇒ 85% are ≥ 5
⇒ error % = 15%

How to plot CDF?