

finding_donors

October 14, 2018

0.1 Supervised Learning

0.2 Project: Finding Donors for *CharityML*

In this notebook, some template code has already been provided for you, and it will be your job to implement the additional functionality necessary to successfully complete this project. Sections that begin with '**Implementation**' in the header indicate that the following block of code will require additional functionality which you must provide. Instructions will be provided for each section and the specifics of the implementation are marked in the code block with a '`TODO`' statement. Please be sure to read the instructions carefully!

In addition to implementing code, there will be questions that you must answer which relate to the project and your implementation. Each section where you will answer a question is preceded by a '**Question X**' header. Carefully read each question and provide thorough answers in the following text boxes that begin with '**Answer:**'. Your project submission will be evaluated based on your answers to each of the questions and the implementation you provide.

Note: Please specify WHICH VERSION OF PYTHON you are using when submitting this notebook. Code and Markdown cells can be executed using the **Shift + Enter** keyboard shortcut. In addition, Markdown cells can be edited by typically double-clicking the cell to enter edit mode.

0.3 Getting Started

In this project, you will employ several supervised algorithms of your choice to accurately model individuals' income using data collected from the 1994 U.S. Census. You will then choose the best candidate algorithm from preliminary results and further optimize this algorithm to best model the data. Your goal with this implementation is to construct a model that accurately predicts whether an individual makes more than \$50,000. This sort of task can arise in a non-profit setting, where organizations survive on donations. Understanding an individual's income can help a non-profit better understand how large of a donation to request, or whether or not they should reach out to begin with. While it can be difficult to determine an individual's general income bracket directly from public sources, we can (as we will see) infer this value from other publically available features.

The dataset for this project originates from the [UCI Machine Learning Repository](#). The dataset was donated by Ron Kohavi and Barry Becker, after being published in the article "*Scaling Up the Accuracy of Naive-Bayes Classifiers: A Decision-Tree Hybrid*". You can find the article by Ron Kohavi [online](#). The data we investigate here consists of small changes to the original dataset, such as removing the '`fnlwgt`' feature and records with missing or ill-formatted entries.

0.4 Exploring the Data

Run the code cell below to load necessary Python libraries and load the census data. Note that the last column from this dataset, 'income', will be our target label (whether an individual makes more than, or at most, \$50,000 annually). All other columns are features about each individual in the census database.

```
In [1]: # Import libraries necessary for this project
import numpy as np
import pandas as pd
from time import time
from IPython.display import display # Allows the use of display() for DataFrames

# Import supplementary visualization code visuals.py
import visuals as vs

# Pretty display for notebooks
%matplotlib inline

# Load the Census dataset
data = pd.read_csv("census.csv")

# Success - Display the first record
display(data.head())
```

	age	workclass	education_level	education-num	marital-status	\
0	39	State-gov	Bachelors	13.0	Never-married	
1	50	Self-emp-not-inc	Bachelors	13.0	Married-civ-spouse	
2	38	Private	HS-grad	9.0	Divorced	
3	53	Private	11th	7.0	Married-civ-spouse	
4	28	Private	Bachelors	13.0	Married-civ-spouse	

	occupation	relationship	race	sex	capital-gain	\
0	Adm-clerical	Not-in-family	White	Male	2174.0	
1	Exec-managerial	Husband	White	Male	0.0	
2	Handlers-cleaners	Not-in-family	White	Male	0.0	
3	Handlers-cleaners	Husband	Black	Male	0.0	
4	Prof-specialty	Wife	Black	Female	0.0	

	capital-loss	hours-per-week	native-country	income
0	0.0	40.0	United-States	<=50K
1	0.0	13.0	United-States	<=50K
2	0.0	40.0	United-States	<=50K
3	0.0	40.0	United-States	<=50K
4	0.0	40.0	Cuba	<=50K

0.4.1 Implementation: Data Exploration

A cursory investigation of the dataset will determine how many individuals fit into either group, and will tell us about the percentage of these individuals making more than \$50,000. In the code cell below, you will need to compute the following: - The total number of records, 'n_records' - The number of individuals making more than \$50,000 annually, 'n_greater_50k'. - The number of individuals making at most \$50,000 annually, 'n_at_most_50k'. - The percentage of individuals making more than \$50,000 annually, 'greater_percent'.

**** HINT: **** You may need to look at the table above to understand how the 'income' entries are formatted.

```
In [2]: # TODO: Total number of records
        n_records = data.shape[0]

        # TODO: Number of records where individual's income is more than $50,000
        n_greater_50k = data[data['income'] == ">50K"].shape[0]

        # TODO: Number of records where individual's income is at most $50,000
        n_at_most_50k = data[data['income'] == "<=50K"].shape[0]

        # TODO: Percentage of individuals whose income is more than $50,000
        greater_percent = (n_greater_50k * 100)/n_records

        # Print the results
        print("Total number of records: {}".format(n_records))
        print("Individuals making more than $50,000: {}".format(n_greater_50k))
        print("Individuals making at most $50,000: {}".format(n_at_most_50k))
        print("Percentage of individuals making more than $50,000: {:.3f}%".format(greater_perce
```

Total number of records: 45222

Individuals making more than \$50,000: 11208

Individuals making at most \$50,000: 34014

Percentage of individuals making more than \$50,000: 24.784%

**** Featureset Exploration ****

- **age:** continuous.
- **workclass:** Private, Self-emp-not-inc, Self-emp-inc, Federal-gov, Local-gov, State-gov, Without-pay, Never-worked.
- **education:** Bachelors, Some-college, 11th, HS-grad, Prof-school, Assoc-acdm, Assoc-voc, 9th, 7th-8th, 12th, Masters, 1st-4th, 10th, Doctorate, 5th-6th, Preschool.
- **education-num:** continuous.
- **marital-status:** Married-civ-spouse, Divorced, Never-married, Separated, Widowed, Married-spouse-absent, Married-AF-spouse.
- **occupation:** Tech-support, Craft-repair, Other-service, Sales, Exec-managerial, Prof-specialty, Handlers-cleaners, Machine-op-inspct, Adm-clerical, Farming-fishing, Transport-moving, Priv-house-serv, Protective-serv, Armed-Forces.
- **relationship:** Wife, Own-child, Husband, Not-in-family, Other-relative, Unmarried.

- **race:** Black, White, Asian-Pac-Islander, Amer-Indian-Eskimo, Other.
 - **sex:** Female, Male.
 - **capital-gain:** continuous.
 - **capital-loss:** continuous.
 - **hours-per-week:** continuous.
 - **native-country:** United-States, Cambodia, England, Puerto-Rico, Canada, Germany, Outlying-US(Guam-USVI-etc), India, Japan, Greece, South, China, Cuba, Iran, Honduras, Philippines, Italy, Poland, Jamaica, Vietnam, Mexico, Portugal, Ireland, France, Dominican-Republic, Laos, Ecuador, Taiwan, Haiti, Columbia, Hungary, Guatemala, Nicaragua, Scotland, Thailand, Yugoslavia, El-Salvador, Trinidad&Tobago, Peru, Hong, Holand-Netherlands.
-

0.5 Preparing the Data

Before data can be used as input for machine learning algorithms, it often must be cleaned, formatted, and restructured — this is typically known as **preprocessing**. Fortunately, for this dataset, there are no invalid or missing entries we must deal with, however, there are some qualities about certain features that must be adjusted. This preprocessing can help tremendously with the outcome and predictive power of nearly all learning algorithms.


0.5.1 Transforming Skewed Continuous Features

A dataset may sometimes contain at least one feature whose values tend to lie near a single number, but will also have a non-trivial number of vastly larger or smaller values than that single number. Algorithms can be sensitive to such distributions of values and can underperform if the range is not properly normalized. With the census dataset two features fit this description: 'capital-gain' and 'capital-loss'.

Run the code cell below to plot a histogram of these two features. Note the range of the values present and how they are distributed.

```
In [3]: # Split the data into features and target label
income_raw = data['income']
features_raw = data.drop('income', axis = 1)

# Visualize skewed continuous features of original data
vs.distribution(data)
```




For highly-skewed feature distributions such as 'capital-gain' and 'capital-loss', it is common practice to apply a logarithmic transformation on the data so that the very large and very small values do not negatively affect the performance of a learning algorithm. Using a logarithmic transformation significantly reduces the range of values caused by outliers. Care must be taken when applying this transformation however: The logarithm of 0 is undefined, so we must translate the values by a small amount above 0 to apply the the logarithm successfully.

Run the code cell below to perform a transformation on the data and visualize the results. Again, note the range of values and how they are distributed.

```
In [4]: # Log-transform the skewed features
skewed = ['capital-gain', 'capital-loss']
features_log_transformed = pd.DataFrame(data = features_raw)
features_log_transformed[skewed] = features_raw[skewed].apply(lambda x: np.log(x + 1))

# Visualize the new log distributions
vs.distribution(features_log_transformed, transformed = True)
```



0.5.2 Normalizing Numerical Features

In addition to performing transformations on features that are highly skewed, it is often good practice to perform some type of scaling on numerical features. Applying a scaling to the data does not change the shape of each feature's distribution (such as 'capital-gain' or 'capital-loss' above); however, normalization ensures that each feature is treated equally when applying supervised learners. Note that once scaling is applied, observing the data in its raw form will no longer have the same original meaning, as exemplified below.

Run the code cell below to normalize each numerical feature. We will use `sklearn.preprocessing.MinMaxScaler` for this.

```
In [5]: # Import sklearn.preprocessing.StandardScaler
        from sklearn.preprocessing import MinMaxScaler

        # Initialize a scaler, then apply it to the features
        scaler = MinMaxScaler() # default=(0, 1)
        numerical = ['age', 'education-num', 'capital-gain', 'capital-loss', 'hours-per-week']

        features_log_minmax_transform = pd.DataFrame(data = features_log_transformed)
        features_log_minmax_transform[numerical] = scaler.fit_transform(features_log_transformed[numerical])

        # Show an example of a record with scaling applied
        display(features_log_minmax_transform.head(n = 5))
```

	age	workclass	education_level	education-num \
0	0.301370	State-gov	Bachelors	0.800000
1	0.452055	Self-emp-not-inc	Bachelors	0.800000
2	0.287671	Private	HS-grad	0.533333
3	0.493151	Private	11th	0.400000
4	0.150685	Private	Bachelors	0.800000

	marital-status	occupation	relationship	race	sex \
0	Never-married	Adm-clerical	Not-in-family	White	Male
1	Married-civ-spouse	Exec-managerial	Husband	White	Male
2	Divorced	Handlers-cleaners	Not-in-family	White	Male
3	Married-civ-spouse	Handlers-cleaners	Husband	Black	Male
4	Married-civ-spouse	Prof-specialty	Wife	Black	Female

	capital-gain	capital-loss	hours-per-week	native-country
0	0.667492	0.0	0.397959	United-States
1	0.000000	0.0	0.122449	United-States
2	0.000000	0.0	0.397959	United-States
3	0.000000	0.0	0.397959	United-States
4	0.000000	0.0	0.397959	Cuba

0.5.3 Implementation: Data Preprocessing

From the table in **Exploring the Data** above, we can see there are several features for each record that are non-numeric. Typically, learning algorithms expect input to be numeric, which requires that non-numeric features (called *categorical variables*) be converted. One popular way to convert categorical variables is by using the **one-hot encoding** scheme. One-hot encoding creates a "dummy" variable for each possible category of each non-numeric feature. For example, assume someFeature has three possible entries: A, B, or C. We then encode this feature into someFeature_A, someFeature_B and someFeature_C.

```
| someFeature | | someFeature_A | someFeature_B | someFeature_C |
:- | :- | | :- | :- | :- |
0 | B | | 0 | 1 | 0 |
1 | C | ----> one-hot encode ----> | 0 | 0 | 1 |
2 | A | | 1 | 0 | 0 |
```

Additionally, as with the non-numeric features, we need to convert the non-numeric target label, 'income' to numerical values for the learning algorithm to work. Since there are only two possible categories for this label (" $\leq 50K$ " and " $> 50K$ "), we can avoid using one-hot encoding and simply encode these two categories as 0 and 1, respectively. In code cell below, you will need to implement the following: - Use `pandas.get_dummies()` to perform one-hot encoding on the 'features_log_minmax_transform' data. - Convert the target label 'income_raw' to numerical entries. - Set records with " $\leq 50K$ " to 0 and records with " $> 50K$ " to 1.

```
In [6]: # TODO: One-hot encode the 'features_log_minmax_transform' data using pandas.get_dummies
features_final = pd.get_dummies(features_log_minmax_transform)

# TODO: Encode the 'income_raw' data to numerical values
income = income_raw.replace({'<=50K':0, '>50K':1})

# Print the number of features after one-hot encoding
encoded = list(features_final.columns)
print("{} total features after one-hot encoding.".format(len(encoded)))
```

```

# Uncomment the following line to see the encoded feature names
# print encoded
print(income)

```

103 total features after one-hot encoding.

0	0
1	0
2	0
3	0
4	0
5	0
6	0
7	1
8	1
9	1
10	1
11	1
12	0
13	0
14	0
15	0
16	0
17	0
18	1
19	1
20	0
21	0
22	0
23	0
24	1
25	0
26	0
27	0
28	0
29	0
..	..
45192	0
45193	0
45194	1
45195	1
45196	0
45197	1
45198	1
45199	0
45200	0
45201	0
45202	0
45203	0


```
45204    1
45205    0
45206    0
45207    0
45208    0
45209    0
45210    0
45211    0
45212    0
45213    0
45214    0
45215    0
45216    0
45217    0
45218    0
45219    0
45220    0
45221    1
Name: income, Length: 45222, dtype: int64
```

0.5.4 Shuffle and Split Data

Now all *categorical variables* have been converted into numerical features, and all numerical features have been normalized. As always, we will now split the data (both features and their labels) into training and test sets. 80% of the data will be used for training and 20% for testing.

Run the code cell below to perform this split.

```
In [7]: # Import train_test_split
        from sklearn.cross_validation import train_test_split

        # Split the 'features' and 'income' data into training and testing sets
        X_train, X_test, y_train, y_test = train_test_split(features_final,
                                                            income,
                                                            test_size = 0.2,
                                                            random_state = 0)

        # Show the results of the split
        print("Training set has {} samples.".format(X_train.shape[0]))
        print("Testing set has {} samples.".format(X_test.shape[0]))
```

```
Training set has 36177 samples.
Testing set has 9045 samples.
```

```
/opt/conda/lib/python3.6/site-packages/sklearn/cross_validation.py:41: DeprecationWarning: This
    "This module will be removed in 0.20.", DeprecationWarning)
```

0.6 Evaluating Model Performance

In this section, we will investigate four different algorithms, and determine which is best at modeling the data. Three of these algorithms will be supervised learners of your choice, and the fourth algorithm is known as a *naive predictor*.

0.6.1 Metrics and the Naive Predictor

CharityML, equipped with their research, knows individuals that make more than \$50,000 are most likely to donate to their charity. Because of this, *CharityML* is particularly interested in predicting who makes more than \$50,000 accurately. It would seem that using **accuracy** as a metric for evaluating a particular model's performance would be appropriate. Additionally, identifying someone that *does not* make more than \$50,000 as someone who does would be detrimental to *CharityML*, since they are looking to find individuals willing to donate. Therefore, a model's ability to precisely predict those that make more than \$50,000 is *more important* than the model's ability to **recall** those individuals. We can use **F-beta score** as a metric that considers both precision and recall:

$$F_{\beta} = (1 + \beta^2) \cdot \frac{\text{precision} \cdot \text{recall}}{(\beta^2 \cdot \text{precision}) + \text{recall}}$$

In particular, when $\beta = 0.5$, more emphasis is placed on precision. This is called the **F_{0.5} score** (or F-score for simplicity).

Looking at the distribution of classes (those who make at most \$50,000, and those who make more), it's clear most individuals do not make more than \$50,000. This can greatly affect **accuracy**, since we could simply say "*this person does not make more than \$50,000*" and generally be right, without ever looking at the data! Making such a statement would be called **naive**, since we have not considered any information to substantiate the claim. It is always important to consider the *naive prediction* for your data, to help establish a benchmark for whether a model is performing well. That been said, using that prediction would be pointless: If we predicted all people made less than \$50,000, *CharityML* would identify no one as donors.

Note: Recap of accuracy, precision, recall ** Accuracy ** measures how often the classifier makes the correct prediction. It's the ratio of the number of correct predictions to the total number of predictions (the number of test data points).

** Precision ** tells us what proportion of messages we classified as spam, actually were spam. It is a ratio of true positives(words classified as spam, and which are actually spam) to all positives(all words classified as spam, irrespective of whether that was the correct classificatio), in other words it is the ratio of

[True Positives/(True Positives + False Positives)]

** Recall(sensitivity)** tells us what proportion of messages that actually were spam were classified by us as spam. It is a ratio of true positives(words classified as spam, and which are actually spam) to all the words that were actually spam, in other words it is the ratio of

[True Positives/(True Positives + False Negatives)]

For classification problems that are skewed in their classification distributions like in our case, for example if we had a 100 text messages and only 2 were spam and the rest 98 weren't, accuracy by itself is not a very good metric. We could classify 90 messages as not spam(including the 2 that were spam but we classify them as not spam, hence they would be false negatives) and 10 as spam(all 10 false positives) and still get a reasonably good accuracy score. For such cases, precision and recall come in very handy. These two metrics can be combined to get the F1 score, which is

weighted average(harmonic mean) of the precision and recall scores. This score can range from 0 to 1, with 1 being the best possible F1 score(we take the harmonic mean as we are dealing with ratios).

0.6.2 Question 1 - Naive Predictor Performace

- If we chose a model that always predicted an individual made more than \$50,000, what would that model's accuracy and F-score be on this dataset? You must use the code cell below and assign your results to 'accuracy' and 'fscore' to be used later.

**** Please note **** that the the purpose of generating a naive predictor is simply to show what a base model without any intelligence would look like. In the real world, ideally your base model would be either the results of a previous model or could be based on a research paper upon which you are looking to improve. When there is no benchmark model set, getting a result better than random choice is a place you could start from.

**** HINT: ****

- When we have a model that always predicts '1' (i.e. the individual makes more than 50k) then our model will have no True Negatives(TN) or False Negatives(FN) as we are not making any negative('0' value) predictions. Therefore our Accuracy in this case becomes the same as our Precision(True Positives/(True Positives + False Positives)) as every prediction that we have made with value '1' that should have '0' becomes a False Positive; therefore our denominator in this case is the total number of records we have in total.
- Our Recall score(True Positives/(True Positives + False Negatives)) in this setting becomes 1 as we have no False Negatives.

```
In [8]: '''
        TP = np.sum(income) # Counting the ones as this is the naive case. Note that 'income' is
        encoded to numerical values done in the data preprocessing step.
        FP = income.count() - TP # Specific to the naive case

        TN = 0 # No predicted negatives in the naive case
        FN = 0 # No predicted negatives in the naive case
        '''

        # TODO: Calculate accuracy, precision and recall
        accuracy = (np.sum(income))/((np.sum(income)) + ((income.count())))
        recall = (np.sum(income))/((np.sum(income)) + 0)
        precision = accuracy

        # TODO: Calculate F-score using the formula above for beta = 0.5 and correct values for
        row1=precision*recall
        row2=((0.5**2)*precision)+recall
        fscore = (1+pow(0.5,2))*(row1/row2)

        # Print the results
        print("Naive Predictor: [Accuracy score: {:.4f}, F-score: {:.4f}]" . format(accuracy, fscore))
```

Naive Predictor: [Accuracy score: 0.1986, F-score: 0.2365]

0.6.3 Supervised Learning Models

The following are some of the supervised learning models that are currently available in [scikit-learn](#) that you may choose from: - Gaussian Naive Bayes (GaussianNB) - Decision Trees - Ensemble Methods (Bagging, AdaBoost, Random Forest, Gradient Boosting) - K-Nearest Neighbors (KNeighbors) - Stochastic Gradient Descent Classifier (SGDC) - Support Vector Machines (SVM) - Logistic Regression

0.6.4 Question 2 - Model Application

List three of the supervised learning models above that are appropriate for this problem that you will test on the census data. For each model chosen

- Describe one real-world application in industry where the model can be applied.
- What are the strengths of the model; when does it perform well?
- What are the weaknesses of the model; when does it perform poorly?
- What makes this model a good candidate for the problem, given what you know about the data?

**** HINT: ****

Structure your answer in the same format as above, with 4 parts for each of the three models you pick. Please include references with your answer.

Answer:

Here are the three applications where we can apply models in real-world Application

1. Support Vector Machines (Support Vector Classifier): Real world application: Image classification. Strengths: It uses a technique called the kernel trick which can do different complex transformations on your data to help find the optimal boundaries. Works well on smaller cleaner datasets. Weaknesses: Less effective on noisier datasets with overlapping classes. The training time is much longer because it is computationally intensive. It will perform poorly on large datasets. Candidacy: SVMs were chosen for this problem because of their high effectiveness on datasets with high dimensionality. Our dataset grew vastly in terms of features due to our one-hot encoding feature transformation. Also, our dataset isn't that large (<100k records) so it shouldn't be a deterrent.
2. K-Nearest Neighbors (KNeighbors Classifier): Real world application: Recommender Systems. If you know a user likes an item, then you can recommend similar items for them. Strengths: It is an easy to understand algorithm. It works well with a small number of features (low dimensionality). Weaknesses: Lazy learner - all computation is deferred until classification therefore making it computationally intensive for large datasets. If the dataset has many features this algorithm will suffer from the curse of dimensionality because in high dimensions, points that may be similar may have very large distances. To solve this, one might try to lower dimensionality or apply feature selection. Candidacy: I chose KNN here because it's a simple and reliable classifier for datasets with numerical data that don't have a large sample size. Even though we have a higher amount of features now, I wanted to see how this simple algorithm would compare.
3. Ensemble Methods (AdaBoost): Real world application: Image detection. For example, identifying a basketball player during a game. Strengths: More robust than single estimators because it can have improved generalizability by using multiple weak classifiers. Simple models can be combined to build a complex model which is computationally fast. Weaknesses:

If our underlying classifier is biased it will lead to a biased boosted model. Candidacy: Ensemble methods are considered to be high quality classifiers, and adaboost is the one of most popular boosting algorithms. We also have a class imbalance in our dataset, which boosting might be robust to.

0.6.5 Implementation - Creating a Training and Predicting Pipeline

To properly evaluate the performance of each model you've chosen, it's important that you create a training and predicting pipeline that allows you to quickly and effectively train models using various sizes of training data and perform predictions on the testing data. Your implementation here will be used in the following section. In the code block below, you will need to implement the following: - Import `fbeta_score` and `accuracy_score` from `sklearn.metrics`. - Fit the learner to the sampled training data and record the training time. - Perform predictions on the test data `X_test`, and also on the first 300 training points `X_train[:300]`. - Record the total prediction time. - Calculate the accuracy score for both the training subset and testing set. - Calculate the F-score for both the training subset and testing set. - Make sure that you set the beta parameter!

```
In [9]: # TODO: Import two metrics from sklearn - fbeta_score and accuracy_score
        from sklearn.metrics import fbeta_score, accuracy_score

        def train_predict(learner, sample_size, X_train, y_train, X_test, y_test):
            '''
            inputs:
            - learner: the learning algorithm to be trained and predicted on
            - sample_size: the size of samples (number) to be drawn from training set
            - X_train: features training set
            - y_train: income training set
            - X_test: features testing set
            - y_test: income testing set
            '''

            results = {}

            # TODO: Fit the learner to the training data using slicing with 'sample_size' using
            start = time() # Get start time
            learner = learner.fit(X_train[:sample_size], y_train[:sample_size])
            end = time() # Get end time

            # TODO: Calculate the training time
            results['train_time'] = end - start

            # TODO: Get the predictions on the test set(X_test),
            #         then get predictions on the first 300 training samples(X_train) using .predict
            start = time() # Get start time
            predictions_test=learner.predict(X_test)
            predictions_train=learner.predict(X_train[:300])
            end = time() # Get end time
```

```

# TODO: Calculate the total prediction time
results['pred_time'] = end-start

# TODO: Compute accuracy on the first 300 training samples which is y_train[:300]
results['acc_train'] = accuracy_score(y_train[:300], predictions_train.round())

# TODO: Compute accuracy on test set using accuracy_score()
results['acc_test'] = accuracy_score(y_test, predictions_test.round())

# TODO: Compute F-score on the the first 300 training samples using fbeta_score()
results['f_train'] = fbeta_score(y_train[:300], predictions_train.round(), beta=0.5)

# TODO: Compute F-score on the test set which is y_test
results['f_test'] = fbeta_score(y_test, predictions_test.round(), beta=0.5)

# Success
print("{} trained on {} samples.".format(learner.__class__.__name__, sample_size))

# Return the results
return results

```

0.6.6 Implementation: Initial Model Evaluation

In the code cell, you will need to implement the following: - Import the three supervised learning models you've discussed in the previous section. - Initialize the three models and store them in 'clf_A', 'clf_B', and 'clf_C'. - Use a 'random_state' for each model you use, if provided. - **Note:** Use the default settings for each model — you will tune one specific model in a later section. - Calculate the number of records equal to 1%, 10%, and 100% of the training data. - Store those values in 'samples_1', 'samples_10', and 'samples_100' respectively.

Note: Depending on which algorithms you chose, the following implementation may take some time to run!

```

In [10]: # TODO: Import the three supervised learning models from sklearn
from sklearn.ensemble import AdaBoostClassifier
from sklearn.svm import SVC
from sklearn.ensemble import RandomForestClassifier

# TODO: Initialize the three models
clf_A = AdaBoostClassifier()
clf_B = SVC()
clf_C = RandomForestClassifier()

# TODO: Calculate the number of samples for 1%, 10%, and 100% of the training data
# HINT: samples_100 is the entire training set i.e. len(y_train)
# HINT: samples_10 is 10% of samples_100 (ensure to set the count of the values to be `int`)
# HINT: samples_1 is 1% of samples_100 (ensure to set the count of the values to be `int`)
samples_100 = len(y_train)
samples_10 = int(samples_100 * 0.10)

```

```

samples_1 = int(samples_100 * 0.01)

#samples_100=36177
#samples_10=3617
#samples_1=361

# Collect results on the learners
results = {}
for clf in [clf_A, clf_B, clf_C]:
    clf_name = clf.__class__.__name__
    results[clf_name] = {}
    for i, samples in enumerate([samples_1, samples_10, samples_100]):
        results[clf_name][i] = train_predict(clf, samples, X_train, y_train, X_test, y_

# Run metrics visualization for the three supervised learning models chosen
vs.evaluate(results, accuracy, fscore)

```

AdaBoostClassifier trained on 361 samples.
AdaBoostClassifier trained on 3617 samples.
AdaBoostClassifier trained on 36177 samples.


```

/opt/conda/lib/python3.6/site-packages/sklearn/metrics/classification.py:1135: UndefinedMetricWarning:
'precision', 'predicted', average, warn_for)

```

SVC trained on 361 samples.
SVC trained on 3617 samples.
SVC trained on 36177 samples.
RandomForestClassifier trained on 361 samples.
RandomForestClassifier trained on 3617 samples.
RandomForestClassifier trained on 36177 samples.

Performance Metrics for Three Supervised Learning Models



0.7 Improving Results

In this final section, you will choose from the three supervised learning models the *best* model to use on the student data. You will then perform a grid search optimization for the model over the entire training set (`X_train` and `y_train`) by tuning at least one parameter to improve upon the untuned model's F-score.

0.7.1 Question 3 - Choosing the Best Model

- Based on the evaluation you performed earlier, in one to two paragraphs, explain to *CharityML* which of the three models you believe to be most appropriate for the task of identifying individuals that make more than \$50,000.

**** HINT: **** Look at the graph at the bottom left from the cell above (the visualization created by `vs.evaluate(results, accuracy, fscore)`) and check the F score for the testing set when 100% of the training set is used. Which model has the highest score? Your answer should include discussion of the: * metrics - F score on the testing when 100% of the training data is used, * prediction/training time * the algorithm's suitability for the data.

Answer:

If I carefully look at the graph then there are around three supervised models which are `AdaBoostClassifier`, `RandomForestClassifier` and `Support Vector Machine`

According to the graph the RandomForestClassifier is doing very good in fscore in the training set but very poor in testing set but the AdaBoostClassifier is doing very good in training set but it is also doing very good in testing set when checked the size and the score The score is also increasing when the training size is increasing Comparing between the two models there is no much difference between the two but we have to take the best of the f-score and accuracy score so that the model will predict accurate and correct answer when the new values are given to the model.

1) The metrics of AdaBosstClassifier is 0.7 The metrics of RandomForestClassifier is 0.68 The metrics of Suport Vector Machine is 0.66 The AdaBoostClassifier have done the best job in terms of f-score when 100% of the training data is used as compared to RandomForestClassifier and Support Vecotr Machine

2)The maximum of the training time is taken by Support Vecotr Machine as it is one of the disadvantage in Support Vector Machine as mentioned above on question 2. Mathematically,the SVC is taking the most time for 100% training whereas the AdaBoostClassifier is taking the minimum time for 100% training time when the model is training. But when the model is testing the SVC is taking the maximum time for predicting in 100% training data and the both of the models is taking minimum time.

3)The algorithm's suitability for the data is AdaBoostClassifier after looking at the f-score and the accuracy score when 100% training of the data is being used and the time taken for the model for training.

0.7.2 Question 4 - Describing the Model in Layman's Terms

- In one to two paragraphs, explain to *CharityML*, in layman's terms, how the final model chosen is supposed to work. Be sure that you are describing the major qualities of the model, such as how the model is trained and how the model makes a prediction. Avoid using advanced mathematical jargon, such as describing equations.

**** HINT: ****

When explaining your model, if using external resources please include all citations.

Answer:

AdaBoost works by combining multiple weak classifiers to create a strong classifier. A weak classifier being a classifier that simply does better than random guessing but still not necessarily that well overall. But AdaBoost can be applied to any classification algorithm so you could yourself train a bunch of weak classifiers and combine the results - but would it be the same? No, because AdaBoost also handles choosing the training set for each new classifier based on the results of the previous classifier by looking at instances where it predicted poorly and prioritizing the correct prediction of those instances in the next round of training. It also determines how much weight each classifier should be given when they "vote" for the final result.

0.7.3 Implementation: Model Tuning

Fine tune the chosen model. Use grid search (GridSearchCV) with at least one important parameter tuned with at least 3 different values. You will need to use the entire training set for this. In the code cell below, you will need to implement the following: - Import `sklearn.grid_search.GridSearchCV` and `sklearn.metrics.make_scorer`. - Initialize the classifier you've chosen and store it in `clf`. - Set a `random_state` if one is available to the same state you

set before. - Create a dictionary of parameters you wish to tune for the chosen model. - Example: `parameters = {'parameter' : [list of values]}`. - **Note:** Avoid tuning the `max_features` parameter of your learner if that parameter is available! - Use `make_scorer` to create an `fbeta_score` scoring object (with $\beta = 0.5$). - Perform grid search on the classifier `clf` using the '`scorer`', and store it in `grid_obj`. - Fit the grid search object to the training data (`X_train`, `y_train`), and store it in `grid_fit`.

Note: Depending on the algorithm chosen and the parameter list, the following implementation may take some time to run!

```
In [11]: # TODO: Import 'GridSearchCV', 'make_scorer', and any other necessary libraries
from sklearn.grid_search import GridSearchCV
from sklearn.metrics import make_scorer
from sklearn.cross_validation import ShuffleSplit
from sklearn.ensemble import AdaBoostClassifier
# TODO: Initialize the classifier
clf = AdaBoostClassifier()

# TODO: Create the parameters list you wish to tune, using a dictionary if needed.
# HINT: parameters = {'parameter_1': [value1, value2], 'parameter_2': [value1, value2]}
parameters = {"n_estimators": [50, 100, 150, 200], "learning_rate": [0.1, 0.2, 0.5]}

cv = ShuffleSplit(X_train.shape[0], n_iter=10, test_size=0.2, random_state=0)

# TODO: Make an fbeta_score scoring object using make_scorer()
scorer = make_scorer(fbeta_score, beta=0.5)

# TODO: Perform grid search on the classifier using 'scorer' as the scoring method using
grid_obj = GridSearchCV(estimator=clf, param_grid=parameters, scoring=scorer, cv=cv)

# TODO: Fit the grid search object to the training data and find the optimal parameters
grid_fit = grid_obj.fit(X_train, y_train)

# Get the estimator
best_clf = grid_fit.best_estimator_

# Make predictions using the unoptimized and model
predictions = (clf.fit(X_train, y_train)).predict(X_test)
best_predictions = best_clf.predict(X_test)

# Report the before-and-afterscores
print("Unoptimized model\n-----")
print("Accuracy score on testing data: {:.4f}".format(accuracy_score(y_test, predictions)))
print("F-score on testing data: {:.4f}".format(fbeta_score(y_test, predictions, beta=0.5)))
print("\nOptimized Model\n-----")
print("Final accuracy score on the testing data: {:.4f}".format(accuracy_score(y_test, best_predictions)))
print("Final F-score on the testing data: {:.4f}".format(fbeta_score(y_test, best_predictions, beta=0.5)))
```

/opt/conda/lib/python3.6/site-packages/sklearn/grid_search.py:42: DeprecationWarning: This module

DeprecationWarning)

Unoptimized model

Accuracy score on testing data: 0.8576

F-score on testing data: 0.7246

Optimized Model

Final accuracy score on the testing data: 0.8609

Final F-score on the testing data: 0.7315

0.7.4 Question 5 - Final Model Evaluation

- What is your optimized model's accuracy and F-score on the testing data?
- Are these scores better or worse than the unoptimized model?
- How do the results from your optimized model compare to the naive predictor benchmarks you found earlier in **Question 1**?_

Note: Fill in the table below with your results, and then provide discussion in the **Answer** box.

Metric	Unoptimized Model	Optimized Model
Accuracy Score	0.8576	0.8609
F-score	0.7246	0.7315

Results: Answer:

These scores are much better than the unoptimized model and because of the GridSearchCV which helps to make the model optimized I agree that the scores are better than the unoptimized model but i would say there is no much difference in the scores if you compare the scores of the optimized model and unoptimized model.

The difference between are as follows are:- F-score 0.495 Accuracy Score 0.6623

0.8 Feature Importance

An important task when performing supervised learning on a dataset like the census data we study here is determining which features provide the most predictive power. By focusing on the relationship between only a few crucial features and the target label we simplify our understanding of the phenomenon, which is most always a useful thing to do. In the case of this project, that means we wish to identify a small number of features that most strongly predict whether an individual makes at most or more than \$50,000.

Choose a scikit-learn classifier (e.g., adaboost, random forests) that has a `feature_importance_` attribute, which is a function that ranks the importance of features

according to the chosen classifier. In the next python cell fit this classifier to training set and use this attribute to determine the top 5 most important features for the census dataset.

0.8.1 Question 6 - Feature Relevance Observation

When **Exploring the Data**, it was shown there are thirteen available features for each individual on record in the census data. Of these thirteen records, which five features do you believe to be most important for prediction, and in what order would you rank them and why?

Answer:

1)Education-num I firmly believe that the Education-Level is the most important feature selection for donation. Depending upon the Education-Level in this case of the person will be known by the literacy which will be able to donate the money for the better cause of the society or organisation.

2)Hours_per_week Hours_per_week would indicate that how many hours the person is working and the amount of money he would receive

3)Age Age is also another important feature in the case of the donation of the money. Age of the person how well the person is experienced with the charity.

4)Capital Gain Capital Gain is another important feature which would indicate that how much the person is gained at capital

5)Occupation Occupation of the person would tell us the amount of money the person will be able to give it to the charity

0.8.2 Implementation - Extracting Feature Importance

Choose a scikit-learn supervised learning algorithm that has a `feature_importance_` attribute available for it. This attribute is a function that ranks the importance of each feature when making predictions based on the chosen algorithm.


In the code cell below, you will need to implement the following: - Import a supervised learning model from sklearn if it is different from the three used earlier. - Train the supervised model on the entire training set. - Extract the feature importances using `'.feature_importances_'`.

```
In [14]: # TODO: Import a supervised learning model that has 'feature_importances_'
         from sklearn.ensemble import AdaBoostClassifier

         # TODO: Train the supervised model on the training set using .fit(X_train, y_train)
         model = AdaBoostClassifier()
         model=model.fit(X_train,y_train)

         # TODO: Extract the feature importances using .feature_importances_
         importances = model.feature_importances_

         # Plot
         vs.feature_plot(importances, X_train, y_train)
```



0.8.3 Question 7 - Extracting Feature Importance

Observe the visualization created above which displays the five most relevant features for predicting if an individual makes at most or above \$50,000.

* How do these five features compare to the five features you discussed in **Question 6**? * If you were close to the same answer, how does this visualization confirm your thoughts? * If you were not close, why do you think these features are more relevant?

Answer:

My Personal Opinion on this all most the features which I have described on question 6 is close of what i have predicted except of occupation as I thought depending upon the feature of the occupation the model would be able to predict that the person will be able to donate to the charity for the good cause. Capital Loss is the unexpected feature importance in this model which is given much importance more than education-num

0.8.4 Feature Selection

How does a model perform if we only use a subset of all the available features in the data? With less features required to train, the expectation is that training and prediction time is much lower — at the cost of performance metrics. From the visualization above, we see that the top five most important features contribute more than half of the importance of **all** features present in the data. This hints that we can attempt to *reduce the feature space* and simplify the information required for the model to learn. The code cell below will use the same optimized model you found earlier, and train it on the same training set *with only the top five important features*.

```
In [15]: # Import functionality for cloning a model
         from sklearn.base import clone
```

```

# Reduce the feature space
X_train_reduced = X_train[X_train.columns.values[(np.argsort(importances)[:,-1])[:5]]]
X_test_reduced = X_test[X_test.columns.values[(np.argsort(importances)[:,-1])[:5]]]

# Train on the "best" model found from grid search earlier
clf = (clone(best_clf)).fit(X_train_reduced, y_train)

# Make new predictions
reduced_predictions = clf.predict(X_test_reduced)

# Report scores from the final model using both versions of data
print("Final Model trained on full data\n-----")
print("Accuracy on testing data: {:.4f}".format(accuracy_score(y_test, best_predictions)))
print("F-score on testing data: {:.4f}".format(fbeta_score(y_test, best_predictions, beta=1)))
print("\nFinal Model trained on reduced data\n-----")
print("Accuracy on testing data: {:.4f}".format(accuracy_score(y_test, reduced_predictions)))
print("F-score on testing data: {:.4f}".format(fbeta_score(y_test, reduced_predictions, beta=1)))

```

Final Model trained on full data

Accuracy on testing data: 0.8609

F-score on testing data: 0.7315

Final Model trained on reduced data

Accuracy on testing data: 0.8320

F-score on testing data: 0.6735

0.8.5 Question 8 - Effects of Feature Selection

- How does the final model's F-score and accuracy score on the reduced data using only five features compare to those same scores when all features are used?
- If training time was a factor, would you consider using the reduced data as your training set?

Answer:

According to the above score I would say that the F-score have decreased to approx 0.4 which is very bad as during the testing time the model will not be very good to tell whether the particular person will be able to donate to the charity for the organization. Hence I would rather try to keep all the features(full data) of optimized model or change the model so as to aim the higher f-score and accuracy score.

If training was the factor and looking at the f-score then I would rather try to change the model or keep full data. As reducing the data the model would not be able to predict as all the training features are being reduced.

Note: Once you have completed all of the code implementations and successfully answered each question above, you may finalize your work by exporting the iPython

Notebook as an HTML document. You can do this by using the menu above and navigating to

File -> Download as -> HTML (.html). Include the finished document along with this notebook as your submission.

0.9 Before You Submit

You will also need run the following in order to convert the Jupyter notebook into HTML, so that your submission will include both files.

```
In [ ]: !!jupyter nbconvert *.ipynb
```

```
In [ ]:
```