Exploratory Automated Testing

CAST 2013 August 27, 2013

Douglas Hoffman, BACS, MBA, MSEE, ASQ-CSQE, ASQ-CMQ/OE, ASQ Fellow Software Quality Methods, LLC. (SQM)

www.SoftwareQualityMethods.com doug.hoffman@acm.org

Douglas Hoffman

Copyright © 2013, SQM, LLC.

1

About Doug Hoffman

 $I\ am\ a\ management\ consultant\ in\ testing/QA\ strategy\ and\ tactics.\ I\ help\ transform\ organizations.$

Effective software testing requires a special skillset and mindset. The problems and solutions are unique and specific to every set of relevant factors; the context. Over several decades in the business I have learned a great deal about software testing and automation in a large range of contexts from big government and commercial companies to Silicon Valley startups; from hardware and microcode to full blown applications. I enjoy sharing what I've learned with interested people.

Current employment

- President of Software Quality Methods, LLC. (SQM)
- Management consultant in strategic and tactical planning for software quality

Education

- B.A. in Computer Science
- MS in Electrical Engineering, (Digital Design and Information Science)
- MBA

Professional

- Board of Directors and Past President, Association for Software Testing
- Past Chair, Silicon Valley Section, American Society for Quality (ASQ)
- Founding Member and current Chair, Santa Clara Valley Software Quality Association (SSQA)
- Certified in Software Quality Engineering (ASQ-CSQE)
- Certified Quality Manager (ASQ-CMQ/OE)
- Participant in the Los Altos Workshops on Software Testing and many others

Douglas Hoffman

Copyright © 2004-13, SQM, LLC.

2

Automation For This Discussion

Get the computer to do one or more of:

- Test data generation
- Setting-up or capturing pre-conditions
- Controlling test execution
- Selecting/generating inputs
- Running the test exercise
- Outcome monitoring
- Verdict determination:
 - Expected outcome generation
 - Actual outcome monitoring and/or capture
 - Outcome evaluation

Douglas Hoffman

Copyright © 2004-13, SQM, LLC.

3

Most Automated Tests Today

- Are based on the functions of a test tool
- Automate a manual tester's actions
- Are a specific set of test activities (script)
- Work only at the UI or API level
- Do program checking at specified points in the script
- Are used to repeat and speed up manual testing

Douglas Hoffman

Copyright © 2004-13, SQM, LLC.

4

The Regression Test Approach

- Identify potential problems and tests necessary to expose them
- Identify and prioritize important risks
- Standardize documentation and procedures
- Design and create tests that are repeatable
- Rerun the tests often

Regression testing targets specific potential errors and repeatedly (and only) checks for those errors

Douglas Hoffman

Copyright © 2004-13, SQM, LLC.

5

Questions We Should Ask About Testing and Automation

- Should we limit our thinking to what a tool does?
- Should we focus automation on things we can do manually and then script?
- Should we limit ourselves to UIs and APIs?
- Are we checking everything that's important?
- Do speedy manual tests find more or different bugs than manually running tests?
- Can inefficient or approximate tests be valuable?
- Must tests do the same things every time?

Douglas Hoffman

Copyright © 2004-13, SQM, LLC.

6

Exploratory Test Automation


- Does something new every time (except...)
- Does things a manual tester cannot do
- Gets 'behind the scenes" or "under the covers"
- May use massive numbers of iterations
- May use multiple parallel oracles

Exploratory test automation can find bugs we never imagined and couldn't find any other way

Douglas Hoffman

Copyright © 2004-13, SQM, LLC.

7



Some Implications of the Model

- We don't control all inputs
- We can't verify everything
- Multiple domains are involved
- We don't even know all the factors
- The test exercise is the easy part

Douglas Hoffman

Copyright © 2004-13, SQM, LLC.

9

The Oracle Is Key For Test Automation:

- The principle or mechanism for telling whether the SUT behavior appears OK or if further investigation is warranted
- Addresses the question "is this unexpected behavior?"
- It's a basic part of every test execution

Our ability to automate testing is fundamentally constrained by our ability to create and use oracles.

Douglas Hoffman

Copyright © 2011-13, SQM, LLC.

10

Types of Test Oracles

- None
- Independent implementation
- Consistency
 - Saved master
 - Function equivalence
- Self-Verifying
- · Model based

- · Constraint based
- Probabilistic
- · Property based
- Computational
- Diagnostic
- · Hand-crafted
- Human

Douglas Hoffman

Copyright © 2004-13, SQM, LLC.

11

High Volume Random Tests

- Principle idea
 - High-volume testing using varied stimulus
 - Results checking based on individual results or population's statistical characteristics
- Fundamental goal is to have a huge number of iterations
 - The individual tests may not be not all that powerful or compelling
 - Stimulus is varied for each step
 - Individual results may not be checked for correctness (e.g., heuristics or population statistics)
 - The power of the approach lies in the large number of tests

Douglas Hoffman

Copyright © 2004-13, SQM, LLC.

12

Randomness and Tests

- Random number generators
 - Pseudo-Random numbers
 - Generating random seeds
 - Repeatable by entering seed value
- Randomized input values
- Randomized data generation

Douglas Hoffman

Douglas Hoffman

Copyright © 2004-13, SQM, LLC.

13

Repeatable Random Series

```
# RUBY code
MAX_SEED = 1_000_000_000
def initial_RNG_seed(myseed)
  if (myseed == nil) # Check if seed is provided
    # Create a random number to seed RNG
    puts "(no seed passed in, so generate one)"
    myseed = srand()
    myseed = rand(MAX_SEED)
    end
# print the seed so that we know the seed used
    puts "myseed is #{myseed.to_s}\n"
    foo2 = srand (myseed) # initialize the RNG
    foo = rand() # generate the [first] random number
    return foo
end
```

Doug Hoffman 7

Copyright © 2012-13, SQM, LLC.

Random Series Output Example

```
puts ("First run: #{initial_RNG_seed(nil)} \n \n")
puts ("Second run: #{initial_RNG_seed(400)} \n \n")
puts ("Third run: #{initial_RNG_seed(nil)} \n")

(no seed passed in, so generate one)
myseed is 144288918
First run: 0.3705579466087263

myseed is 400
Second run: 0.6687289088341747

(no seed passed in, so generate one)
myseed is 108495905
Third run: 0.0983889898988143

RandSeed

Douglas Hoffman Copyright © 2012-13, SQM, LLC. 15
```

Running Randomly Selected Regression

```
# Ruby
                          Tests
threads = []
list = []
list = Dir.entries ("./executables")
list3 = list.reject { |s| s = ~/^{.}/ }
TestCount = list3.length
for y in (1..10)
 name = list3[rand(TestCount)]
 threads << Thread.new(name) do |x|
   print "running \n"
   print x.to s
# use ruby for running all types of scripts and programs
   system ('ruby ./executables/' + x)
  threads.each {|thr| thr.join}
end
puts ""
puts "Exiting"
#puts rand(TestCount)
#puts list3[rand(TestCount)]
```

Doug Hoffman 8

Copyright © 2012-13, SQM, LLC.

Douglas Hoffman

17

Douglas Hoffman

Well-Formed Input

```
#RUBY program that generates simple arithmetic phrases
def eq_gen
  jubilee = 1 + rand(8) # 8 choices for the 4 defined cases
  case jubilee
    when 1
        "(" << eq_gen() << ") + (" << eq_gen() << ")"
    when 2
        "(" << eq_gen() << ") - (" << eq_gen() << ")"
    when 3
        "(" << eq_gen() << ") * (" << eq_gen() << ")"
    when 4
        "(" << eq_gen() << ") / (" << eq_gen() << ")"
    else # generate number half the time
        rand(100).to_s
    end
end</pre>
```

Copyright © 2012-13, SQM, LLC.

Example of Well-Formed Input

```
puts eq_gen.to_s
puts eq_gen.to_s
puts eq_gen.to_s

puts eq_gen.to_s

(77) - ((62) / (6))

((10) - (40)) + (67)

53

(62) - ((96) * ((((77) - (72)) - ((7) * ((47) - (91)))) / ((34) + (((70) - (18)) + (4)))))
```

Douglas Hoffman Copyright © 2012-13, SQM, LLC.

Low Volume Exploratory Tests

- Principle idea
 - One-at-a-time testing using varied inputs
 - Use automation to make exploration easier
- Fundamental goal is to enable exploration
 - Variations on a theme (modification of existing tests)
 - Quick-and-dirty generation of tests/data/comparisons
 - Checking in the background
 - · Memory leak detection
 - · File modification
 - Etc.

Douglas Hoffman

Copyright © 2004-13, SQM, LLC.

19

Examples of Exploratory Automation

- Random events (Cem Kaner's "Telenova" example)
- "Dumb monkeys" (Noel Nyman)
- "Sandboxed" random regression tests (Kaner/Hoffman)
- Single and multi-threaded database locking (Hoffman)
- Statistical packet profiles for data link testing (Hoffman)
- Random machine instruction generation (Hoffman)
- Database unbalanced splitting (Hoffman)
- Database load/unload dropouts (Hoffman)
- Database forward/backward link consistency (Hoffman)
- Device front panel state machine long walks (Hoffman)
- Periodic database unload/check (Hoffman)
- 1/3 or 3x timing difference heuristic in test harness (Oracle)

Douglas Hoffman

Copyright © 2004-13, SQM, LLC.

20

Advantages of Exploratory Automation

- Does things a manual tester cannot do
- Does something new every time
- May use massive numbers of iterations
- · May feed inputs directly to SUT
- Oracles may check internal information
- May have multiple parallel oracles
- Supplements baseline tests
- Can uncover obscure bugs
- Can uncover bugs impossible to find manually

Douglas Hoffman

Copyright © 2004-13, SQM, LLC.

21

Disadvantages of Exploratory Automation

- May not be repeatable
- Difficulty capturing program and system information for diagnosis
- May have multiple parallel oracles
- Coordination of autonomous oracles with the test
- Does not provide rigorous coverage
- Can uncover bugs that can't be fixed

Douglas Hoffman

Copyright © 2004-13, SQM, LLC.

22

Summary

- Exploratory Automated Testing uses tests that get the computer to look for unexpected conditions
- Varies what the test does
- Opposite of regression tests
- Test oracles are fundamental in testing, especially in exploratory automated testing

Douglas Hoffman

Copyright © 2004-13, SQM, LLC.

23