

VacuMobilift

Easy lifting, flexible order picking

Your mobile solution for unlimited flexibility in the warehouse!

Flexibility, ergonomics, and efficiency – finally combined in everyday warehouse operations.

With the new VacuMobilift, you are choosing a mobile lifting solution that transforms your workflows sustainably. Equipped with an integrated articulated pivot arm, the tube lifter offers maximum freedom of movement and intuitive operation — enabling ergonomic and efficient work at various heights and angles.



Mobility redefined

The VacuMobilift can be conveniently transported using your existing forklift and offers up to 6 hours of operating time thanks to its replaceable battery. Ideal for flexible use throughout the entire warehouse.



Flexibly positionable

Thanks to its well-engineered design, the VacuMobilift can be used precisely where it is needed. The result: efficient work at different heights and in various positions — without any limitations.



Precision meets performance

With the optional tube lifter, you can move loads safely and precisely. Its load capacity of 60–80 kg (depending on material) makes it the ideal assistant for cartons, panels, and bags.

ASSURICH www.assurich.com

VacuMobilift
Assembly overview





Retention net for transport

The retention net ensures a secure and stable hold of the tube lifter during transport and reliably prevents uncontrolled movements.



User-friendly control panel

Control interface with LED buttons and integrated battery indicator for easy and safe operation of the device.



Support feet

The support feet ensure stable footing and increase safety during order picking.



Replaceable battery


The replaceable battery pack enables continuous operation for up to 6 hours and can be exchanged in approximately 10 minutes.




Powerful vacuum pump

The vacuum pump with a 24 V drive ensures safe, independent operation and is suitable for a wide range of applications.


VacuMobilift
Technical data




VacuMobilift




VacuMobilift – articulated jib operating range (in mm)



VacuMobilift – left-hand version



VacuMobilift – right-hand version



VacuMobilift

All dimensions in mm	B	H max.	H min.	H2	H3	H4	L	L1	L2	L3	W1	W2	W3
EU (EPAL)	1.140	1.900	2.400	1.660	1.713	93	2.290	1.000	1.000	1.178	593	220	153
US (GMA)	1.165	1.907	2.407	1.631	1.813	70	2.225	1.100	900	1.200	837	342	153