

Computational Content of the Axiom of Choice in Evidenced Frames

Vladimir Ivanov

July 8, 2023

1 The Computational System

The additional codes are `makeaxiom`, `axiomn` for $n \in \mathbb{N}$ and c_f for $f : \mathbb{N} \rightarrow C$.
The additional reduction relations are

$$\frac{}{\text{makeaxiom} \cdot \bar{k} \downarrow \text{axiom}_k}$$

$$\frac{}{c_f \cdot \bar{n} \downarrow f(n)}$$

The additional termination rules are

$$\frac{}{\text{makeaxiom} \cdot \bar{k} \downarrow}$$

$$\frac{}{c_f \cdot \bar{n} \downarrow}$$

2 The Evidenced Frame

We take the separator \mathcal{S}_\top . We interpret non determinism angelically.

For all $n \in \mathbb{N}$, let nat_n be the predicate realized only by \bar{n} . We define universal quantification over naturals:

$$\forall n. \phi_n$$

as $\prod\{\text{nat}_n \rightarrow \phi_n \mid n \in \mathbb{N}\}$

We define \perp as the predicate realized by all `axiomk`, $k \in \mathbb{N}$.

We allow arbitrary expressions, and not just pairs of codes, on the left of \Downarrow .

3 Pragmatics

We write $\lambda x_0 \dots x_k. e[x_0] \dots [x_k]$ for $c_{\lambda^k.e}$. Not that not all lambda terms can be easily encoded, for example, we can't encode $\lambda x.x(\lambda y.xy)$ and should work around by encoding it as $\lambda x.x((\lambda x'.y.x'y)x)$. We leave such conversions implicit. We do not always write the \cdot .

We write $\exists x \in X. \phi_x$ for $\prod\{\phi_x \mid x \in X\}$ and omit the $\in X$ when X is clear from context.

4 Preliminaries

Fact 1. *There exist codes $\text{intro}_\exists, \text{intro}_\forall, \text{elim}_\exists, \text{elim}_\forall \in \mathcal{S}_\top$ such that for all family of proposition $(\phi_n)_{n \in \mathbb{N}}$, all set X , and all family of propositions $(\psi_x)_{x \in X}$*

1. *If for all n , $c \cdot \bar{n} \Downarrow \phi_n$, then $c \xrightarrow{\text{intro}_\forall} \forall n. \phi_n$.*
2. *If $c \models \forall n. \phi_n$, then for all n , $\text{elim}_\forall \cdot c \cdot n \models \phi_n$.*
3. *For all x , $\psi_x \xrightarrow{\text{intro}_\exists} \exists x. \phi_x$.*
4. *If $\prod\{\phi_x \mid x \in X\}$ has a realizer, then there exists $x \in X$ such that $\prod\{\phi_x \mid x \in X\} \xrightarrow{\text{elim}_\exists} \psi_x$*

Proof. Take

$$\begin{aligned} \text{intro}_\forall &:= \lambda c. \lambda (e_{\text{snd}}; c) \\ \text{elim}_\forall &:= \lambda c. n. c \ n \ n \\ \text{intro}_\exists &:= \lambda c. \lambda (< |c, < |e_{\text{id}}, e_\top| >; e_{\text{eval}}| >; e_{\text{eval}}) \\ \text{elim}_\exists &:= < |\lambda (e_{\text{fst}}; e_\top; \lambda (e_{\text{fst}}; e_{\text{id}})), | >; e_{\text{eval}} \end{aligned}$$

□

Definition 1 (Behaves Like). *We say that code c'_f behaves like code c_f if $\forall c_a, c_r. c_f \cdot c_a \downarrow c_r \Rightarrow c'_f \cdot c_a \downarrow c_r$. If we have an equivalence instead of an implication, we say that they are extensionally equal.*

Lemma 1. *If $c \cdot \bar{n} \Downarrow \perp$ for all k and $e \Downarrow \perp$, then $e[\text{makeaxiom} := c] \Downarrow \perp$.*

Proof. Structural induction over the proof of $e \downarrow \text{axiom}_k$. □

Lemma 2. *If c and c' are extensionally equal, so are $e[x := c]$ and $e[x := c']$ for all expression e with a hole x .*

Proof. Structural induction over the proof of $e[x := c] \downarrow c_r$. □

5 The Proof

Let

$$\begin{aligned} KCC' &:= (\forall n. \nabla \exists i. \neg R(n, i)) \Rightarrow \nabla \exists f. \forall n. \neg R(n, f(n)) \\ \text{fix}_f &:= (\lambda x. f(xx))(\lambda x. f(xx)) \\ \text{fix} &:= \lambda f. \text{fix}_f \\ \Phi_{H,P,\phi,L} &:= P(\text{intro}_\exists(\text{intro}_\forall(\lambda n. \text{assoc } L \ n \ (\lambda _. (\lambda m. Hm(\lambda q. \phi((m, q) : L))))n)))) \\ \Phi_{H,P} &:= \text{fix}_{\lambda \phi L. \Phi_{H,P,\phi,L}} \\ H &\models \forall n. \nabla \exists i. \neg R(n, i) \end{aligned}$$

$$P \models \neg \exists f. \forall n. \neg R(n, f(n))$$

It suffices to prove the following lemma, the rest of the proof is stricly identical to the original paper.

Definition 2 (Cache). *A cache is a church encoded list L of church encoded pairs of the form $(\bar{n}, q), n \in \mathbb{N}, q \in C$ such that*

- *For all $(\bar{n}, q) \in L$ there exists i such that $q \models R(n, i)$.*
- *The first elements of pairs in L are pairwise distinct.*

Lemma 3. *Let L be a chache such that $\Phi_{P,H} \cdot L \not\Downarrow \perp$. Then there exist n and q such that $(n, q) : L$ is a cache and $\Phi_{P,H} \cdot ((n, q) : L) \not\Downarrow \perp$.*

Proof. Define $f_0(n)$ to be i such that $q \models \neg R(n, i)$ if $(n, i) \in L$ for some i , and take $f_0(n)$ to be arbitrary if $n \notin I$.

Claim 1. *We have*

$$P(\text{intro}_{\exists}(\text{intro}_{\forall}(\lambda n. \text{assoc } L \ n \ (\lambda _ . \text{makeaxiom } n)))) \Downarrow \perp$$

Let $n \in \mathbb{N}$. Since $\text{axiom}_n \models \perp$, $\lambda _ . \text{makeaxiom } \bar{n} \models \neg R(n, i)$ for all i . Thus,

$$\text{assoc } L \ \bar{n} \ (\lambda _ . \text{makeaxiom } \bar{n}) \models \neg R(n, f(n))$$

, by the previous discussion if n is not in L and by the definition of a cache if n is in L . This holds for all n , so

$$\text{intro}_{\forall}(\lambda n. \text{assoc } L \ n \ (\lambda _ . \text{makeaxiom } n)) \models \forall n. \neg R(n, f_0(n))$$

. Therefore,

$$\text{intro}_{\exists}(\text{intro}_{\forall}(\lambda n. \text{assoc } L \ n \ (\lambda _ . \text{makeaxiom } n))) \models \exists f. \forall n. \neg R(n, f(n))$$

. This concludes since $P \models \neg \exists f. \forall n. \neg R(n, f(n))$.

Claim 2. $\Phi_{H,P,\Phi_{H,P},L} \not\Downarrow \perp$, *that is (unfolding Φ),*

$$P(\text{intro}_{\exists}(\text{intro}_{\forall}(\lambda n. \text{assoc } L \ n \ (\lambda _ . (\lambda m. H \ m \ (\lambda q. \Phi_{H,P} ((m, q) : L))n)))) \not\Downarrow \perp$$

Proof. Suppose for the sake of contradiction $\Phi_{H,P,\Phi_{H,P},L} \Downarrow \perp$, that is, $\Phi_{H,P,\Phi_{H,P},L} \downarrow \text{axiom}_k$ for some k . So $(\lambda \phi L'. \Phi_{H,P,\phi L'}) \cdot \Phi_{H,P} \cdot L \downarrow \text{axiom}_k$, and since $\Phi_{H,P} = \text{fix}_{\lambda \phi L'. \Phi_{H,P,\phi L'}}$, we have $\Phi_{H,P} \cdot L \downarrow \text{axiom}_k$, which was supposed to not hold. \square

Claim 3. *There exists $k_{\text{new}} \in \mathbb{N}$ such that*

$$\text{elim}_{\forall} H \ \overline{k_{\text{new}}} \ (\lambda q. \Phi_{H,P}((\overline{k_{\text{new}}}, q) : L)) \not\Downarrow \perp$$

Proof. Suppose that $\text{elim}_{\forall} H \ \bar{k} \ (\lambda q. \Phi_{H,P}((\bar{k}, q) : L)) \downarrow \text{axiom}_l$ for some l for all k . It now suffices to find a contradiction. We have $c \cdot \bar{k} \downarrow \text{axiom}_l$ for some l for all k , where $c := \lambda m. \text{elim}_{\forall} H \ m \ (\lambda q. \Phi_{H,P}((m, q) : L))$. Thus, c behaves like makeaxiom , so by applying lemma 1 to claim 1 contradicts claim 2. \square

Now, let k be as in claim 3.

Claim 4. *There exists a $q \in C$ such that $q \models \neg R(k, i)$ for some i .*

Proof. Suppose, for the sake of contradiction, that there is no such q . Since $H \models \forall k. \nabla \exists i. \neg R(n, i)$, it follows from claim 3 that $\lambda q. \Phi_{H,P}((k, q) : L)$ does not realize $\neg \exists i. \neg R(k, i)$. Thus, there exists at least one realizer of $\exists i. \neg R(k, i)$ (since otherwise any code would realize its negation). Now, $\exists i. \neg R(k, i) \xrightarrow{\text{elim}\exists} \neg R(k, i)$ for some i , which concludes that there exists a realizer of $\neg R(k, i)$ for some i . \square

Claim 5. *k is not in L .*

Proof. For all n , $\text{assoc } L \bar{n} (\lambda m. \text{if mem } m L \text{ then } (\lambda x.x) \text{ else makeaxiom } m)$ realizes $\neg R(n, f_0(n))$, by the definition of a cache if n is in L and since it the else branch is taken otherwise. Thus,

$P(\text{intro}\exists(\text{intro}\forall(\lambda n. \text{assoc } L n (\lambda m. \text{if mem } m L \text{ then } (\lambda x.x) \text{ else makeaxiom } n)))) \downarrow \text{axiom}$

since it realizes \perp . Then, since for all n , $\text{assoc } L n \text{ makeaxiom} \models \perp$, we have

$P(\text{intro}\exists(\text{intro}\forall(\lambda n. \text{assoc } L n (\lambda m. \text{makeaxiom})))) \downarrow \text{axiom}$

Then, by lemma 1 and lemma 2,

$\text{if } (\text{mem } \bar{k} L) \text{ then } (\lambda x.x) \text{ else makeaxiom } \bar{k} \Downarrow \perp$

Thus, k is not in L since $\lambda x.x \not\models \perp$. \square

We are finished by taking $n = k_{\text{new}}$ from claim 3 and q from claim 4. \square