

PRESENTATION ON THE WEB: CSS

INFO20002: Foundations of Informatics
March, 2016

CASCADING STYLE SHEETS (CSS)

CASCADING STYLE SHEETS (CSS)

- Declarative language for specifying HTML presentation

CASCADING STYLE SHEETS (CSS)

- Declarative language for specifying HTML presentation
- Separates content from presentation

CASCADING STYLE SHEETS (CSS)

- Declarative language for specifying HTML presentation
- Separates content from presentation
- Reduces the amount of effort required to style a document or web site

THREE APPROACHES TO STYLING

- Inline - specify **style** attribute on each element
- Embedded - specify styles in the **head** of the document
- Linked or Imported - load styles from one or more external files

INLINE STYLES

- HTML elements have a variety of properties that control how they are rendered to the screen
- The `style` attribute can be used to specify the properties of a single element

```
<div>Before!</div>
```

Before!


```
<div style="border:1px solid red;padding:10px;">After!</div>
```

After!

EMBEDDED STYLES

- Specified as rules that tell the browser what styles to apply and to which elements
- Declared in a `style` block inside the document `head`

STYLE RULE

```
selector {  
  property: value;  
  property: value;  
}
```


SELECTORS

"Selectors" in Cascading Style Sheets Level 2 Revision 1 (CSS 2.1) Specification. <https://www.w3.org/TR/CSS2/selector.html>.

SELECTORS

- Type, Universal

"Selectors" in Cascading Style Sheets Level 2 Revision 1 (CSS 2.1) Specification. <https://www.w3.org/TR/CSS2/selector.html>.

SELECTORS

- Type, Universal
- ID

"Selectors" in Cascading Style Sheets Level 2 Revision 1 (CSS 2.1) Specification. <https://www.w3.org/TR/CSS2/selector.html>.

SELECTORS

- Type, Universal
- ID
- Attribute, Class

"Selectors" in Cascading Style Sheets Level 2 Revision 1 (CSS 2.1) Specification. <https://www.w3.org/TR/CSS2/selector.html>.

SELECTORS

- Type, Universal
- ID
- Attribute, Class
- Pseudo-class

"Selectors" in Cascading Style Sheets Level 2 Revision 1 (CSS 2.1) Specification. <https://www.w3.org/TR/CSS2/selector.html>.

SELECTORS

- Type, Universal
- ID
- Attribute, Class
- Pseudo-class
- Adjacent, Child, Descendent

"Selectors" in Cascading Style Sheets Level 2 Revision 1 (CSS 2.1) Specification. <https://www.w3.org/TR/CSS2/selector.html>.

TYPE SELECTORS

Define style rules for a particular type of HTML element.

TYPE SELECTORS

Define style rules for a particular type of HTML element.

```
body {  
    background-color: black;  
    color: white;  
}
```

TYPE SELECTORS

Define style rules for a particular type of HTML element.

```
body {  
    background-color: black;  
    color: white;  
}
```

```
div {  
    border: 1px dashed blue;  
    padding: 5px;  
}
```

UNIVERSAL SELECTOR

Applies a style to all HTML elements.

```
* {  
  font-family: Helvetica, sans-serif;  
}
```

ID SELECTORS

ID SELECTORS

- Elements can be assigned a unique identifier using the `id` attribute

ID SELECTORS

- Elements can be assigned a unique identifier using the `id` attribute
- The ID selector is the element ID prefixed with a # (hash) character

A `div` element with an `id` attribute value of `summary`.

```
<div id="summary">...</div>
```

A `div` element with an `id` attribute value of `summary`.

```
<div id="summary">...</div>
```

A style that targets the `summary` element.

```
#summary {  
  color: blue;  
}
```

ATTRIBUTE SELECTOR

ATTRIBUTE SELECTOR

- Selects elements that have a property setting or have a property setting of a particular value

CLASS SELECTOR

CLASS SELECTOR

- HTML elements have an attribute called `class`

CLASS SELECTOR

- HTML elements have an attribute called `class`
- Elements can be assigned zero or more classes by adding the CSS class name to its class attribute


```
<span class='big'>Big</span> text.
```

```
span.big { font-size: 1.5em; }
```

```
*.big { font-size: 1.5em; }
```

```
.big { font-size: 1.5em; }
```

Big text.

PSEUDO-CLASSES

PSEUDO-CLASSES

- HTML elements may have one or more states associated with them

PSEUDO-CLASSES

- HTML elements may have one or more states associated with them
- Pseudo-class selectors enable selection of elements in a specified state

DESCENDENT SELECTOR

Select elements that are a child of another element

DESCENDENT SELECTOR

Select elements that are a child of another element

```
selector1 selector2 { property: value }
```

CHILD SELECTOR

Select the first child matching the selector

CHILD SELECTOR

Select the first child matching the selector

```
selector1 > selector2 { property: value }
```

ADJACENT SELECTOR OR NEXT-SIBLING SELECTOR

Select the next element matching the selector

"Adjacent sibling selectors" in CSS Selectors. Retrieved from https://developer.mozilla.org/en/docs/Web/CSS/Adjacent_sibling_selectors

ADJACENT SELECTOR OR NEXT-SIBLING SELECTOR

Select the next element matching the selector

```
previousElement + nextElement { property: value }
```

"Adjacent sibling selectors" in CSS Selectors. Retrieved from https://developer.mozilla.org/en/docs/Web/CSS/Adjacent_sibling_selectors

ADJACENT SELECTOR OR NEXT-SIBLING SELECTOR


Select the next element matching the selector

```
previousElement + nextElement { property: value }
```

```
img + span.caption { font-style: italic; }
```

"Adjacent sibling selectors" in CSS Selectors. Retrieved from https://developer.mozilla.org/en/docs/Web/CSS/Adjacent_sibling_selectors

THE CSS BOX MODEL



"Box model" in Cascading Style Sheets Level 2 Revision 1 (CSS 2.1) Specification. Retrieved from <https://www.w3.org/TR/CSS2/box.html>.

MARGIN & PADDING

MARGIN & PADDING

```
.spaced {  
  margin: 10px;  
  padding: 5px;  
}
```

MARGIN & PADDING

```
.spaced {  
  margin: 10px;  
  padding: 5px;  
}
```

```
.spaced {  
  margin-top: 10px;  
  padding-left: 5px;  
}
```

You can concisely specify each side in order of top, right,
bottom, left:

You can concisely specify each side in order of top, right, bottom, left:

```
.spaced {  
  margin: 10px 9px 8px 7px;  
  padding: 5px 4px 3px 2px;  
}
```

BORDER

BORDER

Has properties of thickness, line style and line colour.


```
.outline {  
  border: 1px solid orange;  
}
```

Orange border


```
.outline {  
  border-bottom: 1px dashed orange;  
}
```

Orange border

HEIGHT & WIDTH

"EM, PX, PT, CM, IN ..." in Web Style Sheets, CSS tips & tricks. Retrieved from <https://www.w3.org/Style/Examples/007/units.en.html>.

HEIGHT & WIDTH

- Specified in either absolute or relative lengths

"EM, PX, PT, CM, IN ..." in Web Style Sheets, CSS tips & tricks. Retrieved from <https://www.w3.org/Style/Examples/007/units.en.html>.

HEIGHT & WIDTH

- Specified in either absolute or relative lengths
- Absolute lengths are specified in pixels (px)

"EM, PX, PT, CM, IN ..." in Web Style Sheets, CSS tips & tricks. Retrieved from <https://www.w3.org/Style/Examples/007/units.en.html>.

HEIGHT & WIDTH

- Specified in either absolute or relative lengths
- Absolute lengths are specified in pixels (px)
- Relative lengths are specified as a percentage of the parent element's dimension

"EM, PX, PT, CM, IN ..." in Web Style Sheets, CSS tips & tricks. Retrieved from <https://www.w3.org/Style/Examples/007/units.en.html>.

RELATIVE DIMENSIONS

RELATIVE DIMENSIONS

```
.child {  
  width: 50%;  
}
```

RELATIVE DIMENSIONS

```
.child {  
  width: 50%;  
}
```

The parent

RELATIVE DIMENSIONS

```
.child {  
  width: 50%;  
}
```

The parent

The child

ABSOLUTE DIMENSIONS

ABSOLUTE DIMENSIONS

```
.child {  
  height: 80px;  
  width: 400px;  
}
```


ABSOLUTE DIMENSIONS

```
.child {  
  height: 80px;  
  width: 400px;  
}
```

The parent

ABSOLUTE DIMENSIONS

```
.child {  
  height: 80px;  
  width: 400px;  
}
```



POSITION

- Relative - relative to the top left corner of parent
- Absolute - document coordinate position
- Fixed - screen coordinate position

ABSOLUTE POSITION

```
.child {  
  position: absolute;  
  top: 100px;  
  left: 100px;  
  height: 100px;  
  width: 100px;  
  background-color: #2E93F2;  
}
```

FIXED POSITION

```
.child {  
  position: fixed;  
  top: 100px;  
  left: 100px;  
  height: 100px;  
  width: 100px;  
  background-color: #2E93F2;  
}
```

COLOUR

COLOUR

- Named - red, green, blue, ...

COLOUR

- Named - red, green, blue, ...
- Hexadecimal value - #10FFA9

COLOUR

- Named - `red`, `green`, `blue`, ...
- Hexadecimal value - `#10FFA9`
- RGB decimal value - `rgb(255, 255, 255)`

COLOUR

- Named - `red`, `green`, `blue`, ...
- Hexadecimal value - `#10FFA9`
- RGB decimal value - `rgb(255, 255, 255)`
- RGBA decimal value - `rgba(255, 255, 255, 0.5)`

FO NTS

FONTS

- Fonts must be available to the browser on the local system or linked into the document

FONTS

- Fonts must be available to the browser on the local system or linked into the document
- Specify the font using the `font-family` attribute

FONTS

- Fonts must be available to the browser on the local system or linked into the document
- Specify the font using the `font-family` attribute

```
body {  
    font-family: 'Helvetica Neue', Helvetica, sans-serif;  
}
```

GENERIC AND FALLBACKS

GENERIC AND FALLBACKS

- The browser predefines a number of generic fonts: `serif`, `sans-serif`, `monospace`, ...

GENERIC AND FALLBACKS

- The browser predefines a number of generic fonts: `serif`, `sans-serif`, `monospace`, ...
- The actual font used for each of the above depends on the OS, so you will get varying results

GENERIC AND FALLBACKS

- The browser predefines a number of generic fonts: `serif`, `sans-serif`, `monospace`, ...
- The actual font used for each of the above depends on the OS, so you will get varying results
- If multiple fonts are specified, the browser will fall back to the next font in the list if the prior font is not found

GENERIC AND FALLBACKS


- The browser predefines a number of generic fonts: `serif`, `sans-serif`, `monospace`, ...
- The actual font used for each of the above depends on the OS, so you will get varying results
- If multiple fonts are specified, the browser will fall back to the next font in the list if the prior font is not found

```
body { font-family: 'Helvetica Neue', Helvetica, Arial, sans-serif; }
```


LINKING FONTS


LINKING FONTS

```
<link href='https://fonts.googleapis.com/css?family=Raleway' rel='stylesheet' type='text/css' />
```



LINKING FONTS

```
<link href='https://fonts.googleapis.com/css?family=Raleway' rel='stylesheet' type='text/css'>
```



```
font-family: 'Raleway', sans-serif;
```

IMPORTED STYLES

IMPORTED STYLES

- Styles can be imported from an external file using the [link](#)

IMPORTED STYLES

- Styles can be imported from an external file using the `link`
- Styles are applied in the order they are loaded

MEDIA QUERIES

"Use CSS media queries for responsiveness" in Web Fundamentals. Retrieved from <https://developers.google.com/web/fundamentals/design-and-ui/responsive/fundamentals/use-media-queries?hl=en>.

MEDIA QUERIES

- Media queries are filters that enable the browser to change styles depending on the device rendering the document or its state

"Use CSS media queries for responsiveness" in Web Fundamentals. Retrieved from <https://developers.google.com/web/fundamentals/design-and-ui/responsive/fundamentals/use-media-queries?hl=en>.

MEDIA QUERIES

- Media queries are filters that enable the browser to change styles depending on the device rendering the document or its state
- Queries can be specified either on the stylesheet link or in the CSS itself

"Use CSS media queries for responsiveness" in Web Fundamentals. Retrieved from <https://developers.google.com/web/fundamentals/design-and-ui/responsive/fundamentals/use-media-queries?hl=en>.

CASCADING STYLES

"Inheritance" in Cascading Style Sheets Level 2 Revision 1 (CSS 2.1) Specification. Retrieved from <https://www.w3.org/TR/2011/REC-CSS2-20110607/#minitoc>.

CASCADING STYLES

- HTML elements inherit some or all presentation properties from their parent elements

"Inheritance" in Cascading Style Sheets Level 2 Revision 1 (CSS 2.1) Specification. Retrieved from <https://www.w3.org/TR/2011/REC-CSS2-20110607/#minitoc>.

CASCADING STYLES

- HTML elements inherit some or all presentation properties from their parent elements
- The result is that properties 'cascade' down the DOM

"Inheritance" in Cascading Style Sheets Level 2 Revision 1 (CSS 2.1) Specification. Retrieved from <https://www.w3.org/TR/2011/REC-CSS2-20110607/#minitoc>.

PRIORITY OF APPLICATION

PRIORITY OF APPLICATION

- Styles are sorted by importance, origin and specificity

PRIORITY OF APPLICATION

- Styles are sorted by importance, origin and specificity
- The most specific selector has the greatest priority

PRIORITY OF APPLICATION

- Styles are sorted by importance, origin and specificity
- The most specific selector has the greatest priority
- If two selectors have the same priority, the one defined latest is applied

CLASSES ARE ADDITIVE

CLASSES ARE ADDITIVE

```
.big { font-size: 1.5em; }
```

CLASSES ARE ADDITIVE

```
.big { font-size: 1.5em; }
```

```
.red { color: red; }
```

CLASSES ARE ADDITIVE

```
.big { font-size: 1.5em; }
```

```
.red { color: red; }
```

```
.uppercase { text-transform: uppercase; }
```

CLASSES ARE ADDITIVE

```
.big { font-size: 1.5em; }
```

```
.red { color: red; }
```

```
.uppercase { text-transform: uppercase; }
```

```
<span class='big red uppercase'>Big</span> <span>text.</span>
```

CLASSES ARE ADDITIVE

```
.big { font-size: 1.5em; }
```

```
.red { color: red; }
```

```
.uppercase { text-transform: uppercase; }
```

```
<span class='big red uppercase'>Big</span> <span>text.</span>
```

BIG text.

RESOURCES

- Cascading Style Sheets Level 2 Revision 1 (CSS 2.1) Specification. <https://www.w3.org/TR/CSS2/selector.html>
- [CSS Tricks](#)
- [sitepoint](#)
- [w3schools.com](#)