

Safety Data Sheet

ULTRAMID® A3WG6 BLACK 00564 POLYAMIDE

Revision date : 2018/01/01

Version: 3.0

Page: 1/9

(30045126/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

ULTRAMID® A3WG6 BLACK 00564 POLYAMIDE

Recommended use of the chemical and restriction on use

Recommended use*: Polymer; for industrial processing only

Suitable for use in industrial sector: Polymers industry

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Synonyms: Polyamide (PA 66)

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

No need for classification according to GHS criteria for this product.

Label elements

The product does not require a hazard warning label in accordance with GHS criteria.

Safety Data Sheet

ULTRAMID® A3WG6 BLACK 00564 POLYAMIDE

Revision date : 2018/01/01

Version: 3.0

Page: 2/9

(30045126/SDS_GEN_US/EN)

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

Labeling of special preparations (GHS):

UNDER HOT MELT PROCESSING CONDITIONS, WEAR PERSONAL PROTECTIVE EQUIPMENT TO PREVENT THERMAL BURNS.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

| <u>CAS Number</u> | <u>Weight %</u> | <u>Chemical name</u> |
|-------------------|-----------------|----------------------|
| 1333-86-4 | >= 0.3 - < 1.0% | carbon black |

4. First-Aid Measures

Description of first aid measures

General advice:

Avoid contact with the skin, eyes and clothing. Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If difficulties occur after dust has been inhaled, remove to fresh air and seek medical attention.

If on skin:

Burns caused by molten material require hospital treatment.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

If swallowed:

Rinse mouth and then drink plenty of water. Ingestion is not likely in the available physical form. If ingested, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: No significant reaction of the human body to the product known.

Hazards: No hazard is expected under intended use and appropriate handling.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat symptomatically.

5. Fire-Fighting Measures

Extinguishing media

Safety Data Sheet

ULTRAMID® A3WG6 BLACK 00564 POLYAMIDE

Revision date : 2018/01/01

Version: 3.0

Page: 3/9

(30045126/SDS_GEN_US/EN)

Suitable extinguishing media:
water spray, foam, dry powder

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Ammonium hydroxide, carbon monoxide, cyclopentanone, hydrogen cyanide, amine derivatives, nitriles

Under special fire conditions traces of other toxic substances are possible. Formation of further decomposition and oxidation products depends upon the fire conditions.

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear. Wear self-contained breathing apparatus and chemical-protective clothing.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Keep adjacent fire-exposed buildings, equipment, and materials cool with water spray.

6. Accidental release measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures

No special precautions necessary.

Environmental precautions

No special precautions necessary. This product is not regulated by RCRA. This product is not regulated by CERCLA ('Superfund').

Methods and material for containment and cleaning up

For small amounts: Pick up with suitable appliance and dispose of.

For large amounts: Pick up with suitable appliance and dispose of.

7. Handling and Storage

Precautions for safe handling

Provide suction extractors if dust is formed. Any unavoidable deposit of dust must be regularly removed.

Protection against fire and explosion:

Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

The product in undamaged packing need not be stored separately.

Suitable materials for containers: Low density polyethylene (LDPE), High density polyethylene (HDPE), Aluminium, Carbon steel (Iron)

Further information on storage conditions: Keep container tightly closed. Avoid deposition of dust. Protect against moisture.

Safety Data Sheet

ULTRAMID® A3WG6 BLACK 00564 POLYAMIDE

Revision date : 2018/01/01

Page: 4/9

Version: 3.0

(30045126/SDS_GEN_US/EN)

Storage stability:
Protect against moisture.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

| | | |
|-------------------------|-----------------------|---|
| carbon black | OSHA PEL ACGIH TLV | PEL 3.5 mg/m ³ ; TWA value 3.5 mg/m ³ ; TWA value 3 mg/m ³ Inhalable fraction ; |
| Glass, oxide, chemicals | ACGIH TLV | TWA value 5 mg/m ³ Inhalable fraction ; TWA value 1 fibers/cm ³ Fiber ; Respirable fibers: length > 5 micrometers; aspect ration >= 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase-contrast illumination. TWA value 0.2 fibers/cm ³ Fiber ; Respirable fibers: length > 5 micrometers; aspect ration >= 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase-contrast illumination. |
| Polyethylene wax | OSHA PEL | PEL 5 mg/m ³ Respirable fraction ; PEL 15 mg/m ³ Total dust ; |

Advice on system design:

Ensure adequate ventilation. Provide local exhaust ventilation to control dusts/vapours.

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection:

Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

Eye protection:

Safety glasses with side-shields. Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

No special precautions necessary. Wash soiled clothing immediately.

9. Physical and Chemical Properties

| | |
|------------------|-------------------------------------|
| Form: | pellets |
| Odour: | odourless |
| Odour threshold: | not applicable |
| Colour: | various, depending on the colourant |
| pH value: | not applicable |

Safety Data Sheet

ULTRAMID® A3WG6 BLACK 00564 POLYAMIDE

Revision date : 2018/01/01

Page: 5/9

Version: 3.0

(30045126/SDS_GEN_US/EN)

| | | |
|---|---|-----------------|
| Melting temperature: | approx. 260 °C | (DIN 53765) |
| Boiling range: | The substance / product decomposes therefore not determined. | |
| Sublimation point: | No applicable information available. | |
| Flash point: | > 400 °C | (Unspecified) |
| Flammability: | not self-igniting | |
| Flammability of Aerosol Products: | not applicable, the product does not form flammable aerosoles | |
| Lower explosion limit: | For solids not relevant for classification and labelling. | |
| Upper explosion limit: | For solids not relevant for classification and labelling. | |
| Autoignition: | > 400 °C | (ASTM D1929) |
| Vapour pressure: | not applicable | |
| Density: | 1.15 - 1.60 g/cm3 (20 °C) | (EN ISO 1183-1) |
| Relative density: | Study does not need to be conducted. | |
| Bulk density: | 500 - 800 kg/m3 | |
| Vapour density: | not applicable | |
| Partitioning coefficient n-octanol/water (log Pow): | not applicable | |
| Self-ignition temperature: | not self-igniting | |
| Thermal decomposition: | > 320 °C (TGA) | |
| Viscosity, dynamic: | not applicable, the product is a solid | |
| Viscosity, kinematic: | not applicable, the product is a solid | |
| Solubility in water: | insoluble | |
| Solubility (quantitative): | No applicable information available. | |
| Solubility (qualitative): | No applicable information available. | |
| Evaporation rate: | The product is a non-volatile solid. | |

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:
not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is chemically stable.
No hazardous reactions known.

Conditions to avoid

Temperature: > 320 degrees Celsius

Incompatible materials

No substances known that should be avoided.

Hazardous decomposition products

Decomposition products:

Safety Data Sheet

ULTRAMID® A3WG6 BLACK 00564 POLYAMIDE

Revision date : 2018/01/01

Page: 6/9

Version: 3.0

(30045126/SDS_GEN_US/EN)

Hazardous decomposition products: Ammonium hydroxide, carbon monoxide, carbon dioxide, cyclopentanone, hydrogen cyanide, amines, nitriles

Thermal decomposition:
> 320 °C (TGA)

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Contact with molten product may cause thermal burns. The resin in pelleted form poses a low hazard.

Inhalation

Not inhalable due to the physico-chemical properties of the product.

Assessment other acute effects

No applicable information available.

Irritation / corrosion

Assessment of irritating effects: Thermal decomposition products of the substance can irritate the eyes, skin, and respiratory tract.

Sensitization

Assessment of sensitization: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Genetic toxicity

Assessment of mutagenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Carcinogenicity

Information on: carbon black

Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term animal studies in which the substance was given by inhalation in high concentrations, a carcinogenic effect

Safety Data Sheet

ULTRAMID® A3WG6 BLACK 00564 POLYAMIDE

Revision date : 2018/01/01

Page: 7/9

Version: 3.0

(30045126/SDS_GEN_US/EN)

was observed. A clear indication of an increased risk of cancer in humans has so far not been shown. No carcinogenic potential can be deduced from other studies with rats and mice.

Reproductive toxicity

Assessment of reproduction toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Symptoms of Exposure

No significant reaction of the human body to the product known.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

The product has not been tested. The statement has been derived from the structure of the product. There is a high probability that the product is not acutely harmful to aquatic organisms.

Aquatic toxicity

Information on: Glass, oxide, chemicals

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. Based on long-term (chronic) toxicity study data, the product is very likely not harmful to aquatic organisms.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

Experience shows this product to be inert and non-degradable.

The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants.

Bioaccumulative potential

Bioaccumulation potential

Because of the product's consistency and low water solubility, bioavailability is improbable.

13. Disposal considerations

Waste disposal of substance:

Check for possible recycling. Dispose of in accordance with national, state and local regulations.

Container disposal:

Packs must be completely emptied. Completely emptied packagings can be given for recycling.

Safety Data Sheet

ULTRAMID® A3WG6 BLACK 00564 POLYAMIDE

Revision date : 2018/01/01

Page: 8/9

Version: 3.0

(30045126/SDS_GEN_US/EN)

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

State regulations

State RTK

CAS Number

Chemical name

NJ

65997-17-3

Glass, oxide, chemicals

1333-86-4

carbon black

PA

65997-17-3

Glass, oxide, chemicals

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including GLASS WOOL FIBERS (INHALABLE AND BIOPERSISTENT), which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

[Other Prop 65 components may be present in the product.]

NFPA Hazard codes:

Health: 1

Fire: 1

Reactivity: 0

Special:

HMIS III rating

Health: 1

Flammability: 1

Physical hazard: 0

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2018/01/01

Safety Data Sheet

ULTRAMID® A3WG6 BLACK 00564 POLYAMIDE

Revision date : 2018/01/01

Page: 9/9

Version: 3.0

(30045126/SDS_GEN_US/EN)

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

ULTRAMID® A3WG6 BLACK 00564 POLYAMIDE is a registered trademark of BASF Corporation or BASF SE

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET