

节点群发API文档

更新必读2026-03-13 (Update Required)

开发指南 (development Guide)

[公共请求参数\(common request parameters \)](#)

[通用响应定义 \(Common response definition \)](#)

[Code码相关释义 \(Explanation of Code Symbols\)](#)

[计算签名 \(calculate the sign\)](#)

[筛选目前支持的业务和类别字典 \(Filter currently supported businesses and categories\)](#)

[群发目前支持的业务和类别字典 \(Group sending currently supported businesses and categories\)](#)

筛选 (filter)

[创建任务 \(create task\)](#)

[请求参数 \(request parameters\)](#)

[请求示例 \(request example\)](#)

[返回参数 \(return parameter\)](#)

[成功响应 \(success response\)](#)

[获取任务结果 \(Get task results\)](#)

[请求参数 \(request parameters\)](#)

[返回参数 \(return parameter\)](#)

[成功响应 \(success response\)](#)

[取消任务 \(cancel the task\)](#)

[请求参数 \(request parameters\)](#)

[成功响应 \(success response\)](#)

[文件下载 \(file download\)](#)

[请求参数 \(request parameters\)](#)

[请求示例 \(request example\)](#)

[成功响应 \(success response\)](#)

群发 (group sending)

[创建任务 \(create task\)](#)

[请求参数 \(request parameters\)](#)

content

请求示例 (request example)

返回参数 (return parameter)

成功响应 (success response)

获取任务结果 (Get task results)

请求参数 (request parameters)

返回参数 (return parameter)

成功响应 (success response)

撤销任务 (revoked task)

请求参数 (request parameters)

成功响应 (success response)

暂停任务

请求参数 (request parameters)

成功响应 (success response)

恢复任务

请求参数 (request parameters)

成功响应 (success response)

中断任务

请求参数 (request parameters)

成功响应 (success response)

修改发送内容

请求参数 (request parameters)

成功响应 (success response)

文件下载 (file download) (TXT)

请求参数 (request parameters)

请求示例 (request example)

成功响应 (success response)

自研rcs群发余量查询 (Self-developed RCS group sending remaining quantity query)

请求参数 (request parameters)

请求示例 (request example)

成功响应 (success response)

更新必读2026-03-13 (Update Required)

2026-03-13 本次更新内容在以下内容中用红字标识 (The updated content of this time is marked in red in the following sections.)

- 1.优化创建任务响应code码类型
- 2.rcs群发，新增rcs图文类型，新增群发前置筛选传参逻辑（群发接口）
- 3.自研RCS系统余量查询接口
1. Optimize the code type for creating task responses.
2. RCS mass messaging: Add RCS image/text type, and add the logic for pre-filtering parameters before mass messaging (mass messaging interface)
3. Self-developed RCS system surplus query interface

开发指南 (development Guide)

公共定义(common definitions)

必传全称 (Full name must be passed on)	说明 (description)
Mandatory	必传参数，在请求报文中时必传；在响应报文中时必返 Mandatory parameters, which are required in request messages; must be returned in response messages
Conditional	特定条件下必传，在请求报文中且满足前置条件时必传；在响应报文中且满足前置条件时必返 Must be transmitted under certain conditions, must be transmitted in the request message and when the preconditions are met; must be returned in the response message and when the preconditions are met
Optional	可选参数，在请求报文中时可按照合作方业务需求选择传入；在响应报文中时可按照合作方业务需求选择解析 Optional parameters, which can be passed in according to the partner's business needs in the request message; can be resolved according to the partner's business needs in the response message

公共请求参数(common request parameters)

环境(env)	请求地址(request address)
sandbox	--
production	https://apip.nodesms.com

Header	类型 type	必填 required	值 value	备注 remark
Content-Type	String	M	application/json;charset=utf-8	指定参数类型为json格式 Specifies that the parameter type is in json format
X-Signature	String	M	MOG1YP7eP+hwD9FKJ QtEaqoKCDRBfKkxl2q QVQhb7BU=	签名 sign

请求参数 request	类型 type	长度限制 long	必填 required	说明 remark
account	String		M	调用者账号 由服务方提供 The caller account is provided by the service provider
secret	String		M	调用者secret 由服务方提供 The caller secret is provided by the service party

通用响应定义 (Common response definition)

参数 param	类型 type	必填 required	说明 remrk
code	Int	M	请求响应码；响应说明：code 非 200 即为失败 Request response code; response description: code other than 200 means failure
msg	String	M	响应信息 response information
data	Array	C	业务数据返回值 Business data return value

Code码相关释义（Explanation of Code Symbols）

红色部分为本次新增部分，主要替换原返回code：402,405部分释义不清的问题，更新时间：2026-03-13

注意：释义只代表通俗解释，具体错误详情请结合返回结构体msg查看

The red part represents the newly added content. It mainly replaces the original error codes 402 and 405. Update time: 2026-03-13.

Note: The explanation only represents a general interpretation. For specific error details, please refer to the returned structure "msg".

code	释义 cn	en
200	成功	Success
400	无权操作	Unauthorized operation
402	参数值不对	Parameter value illegal
405	系统错误,请稍后再试	System error, please try later
404	目标不存在或已被删除	Target not found or deleted
601	请稍后再试	Please try again later
701	余额不足，请充值	Insufficient balance, please recharge

702	产品未配置价格	Product price not set
703	产品不存在	Product not found
704	通道不存在	Channel not found
705	文件错误	File error
706	国家错误	Country error
707	通道已关闭	Channel closed
708	扣费失败	Deduction failed
709	订单号已存在	Order number already exists
799	未知错误, 请联系管理员	Unknown error, please contact administrator
710	用户认证失败或权限不足	User authentication failed or insufficient permissions
711	验签失败	Signature verification failed

计算签名 (calculate the sign)

在调用接口进行编码前, 开发者需先计算签名, 计算方式如下:

Before calling the interface for encoding, the developer needs to calculate the signature first, and the calculation method is as follows:

- 签名放到 Header 里,生成规则:使用 hmac 方式对请求数据进行签名
- Put the signature into the Header and generate rules: use hmac method to sign the request data
- php eg:base64_encode(hash_hmac('sha256',\$dataJson,\$secret,true));

筛选目前支持的业务和类别字典 (Filter currently supported businesses and categories)

具体受产品开通权限限制, 如需开通更多业务请联系客服

Specific restrictions are subject to product activation rights. If you need to open more services, please contact customer service.

business	category	remark
WS	WS_Open	whatsapp开通
	WS_Active	whatsapp活跃
RCS	RCS_Open	RCS开通
	RCS_Active	RCS活跃
Phone	Phone_Check	手机号空号检测
待开通。。。		

群发目前支持的业务和类别字典（Group sending currently supported businesses and categories）

具体受产品开通权限限制，如需开通更多业务请联系客服

Specific restrictions are subject to product activation rights. If you need to open more services, please contact customer service.

business	category	remark
RCS	RCS_Text	RCS文本
	RCS_ImgText	RCS图文
待开通。。。		

筛选（filter）

创建任务（create task）

- URL: /api/filter/createTask
- Method: POST
- 需要签名（require a signature）：YES

请求参数 (request parameters)

参数 param	类型 type	长度限制 long	必填 required	说明 remark
account	String		M	调用者账号 由服务方提供 The caller account is provided by the service provider
productId	String		M	分配的产品ID； 由服务方提供 Assigned product ID; provided by service provider
orderId	String	64	M	商户订单号（字母、数字、下划线） 需保证在合作方系统中不重复 Merchant order number (letters, numbers, underscores) Need to ensure that there is no duplication in the partner system
business	String		M	业务；节点筛选业务 Business; Node Screening Business https://www.yuque.com/chenchao-j4ado/aa9xy0/ktykygg7ezbawguz#ckxhH
category	String		M	类别；节点筛选业务类别 Category; Node Filter Business Category https://www.yuque.com/chenchao-j4ado/aa9xy0/ktykygg7ezbawguz#ckxhH
countryCode	String		M	国际标准国家短码； 由服务方提供 International standard national short code; provided by the service provider
numberUrl	String		M	号码链接； 文件格式是TXT， 每行一个号码 Number link; file format is TXT, one number per line

请求示例 (request example)

JSON |

```
1 {
2   "account": "c",
3   "productId": "100000193",
4   "orderId": "1112",
5   "business": "RCS",
6   "category": "RCS_Open",
7   "countryCode": "BR",
8   "numberUrl": "https://tapip.nodesms.com/storage/mass/100078_全部有效1752
649794.txt"
9 }
```

返回参数 (return parameter)

参数	类型	长度限制	必填	说明
param	type	long	required	remark
sn	String		M	节点订单号 Node order number

成功响应 (success response)

状态码: 200 OK

JSON |

```
1 {
2   "code": 200,
3   "msg": "添加成功",
4   "data": {
5     "sn": "FRPX6625PVYGD3AF"
6   }
7 }
```

获取任务结果 (Get task results)

- URL: `/api/filter/getTask`
- Method: `POST`
- 需要签名 (require a signature) : YES

请求参数 (request parameters)

参数 param	类型 type	长度限制 long	必填 required	说明 remark
account	String		M	调用者账号 由服务方提供 The caller account is provided by the service provider
sn	String		M	节点订单号 Node order number

返回参数 (return parameter)

参数 param	类型 type	长度限制 long	必填 required	说明 remark
name	String		M	节点任务名称 Node task name
sn	String		M	节点订单号 Node order number
business	String		M	节点筛选业务 Node screening bussiness
category	String		M	节点筛选业务类别 Node screening category
sum	Int		M	商户提交量 Merchant submissions

submitNum	Int		M	节点计量 node measurement
totalNum	Int		M	节点筛选量 Node screening quantity
status	Int		M	节点任务状态 Node task status 0等待审核 1待开始 2筛选中 3群发中 4已取消 5已完成 6结算中 7已拒绝 8失败 9中断 10暂停 11撤单
sendTime	Int		M	节点发送时间 node sending time
finishTime	Int		M	节点完成时间 Node completion time

成功响应 (success response)

状态码: 200 OK

```

1  {
2      "code": 200,
3      "msg": "成功",
4      "data": {
5          "name": "100078_全部有效1752649794",
6          "taskSn": "FGD665YHDE806X1V",
7          "business": "RCS",
8          "category": "RCS_Open",
9          "sum": 1005,
10         "submitNum": 0,
11         "totalNum": 0,
12         "status": 11,
13         "sendTime": 0,
14         "finishTime": 0
15     }
16 }

```

取消任务 (cancel the task)

- URL: `/api/filter/cancelTask`
- Method: `POST`
- 需要签名 (require a signature) : YES

请求参数 (request parameters)

参数	类型	长度限制	必填	说明
param	type	long	required	remark
account	String		M	调用者账号 由服务方提供 The caller account is provided by the service provider
sn	String		M	节点订单号 Node order number

成功响应 (success response)

状态码: 200 OK

▼

JSON |

```
1 {  
2   "code": 200,  
3   "msg": "成功",  
4   "data": {}  
5 }
```

文件下载 (file download)

- URL: /api/filter/getFile
- Method: POST
- 需要签名 (require a signature) : YES

请求参数 (request parameters)

参数 param	类型 type	长度限制 long	必填 required	说明 remark
account	String		M	调用者账号 由服务方提供 The caller account is provided by the service provider
sn	String		M	节点订单号 Node order number
exportType	Sting		O	下载文件类型 txt csv 默认csv Download file type txt csv default csv

请求示例 (request example)

▼JSON |

```
1 {  
2     "account": "c",  
3     "sn": "FBQ664KLC51LR24D",  
4     "exportType": "csv"  
5 }
```

成功响应 (success response)

状态码: 200 OK

▼JSON |

```
1 {  
2     "code": 200,  
3     "msg": "成功",  
4     "data": {  
5         "url": "http://tapipcc.nodesms.com/storage/mass/20250926/FBQ664KLC5  
1LR24D_全部有效_1758879598.csv"  
6     }  
7 }
```

群发 (group sending)

创建任务 (create task)

- URL: /api/send/createTask
- Method: POST
- 需要签名 (require a signature) : YES

请求参数 (request parameters)

参数	类型	长度限制	必填	说明
param	type	long	required	remark

account	String		M	调用者账号 由服务方提供 The caller account is provided by the service provider
productId	String		M	分配的产品ID； 由服务方提供 Assigned product ID; provided by service provider
orderId	String	64	M	商户订单号（字母、数字、下划线） 需保证在合作方系统中不重复 Merchant order number (letters, numbers, underscores) Need to ensure that there is no duplication in the partner system
business	String		M	业务； 节点筛选业务 Business; Node Screening Business https://www.yuque.com/chenchao-j4ado/aa9xy0/ktykygg7ezbawguz#WLgQt
category	String		M	类别； 节点筛选业务类别 Category; Node Filter Business Category https://www.yuque.com/chenchao-j4ado/aa9xy0/ktykygg7ezbawguz#WLgQt
countryCode	String		M	国际标准国家短码； 由服务方提供 International standard national short code; provided by the service provider
numberUrl	String		M	号码链接； 文件格式是TXT， 每行一个号码 Number link; file format is TXT, one number per line
content	Json		M	群发文案； 结构如下 Group copy; the structure is as follows

variable	Json		C	随机变量必传，否则默认普通发送，一条消息仅支持一个变量 Random variables must be passed, otherwise normal sending will be performed by default. Only one variable is supported for each message. ["https://xxx.xx", "https://yyy.yy"]
----------	------	--	---	--

content

参数 param	类型 type	长度限制 long	必填 required	说明 remark
text	String		M	群发文案 随机变量替换符 \${var} Mass copy random variable substitution character \${var}
thumbnail	String	40KB	O	群发图片完整地址,图片大小控制在40KB一下 类型 jpg png，其他情况会造成提交成功发送失败 (目前只有自研rcs图文支持)，使用前请服务方确认，例如:https://img.nodesms.com/rcs-img/20260312/17733044291426_5AB0B037-1A15-41E8-B62A-10C5FD117531.jpg The complete address of the group-sent images, with the image size controlled to be under 40KB. The file types should be jpg or png. In any other cases, it may result in successful submission but failed sending. (Currently, only the self-developed RCS image and text support is available). Please confirm with the service provider before using, for example

isFilter	int		C	判断群发前是否需要筛选，默认1，筛选发送必填 枚举值：1=直接发送；2=筛选发送 Determine whether to perform filtering before mass sending. The default setting is 1. Filtering is mandatory for sending. Enumeration values: 1 = Direct sending; 2 = Filtering sending
----------	-----	--	---	---

请求示例 (request example)

JSON |

```
1 {
2     "account": "c",
3     "productId": "100000172",
4     "orderId": "11111",
5     "business": "RCS",
6     "category": "RCS_Text", // RCS_ImgText
7     "countryCode": "BR",
8     "numberUrl": "https://tapip.nodesms.com/storage/mass/100078_全部有效175
2649794.txt",
9     "content": {
10         "text": "1232",
11         "isFilter": 2,
12         "thumbnail": "https://img.nodesms.com/rcs-img/20260312/17733044291
426_5AB0B037-1A15-41E8-B62A-10C5FD117531.jpg"
13     },
14     "variable": [
15         "https://xxx.xx",
16         "https://yyy.yy"
17     ]
18 }
```

返回参数 (return parameter)

参数	类型	长度限制	必填	说明
param	type	long	required	remark

account	String		M	调用者账号 由服务方提供 The caller account is provided by the service provider
sn	String		M	节点订单号 Node order number

成功响应 (success response)

状态码: 200 OK

		JSON		
1	{			
2	"code": 200,			
3	"msg": "添加成功",			
4	"data": {			
5	"sn": "FRPX6625PVYGD3AF"			
6	}			
7	}			

获取任务结果 (Get task results)

允许已授权的用户通过此接口更新任务的信息。

Allow authorized users to update task information through this interface.

- URL: /api/send/getTask
- Method: POST
- 需要签名 (require a signature) : YES

请求参数 (request parameters)

参数	类型	长度限制	必填	说明
param	type	long	required	remark

account	String		M	调用者账号 由服务方提供 The caller account is provided by the service provider
sn	String		M	节点订单号 Node order number

返回参数 (return parameter)

参数 param	类型 type	长度限制 long	必填 required	说明 remark
name	String		M	节点任务名称 Node task name
sn	String		M	节点订单号 Node order number
business	String		M	节点筛选业务 Node screening bussiness
category	String		M	节点筛选业务类别 Node screening category
sum	Int		M	商户提交量 Merchant submissions
submitNum	Int		M	节点计量 node measurement
totalNum	Int		M	节点计费量 Node screening quantity

status	Int		M	节点任务状态 Node task status 0等待审核 1待开始 2筛选中 3群发中 4已取消 5已完成 6结算中 7已拒绝 8失败 9中断 10暂停 11撤单
sendTime	Int		M	节点发送时间 node sending time
finishTime	Int		M	节点完成时间 Node completion time

成功响应 (success response)

状态码: 200 OK

JSON

```

1  {
2      "code": 200,
3      "msg": "成功",
4      "data": {
5          "name": "100078_全部有效1752649794",
6          "taskSn": "FGD665YHDE806X1V",
7          "business": "RCS",
8          "category": "RCS_Open",
9          "sum": 1005,
10         "submitNum": 0,
11         "totalNum": 0,
12         "status": 11,
13         "sendTime": 0,
14         "finishTime": 0
15     }
16 }
```

撤销任务 (revoked task)

允许已授权的用户，待执行的任务可以通过此接口取消

Allow authorized users to cancel pending tasks through this interface

- URL: /api/send/revoke
- Method: POST
- 需要签名 (require a signature) : YES

请求参数 (request parameters)

参数 param	类型 type	长度限制 long	必填 required	说明 remark
account	String		M	调用者账号 由服务方提供 The caller account is provided by the service provider
sn	String		M	节点订单号 Node order number

成功响应 (success response)

状态码: 200 OK

▼ JSON |

```
1 {
2   "code": 200,
3   "msg": "成功",
4   "data": {}
5 }
```

暂停任务

允许已授权的用户，群发中的任务可以通过此接口暂停，接口返回成功不代表一定暂停，有一定拦截失败的概率，请通过结果接口获取最新状态

Allow authorized users to suspend tasks in group sending through this interface. A successful return from the interface does not mean that they have been suspended. There is a certain probability that interception will fail. Please use the results interface to obtain the latest status.

- URL: /api/send/pause
- Method: POST
- 需要签名 (require a signature) : YES

请求参数 (request parameters)

参数 param	类型 type	长度限制 long	必填 required	说明 remark
account	String		M	调用者账号 由服务方提供 The caller account is provided by the service provider
sn	String		M	节点订单号 Node order number

成功响应 (success response)

状态码: 200 OK

▼JSON |

```
1 {  
2   "code": 200,  
3   "msg": "成功",  
4   "data": {}  
5 }
```

恢复任务

允许已授权的用户，群发中的任务可以通过此接口恢复继续发送

- URL: `/api/send/recover`
- Method: `POST`
- 需要签名 (require a signature) : YES

请求参数 (request parameters)

参数 param	类型 type	长度限制 long	必填 required	说明 remark
account	String		M	调用者账号 由服务方提供 The caller account is provided by the service provider
sn	String		M	节点订单号 Node order number

成功响应 (success response)

状态码: `200 OK`

JSON

```
1 {  
2   "code": 200,  
3   "msg": "成功",  
4   "data": {}  
5 }
```

中断任务

允许已授权的用户，群发中的任务可以通过此接口中断，接口返回成功不代表一定中断，有一定拦截失败的概率，请通过结果接口获取最新状态，中断任务的状态终态是任务完成，发送量会跟随中断时机变少

Authorized users are allowed to interrupt tasks in group sending through this interface. A successful return from the interface does not mean a certain interruption. There is a certain probability of failure in interception. Please use the result interface to obtain the latest status. The final state of the interrupted task is task completion, and the amount of transmission will decrease with the interruption opportunity.

- URL: /api/send/interrupt
- Method: POST
- 需要签名 (require a signature) : YES

请求参数 (request parameters)

参数 param	类型 type	长度限制 long	必填 required	说明 remark
account	String		M	调用者账号 由服务方提供 The caller account is provided by the service provider
sn	String		M	节点订单号 Node order number

成功响应 (success response)

状态码: 200 OK

▼JSON |

```
1 {  
2   "code": 200,  
3   "msg": "成功",  
4   "data": {}  
5 }
```

修改发送内容

群发中的任务可以通过此接口调整发送内容，接口返回成功不代表一定全部修改，有一定拦截失败的概率

Tasks in group sending can be adjusted through this interface. Successful return from the interface does not mean that all changes will be made, and there is a certain probability that interception will fail.

- URL: /api/send/updateTask
- Method: POST
- 需要签名 (require a signature) : YES

请求参数 (request parameters)

参数 param	类型 type	长度限制 long	必填 required	说明 remark
account	String		M	调用者账号 由服务方提供 The caller account is provided by the service provider
sn	String		M	节点订单号 Node order number
content	Json		M	群发文案 无更改请原样提交 If there is no change to the group copy, please submit it as it is
variable	Json		C	随机变量必传，无更改请原样提交 Random variables must be passed. If there is no change, please submit as it is

成功响应 (success response)

状态码: 200 OK

▼JSON |

```
1 {  
2     "code": 200,  
3     "msg": "成功",  
4     "data": {}  
5 }
```

文件下载（file download）（TXT）

- URL: `/api/send/getFile`
- Method: `POST`
- 需要签名（require a signature）：YES

请求参数（request parameters）

参数	类型	长度限制	必填	说明
param	type	long	required	remark
account	String		M	调用者账号 由服务方提供 The caller account is provided by the service provider
sn	String		M	节点订单号 Node order number

请求示例（request example）

▼JSON |

```
1 {  
2     "account": "c",  
3     "sn": "FBQ664KLC51LR24D"  
4 }
```

成功响应 (success response)

状态码: 200 OK

JSON |

```
1 {
2   "code": 200,
3   "msg": "成功",
4   "data": {
5     "url": "http://tapipcc.nodesms.com/storage/mass/20250929/FBQ664KLC5
1LR24D_全部有效_9.txt"
6   }
7 }
```

自研rcs群发余量查询 (Self-developed RCS group sending remaining quantity query)

- URL: /api/send/getValNumByShortCode
- Method: GET
- 需要签名 (require a signature) : YES

请求参数 (request parameters)

参数	类型	长度限制	必填	说明
param	type	long	required	remark
account	String		M	调用者账号 由服务方提供 The caller account is provided by the service provider

请求示例 (request example)

JSON |

```
1 {  
2   "account": "c",  
3 }
```

成功响应 (success response)

状态码: 200 OK

JSON |

```
1 {  
2   "code": 200,  
3   "msg": "成功",  
4   "data": [  
5     {  
6       "shortCode": "ID",  
7       "count": 100  
8     }  
9   ]  
10 }
```