Button 1 (internal)

long button, length: 8.35mm (from pin)



Button 2 (ext. with ADC)



D8–9 & C5–6 might be DNP in construction kit

Note: if external power supply is needed (e.g. sensor connected via jack plug), bridge JP1.
Via pin D3 (input_pulldown) the voltage can be detected.
Button 2 is connected to D1 (v2 & v3 board) and D15/A1 (v3 board only).

IR (infrared) RX



IR (infrared) TX



If=40mA (cont.)
Vf=~1.33V
58.5R -> 56R (cont.)
Pulsed to 50mA
(50mA is abs. max cont.)
Vf=~1.45V
39R should be safe
if firmware hangs

Arduino Nano Connect RP2040



Sensors



Button 3 (external)



Jacks (same as on FABI)
Cliff FC68125
RS Pro 805-1655
Lumberg 1503 19
Aliexpress: "PJ321C" hard to find, here is a link: www.aliexpress.com/item/32665420060.html
Note: might not fit that well!

Buzzer



Mechanical

Pressure sensor

Alternative: DNP MPVX sensor and use the pin header for an external sensor (e.g. hall sensor for FLipPad)



EITHER

place the sensor board with the pressure sensor here

Neopixel



Note: place only if necessary (e.g. NP ring in case)

Orders in addition to BOM

FLipMouse
* Silicon tube, 2x4mm, ~5cm length
* LuerLock with M5 screw
* Sensor board PCB (see second KiCAD project & BOM)
* screws according to case (4x M2x12; 2x M2x20)
* Mouthpiece

FLipPad
* Glide adapter PCB (see addons folder for KiCAD project & BOM)

Both:
* Neopixel Strip (two LEDs needed)
* 3D printed case (depending on type)
* HotShoe Adapter
* USB cable with magnetic plug
* Packaging

These parts should be placed in the .xls BOM file.

Notes on Button2:
* D6/GPIO18 can be used to detect if there are 3V3 on button 2
* If JP1 is closed, a 3pin Jackplug can be connected, which carries 3V3, GND and a GPIO pin
* If JP2 is switched, button 2 pin is connected to A2 as well (external analog sensors)

Notes on pressure sensor:
* Instead of MPX pressure sensor, a breakout for Honeywell MPR series (I2C) can be connected to J7
* If the firmware does not detect a MPRLS sensor on I2C, analog values are read

<beni@asterics-foundation.org>
Benjamin Aigner
AsTeRICS Foundation

Sheet: /
File: FM3_mainboard.kicad_sch

Title: FLipMouse (FLipPad) Mainboard

Size: A3	Date: 2022-04-07	**Rev: v3.1**
KiCad E.D.A. kicad 6.0.7+dfsg-1+b1		Id: 1/1