










Construction Manual









Rubber pad plate




small flaps



spring




adapter nut




PCB




luer lock




M3x6 screws



pin header 14




angled pin header




pin header 5



short-nosed button




IR receiver




MOSFET




pressure sensor



big flaps




Sensor PCB



M4x25 screws




shims



FSR sensors




adapter screw




EEPROM




pin header 2x5




teensy




rubber pads



pin header 1x2




buzzer




infrared LED



female pin header



LED



22R resistor



120R resistor



4k7 resistor

FlipMouse Manual

Welcome!

This manual covers detailed step-by-step instructions for building the FlipMouse alternative input system. As additional tools you will need a soldering iron with a fine tip, sharp side-cutting pliers, a slotted screwdriver and optionally a PCB holder. The required materials are tin-solder (small diameter) and adhesive tape (Scotch tape).

You can find additional information including a video of the construction process and software downloads at our homepage <http://www.asterics-academy.net/flip>. If you experience problems or need replacement part, contact us at: office@asterics-academy.net

Have fun building your FlipMouse device !

Legend



Solder with soldering iron.



Clip with pliers.



Fix with tape.





Glue with provided glue.




10min


Wait the displayed amount of time.





Put the pieces together, so that the words AsTeRiCs AcAdEmY are readable.




Make sure there is glue on each edge/corner.
Glue hardens due to light exposure.
Attention: glue residue can hardly be removed
from acrylic glass!




Do not glue the top cover! Wait 30 minutes.







Remove the top cover.





Glue the inside flaps in a straight angle.




Glue the outside flaps in a straight angle.




1hr





Place the pin header.




Use tape to fix the part.




Solder and remove the tape.




Place the capacitors.





Bend the pins to fix the part.




Solder the pins.




Clip the remaining pins of the capacitors.





Place the pinheader.




Use tape to fix the part.




Solder and remove the tape.





Place the 3 pin headers on the Teensy.




Place the Teensy board on the PCB.





Solder the pins on the Teensy.
Don't leave space between Teensy and pin headers.




Solder the pins of the Teensy on the PCB.
Don't leave space between Teensy and PCB.




Make sure that the pins are clipped very close
to the PCB surface





Bend the pins of the pressure sensor downwards.




Place it on the PCB.




Solder it.






Bend all 4 pins of the jack plugs downwards.





Place them on the PCB.




Solder the pins. Make sure that they are connected but avoid short cuts (fine solder tip needed)








Place the EEPROM.




Solder it.



Place the IR receiver and bend pins.




Solder it.





Clip the pins.








Place the MOSFET,
bend the pins to fit into the PCB.




Solder it.





Clip the pins.




Place the long-nosed button.




Solder it.




Place the short-nosed button.




Solder it.




Bend one leg of each resistor as tight as possible to 180°.




Place the resistor, bend the legs to fix it. Make sure to place the resistor as close as possible to the PCB





Solder it.




Clip the pins.







Place the LEDs with 3mm space.
Please note the position! The smaller part
inside the LED should be at the "+" sign
on the PCB!



Bend the LED.
Take care of the orientation!




Put the LEDs to the PCB
Take care of the orientation!



Solder, and clip the pins






Bend the LED with 5mm pins left.
Take care of the orientation, as it is shown on the other pictures. Inside the LED there is a bigger and a smaller part. Outside is a flat space on the housing, placed on the edge of the PCB.





Put the LED into the PCB
Take care of the orientation!




Solder the LED and clip the pins.
Take care of the orientation!








Place the buzzer over the LEDs.





Solder it.





Carefully remove the cover of the 2-side adhesive tape
on the sensor. Attention: this is a transparent foil.
DO NOT remove the black foil!





Place the sensor on the acrylic part.




Put the pins through the cuts on the other side.







Solder the pins. Attention: do not buckle the sensor.
Solder **for a short time**, the sensor is made of plastic.





Place the pin header on the sensor carrier.



Solder one pin first, bend the pin header to a straight angle and solder the remaining pins.
This might be tricky, use a fine solder tip.








Use the top cover to align the main PCB straight.
Attention: Please make sure all parts fit well and the alignment is straight. There is no possibility to change the positioning after soldering!




Put the angled pin header to the PCB.





Put both parts together and use the top cover to align them. Solder all 5 pins.




Mount the adapter.




Put the tube on the pressure sensor and the sensor carrier.



Place both PCBs into the case, put it in from the front.
Be careful to fit the LEDs to the corresponding holes.
Mount the top cover.



Mount the front cover. Optionally remove sharp edges
and corners using fine sandpaper.



Attach the mouthpiece.

