

Araxis Merge file comparison between
No File and No File

1
2 I (467) system_api: Base MAC address is not set, read default base MAC address from BLK0 of EFUSE
3 D (717) phy_init: loading PHY init data from application binary
4 D (717) nvs: nvs_open_from_partition phy 0
5 D (717) nvs: nvs_get cal_version 4
6 V (727) phy_init: phy_get_rf_cal_version: 3910
7
8 D (727) nvs: nvs_get_str_or_blob cal_mac
9 D (737) nvs: nvs_get_str_or_blob cal_data
10 D (747) nvs: nvs_close 2
11 I (797) phy: phy_version: 3910, c0c45a3, May 21 2018, 18:07:06, 0, 0
12 I (797) BT_GATT: GATT_Register
13 D (797) BT_GATT: UUID=[0x81818181818181818181818181818181]
14 I (797) BT_GATT: allocated gatt_if=1
15
16 I (807) BT_GATT: GATT_StartIf gatt_if=1
17 D (807) BT_GATT: gatt_find_the_connected_bda start_idx=0
18 D (817) BT_GATT: gatt_find_the_connected_bda found=0 found_idx=4
19 I (817) BT_GATT: GATTS_CreateService
20
21 D (827) BT_GATT: allocate_svc_db_buf allocating extra buffer
22 D (827) BT_GATT: gatts_init_service_db
23
24 D (837) BT_GATT: s_hdl = 1 num_handle = 5
25
26 D (837) BT_GATT: add_service_declaration
27 D (847) BT_GATT: allocate attr 20 bytes
28
29 D (847) BT_GATT: =====> handle = [0x0001] uuid16 = [0x2800] perm=0x01
30
31 D (857) BT_GATT: GATTS_CreateService: handle of service handle1
32 D (857) BT_GATT: gatts_add_characteristic perm=0x0 property=0x20
33
34 D (867) BT_GATT: allocate attr 20 bytes
35
36 D (867) BT_GATT: =====> handle = [0x0002] uuid16 = [0x2803] perm=0x01
37
38 D (877) BT_GATT: allocate attr 20 bytes
39
40 D (877) BT_GATT: =====> handle = [0x0003] uuid16 = [0x2a05] perm=0x00
41
42 D (887) BT_GATT: gatt_profile_db_init: handle of service changed3
43

1
2 I (466) system_api: Base MAC address is not set, read default base MAC address from BLK0 of EFUSE
3 D (706) phy_init: loading PHY init data from application binary
4 D (706) nvs: nvs_open_from_partition phy 0
5 D (706) nvs: nvs_get cal_version 4
6 V (706) phy_init: phy_get_rf_cal_version: 3910
7
8 D (716) nvs: nvs_get_str_or_blob cal_mac
9 D (716) nvs: nvs_get_str_or_blob cal_data
10 D (726) nvs: nvs_close 2
11 I (776) phy: phy_version: 3910, c0c45a3, May 21 2018, 18:07:06, 0, 0
12 I (786) BT_GATT: GATT_Register
13 D (786) BT_GATT: UUID=[0x81818181818181818181818181818181]
14 I (786) BT_GATT: allocated gatt_if=1
15
16 I (786) BT_GATT: GATT_StartIf gatt_if=1
17 D (796) BT_GATT: gatt_find_the_connected_bda start_idx=0
18 D (796) BT_GATT: gatt_find_the_connected_bda found=0 found_idx=4
19 I (806) BT_GATT: GATTS_CreateService
20
21 D (806) BT_GATT: allocate_svc_db_buf allocating extra buffer
22 D (816) BT_GATT: gatts_init_service_db
23
24 D (816) BT_GATT: s_hdl = 1 num_handle = 5
25
26 D (826) BT_GATT: add_service_declaration
27 D (826) BT_GATT: allocate attr 20 bytes
28
29 D (836) BT_GATT: =====> handle = [0x0001] uuid16 = [0x2800] perm=0x01
30
31 D (836) BT_GATT: GATTS_CreateService: handle of service handle1
32 D (846) BT_GATT: gatts_add_characteristic perm=0x0 property=0x20
33
34 D (856) BT_GATT: allocate attr 20 bytes
35
36 D (856) BT_GATT: =====> handle = [0x0002] uuid16 = [0x2803] perm=0x01
37
38 D (866) BT_GATT: allocate attr 20 bytes
39
40 D (866) BT_GATT: =====> handle = [0x0003] uuid16 = [0x2a05] perm=0x00
41
42 D (876) BT_GATT: gatt_profile_db_init: handle of service changed3
43

Araxis Merge file comparison between
No File and No File

43		43
44	I (897) BT_GATT: GATTS_StartService	44 I (876) BT_GATT: GATTS_StartService
45	D (897) BT_GATT: total buffer in db [1]	45 D (886) BT_GATT: total buffer in db [1]
46	D (907) BT_GATT: gatt_add_sdp_record s_hdl=0x1 s_hdl=0x5	46 D (886) BT_GATT: gatt_add_sdp_record s_hdl=0x1 s_hdl=0x5
47	D (907) BT_GATT: allocated i_sreg=0	47 D (896) BT_GATT: allocated i_sreg=0
48		48
49	D (907) BT_GATT: s_hdl=1 e_hdl=5 type=0x2800 svc_inst=0 sdp_hdl=0x10000	49 D (896) BT_GATT: s_hdl=1 e_hdl=5 type=0x2800 svc_inst=0 sdp_hdl=0x10000
50		50
51	D (917) BT_GATT: gatt_profile_db_init: gatt_if=1 start status=0	51 D (906) BT_GATT: gatt_profile_db_init: gatt_if=1 start status=0
52		52
53	I (927) BT_GATT: GATT_Register	53 I (906) BT_GATT: GATT_Register
54	D (927) BT_GATT: UUID=[0x82828282828282828282828282828282]	54 D (916) BT_GATT: UUID=[0x82828282828282828282828282828282]
55	I (937) BT_GATT: allocated gatt_if=2	55 I (916) BT_GATT: allocated gatt_if=2
56		56
57	I (937) BT_GATT: GATT_StartIf gatt_if=2	57 I (926) BT_GATT: GATT_StartIf gatt_if=2
58	D (947) BT_GATT: gatt_find_the_connected_bda start_idx=0	58 D (926) BT_GATT: gatt_find_the_connected_bda start_idx=0
59	D (947) BT_GATT: gatt_find_the_connected_bda found=0 found_idx=4	59 D (936) BT_GATT: gatt_find_the_connected_bda found=0 found_idx=4
60	I (957) BT_GATT: GATTS_CreateService	60 I (936) BT_GATT: GATTS_CreateService
61		61
62	D (957) BT_GATT: allocate_svc_db_buf allocating extra buffer	62 D (946) BT_GATT: allocate_svc_db_buf allocating extra buffer
63	D (967) BT_GATT: gatts_init_service_db	63 D (946) BT_GATT: gatts_init_service_db
64		64
65	D (967) BT_GATT: s_hdl = 20 num_handle = 9	65 D (956) BT_GATT: s_hdl = 20 num_handle = 9
66		66
67	D (977) BT_GATT: add_service_declaration	67 D (956) BT_GATT: add_service_declaration
68	D (977) BT_GATT: allocate attr 20 bytes	68 D (966) BT_GATT: allocate attr 20 bytes
69		69
70	D (977) BT_GATT: =====> handle = [0x0014] uuid16 = [0x2800] perm=0x01	70 D (966) BT_GATT: =====> handle = [0x0014] uuid16 = [0x2800] perm=0x01
71		71
72	D (987) BT_GATT: gatts_add_characteristic perm=0x1 property=0x2	72 D (976) BT_GATT: gatts_add_characteristic perm=0x1 property=0x2
73		73
74	D (997) BT_GATT: allocate attr 20 bytes	74 D (976) BT_GATT: allocate attr 20 bytes
75		75
76	D (997) BT_GATT: =====> handle = [0x0015] uuid16 = [0x2803] perm=0x01	76 D (986) BT_GATT: =====> handle = [0x0015] uuid16 = [0x2803] perm=0x01
77		77
78	D (1007) BT_GATT: allocate attr 20 bytes	78 D (986) BT_GATT: allocate attr 20 bytes
79		79
80	D (1007) BT_GATT: =====> handle = [0x0016] uuid16 = [0x2a00] perm=0x01	80 D (996) BT_GATT: =====> handle = [0x0016] uuid16 = [0x2a00] perm=0x01
81		81
82	D (1017) BT_GATT: gatts_add_characteristic perm=0x1 property=0x2	82 D (996) BT_GATT: gatts_add_characteristic perm=0x1 property=0x2
83		83
84	D (1017) BT_GATT: allocate attr 20 bytes	84 D (1006) BT_GATT: allocate attr 20 bytes
85		85
86	D (1027) BT_GATT: =====> handle = [0x0017] uuid16 = [0x2803] perm=0x01	86 D (1016) BT_GATT: =====> handle = [0x0017] uuid16 = [0x2803] perm=0x01

Araxis Merge file comparison between
No File and No File

86 D (1027) BT_GATT: =====> handle = [0x0017] uuid16 = [0x2803] perm=0x01	86 D (1016) BT_GATT: =====> handle = [0x0017] uuid16 = [0x2803] perm=0x01
87	87
88 D (1037) BT_GATT: allocate attr 20 bytes	88 D (1016) BT_GATT: allocate attr 20 bytes
89	89
90 D (1037) BT_GATT: =====> handle = [0x0018] uuid16 = [0x2a01] perm=0x01	90 D (1026) BT_GATT: =====> handle = [0x0018] uuid16 = [0x2a01] perm=0x01
91	91
92 D (1047) BT_GATT: gatts_add_characteristic perm=0x1 property=0x2	92 D (1026) BT_GATT: gatts_add_characteristic perm=0x1 property=0x2
93	93
94 D (1047) BT_GATT: allocate attr 20 bytes	94 D (1036) BT_GATT: allocate attr 20 bytes
95	95
96 D (1057) BT_GATT: allocate_svc_db_buf allocating extra buffer	96 D (1036) BT_GATT: allocate_svc_db_buf allocating extra buffer
97 D (1057) BT_GATT: =====> handle = [0x0019] uuid16 = [0x2803] perm=0x01	97 D (1046) BT_GATT: =====> handle = [0x0019] uuid16 = [0x2803] perm=0x01
98	98
99 D (1067) BT_GATT: allocate attr 20 bytes	99 D (1056) BT_GATT: allocate attr 20 bytes
100	100
101 D (1067) BT_GATT: =====> handle = [0x001a] uuid16 = [0x2aa6] perm=0x01	101 D (1056) BT_GATT: =====> handle = [0x001a] uuid16 = [0x2aa6] perm=0x01
102	102
103 I (1077) BT_GATT: GATTS_StartService	103 I (1066) BT_GATT: GATTS_StartService
104 D (1077) BT_GATT: total buffer in db [2]	104 D (1066) BT_GATT: total buffer in db [2]
105 D (1087) BT_GATT: gatt_add_sdp_record s_hdl=0x14 s_hdl=0x1c	105 D (1076) BT_GATT: gatt_add_sdp_record s_hdl=0x14 s_hdl=0x1c
106 D (1087) BT_GATT: allocated i_sreg=1	106 D (1076) BT_GATT: allocated i_sreg=1
107	107
108 D (1097) BT_GATT: s_hdl=20 e_hdl=28 type=0x2800 svc_inst=0 sdp_hdl=0x10001	108 D (1076) BT_GATT: s_hdl=20 e_hdl=28 type=0x2800 svc_inst=0 sdp_hdl=0x10001
109	109
110 D (1107) nvs: nvs_open_from_partition bt_config.conf 1	110 D (1086) nvs: nvs_open_from_partition bt_config.conf 1
111 D (1107) nvs: nvs_get_str_or_blob bt_cfg_key0	111 D (1096) nvs: nvs_get_str_or_blob bt_cfg_key0
112 D (1117) nvs: nvs_get_str_or_blob bt_cfg_key0	112 D (1096) nvs: nvs_get_str_or_blob bt_cfg_key0
113 D (1117) nvs: nvs_close 3	113 D (1106) nvs: nvs_close 3
114 D (1117) nvs: nvs_open_from_partition bt_config.conf 1	114 D (1106) nvs: nvs_open_from_partition bt_config.conf 1
115 D (1127) nvs: nvs_set_blob bt_cfg_key0 863	115 D (1106) nvs: nvs_set_blob bt_cfg_key0 863
116 D (1137) nvs: nvs_close 4	116 D (1116) nvs: nvs_close 4
117 I (1157) BT_GATT: GATT_Register	117 I (1136) BT_GATT: GATT_Register
118 D (1157) BT_GATT: UUID=[0x87878787878787878787878787878787]	118 D (1136) BT_GATT: UUID=[0x87878787878787878787878787878787]
119 I (1157) BT_GATT: allocated gatt_if=3	119 I (1136) BT_GATT: allocated gatt_if=3
120	120
121 I (1157) BT_GATT: GATT_StartIf gatt_if=3	121 I (1146) BT_GATT: GATT_StartIf gatt_if=3
122 D (1157) BT_GATT: gatt_find_the_connected_bda start_idx=0	122 D (1146) BT_GATT: gatt_find_the_connected_bda start_idx=0
123 D (1167) BT_GATT: gatt_find_the_connected_bda found=0 found_idx=4	123 D (1156) BT_GATT: gatt_find_the_connected_bda found=0 found_idx=4
124 D (1187) BT_GATT: gatt_init_srv_chg	124 D (1166) BT_GATT: gatt_init_srv_chg
125 I (1187) BT_GATT: GATT_Register	125 I (1166) BT_GATT: GATT_Register
126 D (1187) BT_GATT: UUID=[0x180f]	126 D (1166) BT_GATT: UUID=[0x180f]
127 I (1187) BT_GATT: allocated gatt_if=4	127 I (1166) BT_GATT: allocated gatt_if=4
128	128

Araxis Merge file comparison between
No File and **No File**

128		128
129	I (1187) BT_GATT: GATT_StartIf gatt_if=4	129 I (1176) BT_GATT: GATT_StartIf gatt_if=4
130	D (1197) BT_GATT: gatt_find_the_connected_bda start_idx=0	130 D (1176) BT_GATT: gatt_find_the_connected_bda start_idx=0
131	D (1197) BT_GATT: gatt_find_the_connected_bda found=0 found_idx=4	131 D (1186) BT_GATT: gatt_find_the_connected_bda found=0 found_idx=4
132	E (1207) FABI/FLIPMOUSE: hidd_event_callback(), ESP_BAT_EVENT_REG	132 E (1186) FABI/FLIPMOUSE: hidd_event_callback(), ESP_BAT_EVENT_REG
133	I (1207) BT_GATT: GATT_Register	133 I (1196) BT_GATT: GATT_Register
134	D (1217) BT_GATT: UUID=[0x1812]	134 D (1196) BT_GATT: UUID=[0x1812]
135	I (1217) BT_GATT: allocated gatt_if=5	135 I (1206) BT_GATT: allocated gatt_if=5
136		136
137	I (1227) BT_GATT: GATT_StartIf gatt_if=5	137 I (1206) BT_GATT: GATT_StartIf gatt_if=5
138	D (1227) BT_GATT: gatt_find_the_connected_bda start_idx=0	138 D (1216) BT_GATT: gatt_find_the_connected_bda start_idx=0
139	D (1237) BT_GATT: gatt_find_the_connected_bda found=0 found_idx=4	139 D (1216) BT_GATT: gatt_find_the_connected_bda found=0 found_idx=4
140	E (1237) FABI/FLIPMOUSE: hidd_event_callback(), ESP_HIDD_EVENT_REG_FINI SH	140 E (1226) FABI/FLIPMOUSE: hidd_event_callback(), ESP_HIDD_EVENT_REG_FINI SH
141	I (1247) BT_GATT: GATTS_CreateService	141 I (1236) BT_GATT: GATTS_CreateService
142		142
143	D (1247) BT_GATT: gatt_add_pending_new_srv_start	143 D (1236) BT_GATT: gatt_add_pending_new_srv_start
144	D (1257) BT_GATT: enqueue a new pending new srv start	144 D (1236) BT_GATT: enqueue a new pending new srv start
145	D (1257) BT_GATT: Add a new srv chg item	145 D (1246) BT_GATT: Add a new srv chg item
146		146
147	D (1267) BT_GATT: allocate_svc_db_buf allocating extra buffer	147 D (1246) BT_GATT: allocate_svc_db_buf allocating extra buffer
148	D (1267) BT_GATT: gatts_init_service_db	148 D (1256) BT_GATT: gatts_init_service_db
149		149
150	D (1277) BT_GATT: s_hdl = 40 num_handle = 5	150 D (1256) BT_GATT: s_hdl = 40 num_handle = 5
151		151
152	D (1277) BT_GATT: add_service_declaration	152 D (1266) BT_GATT: add_service_declaration
153	D (1287) BT_GATT: allocate attr 20 bytes	153 D (1266) BT_GATT: allocate attr 20 bytes
154		154
155	D (1287) BT_GATT: =====> handle = [0x0028] uuid16 = [0x2800] perm=0x01	155 D (1276) BT_GATT: =====> handle = [0x0028] uuid16 = [0x2800] perm=0x01
156		156
157	D (1297) BT_GATT: gatts_add_characteristic perm=0x1 property=0x12	157 D (1276) BT_GATT: gatts_add_characteristic perm=0x1 property=0x12
158		158
159	D (1297) BT_GATT: allocate attr 20 bytes	159 D (1286) BT_GATT: allocate attr 20 bytes
160		160
161	D (1307) BT_GATT: =====> handle = [0x0029] uuid16 = [0x2803] perm=0x01	161 D (1286) BT_GATT: =====> handle = [0x0029] uuid16 = [0x2803] perm=0x01
162		162
163	D (1307) BT_GATT: allocate attr 20 bytes	163 D (1296) BT_GATT: allocate attr 20 bytes
164		164
165	D (1317) BT_GATT: =====> handle = [0x002a] uuid16 = [0x2a19] perm=0x01	165 D (1296) BT_GATT: =====> handle = [0x002a] uuid16 = [0x2a19] perm=0x01
166		166
167	D (1317) BT_GATT: attr_val->attr_len = 1, attr_val->attr_max_len = 1	167 D (1306) BT_GATT: attr_val->attr_len = 1, attr_val->attr_max_len = 1
168		168
169	D (1327) BT_GATT: attribute handle = 2a	169 D (1316) BT_GATT: attribute handle = 2a
170		170

Araxis Merge file comparison between
No File and **No File**

170		170
171	D (1337) BT_GATT: gatts_add_char_descr uuid=0x2902	171 D (1316) BT_GATT: gatts_add_char_descr uuid=0x2902
172		172
173	D (1337) BT_GATT: allocate attr 20 bytes	173 D (1326) BT_GATT: allocate attr 20 bytes
174		174
175	D (1337) BT_GATT: =====> handle = [0x002b] uuid16 = [0x2902] perm=0x11	175 D (1326) BT_GATT: =====> handle = [0x002b] uuid16 = [0x2902] perm=0x11
176		176
177	D (1347) BT_GATT: gatts_add_char_descr uuid=0x2904	177 D (1336) BT_GATT: gatts_add_char_descr uuid=0x2904
178		178
179	D (1357) BT_GATT: allocate attr 20 bytes	179 D (1336) BT_GATT: allocate attr 20 bytes
180		180
181	D (1357) BT_GATT: allocate_svc_db_buf allocating extra buffer	181 D (1346) BT_GATT: allocate_svc_db_buf allocating extra buffer
182	D (1367) BT_GATT: =====> handle = [0x002c] uuid16 = [0x2904] perm=0x01	182 D (1346) BT_GATT: =====> handle = [0x002c] uuid16 = [0x2904] perm=0x01
183		183
184	I (1367) HID_DEVICE: esp_hidd_prf_cb_hdl(), start added the hid service to the stack database. incl_handle = 40	184 I (1356) HID_DEVICE: esp_hidd_prf_cb_hdl(), start added the hid service to the stack database. incl_handle = 40
185	E (1377) FABI/FLIPMOUSE: gap_event_handler(), ESP_GAP_BLE_ADV_DATA_SET_COMPLETE_EVT	185 E (1366) FABI/FLIPMOUSE: gap_event_handler(), ESP_GAP_BLE_ADV_DATA_SET_COMPLETE_EVT
186	I (1387) BT_GATT: GATTS_CreateService	186 I (1376) BT_GATT: GATTS_CreateService
187		187
188	D (1397) BT_GATT: gatt_add_pending_new_srv_start	188 D (1376) BT_GATT: gatt_add_pending_new_srv_start
189	D (1397) BT_GATT: enqueue a new pending new srv start	189 D (1386) BT_GATT: enqueue a new pending new srv start
190	D (1407) BT_GATT: Add a new srv chg item	190 D (1386) BT_GATT: Add a new srv chg item
191		191
192	D (1407) BT_GATT: allocate_svc_db_buf allocating extra buffer	192 D (1396) BT_GATT: allocate_svc_db_buf allocating extra buffer
193	D (1417) BT_GATT: gatts_init_service_db	193 D (1396) BT_GATT: gatts_init_service_db
194		194
195	D (1417) BT_GATT: s_hdl = 45 num_handle = 37	195 D (1406) BT_GATT: s_hdl = 45 num_handle = 37
196		196
197	D (1427) BT_GATT: add_service_declaration	197 D (1406) BT_GATT: add_service_declaration
198	D (1427) BT_GATT: allocate attr 20 bytes	198 D (1416) BT_GATT: allocate attr 20 bytes
199		199
200	D (1427) BT_GATT: =====> handle = [0x002d] uuid16 = [0x2800] perm=0x01	200 D (1416) BT_GATT: =====> handle = [0x002d] uuid16 = [0x2800] perm=0x01
201		201
202	D (1437) BT_GATT: gatts_add_included_service: s_hdl = 0x0028 e_hdl = 0x002c uuid = 0x180f	202 D (1426) BT_GATT: gatts_add_included_service: s_hdl = 0x0028 e_hdl = 0x002c uuid = 0x180f
203	D (1447) BT_GATT: allocate attr 20 bytes	203 D (1426) BT_GATT: allocate attr 20 bytes
204		204
205	D (1447) BT_GATT: =====> handle = [0x002e] uuid16 = [0x2802] perm=0x01	205 D (1436) BT_GATT: =====> handle = [0x002e] uuid16 = [0x2802] perm=0x01
206		206
207	D (1457) BT_GATT: gatts_add_characteristic perm=0x1 property=0xa	207 D (1446) BT_GATT: gatts_add_characteristic perm=0x1 property=0xa
208		208
209	D (1467) BT_GATT: allocate attr 20 bytes	209 D (1446) BT_GATT: allocate attr 20 bytes
210		210

Araxis Merge file comparison between
No File and **No File**

210		210
211	D (1467) BT_GATT: =====> handle = [0x002f] uuid16 = [0x2803] perm=0x01	211 D (1456) BT_GATT: =====> handle = [0x002f] uuid16 = [0x2803] perm=0x01
212		212
213	D (1477) BT_GATT: allocate attr 20 bytes	213 D (1456) BT_GATT: allocate attr 20 bytes
214		214
215	D (1477) BT_GATT: =====> handle = [0x0030] uuid16 = [0x2a4a] perm=0x01	215 D (1466) BT_GATT: =====> handle = [0x0030] uuid16 = [0x2a4a] perm=0x01
216		216
217	D (1487) BT_GATT: allocate_svc_db_buf allocating extra buffer	217 D (1466) BT_GATT: allocate_svc_db_buf allocating extra buffer
218	D (1487) BT_GATT: attr_val->attr_len = 4, attr_val->attr_max_len = 4	218 D (1476) BT_GATT: attr_val->attr_len = 4, attr_val->attr_max_len = 4
219		219
220	D (1497) BT_GATT: attribute handle = 30	220 D (1486) BT_GATT: attribute handle = 30
221		221
222	D (1497) BT_GATT: gatts_add_characteristic perm=0x10 property=0x8	222 D (1486) BT_GATT: gatts_add_characteristic perm=0x10 property=0x8
223		223
224	D (1507) BT_GATT: allocate attr 20 bytes	224 D (1496) BT_GATT: allocate attr 20 bytes
225		225
226	D (1507) BT_GATT: =====> handle = [0x0031] uuid16 = [0x2803] perm=0x01	226 D (1496) BT_GATT: =====> handle = [0x0031] uuid16 = [0x2803] perm=0x01
227		227
228	D (1517) BT_GATT: allocate attr 20 bytes	228 D (1506) BT_GATT: allocate attr 20 bytes
229		229
230	D (1527) BT_GATT: =====> handle = [0x0032] uuid16 = [0x2a4c] perm=0x10	230 D (1506) BT_GATT: =====> handle = [0x0032] uuid16 = [0x2a4c] perm=0x10
231		231
232	D (1527) BT_GATT: attr_val->attr_len = 0, attr_val->attr_max_len = 1	232 D (1516) BT_GATT: attr_val->attr_len = 0, attr_val->attr_max_len = 1
233		233
234	D (1537) BT_GATT: attribute handle = 32	234 D (1526) BT_GATT: attribute handle = 32
235		235
236	D (1537) BT_GATT: gatts_add_characteristic perm=0x1 property=0x2	236 D (1526) BT_GATT: gatts_add_characteristic perm=0x1 property=0x2
237		237
238	D (1547) BT_GATT: allocate attr 20 bytes	238 D (1536) BT_GATT: allocate attr 20 bytes
239		239
240	D (1547) BT_GATT: =====> handle = [0x0033] uuid16 = [0x2803] perm=0x01	240 D (1536) BT_GATT: =====> handle = [0x0033] uuid16 = [0x2803] perm=0x01
241		241
242	D (1557) BT_GATT: allocate attr 20 bytes	242 D (1546) BT_GATT: allocate attr 20 bytes
243		243
244	D (1557) BT_GATT: =====> handle = [0x0034] uuid16 = [0x2a4b] perm=0x01	244 D (1546) BT_GATT: =====> handle = [0x0034] uuid16 = [0x2a4b] perm=0x01
245		245
246	D (1567) BT_GATT: attr_val->attr_len = e6, attr_val->attr_max_len = 200	246 D (1556) BT_GATT: attr_val->attr_len = e6, attr_val->attr_max_len = 200
247		247
248	D (1577) BT_GATT: attribute handle = 34	248 D (1556) BT_GATT: attribute handle = 34
249		249
250	D (1577) BT_GATT: gatts_add_char_descr uuid=0x2907	250 D (1566) BT_GATT: gatts_add_char_descr uuid=0x2907
251		251
252	D (1587) BT_GATT: allocate attr 20 bytes	252 D (1566) BT_GATT: allocate attr 20 bytes
253		253

Araxis Merge file comparison between
No File and **No File**

253		253
254	D (1587) BT_GATT: allocate_svc_db_buf allocating extra buffer	254 D (1576) BT_GATT: allocate_svc_db_buf allocating extra buffer
255	D (1597) BT_GATT: =====> handle = [0x0035] uuid16 = [0x2907] perm=0x01	255 D (1576) BT_GATT: =====> handle = [0x0035] uuid16 = [0x2907] perm=0x01
256		256
257	D (1597) BT_GATT: gatts_add_characteristic perm=0x11 property=0xa	257 D (1586) BT_GATT: gatts_add_characteristic perm=0x11 property=0xa
258		258
259	D (1607) BT_GATT: allocate attr 20 bytes	259 D (1596) BT_GATT: allocate attr 20 bytes
260		260
261	D (1607) BT_GATT: =====> handle = [0x0036] uuid16 = [0x2803] perm=0x01	261 D (1596) BT_GATT: =====> handle = [0x0036] uuid16 = [0x2803] perm=0x01
262		262
263	D (1617) BT_GATT: allocate attr 20 bytes	263 D (1606) BT_GATT: allocate attr 20 bytes
264		264
265	D (1627) BT_GATT: =====> handle = [0x0037] uuid16 = [0x2a4e] perm=0x11	265 D (1606) BT_GATT: =====> handle = [0x0037] uuid16 = [0x2a4e] perm=0x11
266		266
267	D (1627) BT_GATT: attr_val->attr_len = 1, attr_val->attr_max_len = 1	267 D (1616) BT_GATT: attr_val->attr_len = 1, attr_val->attr_max_len = 1
268		268
269	D (1637) BT_GATT: attribute handle = 37	269 D (1616) BT_GATT: attribute handle = 37
270		270
271	D (1637) BT_GATT: gatts_add_characteristic perm=0x1 property=0x12	271 D (1626) BT_GATT: gatts_add_characteristic perm=0x1 property=0x12
272		272
273	D (1647) BT_GATT: allocate attr 20 bytes	273 D (1636) BT_GATT: allocate attr 20 bytes
274		274
275	D (1647) BT_GATT: =====> handle = [0x0038] uuid16 = [0x2803] perm=0x01	275 D (1636) BT_GATT: =====> handle = [0x0038] uuid16 = [0x2803] perm=0x01
276		276
277	D (1657) BT_GATT: allocate attr 20 bytes	277 D (1646) BT_GATT: allocate attr 20 bytes
278		278
279	D (1657) BT_GATT: =====> handle = [0x0039] uuid16 = [0x2a4d] perm=0x01	279 D (1646) BT_GATT: =====> handle = [0x0039] uuid16 = [0x2a4d] perm=0x01
280		280
281	D (1667) BT_GATT: allocate_svc_db_buf allocating extra buffer	281 D (1656) BT_GATT: allocate_svc_db_buf allocating extra buffer
282	D (1677) BT_GATT: attr_val->attr_len = 0, attr_val->attr_max_len = 2d	282 D (1656) BT_GATT: attr_val->attr_len = 0, attr_val->attr_max_len = 2d
283		283
284	D (1677) BT_GATT: attribute handle = 39	284 D (1666) BT_GATT: attribute handle = 39
285		285
286	D (1687) BT_GATT: gatts_add_char_descr uuid=0x2902	286 D (1666) BT_GATT: gatts_add_char_descr uuid=0x2902
287		287
288	D (1687) BT_GATT: allocate attr 20 bytes	288 D (1676) BT_GATT: allocate attr 20 bytes
289		289
290	D (1697) BT_GATT: =====> handle = [0x003a] uuid16 = [0x2902] perm=0x11	290 D (1676) BT_GATT: =====> handle = [0x003a] uuid16 = [0x2902] perm=0x11
291		291
292	D (1697) BT_GATT: gatts_add_char_descr uuid=0x2908	292 D (1686) BT_GATT: gatts_add_char_descr uuid=0x2908
293		293
294	D (1707) BT_GATT: allocate attr 20 bytes	294 D (1686) BT_GATT: allocate attr 20 bytes
295		295
296	D (1707) BT_GATT: =====> handle = [0x003b] uuid16 = [0x2908] perm=0x01	296 D (1696) BT_GATT: =====> handle = [0x003b] uuid16 = [0x2908] perm=0x01

Araxis Merge file comparison between No File and No File

296 D (1707) BT_GATT: =====> handle = [0x003b] uuid16 = [0x2908] perm=0x01 297	296 D (1696) BT_GATT: =====> handle = [0x003b] uuid16 = [0x2908] perm=0x01 297
298 D (1717) BT_GATT: gatts_add_characteristic perm=0x1 property=0x12 299	298 D (1706) BT_GATT: gatts_add_characteristic perm=0x1 property=0x12 299
300 D (1727) BT_GATT: allocate attr 20 bytes 301	300 D (1706) BT_GATT: allocate attr 20 bytes 301
302 D (1727) BT_GATT: =====> handle = [0x003c] uuid16 = [0x2803] perm=0x01 303	302 D (1716) BT_GATT: =====> handle = [0x003c] uuid16 = [0x2803] perm=0x01 303
304 D (1737) BT_GATT: allocate attr 20 bytes 305	304 D (1716) BT_GATT: allocate attr 20 bytes 305
306 D (1737) BT_GATT: =====> handle = [0x003d] uuid16 = [0x2a4d] perm=0x01 307	306 D (1726) BT_GATT: =====> handle = [0x003d] uuid16 = [0x2a4d] perm=0x01 307
308 D (1747) BT_GATT: attr_val->attr_len = 0, attr_val->attr_max_len = 2d 309	308 D (1726) BT_GATT: attr_val->attr_len = 0, attr_val->attr_max_len = 2d 309
310 D (1747) BT_GATT: attribute handle = 3d 311	310 D (1736) BT_GATT: attribute handle = 3d 311
312 D (1757) BT_GATT: gatts_add_char_descr uuid=0x2902 313	312 D (1736) BT_GATT: gatts_add_char_descr uuid=0x2902 313
314 D (1757) BT_GATT: allocate attr 20 bytes 315	314 D (1746) BT_GATT: allocate attr 20 bytes 315
316 D (1767) BT_GATT: allocate_svc_db_buf allocating extra buffer 317 D (1767) BT_GATT: =====> handle = [0x003e] uuid16 = [0x2902] perm=0x11 318	316 D (1746) BT_GATT: allocate_svc_db_buf allocating extra buffer 317 D (1756) BT_GATT: =====> handle = [0x003e] uuid16 = [0x2902] perm=0x11 318
319 D (1777) BT_GATT: gatts_add_char_descr uuid=0x2908 320	319 D (1766) BT_GATT: gatts_add_char_descr uuid=0x2908 320
321 D (1787) BT_GATT: allocate attr 20 bytes 322	321 D (1766) BT_GATT: allocate attr 20 bytes 322
323 D (1787) BT_GATT: =====> handle = [0x003f] uuid16 = [0x2908] perm=0x01 324	323 D (1776) BT_GATT: =====> handle = [0x003f] uuid16 = [0x2908] perm=0x01 324
325 D (1797) BT_GATT: gatts_add_characteristic perm=0x11 property=0xa 326	325 D (1776) BT_GATT: gatts_add_characteristic perm=0x11 property=0xa 326
327 D (1797) BT_GATT: allocate attr 20 bytes 328	327 D (1786) BT_GATT: allocate attr 20 bytes 328
329 D (1807) BT_GATT: =====> handle = [0x0040] uuid16 = [0x2803] perm=0x01 330	329 D (1786) BT_GATT: =====> handle = [0x0040] uuid16 = [0x2803] perm=0x01 330
331 D (1807) BT_GATT: allocate attr 20 bytes 332	331 D (1796) BT_GATT: allocate attr 20 bytes 332
333 D (1817) BT_GATT: =====> handle = [0x0041] uuid16 = [0x2a4d] perm=0x11 334	333 D (1796) BT_GATT: =====> handle = [0x0041] uuid16 = [0x2a4d] perm=0x11 334
335 D (1817) BT_GATT: attr_val->attr_len = 0, attr_val->attr_max_len = 2d 336	335 D (1806) BT_GATT: attr_val->attr_len = 0, attr_val->attr_max_len = 2d 336
337 D (1827) BT_GATT: attribute handle = 41 338	337 D (1816) BT_GATT: attribute handle = 41 338
339 D (1837) BT_GATT: gatts add char descr uuid=0x2908	339 D (1816) BT_GATT: gatts add char descr uuid=0x2908

Araxis Merge file comparison between
No File and **No File**

339 D (1837) BT_GATT: gatts_add_char_descr uuid=0x2908 340	339 D (1816) BT_GATT: gatts_add_char_descr uuid=0x2908 340
341 D (1837) BT_GATT: allocate attr 20 bytes 342	341 D (1826) BT_GATT: allocate attr 20 bytes 342
343 D (1837) BT_GATT: =====> handle = [0x0042] uuid16 = [0x2908] perm=0x01 344	343 D (1826) BT_GATT: =====> handle = [0x0042] uuid16 = [0x2908] perm=0x01 344
345 D (1847) BT_GATT: allocate_svc_db_buf allocating extra buffer 346 D (1857) BT_GATT: gatts_add_characteristic perm=0x1 property=0x12 347	345 D (1836) BT_GATT: allocate_svc_db_buf allocating extra buffer 346 D (1836) BT_GATT: gatts_add_characteristic perm=0x1 property=0x12 347
348 D (1857) BT_GATT: allocate attr 20 bytes 349	348 D (1846) BT_GATT: allocate attr 20 bytes 349
350 D (1867) BT_GATT: =====> handle = [0x0043] uuid16 = [0x2803] perm=0x01 351	350 D (1846) BT_GATT: =====> handle = [0x0043] uuid16 = [0x2803] perm=0x01 351
352 D (1867) BT_GATT: allocate attr 20 bytes 353	352 D (1856) BT_GATT: allocate attr 20 bytes 353
354 D (1877) BT_GATT: =====> handle = [0x0044] uuid16 = [0x2a4d] perm=0x01 355	354 D (1856) BT_GATT: =====> handle = [0x0044] uuid16 = [0x2a4d] perm=0x01 355
356 D (1887) BT_GATT: attr_val->attr_len = 0, attr_val->attr_max_len = 2d 357	356 D (1866) BT_GATT: attr_val->attr_len = 0, attr_val->attr_max_len = 2d 357
358 D (1887) BT_GATT: attribute handle = 44 359	358 D (1876) BT_GATT: attribute handle = 44 359
360 D (1897) BT_GATT: gatts_add_char_descr uuid=0x2902 361	360 D (1876) BT_GATT: gatts_add_char_descr uuid=0x2902 361
362 D (1897) BT_GATT: allocate attr 20 bytes 363	362 D (1886) BT_GATT: allocate attr 20 bytes 363
364 D (1907) BT_GATT: =====> handle = [0x0045] uuid16 = [0x2902] perm=0x11 365	364 D (1886) BT_GATT: =====> handle = [0x0045] uuid16 = [0x2902] perm=0x11 365
366 D (1907) BT_GATT: gatts_add_char_descr uuid=0x2908 367	366 D (1896) BT_GATT: gatts_add_char_descr uuid=0x2908 367
368 D (1917) BT_GATT: allocate attr 20 bytes 369	368 D (1896) BT_GATT: allocate attr 20 bytes 369
370 D (1917) BT_GATT: =====> handle = [0x0046] uuid16 = [0x2908] perm=0x01 371	370 D (1906) BT_GATT: =====> handle = [0x0046] uuid16 = [0x2908] perm=0x01 371
372 D (1927) BT_GATT: gatts_add_characteristic perm=0x1 property=0x12 373	372 D (1906) BT_GATT: gatts_add_characteristic perm=0x1 property=0x12 373
374 D (1927) BT_GATT: allocate attr 20 bytes 375	374 D (1916) BT_GATT: allocate attr 20 bytes 375
376 D (1937) BT_GATT: allocate_svc_db_buf allocating extra buffer 377 D (1937) BT_GATT: =====> handle = [0x0047] uuid16 = [0x2803] perm=0x01 378	376 D (1916) BT_GATT: allocate_svc_db_buf allocating extra buffer 377 D (1926) BT_GATT: =====> handle = [0x0047] uuid16 = [0x2803] perm=0x01 378
379 D (1947) BT_GATT: allocate attr 20 bytes 380	379 D (1936) BT_GATT: allocate attr 20 bytes 380
381 D (1957) BT_GATT: =====> handle = [0x0048] uuid16 = [0x2a22] perm=0x01 382	381 D (1936) BT_GATT: =====> handle = [0x0048] uuid16 = [0x2a22] perm=0x01 382

Araxis Merge file comparison between
No File and **No File**

382		382
383	D (1957) BT_GATT: attr_val->attr_len = 0, attr_val->attr_max_len = 8	383 D (1946) BT_GATT: attr_val->attr_len = 0, attr_val->attr_max_len = 8
384		384
385	D (1967) BT_GATT: attribute handle = 48	385 D (1946) BT_GATT: attribute handle = 48
386		386
387	D (1967) BT_GATT: gatts_add_char_descr uuid=0x2902	387 D (1956) BT_GATT: gatts_add_char_descr uuid=0x2902
388		388
389	D (1977) BT_GATT: allocate attr 20 bytes	389 D (1956) BT_GATT: allocate attr 20 bytes
390		390
391	D (1977) BT_GATT: =====> handle = [0x0049] uuid16 = [0x2902] perm=0x11	391 D (1966) BT_GATT: =====> handle = [0x0049] uuid16 = [0x2902] perm=0x11
392		392
393	D (1987) BT_GATT: gatts_add_characteristic perm=0x11 property=0xa	393 D (1966) BT_GATT: gatts_add_characteristic perm=0x11 property=0xa
394		394
395	D (1987) BT_GATT: allocate attr 20 bytes	395 D (1976) BT_GATT: allocate attr 20 bytes
396		396
397	D (1997) BT_GATT: =====> handle = [0x004a] uuid16 = [0x2803] perm=0x01	397 D (1986) BT_GATT: =====> handle = [0x004a] uuid16 = [0x2803] perm=0x01
398		398
399	D (2007) BT_GATT: allocate attr 20 bytes	399 D (1986) BT_GATT: allocate attr 20 bytes
400		400
401	D (2007) BT_GATT: =====> handle = [0x004b] uuid16 = [0x2a32] perm=0x11	401 D (1996) BT_GATT: =====> handle = [0x004b] uuid16 = [0x2a32] perm=0x11
402		402
403	D (2017) BT_GATT: allocate_svc_db_buf allocating extra buffer	403 D (1996) BT_GATT: allocate_svc_db_buf allocating extra buffer
404	D (2017) BT_GATT: attr_val->attr_len = 0, attr_val->attr_max_len = 8	404 D (2006) BT_GATT: attr_val->attr_len = 0, attr_val->attr_max_len = 8
405		405
406	D (2027) BT_GATT: attribute handle = 4b	406 D (2016) BT_GATT: attribute handle = 4b
407		407
408	D (2027) BT_GATT: gatts_add_characteristic perm=0x1 property=0x12	408 D (2016) BT_GATT: gatts_add_characteristic perm=0x1 property=0x12
409		409
410	D (2037) BT_GATT: allocate attr 20 bytes	410 D (2026) BT_GATT: allocate attr 20 bytes
411		411
412	D (2037) BT_GATT: =====> handle = [0x004c] uuid16 = [0x2803] perm=0x01	412 D (2026) BT_GATT: =====> handle = [0x004c] uuid16 = [0x2803] perm=0x01
413		413
414	D (2047) BT_GATT: allocate attr 20 bytes	414 D (2036) BT_GATT: allocate attr 20 bytes
415		415
416	D (2047) BT_GATT: =====> handle = [0x004d] uuid16 = [0x2a33] perm=0x01	416 D (2036) BT_GATT: =====> handle = [0x004d] uuid16 = [0x2a33] perm=0x01
417		417
418	D (2057) BT_GATT: attr_val->attr_len = 0, attr_val->attr_max_len = 8	418 D (2046) BT_GATT: attr_val->attr_len = 0, attr_val->attr_max_len = 8
419		419
420	D (2067) BT_GATT: attribute handle = 4d	420 D (2046) BT_GATT: attribute handle = 4d
421		421
422	D (2067) BT_GATT: gatts_add_char_descr uuid=0x2902	422 D (2056) BT_GATT: gatts_add_char_descr uuid=0x2902
423		423
424	D (2077) BT_GATT: allocate attr 20 bytes	424 D (2056) BT_GATT: allocate attr 20 bytes
425		425

Araxis Merge file comparison between
No File and **No File**

425		425	
426	D (2077) BT_GATT: =====> handle = [0x004e] uuid16 = [0x2902] perm=0x11	426	D (2066) BT_GATT: =====> handle = [0x004e] uuid16 = [0x2902] perm=0x11
427		427	
428	D (2087) BT_GATT: gatts_add_characteristic perm=0x1 property=0xa	428	D (2066) BT_GATT: gatts_add_characteristic perm=0x1 property=0xa
429		429	
430	D (2087) BT_GATT: allocate attr 20 bytes	430	D (2076) BT_GATT: allocate attr 20 bytes
431		431	
432	D (2097) BT_GATT: =====> handle = [0x004f] uuid16 = [0x2803] perm=0x01	432	D (2076) BT_GATT: =====> handle = [0x004f] uuid16 = [0x2803] perm=0x01
433		433	
434	D (2107) BT_GATT: allocate attr 20 bytes	434	D (2086) BT_GATT: allocate attr 20 bytes
435		435	
436	D (2107) BT_GATT: allocate_svc_db_buf allocating extra buffer	436	D (2096) BT_GATT: allocate_svc_db_buf allocating extra buffer
437	D (2117) BT_GATT: =====> handle = [0x0050] uuid16 = [0x2a4d] perm=0x01	437	D (2096) BT_GATT: =====> handle = [0x0050] uuid16 = [0x2a4d] perm=0x01
438		438	
439	D (2117) BT_GATT: attr_val->attr_len = 0, attr_val->attr_max_len = 2d	439	D (2106) BT_GATT: attr_val->attr_len = 0, attr_val->attr_max_len = 2d
440		440	
441	D (2127) BT_GATT: attribute handle = 50	441	D (2106) BT_GATT: attribute handle = 50
442		442	
443	D (2127) BT_GATT: gatts_add_char_descr uuid=0x2908	443	D (2116) BT_GATT: gatts_add_char_descr uuid=0x2908
444		444	
445	D (2137) BT_GATT: allocate attr 20 bytes	445	D (2116) BT_GATT: allocate attr 20 bytes
446		446	
447	D (2137) BT_GATT: =====> handle = [0x0051] uuid16 = [0x2908] perm=0x01	447	D (2126) BT_GATT: =====> handle = [0x0051] uuid16 = [0x2908] perm=0x01
448		448	
449	I (2147) HID_DEVICE: hid svc handle = 2d	449	I (2136) HID_DEVICE: hid svc handle = 2d
450	E (2147) HID_DEVICE: hid_add_id_tbl	450	E (2136) HID_DEVICE: hid_add_id_tbl
451	I (2157) BT_GATT: GATTS_StartService	451	I (2136) BT_GATT: GATTS_StartService
452	D (2157) BT_GATT: total buffer in db [2]	452	D (2146) BT_GATT: total buffer in db [2]
453	D (2167) BT_GATT: allocated i_sreg=2	453	D (2146) BT_GATT: allocated i_sreg=2
454		454	
455	D (2167) BT_GATT: s_hdl=40 e_hdl=44 type=0x2800 svc_inst=0 sdp_hdl=0x0	455	D (2156) BT_GATT: s_hdl=40 e_hdl=44 type=0x2800 svc_inst=0 sdp_hdl=0x0
456		456	
457	D (2177) BT_GATT: gatt_sr_is_new_srv_chg: Yes	457	D (2156) BT_GATT: gatt_sr_is_new_srv_chg: Yes
458	D (2177) BT_GATT: gatt_proc_srv_chg	458	D (2166) BT_GATT: gatt_proc_srv_chg
459	D (2177) BT_GATT: gatt_set_srv_chg	459	D (2166) BT_GATT: gatt_set_srv_chg
460	D (2187) BT_GATT: gatt_find_the_connected_bda start_idx=0	460	D (2166) BT_GATT: gatt_find_the_connected_bda start_idx=0
461	D (2187) BT_GATT: gatt_find_the_connected_bda found=0 found_idx=4	461	D (2176) BT_GATT: gatt_find_the_connected_bda found=0 found_idx=4
462	I (2197) BT_GATT: GATTS_StartService	462	I (2186) BT_GATT: GATTS_StartService
463	D (2197) BT_GATT: total buffer in db [9]	463	D (2186) BT_GATT: total buffer in db [9]
464	D (2207) BT_GATT: allocated i_sreg=3	464	D (2186) BT_GATT: allocated i_sreg=3
465		465	
466	D (2207) BT_GATT: s_hdl=45 e_hdl=81 type=0x2800 svc_inst=0 sdp_hdl=0x0	466	D (2196) BT_GATT: s_hdl=45 e_hdl=81 type=0x2800 svc_inst=0 sdp_hdl=0x0
467		467	
468	D (2217) BT_GATT: gatt sr is new srv chg: Yes	468	D (2196) BT_GATT: gatt sr is new srv chg: Yes

Araxis Merge file comparison between
No File and No File

```
468 D (2217) BT_GATT: gatt_sr_is_new_srv_chg: Yes
469 D (2217) BT_GATT: gatt_proc_srv_chg
470 D (2227) BT_GATT: gatt_set_srv_chg
471 D (2227) BT_GATT: gatt_find_the_connected_bda start_idx=0
472 D (2237) BT_GATT: gatt_find_the_connected_bda found=0 found_idx=4
473 E (2237) FABI/FLIPMOUSE: gap_event_handler(), ESP_GAP_BLE_ADV_START_COM
  PLETE_EVT
474 V (2247) intr_alloc: esp_intr_alloc_intrstatus (cpu 1): checking args
475 V (2257) intr_alloc: esp_intr_alloc_intrstatus (cpu 1): Args okay. Resu
  lting flags 0xE
476 D (2257) intr_alloc: Connected src 34 to int 3 (cpu 1)
477 D (13407) BT_GATT: GATT ATT protocol channel with BDA: 9cb6d0e89cdc i
  s connected
478 D (13407) BT_GATT: gatt_is_bda_in_the_srv_chg_clt_list :9c-b6-d0-e8-9c-
  dc
479 D (13417) BT_GATT: gatt_add_srv_chg_clt
480 D (13417) BT_GATT: enqueue a srv chg client
481 D (13427) BT_GATT: gatt_set_ch_state: old=0 new=4
482 D (13427) BT_GATT: gatt_connect_cback: from 9cb6d0e89cdc connected:1 co
  nn_id=1 reason = 0x0000
483 D (13437) BT_GATT: gatt_get_ch_state: ch_state=4
484 I (13437) BT_GATT: GATT_GetConnIdIfConnected status=1
485
486 D (13447) BT_GATT: gatt_num_apps_hold_link num=0
487 D (13457) BT_GATT: gatt_get_ch_state: ch_state=4
488 D (13457) BT_GATT: gatt_request_cback
489 D (13457) BT_GATT: Get MTU exchange new mtu size: 517
490 I (13467) BT_GATT: GATT_GetConnectionInfor conn_id=4
491 I (13467) BT_GATT: GATT_GetConnectionInfor conn_id=5
492 D (13477) BT_GATT: gatt_get_ch_state: ch_state=4
493 I (13487) FABI/FLIPMOUSE: ESP_GAP_BLE_SEC_REQ_EVT
494 I (13487) FABI/FLIPMOUSE: The passkey Notify number:514780
495 D (13497) BT_GATT: gatt_get_ch_state: ch_state=4
496 D (13507) BT_GATT: gatt_get_ch_state: ch_state=4
497 D (13527) BT_GATT: gatt_get_ch_state: ch_state=4
498 D (13537) BT_GATT: gatt_get_ch_state: ch_state=4
499 D (13557) BT_GATT: gatt_get_ch_state: ch_state=4
500 D (13557) BT_GATT: gatts_process_read_by_type_req, op_code =8, len = 0
501
502 D (13557) BT_GATT: read_attr_value uuid=0x2803 perm=0x1 sec_flag=0x10 o
  ffsset=0 read_long=0
503
504 D (13577) BT_GATT: gatt_get_ch_state: ch_state=4
505 D (13577) BT_GATT: gatts process read by type req, op code =8, len = 0
```

```
468 D (2196) BT_GATT: gatt_sr_is_new_srv_chg: Yes
469 D (2206) BT_GATT: gatt_proc_srv_chg
470 D (2206) BT_GATT: gatt_set_srv_chg
471 D (2216) BT_GATT: gatt_find_the_connected_bda start_idx=0
472 D (2216) BT_GATT: gatt_find_the_connected_bda found=0 found_idx=4
473 E (2226) FABI/FLIPMOUSE: gap_event_handler(), ESP_GAP_BLE_ADV_START_COM
  PLETE_EVT
474 V (2236) intr_alloc: esp_intr_alloc_intrstatus (cpu 1): checking args
475 V (2236) intr_alloc: esp_intr_alloc_intrstatus (cpu 1): Args okay. Resu
  lting flags 0xE
476 D (2246) intr_alloc: Connected src 34 to int 3 (cpu 1)
477 D (19776) BT_GATT: GATT ATT protocol channel with BDA: 5032377e3bcf i
  s connected
478 D (19776) BT_GATT: gatt_is_bda_in_the_srv_chg_clt_list :50-32-37-7e-3b-
  cf
479 D (19786) BT_GATT: gatt_add_srv_chg_clt
480 D (19786) BT_GATT: enqueue a srv chg client
481 D (19786) BT_GATT: gatt_set_ch_state: old=0 new=4
482 D (19796) BT_GATT: gatt_connect_cback: from 5032377e3bcf connected:1 co
  nn_id=1 reason = 0x0000
483 D (19806) BT_GATT: gatt_get_ch_state: ch_state=4
484 I (19806) BT_GATT: GATT_GetConnIdIfConnected status=1
485
486 D (19816) BT_GATT: gatt_num_apps_hold_link num=0
487 D (19836) BT_GATT: gatt_get_ch_state: ch_state=4
488 D (19836) BT_GATT: gatt_request_cback
489 D (19836) BT_GATT: Get MTU exchange new mtu size: 158
490 I (19846) BT_GATT: GATT_GetConnectionInfor conn_id=4
491 I (19846) BT_GATT: GATT_GetConnectionInfor conn_id=5
492 D (19896) BT_GATT: gatt_get_ch_state: ch_state=4
493 D (19896) BT_GATT: Use 0xFFFF for the last primary attribute
494 D (19956) BT_GATT: gatt_get_ch_state: ch_state=4
495 D (19956) BT_GATT: gatts_process_read_by_type_req, op_code =8, len = 0
496
497 D (19956) BT_GATT: read_attr_value uuid=0x2803 perm=0x1 sec_flag=0x0 of
  fset=0 read_long=0
498
499 D (20016) BT_GATT: gatt_get_ch_state: ch_state=4
500 D (20016) BT_GATT: gatts process read by type req, op code =8, len = 0
```

Araxis Merge file comparison between
No File and **No File**

505 D (13577) BT_GATT: gatts_process_read_by_type_req, op_code =8, len = 0 506	500 D (20016) BT_GATT: gatts_process_read_by_type_req, op_code =8, len = 0 501
507 D (13587) BT_GATT: gatt_get_ch_state: ch_state=4	502 D (20076) BT_GATT: gatt_get_ch_state: ch_state=4
508 D (13587) BT_GATT: gatts_process_read_by_type_req, op_code =8, len = 0 509	503 D (20136) BT_GATT: gatt_get_ch_state: ch_state=4
510 D (13587) BT_GATT: read_attr_value uuid=0x2803 perm=0x1 sec_flag=0x10 of ffset=0 read_long=0	504 D (20136) BT_GATT: gatts_process_read_by_type_req, op_code =8, len = 0 505
511	506 D (20136) BT_GATT: read_attr_value uuid=0x2803 perm=0x1 sec_flag=0x0 of fset=0 read_long=0
512 D (13597) BT_GATT: read_attr_value uuid=0x2803 perm=0x1 sec_flag=0x10 of ffset=0 read_long=0	507
513	508 D (20146) BT_GATT: read_attr_value uuid=0x2803 perm=0x1 sec_flag=0x0 of fset=0 read_long=0
514 D (13607) BT_GATT: read_attr_value uuid=0x2803 perm=0x1 sec_flag=0x10 of ffset=0 read_long=0	509
515	510 D (20156) BT_GATT: read_attr_value uuid=0x2803 perm=0x1 sec_flag=0x0 of fset=0 read_long=0
516 D (13627) BT_GATT: gatt_get_ch_state: ch_state=4	511
517 D (13627) BT_GATT: gatts_process_read_by_type_req, op_code =8, len = 0 518	512 D (20166) BT_GATT: read_attr_value uuid=0x2803 perm=0x1 sec_flag=0x0 of fset=0 read_long=0
519 D (13647) BT_GATT: gatt_get_ch_state: ch_state=4	513
520 D (13657) BT_GATT: gatt_get_ch_state: ch_state=4	514 D (20176) BT_GATT: read_attr_value uuid=0x2803 perm=0x1 sec_flag=0x0 of fset=0 read_long=0
521 D (13657) BT_GATT: read_attr_value uuid=0x2a00 perm=0x1 sec_flag=0x10 of ffset=0 read_long=0	515
522	516 D (20186) BT_GATT: read_attr_value uuid=0x2803 perm=0x1 sec_flag=0x0 of fset=0 read_long=0
523 I (13657) BT_GATT: GATTS_SendRsp: conn_id: 2 trans_id: 1 Status: 0x00 00	517
524	518 D (20186) BT_GATT: read_attr_value uuid=0x2803 perm=0x1 sec_flag=0x0 of fset=0 read_long=0
525 D (13667) BT_GATT: gatt_sr_process_app_rsp gatt_if=2	519
526	520 D (20196) BT_GATT: read_attr_value uuid=0x2803 perm=0x1 sec_flag=0x0 of fset=0 read_long=0
527 D (13677) BT_GATT: gatt_dequeue_sr_cmd	521
528 D (13677) BT_GATT: gatt_sr_process_app_rsp ret_code=0	522 D (20206) BT_GATT: read_attr_value uuid=0x2803 perm=0x1 sec_flag=0x0 of fset=0 read_long=0
529	523
530 D (13687) BT_GATT: gatt_get_ch_state: ch_state=4	524 D (20216) BT_GATT: read_attr_value uuid=0x2803 perm=0x1 sec_flag=0x0 of fset=0 read_long=0
531 D (13687) BT_GATT: read_attr_value uuid=0x2a01 perm=0x1 sec_flag=0x10 of ffset=0 read_long=0	525
532	526 D (20226) BT_GATT: read attr value uuid=0x2803 perm=0x1 sec_flag=0x0 of
533 I (13697) BT_GATT: GATTS_SendRsp: conn_id: 2 trans_id: 2 Status: 0x00 00	
534	
535 D (13707) BT_GATT: gatt sr process app rsp gatt if=2	

Araxis Merge file comparison between
No File and No File

535 D (13707) BT_GATT: gatt_sr_process_app_rsp gatt_if=2	526 D (20226) BT_GATT: read_attr_value uuid=0x2803 perm=0x1 sec_flag=0x0 of fset=0 read_long=0
536	527
537 D (13707) BT_GATT: gatt_dequeue_sr_cmd	528 D (20236) BT_GATT: read_attr_value uuid=0x2803 perm=0x1 sec_flag=0x0 of fset=0 read_long=0
538 D (13717) BT_GATT: gatt_sr_process_app_rsp ret_code=0	529
539	530 D (20286) BT_GATT: gatt_get_ch_state: ch_state=4
540 D (13727) BT_GATT: gatt_get_ch_state: ch_state=4	531 D (20286) BT_GATT: gatts_process_read_by_type_req, op_code =8, len = 0
541 D (13727) BT_GATT: read_attr_value uuid=0x2aa6 perm=0x1 sec_flag=0x10 o ffset=0 read_long=0	532
542	533 D (20346) BT_GATT: gatt_get_ch_state: ch_state=4
543 I (13727) BT_GATT: GATTSSendRsp: conn_id: 2 trans_id: 3 Status: 0x00 00	534 D (20346) BT_GATT: read_attr_value uuid=0x2a4a perm=0x1 sec_flag=0x0 of fset=0 read_long=0
544	535
545 D (13737) BT_GATT: gatt_sr_process_app_rsp gatt_if=2	536 I (20346) BT_GATT: GATT_GetConnectionInfor conn_id=5
546	537 D (20356) BT_GATT: gatt_dequeue_sr_cmd
547 D (13747) BT_GATT: gatt_dequeue_sr_cmd	538 D (20406) BT_GATT: gatt_get_ch_state: ch_state=4
548 D (13747) BT_GATT: gatt_sr_process_app_rsp ret_code=0	539 D (20466) BT_GATT: gatt_get_ch_state: ch_state=4
549	540 D (20466) BT_GATT: read_attr_value uuid=0x2a4b perm=0x1 sec_flag=0x0 of fset=0 read_long=0
	541
	542 I (20466) BT_GATT: GATT_GetConnectionInfor conn_id=5
	543 D (20476) BT_GATT: gatt_dequeue_sr_cmd
	544 D (20526) BT_GATT: gatt_get_ch_state: ch_state=4
	545 D (20526) BT_GATT: read_attr_value uuid=0x2a4b perm=0x1 sec_flag=0x0 of fset=157 read_long=1
	546
	547 I (20536) BT_GATT: GATT_GetConnectionInfor conn_id=5
	548 D (20536) BT_GATT: gatt_dequeue_sr_cmd
	549 D (20586) BT_GATT: gatt_get_ch_state: ch_state=4
	550 D (20646) BT_GATT: gatt_get_ch_state: ch_state=4
	551 D (20706) BT_GATT: gatt_get_ch_state: ch_state=4
	552 D (20766) BT_GATT: gatt_get_ch_state: ch_state=4
	553 D (20826) BT_GATT: gatt_get_ch_state: ch_state=4
	554 D (20886) BT_GATT: gatt_get_ch_state: ch_state=4
	555 D (20946) BT_GATT: gatt_get_ch_state: ch_state=4
	556 D (20946) BT_GATT: read_attr_value uuid=0x2908 perm=0x1 sec_flag=0x0 of fset=0 read_long=0
	557
	558 I (20946) BT_GATT: GATT_GetConnectionInfor conn_id=5
	559 D (20956) BT_GATT: gatt_dequeue_sr_cmd
	560 D (21006) BT_GATT: gatt_get ch state: ch state=4

```
560 D (21006) BT_GATT: gatt_get_ch_state: ch_state=4
561 D (21006) BT_GATT: read_attr_value uuid=0x2908 perm=0x1 sec_flag=0x0 of
   fset=0 read_long=0
562
563 I (21006) BT_GATT: GATT_GetConnectionInfor conn_id=5
564 D (21016) BT_GATT: gatt_dequeue_sr_cmd
565 D (21066) BT_GATT: gatt_get_ch_state: ch_state=4
566 D (21066) BT_GATT: read_attr_value uuid=0x2908 perm=0x1 sec_flag=0x0 of
   fset=0 read_long=0
567
568 I (21066) BT_GATT: GATT_GetConnectionInfor conn_id=5
569 D (21076) BT_GATT: gatt_dequeue_sr_cmd
570 D (21126) BT_GATT: gatt_get_ch_state: ch_state=4
571 D (21126) BT_GATT: read_attr_value uuid=0x2908 perm=0x1 sec_flag=0x0 of
   fset=0 read_long=0
572
573 I (21126) BT_GATT: GATT_GetConnectionInfor conn_id=5
574 D (21136) BT_GATT: gatt_dequeue_sr_cmd
575 D (21186) BT_GATT: gatt_get_ch_state: ch_state=4
576 D (21186) BT_GATT: read_attr_value uuid=0x2908 perm=0x1 sec_flag=0x0 of
   fset=0 read_long=0
577
578 I (21186) BT_GATT: GATT_GetConnectionInfor conn_id=5
579 D (21196) BT_GATT: gatt_dequeue_sr_cmd
580 D (21246) BT_GATT: gatt_get_ch_state: ch_state=4
581 D (21246) BT_GATT: gatts_write_attr_perm_check op_code=0x12 handle=0x00
   3a offset=0 len=2 sec_flag=0x0 key_size=0
582 D (21256) BT_GATT: gatts_write_attr_perm_check p_attr->permission =0x00
   11 min_key_size==0x0000
583 I (21266) BT_GATT: GATT_GetConnectionInfor conn_id=5
584 D (21266) BT_GATT: gatt_dequeue_sr_cmd
585 D (21306) BT_GATT: gatt_get_ch_state: ch_state=4
586 D (21306) BT_GATT: gatts_write_attr_perm_check op_code=0x12 handle=0x00
   3e offset=0 len=2 sec_flag=0x0 key_size=0
587 D (21316) BT_GATT: gatts_write_attr_perm_check p_attr->permission =0x00
   11 min_key_size==0x0000
588 I (21326) BT_GATT: GATT_GetConnectionInfor conn_id=5
589 D (21326) BT_GATT: gatt_dequeue_sr_cmd
590 D (21366) BT_GATT: gatt_get_ch_state: ch_state=4
591 D (21366) BT_GATT: gatts_write_attr_perm_check op_code=0x12 handle=0x00
   45 offset=0 len=2 sec_flag=0x0 key_size=0
592 D (21376) BT_GATT: gatts_write_attr_perm_check p_attr->permission =0x00
   11 min_key_size==0x0000
593 I (21386) BT_GATT: GATT_GetConnectionInfor conn id=5
```

```
593 I (21386) BT_GATT: GATT_GetConnectionInfor conn_id=5
594 D (21386) BT_GATT: gatt_dequeue_sr_cmd
595 D (22896) BT_GATT: gatt_get_ch_state: ch_state=4
596 D (22896) BT_GATT: gatts_process_read_by_type_req, op_code =8, len = 0
597
598 D (22896) BT_GATT: read_attr_value uuid=0x2a00 perm=0x1 sec_flag=0x0 of
   fset=0 read_long=0
599
600 I (22906) BT_GATT: GATTS_SendRsp: conn_id: 2 trans_id: 12 Status: 0x0
   000
601
602 D (22916) BT_GATT: gatt_sr_process_app_rsp gatt_if=2
603
604 D (22926) BT_GATT: gatt_dequeue_sr_cmd
605 D (22926) BT_GATT: gatt_sr_process_app_rsp ret_code=0
606
607 D (30126) BT_GATT: gatt_get_ch_state: ch_state=4
608 D (30126) BT_GATT: gatts_process_read_by_type_req, op_code =8, len = 0
609
610 D (30126) BT_GATT: read_attr_value uuid=0x2803 perm=0x1 sec_flag=0x0 of
   fset=0 read_long=0
611
612 D (30186) BT_GATT: gatt_get_ch_state: ch_state=4
613 D (30186) BT_GATT: gatts_process_read_by_type_req, op_code =8, len = 0
614
615 D (30246) BT_GATT: gatt_get_ch_state: ch_state=4
616 D (30306) BT_GATT: gatt_get_ch_state: ch_state=4
617 D (30306) BT_GATT: gatts_write_attr_perm_check op_code=0x12 handle=0x00
   2b offset=0 len=2 sec_flag=0x0 key_size=0
618 D (30316) BT_GATT: gatts_write_attr_perm_check p_attr->permission =0x00
   11 min_key_size==0x0000
619 I (30326) BT_GATT: GATT_GetConnectionInfor conn_id=5
620 D (30326) BT_GATT: gatt_dequeue_sr_cmd
621 D (30366) BT_GATT: gatt_get_ch_state: ch_state=4
622 D (30366) BT_GATT: read_attr_value uuid=0x2a19 perm=0x1 sec_flag=0x0 of
   fset=0 read_long=0
623
624 I (30366) BT_GATT: GATT_GetConnectionInfor conn_id=5
625 D (30376) BT_GATT: gatt_dequeue_sr_cmd
```