



둘 다 long 타입(정수)이라서 둘을 나눌 때, 값이 "0"으로 뜬다 -> 따라서 50.98 같은 꼴의 값을 구할 수 없다.



System.filesystem.free를 Double 타입(실수)로 바꾸고



System.filesystem.total를 Double 타입(실수)로 바꾼다.

Edit field 'free_disk_space'

Index pattern: metricbeat*



Create a label to display in place of the field name in Discover, Maps, and Visualize. Useful for shortening a long field name. Queries and filters use the original field name.




Set a value for the field instead of retrieving it from the field with the same name in _source .

Define script

if (doc['system.filesystem.free'].size()!=0)
return emit(
doc['system.filesystem.total'].value

);



두 행 나누기

Edit field 'free_disk_space2'

Index pattern: metricbeat*





Set custom label

Create a label to display in place of the field name in Discover, Maps, and Visualize. Useful for shortening a long field name. Queries and filters use the original field name.



Set value

Set a value for the field instead of retrieving it from the field with the same name in _source .

Define script


```
if (doc['system.filesystem.free'].size()!=0)
return emit(
(doc['Free Disk Space'].value /
doc['free_disk_space'].value) *100
);
```












≣

Average free_disk_space2


결과값

4



Edit field 'load_1_5_15'

Index pattern: metricbeat*





Set custom label

Create a label to display in place of the field name in Discover, Maps, and Visualize. Useful for shortening a long field name. Queries and filters use the original field name.





Set value

Set a value for the field instead of retrieving it from the field with the same name in _source .

Define script

```
if (doc['system.load.1'].size()!=0)
return emit(
doc['system.load.1'].value+
doc['system.load.5'].value+
doc['system.load.15'].value
);
```





결과값

Create field

Index pattern: metricbeat*

Name	Туре	
MySQL status	Keyword	~



Set custom label

Create a label to display in place of the field name in Discover, Maps, and Visualize. Useful for shortening a long field name. Queries and filters use the original field name.





Set value

Set a value for the field instead of retrieving it from the field with the same name in _source .

Define script


```
if (doc['mysql.status.connections'].size()==0)
return emit("DOWN");
else
return emit("UP");
```





DOWN

Last MySQL status





and Visualize. Useful for shortening a long field name. Queries and filters use the original field name.



Set format

Set your preferred format for displaying the value. Changing the format can affect the value and prevent highlighting in Discover.







Update


11.81 days

Uptime

결과값







riangle Changing name or type can break searches and visualizations that rely on this field.

Enter CHANGE to continue

Cancel

Save changes

X

 \times

유형을 바꾸고 싶으면 해당창에 CHANGE라고 써주어야 된다.

Remove field 'load_1_5_15'

 $\ensuremath{\Delta}$ Removing fields can break searches and visualizations that rely on this field.

Enter REMOVE to confirm

Cancel

Remove field

삭제하고 싶으면 해당창에 REMOVE라고 써주어야 한다.