

DTS207TC Database Development and Design

Lecture 5 Web

Chap 8.2 OR-Mapping

Chap 9 App. Development

Di Zhang, Autumn 2025

*Announcement



The coursework 1 has been released

by [DI ZHANG](#) - Thursday, 9 October 2025, 19:34

Dear students,

The coursework 1 has been released on [LMO](#).

It covers Learning Outcome BCD, and accounts for 60% for your final grade.

Its submission deadline is **23:59, 7th Nov (Friday)**. Please do not miss it.

Thank you!

Di

[Permalink](#)

[Edit](#)


[Delete](#)

[Reply](#)

[Export to portfolio](#)

- Web Architecture
- HTML
- Web Server
- ORM

Overview




- A web server is computer software and underlying hardware that accepts requests via HTTP (the network protocol created to distribute web content).
- A user agent, commonly a web browser or web crawler, initiates communication by making a request for a web page or other resource using HTTP, and the server responds with the content of that resource or an error message.
- A web server can also accept and store resources sent from the user agent if configured to do so.

- A Web server can be a physical computer that provides and hosts website content, or it can be a software program that controls network users' access to files. It receives requests from clients such as browsers via the HTTP (or HTTPS) protocol, looks up and returns the requested web pages, images, videos, and other content.
- Two Meanings of Web Server
 - Hardware (Physical Machine): A computer connected to the Internet that stores all the files of a website, such as HTML files, CSS style sheets, JavaScript files, and images.
 - Software: A program running on the hardware, with the most important part being the HTTP server. It is responsible for processing HTTP requests from clients and sending the corresponding website content back in the form of HTTP responses.

*Hardware


- The hardware used to run a web server can vary according to the volume of requests that it needs to handle. At the low end of the range are embedded systems, such as a router that runs a small web server as its configuration interface. A high-traffic Internet website might handle requests with hundreds of servers that run on racks of high-speed computers.



The world's first web server, a [NeXT Computer](#) workstation with Ethernet, 1990. The case label reads: "This machine is a server. DO NOT POWER IT DOWN!!"



The inside and front of a [Dell PowerEdge](#) server, a computer designed to be mounted in a [rack mount](#) environment. Servers similar to this one are often used as web servers.




Multiple web servers may be used for a high-traffic website.

Working Principle

- Request: When you type a URL into your browser, the browser sends an HTTP request to the Web server corresponding to that website.
- Processing: After receiving the request, the Web server identifies the URL and looks for the relevant web page files.
- Response: The Web server sends the found web page content (such as HTML, images, etc.) as a response back to the browser via the HTTP protocol.
- Display: After receiving the response, the browser parses and displays the content to you, ultimately showing you the web page.

Communication process according to HTTP







```

+ Frame 141 (743 bytes on wire (5864 bytes captured) on interface 0)
+ Ethernet II, Src: 3Com_9b:47:f7 (00:04:75:9b:47:f7), Dst: Cisco-Li_2a:fb:9b (00:18:39:2a:fb:9b)
+ Internet Protocol, Src: 192.168.1.2 (192.168.1.2), Dst: 84.16.81.23 (84.16.81.23)
+ Transmission Control Protocol, Src Port: 3296 (3296), Dst Port: http (80), Seq: 18128, Ack: 411
+ Hypertext Transfer Protocol

```

0000	00	18	39	2a	fb	9b	00	04	75	9b	47	f7	08	00	45	00	..9*....	U.G...E.
0010	02	d9	99	f5	40	00	80	06	f7	57	c0	a8	01	02	54	10@... .w....T.	
0020	51	17	0c	e0	00	50	da	c4	86	38	e1	1a	4f	a3	50	18	Q....P.. .8...O.P.	
0030	fc	7d	69	9d	00	00	47	45	54	20	2f	6c	6f	6f	6b	78	.}i...GE T /lookx	
0040	70	2f	6c	6f	6f	6b	78	70	62	61	63	6b	2e	67	69	66	p/lookxp back.gif	
0050	20	48	54	54	50	2f	31	2e	31	0d	0a	48	6f	73	74	3a	HTTP/1. 1..Host: OPENMANIAK.COM 	
0060	20	6f	70	65	6e	6d	61	6e	69	61	6b	2e	63	6f	6d	0d	openman iak.com.	
0070	0a	55	73	65	72	2d	41	67	65	6e	74	3a	20	4d	6f	7a	.User-Ag ent: Moz	
0080	69	6c	6c	61	2f	35	2e	30	20	28	57	69	6e	64	6f	77	illa/5.0 (window	
0090	73	3b	20	55	3b	20	57	69	6e	64	6f	77	73	20	4e	54	s; U; wi ndows NT	
00a0	20	35	2e	31	3b	20	66	72	3b	20	72	76	3a	31	2e	38	5.1; fr ; rv:1.8	
00b0	2e	31	2e	31	31	29	20	47	65	63	6b	6f	2f	32	30	30	.1.11) G ecko/200	
00c0	37	31	31	32	37	20	46	69	72	65	66	6f	78	2f	32	2e	71127 Fj refox/2.	



- A web server program plays the role of a server in a client–server model by implementing one or more versions of HTTP protocol, often including the HTTPS secure variant and other features and extensions that are considered useful for its planned usage.



Most Popular Open-Source Web Server



Caddy
THE ULTIMATE SERVER



Static content serving

- Static content serving: to be able to serve static content (web files) to clients via HTTP protocol.

Example of a *static request* of an existing file specified by the following URL:

```
http://www.example.com/path/file.html
```

The client's **user agent** connects to `www.example.com` and then sends the following **HTTP/1.1** request:


```
GET /path/file.html HTTP/1.1  
Host: www.example.com  
Connection: keep-alive
```

The result is the local file system resource:


```
/home/www/www.example.com/path/file.html
```

Dynamic content serving

- Dynamic content serving: to be able to serve dynamic content (generated on the fly) to clients via HTTP protocol.



Layers




- Most database users do not use a query language like SQL
- An application program acts as the intermediary between users and the database
 - Applications split into
 - front-end
 - middle layer
 - backend
- Front-end: user interface
 - Forms
 - Graphical user interfaces
 - Many interfaces are Web-based

Application Architecture Evolution




- Three distinct era's of application architecture


- Mainframe (1960' s and 70' s)
- Personal computer era (1980' s)
- Web era (mid 1990' s onwards)
- Web and Smartphone era (2010 onwards)



(a) Mainframe Era



(b) Personal Computer Era



(c) Web era



HISTORY OF THE INTERNET

1969

Arpanet was the first real network to run on packet switching technology

1971

Electronic mail is introduced by Ray Tomlinson



1974

Transmission Control Protocol/ Internet Protocol (TCP/IP) is designed

1982



Scott Fahlman kick starts smiley culture by suggesting using the :-) and :- (smileys to convey emotions in emails

1977

The first PC modern, developed by Dennis Hayes and Dale Heatherington was introduced

1989



AOL is launched

1994

Mosaic's first big competitor, Netscape Navigator, was released

1995



Jerry and David's guide to the World Wide Web is renamed Yahoo!

1998



Google arrives. It pioneers a ranking system that uses links to assess a website's popularity.

2001



Wikipedia is launched

2003

Skype is released to the public, giving a user friendly interface to voice over IP calling. Myspace becomes the most popular social network.

2004



Facebook launches in 2004 by Mark Zuckerberg

2005



Youtube launches bringing free online video hosting and sharing to the masses

2006

Twitter is launched it originally was going to be called Twittr (inspired by Flickr)

2010



4G wireless networks become available in the United States

2007




iPhone was responsible for renewed interest in mobile web applications and design

Web browsers have become the de-facto standard user interface to databases

- Enable large numbers of users to access databases from anywhere
- Avoid the need for downloading/installing specialized code, while providing a good graphical user interface
 - Javascript, Flash and other scripting languages run in browser, but are downloaded transparently
- Examples: banks, airline and rental car reservations, university course registration and grading, an so on.

*Type



The World Wide Web



- The Web is a distributed information system based on hypertext.
- Most Web documents are hypertext documents formatted via the HyperText Markup Language (HTML)
- HTML documents contain
 - text along with font specifications, and other formatting instructions
 - hypertext links to other documents, which can be associated with regions of the text.
 - **forms**, enabling users to enter data which can then be sent back to the Web server

Uniform Resources Locators



Xi'an Jiaotong-Liverpool University
西交利物浦大学

- In the Web, functionality of pointers is provided by Uniform Resource Locators (URLs).

- URL example:

<http://www.acm.org/sigmod>

- The first part indicates how the document is to be accessed
 - “http” indicates that the document is to be accessed using the Hyper Text Transfer Protocol.
- The second part gives the unique name of a machine on the Internet.
- The rest of the URL identifies the document within the machine.

- The local identification can be:

- The path name of a file on the machine, or
- An identifier (path name) of a program, plus arguments to be passed to the program
 - E.g., <http://www.google.com/search?q=silberschatz>



Ping

- HTML provides formatting, hypertext link, and image display features
 - including tables, stylesheets (to alter default formatting), etc.
- HTML also provides input features
 - Select from a set of options
 - Pop-up menus, radio buttons, check lists
 - Enter values
 - Text boxes
 - Filled in input sent back to the server, to be acted upon by an executable at the server
- HyperText Transfer Protocol (HTTP) used for communication with the Web server

HTTP Header

The screenshot displays the Chrome DevTools Network tab. The top toolbar includes icons for Elements, Console, Sources, Network, Performance, Memory, Application, and Security. Below the toolbar, there are checkboxes for 'Preserve log', 'Disable cache', and 'Online'. A filter bar shows 'All' selected, with other filters like XHR, JS, CSS, etc. A timeline at the top shows a request taking approximately 15ms. The main pane shows a list of requests, with 'aaa' selected. The 'Headers' tab is active, showing the following details:

- General**
 - Request URL: `http://127.0.0.1:8081/aaa`
 - Request Method: GET
 - Status Code: 200 OK
 - Remote Address: 127.0.0.1:8081
 - Referrer Policy: no-referrer-when-downgrade
- Response Headers** (view source)
 - Connection: keep-alive
 - Content-type: `text/html; charset=utf-8`
 - Date: Mon, 06 Apr 2020 07:11:40 GMT
 - Transfer-Encoding: chunked
- Request Headers** (view source)
 - Accept: `text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,application/signed-exchange;v=b3;q=0.9`
 - Accept-Encoding: gzip, deflate, br
 - Accept-Language: `en-US,en;q=0.9,zh-CN;q=0.8,zh;q=0.7`
 - Cache-Control: no-cache
 - Connection: keep-alive

Sample HTML Source Text

Xi'an Jiaotong-Liverpool University

西交利物浦大学



5~11

```
<html>
```

```
<body>
```

```
<table border>
```

```
<tr> <th>ID</th> <th>Name</th> <th>Department</th> </tr>
```

```
<tr> <td>00128</td> <td>Zhang</td> <td>Comp. Sci.</td> </tr>
```

```
....
```

```
</table>
```

```
<form action="PersonQuery" method=get>
```

```
Search for:
```

```
<select name="persontype">
```

```
<option value="student" selected>Student </option>
```

```
<option value="instructor"> Instructor </option>
```

```
</select> <br>
```

```
Name: <input type=text size=20 name="name">
```

```
<input type=submit value="submit">
```

```
</form>
```

```
</body> </html>
```

Display of Sample HTML Source



Xi'an Jiaotong-Liverpool University

西交利物浦大学

ID	Name	Department
00128	Zhang	Comp. Sci.
12345	Shankar	Comp. Sci.
19991	Brandt	History

Search for:

Name:


- What is JavaScript?
 - Client-side scripting language – runs in the browser
 - Dynamic interaction – makes web pages interactive
 - Cross-platform – supported by all modern browsers
- Core Features
 - Lightweight interpreted language
 - Supports object-oriented programming
 - Seamless integration with HTML/CSS
 - Rich ecosystem and libraries
- Main Applications
 - Front-end web development
 - Server-side development (Node.js)
 - Mobile app development
 - Game development



This Will be taught in Lab5!

- A Web server can easily serve as a front end to a variety of information services.
- The document name in a URL may identify an executable program, that, when run, generates a HTML document.
 - When an HTTP server receives a request for such a document, it executes the program, and sends back the HTML document that is generated.
 - The Web client can pass extra arguments with the name of the document.
- To install a new service on the Web, one simply needs to create and install an executable that provides that service.
 - The Web browser provides a graphical user interface to the information service.

- Flask is a lightweight Python web framework ideal for building small to medium-sized web applications.



- Modern web applications use meaningful URLs to help users. Users are more likely to like a page and come back if the page uses a meaningful URL they can remember and use to directly visit a page.



Variable Rule

- You can add variable sections to a URL. Your function then receives the as a keyword argument.



Rendering Templates

- Generating HTML from within Python is not fun, and actually pretty cumbersome because you have to do the HTML escaping on your own to keep the application secure.
- Templates can be used to generate any type of text file. For web applications, you'll primarily be generating HTML pages, but you can also generate markdown, plain text for emails, and anything else.



Receiving User Inputs

- Get Method
 - GET is a request method in the HTTP protocol used to request access to a specific resource on a server. It is one of the most commonly used HTTP request methods, primarily used to retrieve data from a server.
 - Parameters are passed in the URL, which reduces security and imposes a request length limit.
- Post Method
 - POST is also a request method in the HTTP protocol used to submit data to a server to create or update resources. It is commonly used for operations such as submitting form data and uploading files.
 - Parameters are passed in the request body, which provides increased security and an unlimited request length.



Object-oriented Programming



Xi'an Jiaotong-Liverpool University
西交利物浦大學

- Object-oriented programming (OOP) is a programming paradigm based on the object – a software entity that encapsulates data and function(s).
- An OOP computer program consists of objects that interact with one another.
- Main features: Encapsulation, Inheritance, and Polymorphism



- **Object-relational data model** provides richer type system
 - with complex data types and object orientation
- Applications are often written in object-oriented programming languages
 - Type system does not match relational type system
 - Switching between imperative language and SQL is troublesome
- Approaches for integrating object-orientation with databases
 - Build an **object-relational database**, adding object-oriented features to a relational database
 - Automatically convert data between programming language model and relational model; data conversion specified by **object-relational mapping**
 - Build an **object-oriented database** that natively supports object-oriented data and direct access from programming language

- Object-relational mapping (ORM) systems allow
 - Specification of mapping between programming language objects and database tuples
 - Automatic creation of database tuples upon creation of objects
 - Automatic update/delete of database tuples when objects are update/deleted
 - Interface to retrieve objects satisfying specified conditions
 - Tuples in database are queried, and object created from the tuples
- Details in Section 9.6.2
 - Hibernate ORM for Java
 - Django ORM for Python

Object-Relational Database Systems



2

- User-defined types
 - **create type** *Person*
 (*ID* **varchar**(20) **primary key**,
 name **varchar**(20),
 address **varchar**(20)) **ref from**(*ID*); /* More on this later */
 create table *people* **of** *Person*;
- Table types
 - **create type** *interest* **as table** (
 topic **varchar**(20),
 degree_of_interest **int**);
 create table *users* (
 ID **varchar**(20),
 name **varchar**(20),
 interests *interest*);
-

Type and Table Inheritance



3

- Type inheritance
 - **create type** *Student* **under** *Person*
(*degree varchar(20)*) ;
create type *Teacher* **under** *Person*
(*salary integer*);
- Table inheritance syntax in PostgreSQL and oracle
 - **create table** *students*
(*degree varchar(20)*)
inherits *people*;
 - create table** *teachers*
(*salary integer*)
inherits *people*;
 - **create table** *people* **of** *Person*;
 - create table** *students* **of** *Student*
under *people*;
 - create table** *teachers* **of** *Teacher*
under *people*;



4


- Creating reference types
 - **create type** *Person*
 (*ID* **varchar**(20) **primary key**,
 name **varchar**(20),
 address **varchar**(20))
 ref from(*ID*);
create table *people* **of** *Person*;
create type *Department* (
 dept_name **varchar**(20),
 head ref(*Person*) **scope** *people*);
create table *departments* **of** *Department*
insert into *departments* **values** ('CS', '12345')
 - System generated references can be retrieved using subqueries
 - (**select** **ref**(*p*) **from** *people* **as** *p* **where** *ID* = '12345')
- Using references in **path expressions**
 - **select** *head->name*, *head->address*
from *departments*;

- A simple web application



17

Performance



Web Cache





18

- Allow data on Web to be accessed using remote procedure call mechanism
- Two approaches are widely used
 - **Representation State Transfer (REST)**: allows use of standard HTTP request to a URL to execute a request and return data
 - Returned data is encoded in XML
 - **Big Web Services**:
 - Uses XML representation for sending request data, as well as for returning results
 - Standard protocol layer built on top of HTTP
 - See Section 23.7.3