

Name and, if possible, ID:

AMERICAN UNIVERSITY OF ARMENIA  
College of Science and Engineering  
COMP120 Introduction to Object-Oriented Programming  
MIDTERM 2 EXAM

Date: Tuesday, March 24 2015

Starting time: 10:30

Duration: 1 hour 20 minutes

Attention: **ANY COMMUNICATION IS STRICTLY PROHIBITED**

Please write down your name at the top of all used pages

**Problem 1**

The easiest way to implement rotation by  $90^\circ$  of a square array is to transpose it and then reverse all its rows separately. Write a C++ function `void rotate(int *a2D, int size)` that takes as its argument a pointer to the first element of a square array `int *a2D` of the specified `int size` and rotates its. Use already implemented functions `void reverse(int a1D[], int length)` and `void transpose(int *a2D, int size)`:

```
void reverse(int a1D[], int length)
{
    for (int i = 0; i < length / 2; i++)
        swap(a1D[i], a1D[length - 1 - i]);
}

void transpose(int *a2D, int size)
{
    for (int row = 0; row < size; row++)
        for (int col = row + 1; col < size; col++)
            swap(a2D[row * size + col], a2D[col * size + row]);
}
```

```
void rotate(int *a2D, int size)
{
    for (int row = 0; row < size; row++)
        for (int col = row + 1; col < size; col++)
            swap(a2D[row * size + col], a2D[col * size + row]);
}

void reverse(int a1D[], int length)
{
    for (int i = 0; i < length / 2; i++)
        swap(a1D[i], a1D[length - 1 - i]);
}

void transpose(int *a2D, int size)
{
    for (int row = 0; row < size; row++)
        for (int col = row + 1; col < size; col++)
            swap(a2D[row * size + col], a2D[col * size + row]);
}
```




Name and, if possible, ID#: \_\_\_\_\_

## Problem 2

Using functions *transpose()* from Problem 1 and *scalar()* from below, write a C++ function *void square(int \*a2D, int \*product, int size)* that takes as its argument a pointer to the first element of a square array *int \*a2D* of the specified *int size*, computes its square (multiplies it by itself) and saves it in another square array of the same size, the pointer to the first element of which is given by *int \*product*. Each element  $p_{ij}$  in the  $i^{\text{th}}$  row and  $j^{\text{th}}$  column of the array *\*product* is the scalar product of the  $i^{\text{th}}$  row and  $j^{\text{th}}$  column of the array *\*a2D* and is calculated by the

$$\text{expression: } p_{ij} = \sum_{k=0}^{\text{size}-1} a_{ik} a_{kj}$$

```
int scalar(int a[], int b[], int length)
{
    int result = 0;
    for (int i = 0; i < length; i++)
        result += a[i] * b[i];
    return result;
}
```



```
void square(size, size)
{
    for (i = 0; i < size; i++)
        for (j = 0; j < size; j++)
            A[i][j] = (a2D + i * size + j)
            transpose(A, size)
    for (i = 0; i < size; i++)
        for (j = 0; j < size; j++)
            A^2 product[i][j] = scalar(a2D[i], A[i], size)
}
```

2



int increment)

```
1) direction = 1, increment = 1
for (; length > 0; length--)
{ * (start + direction) = *start + 1
  start += direction;
} return start;
}
```

```
2) direction = 6, increment = 1
for (; length > 0; length--)
{ * (start + direction) = *start + 1
  start += direction;
} return start;
}
```

3)

1



Name and, if possible, ID#: duffy

### Problem 3

**Problem 3**

Using, if you wish, *segment()* and *rotate()* functions from the C++ Reference Functions section, write a C++ function *void spiral2(int \*a2D, int even\_size)* that takes as its argument pointer to the first element of a square array *int \*a2D* of the specified even size *int even\_size* and fills its top-left and bottom-right quadrants with spirals of successive values from 1 to  $even\_size^2 / 4$ . The remaining two quadrants are filled with zeros. Each spiral propagates horizontally toward the array center, then vertically toward the center, then in opposite directions horizontally and vertically, and so on. Obviously, the spirals do not cross the central axes. A shaded example is shown below:

```
int* segment(int *start, int length, int direction, int increment)
```

```

{
    for (; length > 0; length--)
    {
        *(start + direction) = *start + increment;
        start += direction;
    }
    return start;
}

```

1	2	3	0	0	0
8	9	4	0	0	0
7	6	5	0	0	0
0	0	0	5	6	7
0	0	0	4	9	8
0	0	0	3	2	1

OK R-3, R-3, R-3

oblique spiral (

inter segment KL, EL

Godolphin Institute, in

alt\* frequent (1, ~~alt~~<sup>3</sup>, 1, 1)

for  $\ell_i$  length  $\ell_i$  length  $= x$

\*  $(\text{direction} = 1)$ , increment = 1, start = 1

```
for (length > 0; length --)
```

$$\{ * (start + direction) = * start + \text{incr} \}$$

$$start += direction;$$

```

} return (start;

```

```
int* segment(int* start, int length, int direction, int increment)
direction = 3, increment = 1
```