Gestalt Universal 3D Framework

Research & Exploration Document

Aaron Storey

February 25, 2026

Contents

Gestalt Universal 3D Framework **2**
Research & Exploration Document . . . 2
Abstract . . . 2
Table of Contents . . . 2
Part 1: Why 3D + Hand Tracking Together? . . . 3
Three Core Arguments . . . 3
The Universal Framework Payoff . . . 3
Part 2: Hand Tracking Technology Comparison . . . 3
Head-to-Head Comparison Matrix . . . 3
Detailed Technology Profiles . . . 4
Technology Decision Matrix . . . 5
MediaPipe vs Ultraleap: When to Add Ultraleap . . . 5
Part 3: 50 Use Cases — Full Catalog . . . 6
Category A: Explainable AI & Model Interpretability . . . 6
Category B: Knowledge Graphs & Semantic Networks . . . 7
Category C: Financial Markets & Trading . . . 8
Category D: Healthcare & Biomedical . . . 8
Category E: Engineering & Scientific Computing . . . 9
Category F: Agent Systems & Workflow Orchestration . . . 9
Category G: Data Science & Analytics . . . 10
Category H: Education & Training . . . 10
Category I: Creative & Design . . . 11
Category J: Security & Intelligence . . . 11
Category K: Robotics & Industrial . . . 12
Category L: Immersive Computing & Accessibility . . . 12
Category M: Gaming & Entertainment . . . 12
Category N: Urban Planning & Environmental Science . . . 13
Category O: Advanced / Forward-Looking . . . 13
Part 4: Rendering Primitives — Coverage Analysis . . . 13
10 Core Rendering Primitives . . . 13
Use Case x Rendering Primitive Cross-Reference . . . 14
Primitive Usage Frequency (Primary Role) . . . 16
Minimum Viable Primitive Set (80% Rule) . . . 16
Part 5: Gesture Vocabulary — Coverage & Gap Analysis . . . 16
Current 10-Gesture Vocabulary . . . 16
Gesture Classification Quality . . . 17
Identified Gaps for 50 Use Cases . . . 17
Part 6: Data Format Mapping by Domain . . . 18

Input Formats to Rendering Primitives . . . 18
Graph Format Comparison . . . 18
Part 7: Existing Code Reuse Across Projects . . . 19
Visualization Components Already Built . . . 19
Shared Performance Patterns (Already Validated) . . . 19
Gestalt Performance Benchmarks (Achieved) . . . 19
Part 8: Summary Statistics & Coverage Analysis . . . 20
Readiness Distribution . . . 20
Aaron's Projects Grounded: 19 of 50 . . . 20
Gesture Frequency (All 50 Use Cases) . . . 20
Maximum Utility: What to Build First . . . 21
Part 9: Critical Files . . . 21
Part 10: Next Steps . . . 21

Gestalt Universal 3D Framework

Research & Exploration Document

Author: Aaron Storey **Date:** February 25, 2026 **Project:** Gestalt — `/mnt/projects/tracking/` **Repository:** `astoreyai/gestalt`

Abstract

Gestalt is a universal 3D UI framework built on Three.js, React Three Fiber, and MediaPipe hand tracking. This document presents a comprehensive research exploration covering: the theoretical foundations of 3D + hand tracking interaction, a technology comparison of hand tracking solutions, 50 domain-specific use cases, rendering primitive coverage analysis, gesture vocabulary gap analysis, data format mapping, existing code reuse opportunities, and a maximum-utility implementation roadmap. The analysis demonstrates that adding 3 rendering primitives to Gestalt's existing 4 would achieve 80%+ use case coverage across all 50 domains, and that 3 continuous gesture data exposures would expand interaction capability by 25–35% without adding new gesture types.

Table of Contents

1. Why 3D + Hand Tracking Together?
2. Hand Tracking Technology Comparison
3. 50 Use Cases — Full Catalog
4. Rendering Primitives — Coverage Analysis
5. Gesture Vocabulary — Coverage & Gap Analysis
6. Data Format Mapping by Domain
7. Existing Code Reuse Across Projects
8. Summary Statistics & Coverage Analysis
9. Critical Files
10. Next Steps

Part 1: Why 3D + Hand Tracking Together?

Three Core Arguments

1. The Dimension Argument. A 2D screen encodes X and Y. Adding interactive 3D adds depth, which can represent time, confidence, importance, similarity, cost, or any continuous variable. This is not cosmetic — it is an additional data channel that 2D dashboards physically cannot provide.

2. The Direct Manipulation Argument. A mouse is a translation device: you move a puck on a desk and a cursor moves on a screen. Hand tracking removes that indirection. Degrees of freedom jump from 2 (mouse XY) to 21 landmarks per hand (42 total), enabling simultaneous multi-parameter control.

3. The Spatial Memory Argument. Decades of cognitive science (Haber 1970, Standing 1973, Method of Loci) demonstrate that humans encode and retrieve spatial locations with far higher fidelity than serial lists. "Over to the left and behind" beats "row 47 in the spreadsheet."

The Universal Framework Payoff

One gesture vocabulary + one rendering pipeline = all 50 domains. Learn once, use everywhere.

Part 2: Hand Tracking Technology Comparison

Head-to-Head Comparison Matrix

Feature	MediaPipe 0.10.14	Ultraleap Hyperion	WebXR Hand Input	TensorFlow.js HandPose	OpenCV.js	Handtrack.js
Landmarks	**21/hand**	25–27	25	21	Variable	Bounding box only
Depth type	2.5D monocular	**3D stereo IR**	**3D native**	2.5D monocular	2D only	None
Desktop FPS	**60+ (GPU)**	120+	N/A	30–50	20–40	10–30
Mobile FPS	30–80	N/A	90 (headset)	20–40	N/A	20–40
Joint angle RMSE	22.5 deg	**14.8 deg**	~15 deg	~25 deg	N/A	N/A
Position error	Relative z only	**5.2mm palm**	Sub-mm	Relative z	N/A	N/A
Positional jitter	Needs filtering	**0.4–0.8mm**	Low	Needs filtering	High	N/A
Hardware	**Webcam only**	IR camera ($150+)	VR headset	**Webcam only**	Webcam	Webcam
Web API	**Native browser**	WebSocket bridge	Native (headset)	**TFJS library**	OpenCV.js	TFJS library
GPU accel	WebGL delegate	N/A (hardware)	Native	WebGL/WebGPU	No	WebGL via TFJS
Model size	6MB	N/A	0 (hardware)	12MB	N/A	3–12MB
License	**Apache 2.0**	Commercial	Open (W3C)	**Apache 2.0**	BSD	Varies
Cost	**Free**	$$$ (HW + license)	Free (HW cost)	**Free**	**Free**	**Free**
Gloved hands	Poor	Good	Varies	Poor	N/A	N/A

Feature	MediaPipe 0.10.14	Ultraleap Hyperion	WebXR Hand Input	TensorFlow.js HandPose	OpenCV.js	Handtrack.js
Browser support	All modern	Via server	Quest Browser only	All modern	All modern	All modern
Active dev (2025–26)	Yes	Yes	Yes	Maintenance	Maintenance	Maintenance

Detailed Technology Profiles

MediaPipe Hands (Current Gestalt Choice) **Architecture:** Two-stage pipeline — Palm Detection Model then Hand Landmarks Detection Model (21 keypoints in cropped region).

Strengths:

- Zero hardware cost (any webcam)
- 60+ FPS on desktop GPU with WebGL delegate
- Cross-browser, cross-platform
- Apache 2.0 — no licensing concerns
- Worker mode support (OffscreenCanvas)
- Largest community and ecosystem

Weaknesses:

- Z-axis is the noisiest output (monocular depth estimation)
- Frequently reports false low curl (0.1–0.3) even when fully curled
- Requires heavy filtering stack (One-Euro + median pre-filter)
- No absolute world positioning (relative to wrist)

Gestalt's Filtering Stack (in `tracker/HandTracker.ts`, 649 lines):

- One-Euro filter with 4-tier per-joint tuning (wrist, MCP, PIP, TIP)
- 3-frame median pre-filter to reject single-frame spikes
- Z-axis specific median + normalized depth
- Tremor compensation (band-reject for high-frequency shake)
- Palm-facing blend for orientation-adaptive weights

Gestalt's Stereo Enhancement (in `tracker/stereo-fuser.ts`, 377 lines):

- Dual-camera triangulation for improved depth
- Inverse-variance weighting (Welford's algorithm)
- Configurable baseline (~65mm human IPD default)

Ultraleap / Leap Motion Hyperion **Architecture:** Dedicated IR stereo camera with proprietary ML pipeline.

Strengths:

- Superior accuracy: 14.8 deg RMSE vs MediaPipe's 22.5 deg
- True 3D absolute coordinates (millimeter precision)
- Position stability: 0.4–0.8mm variability
- 120+ FPS
- Works with gloves
- Micro-gesture tracking (Hyperion v6+)
- Fiducial marker tracking

Weaknesses:

- Hardware cost ($150–200 for Leap Motion Controller 2)
- Not a native browser API — requires WebSocket bridge server
- Commercial licensing for production
- Not portable (specific IR camera required)
- Limited ecosystem for web-based deployment

Web Integration Path: `UltraleapTrackingWebSocket` via WebSocket to browser client.

WebXR Hand Input **Architecture:** Native VR headset hand tracking (Quest 2/3/Pro sensors).

Strengths:

- 25 skeleton joints per hand
- 90 FPS native (VR refresh rate)
- True 3D world-space coordinates
- Sub-frame latency
- Free (built into headsets)

Weaknesses:

- Headset-only — not for desktop/mobile web
- Vision Pro does NOT expose hand landmarks through WebXR (eye gaze + pinch only)
- Samsung Galaxy XR: partial support
- Cannot serve as universal desktop framework input

TensorFlow.js HandPose — Not Recommended for New Projects MediaPipe is faster (60+ vs 30–50 FPS), more accurate, better maintained, and smaller (6MB vs 12MB). Only use if locked into TFJS ecosystem.

OpenCV.js / Handtrack.js — Not Suitable Traditional CV or bounding-box-only detection. No fine-grained landmarks. Outperformed by ML-based approaches on every metric.

Technology Decision Matrix

Scenario	Recommended	Reason
Desktop web app (universal)	**MediaPipe**	Zero hardware, cross-browser, free, 60+ FPS
Premium precision workstation	**Ultraleap**	14.8 deg accuracy, absolute 3D, sub-mm stability
VR immersive experience	**WebXR**	Native 25-joint, 90 FPS, world coordinates
Hybrid (desktop + optional precision)	**MediaPipe + Ultraleap fallback**	Start with webcam, upgrade to IR camera for pro users
Mobile-first	**MediaPipe**	Only viable option with acceptable FPS

MediaPipe vs Ultraleap: When to Add Ultraleap

Criterion	MediaPipe Sufficient	Ultraleap Worth Adding
Gesture classification (10 types)	Yes — Gestalt achieves this	Overkill
Precise 3D object manipulation	Marginal (z-noise)	Yes — mm precision
Surgical/medical simulation	No — insufficient depth	**Yes** — critical
Trading/data exploration	Yes — gestures are discrete	Marginal improvement
Accessibility control	Yes — calibrated to range	Yes — more reliable
Molecular docking	Marginal	**Yes** — spatial precision
Large-scale deployment (web)	**Yes** — zero hardware	No — $150/user

Recommendation: Build on MediaPipe as the universal base. Design an abstract `HandTracker` interface (Gestalt already has this pattern) so Ultraleap can be swapped in for precision-critical domains without changing gesture vocabulary or application code.

Part 3: 50 Use Cases — Full Catalog

Category A: Explainable AI & Model Interpretability

#	Use Case	Aaron's Project	Readiness	Key Gestures
1	**XAI Attribution Map Explorer** — Face attribution maps (LIME, SHAP, RIF) as 3D heightmaps; pinch a facial region for RIF decomposition	XAI thesis	NOW	Pinch, Twist, 2H-Pinch
2	**Embedding Space Forensics** — Navigate UMAP/t-SNE 3D clusters of face embeddings; pull apart overlapping identity clusters	XAI + Gestalt	NOW	Point, Pinch, FlatDrag

#	Use Case	Aaron's Project	Readiness	Key Gestures
3	**Neural Network Circuit Tracing** — Anthropic-style circuit tracing as 3D DAG (depth=layer); pinch a neuron, follow paths downstream	T4DW	NEAR	Point, Pinch, Twist
4	**SAE Feature Dashboard** — 4096 SAE features in 3D (XY=similarity, Z=activation freq); sweep to browse, pinch to drill down	T4DW + T4DV	NEAR	FlatDrag, Pinch, 2H-Pinch

Category B: Knowledge Graphs & Semantic Networks

#	Use Case	Aaron's Project	Readiness	Key Gestures
5	**Research Literature Knowledge Graph** — Citation/concept graph with depth=year; find research gaps in empty regions	Survivorship	NOW	Pinch, FlatDrag, L-Shape
6	**Personal Knowledge Base Navigator** — Kymera's memory types as spatial landscape; recent=nearby, semantic clusters	Kymera memory	NEAR	Point, Pinch, FlatDrag
7	**Ontology & Taxonomy Editor** — Hierarchy with cross-links as 3D bridges; sculpt by dragging nodes to new parents	—	NOW	Pinch, FlatDrag, 2H-Pinch

#	Use Case	Aaron's Project	Readiness	Key Gestures
8	**Codebase Dependency Graph** — Depth=dependency hops; grab a module and shake to see impact	T4D platform	NOW	Pinch, Twist, 2H-Push

Category C: Financial Markets & Trading

#	Use Case	Aaron's Project	Readiness	Key Gestures
9	**3D Market Scanner** — Z-score x volume anomaly x time-since-signal; grab the actionable cluster	Mean-reversion	NOW	Pinch, FlatDrag, L-Shape
10	**Portfolio Risk Topology** — Holdings as nodes (size=weight, color=P&L, position=correlation); stress-test	Forecast-go	NEAR	2H-Push, Pinch, Twist
11	**Options Volatility Surface** — Strike x expiry x IV as interactive 3D surface	—	NOW	FlatDrag, Pinch, Twist
12	**Order Flow Microstructure** — Price x time x volume; hidden orders as walls	—	NEAR	FlatDrag, Pinch, 2H-Pinch

Category D: Healthcare & Biomedical

#	Use Case	Aaron's Project	Readiness	Key Gestures
13	**3D Anatomical Dissection** — Pinch-and-peel tissue layers	—	NOW	Pinch, Twist, L-Shape

#	Use Case	Aaron's Project	Readiness	Key Gestures
14	**Cancer Survivorship Care Plan Navigator** — 3D timeline of care trajectory	Survivorship	NEAR	FlatDrag, Pinch, Twist
15	**Surgical Planning & Rehearsal** — Patient-specific CT/MRI rehearsal	—	NEAR	Point, Fist, Twist
16	**Epidemiological Outbreak Mapping** — XY=geography, Z=time	—	NEAR	FlatDrag, Point, Pinch

Category E: Engineering & Scientific Computing

#	Use Case	Aaron's Project	Readiness	Key Gestures
17	**CFD Flow Exploration** — Palm as moving slice plane	—	NOW	OpenPalm, Pinch, Twist
18	**FEA Stress Visualization** — Reach inside transparent model	—	NOW	Pinch, Twist, 2H-Pinch
19	**Molecular Docking** — Grab ligand, rotate into binding pocket	—	NOW	Pinch, Twist, FlatDrag
20	**LIDAR Point Cloud Processing** — Reclassify regions by gesture	—	NOW	Pinch, Fist, FlatDrag
21	**Satellite Imagery / GeoInt** — 3D terrain + temporal scrub	OSINT context	NOW	FlatDrag, Pinch, L-Shape

Category F: Agent Systems & Workflow Orchestration

#	Use Case	Aaron's Project	Readiness	Key Gestures
22	**Agent Swarm Monitor & Director** — Pinch to pause, flick to redirect	Screener/Goblin Forge	NEAR	Pinch, FlatDrag, Fist
23	**3D Workflow Editor** — Depth=pipeline stages, grab-and-connect	Factorio/AgentForge	NEAR	Pinch, FlatDrag, Point
24	**Adversarial Agent Arena** — Red vs blue teams in 3D topology	—	FUTURE	Point, Fist, Pinch

Category G: Data Science & Analytics

#	Use Case	Aaron's Project	Readiness	Key Gestures
25	**Multi-Dimensional Data Exploration** — Swap axes by grabbing labels	Gestalt manifold	NOW	Pinch, Twist, FlatDrag
26	**Real-Time Streaming Data Triage** — Events as colored particles	—	NEAR	Pinch, FlatDrag, Point
27	**Database Query OLAP Cube** — 3D drill-down	—	NOW	Pinch, Twist, FlatDrag

Category H: Education & Training

#	Use Case	Aaron's Project	Readiness	Key Gestures
28	**Chemistry Molecular Modeling** — Build molecules hand-by-hand	—	NOW	Pinch, FlatDrag, Twist
29	**Physics Simulation Sandbox** — Flick to set velocity, resize for mass	—	NOW	Pinch, FlatDrag, 2H-Pinch

#	Use Case	Aaron's Project	Readiness	Key Gestures
30	**Spatial Vocabulary (Memory Palace)** — Place words in 3D rooms	—	NEAR	Pinch, Point, FlatDrag
31	**3D Calculus Visualization** — Touch surface for tangent plane	—	NOW	Point, Pinch, Twist

Category I: Creative & Design

#	Use Case	Aaron's Project	Readiness	Key Gestures
32	**Film/VFX Previs** — Bimanual camera + light control	Blender-MCP	NEAR	Pinch, Two-Hand, Twist
33	**Generative Art / Particle Sculpting** — Palm repels, pinch attracts	—	NOW	OpenPalm, Pinch, Twist
34	**Architectural Walkthrough** — Walk through at any scale	—	NOW	FlatDrag, Pinch, 2H-Push
35	**Spatial Audio Mixing** — Tracks as 3D positioned sound sources	—	NEAR	Pinch, FlatDrag, Twist

Category J: Security & Intelligence

#	Use Case	Aaron's Project	Readiness	Key Gestures
36	**Network Intrusion SOC Dashboard** — Trace attacks through layers	—	NEAR	Pinch, Fist, FlatDrag
37	**OSINT Entity Relationship Graph** — Pull entity to reveal connections	OSINT context	NOW	Pinch, FlatDrag, Twist

#	Use Case	Aaron's Project	Readiness	Key Gestures
38	**Face Recognition Debugging** — Synchronized side-by-side comparison	XAI thesis	NOW	2H-Rotate, Pinch, L-Shape

Category K: Robotics & Industrial

#	Use Case	Aaron's Project	Readiness	Key Gestures
39	**Robot Work Cell Design** — Sweep palm through reach envelope	—	NEAR	Pinch, OpenPalm, Twist
40	**Digital Twin Monitoring** — Walk through live 3D twin	—	NEAR	FlatDrag, Pinch, Fist

Category L: Immersive Computing & Accessibility

#	Use Case	Aaron's Project	Readiness	Key Gestures
41	**Accessibility: Motor-Impaired Control** — Calibrates to individual range	Gestalt overlay	NOW	All 10 (calibrated)
42	**Presentation & Lecture Control** — Point to advance slides	—	NOW	Point, Pinch, Twist
43	**Multi-Monitor 3D Desktop** — Fling windows between monitors	Gestalt overlay	NEAR	Point, Pinch, FlatDrag

Category M: Gaming & Entertainment

#	Use Case	Aaron's Project	Readiness	Key Gestures
44	**RTS Game Command Interface** — Bimanual unit control	—	NEAR	Pinch, Point, Fist

#	Use Case	Aaron's Project	Readiness	Key Gestures
45	**Tabletop RPG Virtual Table** — Place miniatures, sculpt terrain	—	NEAR	Pinch, 2H-Push, Point
46	**Interactive Museum Display** — Contactless artifact exploration	—	NOW	Twist, Pinch, FlatDrag

Category N: Urban Planning & Environmental Science

#	Use Case	Aaron's Project	Readiness	Key Gestures
47	**Urban Development Impact** — Reposition building, watch shadow updates	—	NEAR	Pinch, FlatDrag, 2H-Push
48	**Climate / Weather Data** — Slice atmosphere with palm	—	NEAR	OpenPalm, FlatDrag, Pinch

Category O: Advanced / Forward-Looking

#	Use Case	Aaron's Project	Readiness	Key Gestures
49	**Embodied AI Training Environment** — Hand-sculpt scenarios	—	FUTURE	Pinch, Point, FlatDrag
50	**Personal Digital Twin / Life Dashboard** — All data in one space	All projects	FUTURE	All 10

Part 4: Rendering Primitives — Coverage Analysis

10 Core Rendering Primitives

#	Primitive	Three.js Tech	Drei/R3F Helper	Scale (typical)	Gestalt Status
P1	**Point Clouds**	Points + BufferGeometry	`Preload`	5K–1M+ pts	Production
P2	**Force-Directed Graphs**	InstancedMesh + LineSegments	Custom	100–10K nodes	Production
P3	**Volume Rendering**	Custom shader + 2D tile atlas	AMI toolkit	$256^{3-512}3$ voxels	Not implemented
P4	**Surface Meshes**	BufferGeometry + GLTFLoader	`Gltf` + `Bvh`	100K–1M triangles	Not implemented
P5	**Instanced Meshes**	InstancedMesh	`Instances`	10K–1M instances	Production
P6	**Heightmaps**	PlaneGeometry + displacement shader	THREE.Terrain	$256^{2-2048}2$	Not implemented
P7	**Particle Systems**	InstancedBufferGeometry / GPGPU	None	10K(CPU)–100K+(GPU)	Not implemented
P8	**Lines & Tubes**	LineSegments / TubeGeometry	`Line`, MeshLine	10K edges	Production
P9	**Billboards & Text**	Sprite / troika-three-text	`Html`, `Text`	500–1K labels	Partial
P10	**3D UI Panels**	@react-three/uikit	`Html`	N/A	Partial

Use Case x Rendering Primitive Cross-Reference

Each cell shows primary (**P**) and secondary (s) primitives needed.

Use Case	P1	P2	P3	P4	P5	P6	P7	P8	P9	P10
1 XAI Attribution						**P**			s	s
2 Embedding Forensics	**P**								s	s
3 Circuit Tracing		**P**						**P**	s	
4 SAE Dashboard	**P**								**P**	s
5 Literature Graph		**P**						**P**	s	
6 Knowledge Base		**P**						**P**	s	
7 Ontology Editor		**P**						**P**	**P**	s
8 Codebase Deps		**P**						**P**	s	
9 Market Scanner	**P**				s				s	**P**
10 Portfolio Risk		**P**			**P**			**P**	s	s
11 Vol Surface						**P**			s	s
12 Order Flow			**P**			**P**			s	s
13 Anatomy				**P**					s	s

Use Case	P1	P2	P3	P4	P5	P6	P7	P8	P9	P10
14 Survivorship Plan								**P**	**P**	**P**
15 Surgical Planning			**P**	**P**					s	s
16 Outbreak Mapping	**P**					**P**			s	s
17 CFD Flow			**P**				**P**	**P**		s
18 FEA Stress				**P**		**P**			s	s
19 Molecular Docking				**P**	**P**				s	s
20 LIDAR Point Cloud	**P**								s	s
21 Satellite/GeoInt				**P**		**P**			s	s
22 Agent Swarm		**P**					**P**	**P**	s	s
23 Workflow Editor		**P**						**P**	**P**	**P**
24 Adversarial Arena		**P**					**P**	**P**	s	s
25 Multi-Dim Data	**P**								s	**P**
26 Streaming Triage							**P**		s	**P**
27 OLAP Cube					**P**	**P**			s	s
28 Chemistry				**P**	**P**			**P**	s	
29 Physics Sim					**P**		**P**	**P**		s
30 Memory Palace				**P**					**P**	s
31 Calculus Viz						**P**		**P**	s	s
32 Film/VFX Previs				**P**					s	**P**
33 Generative Art							**P**			s
34 Architecture				**P**					s	s
35 Spatial Audio					**P**				**P**	**P**
36 SOC Dashboard		**P**						**P**	s	**P**
37 OSINT Graph		**P**						**P**	s	s
38 Face Debug						**P**			s	s
39 Robot Work Cell				**P**				**P**	s	s
40 Digital Twin				**P**					s	**P**
41 Accessibility										**P**
42 Presentation				**P**					**P**	**P**
43 3D Desktop									**P**	**P**
44 RTS Game					**P**	**P**			s	**P**
45 Tabletop RPG				**P**	**P**	**P**			s	s

Use Case	P1	P2	P3	P4	P5	P6	P7	P8	P9	P10
46 Museum Display				**P**					s	s
47 Urban Planning				**P**		**P**			s	**P**
48 Weather Data			**P**			**P**	**P**		s	s
49 Embodied AI				**P**	**P**	**P**				s
50 Digital Twin	**P**	**P**			**P**		**P**	**P**	**P**	**P**

Primitive Usage Frequency (Primary Role)

Primitive	Primary in N use cases	% of 50	Gestalt Status
P2 Force-Directed Graphs	14	28%	**Production**
P4 Surface Meshes	14	28%	Not implemented
P6 Heightmaps	12	24%	Not implemented
P8 Lines & Tubes	12	24%	**Production**
P10 3D UI Panels	12	24%	Partial
P9 Billboards & Text	8	16%	Partial
P5 Instanced Meshes	8	16%	**Production**
P1 Point Clouds	6	12%	**Production**
P7 Particle Systems	6	12%	Not implemented
P3 Volume Rendering	4	8%	Not implemented

Minimum Viable Primitive Set (80% Rule)

Tier 1 — Already in Gestalt (covers ~40% of use cases as primary):

- InstancedMesh (P5) — nodes, molecules, 3D bars
- Points + BufferGeometry (P1) — embeddings, scatter, LIDAR
- LineSegments (P8) — edges, trajectories, circuits
- Force-directed graph (P2) — knowledge graphs, dependencies, networks

Tier 2 — Must Add (adds ~35% more coverage):

- Surface Meshes (P4) — anatomy, architecture, terrain, robots — GLTF loading + BVH raycasting
- Heightmaps (P6) — attribution maps, vol surfaces, terrain — PlaneGeometry + displacement shader
- 3D UI Panels (P10) — data overlays, menus — @react-three/uikit

Tier 3 — Specialized (remaining ~5%):

- Volume rendering (P3) — medical imaging, CFD, weather — AMI toolkit or custom shader
- Particle systems (P7) — generative art, streaming, effects — GPGPU compute

Adding Tier 2 brings Gestalt from 40% to ~80% use case coverage with 3 new primitive types.

Part 5: Gesture Vocabulary — Coverage & Gap Analysis

Current 10-Gesture Vocabulary

From `protocol.ts`:

Gesture	Definition	Classifier Detail	Use Cases
Pinch	Thumb-index touch (palm-size normalized)	Approach-vector gating, EMA-smoothed dot product	49/50
FlatDrag	Open palm + hand is flat + moving	Palm normal check + velocity	39/50
Twist	Wrist rotation (2-hand)	Orientation delta tracking	36/50
Point	Index extended, others curled	Per-finger curl thresholds	32/50
Two-Hand Pinch	Both hands pinching + distance change	Bilateral pinch + inter-hand distance	28/50
Fist	All fingers curled	All-finger curl > threshold	18/50
L-Shape	Thumb + index only extended	Specific finger combination	14/50
OpenPalm	All fingers extended	All-finger curl < threshold	12/50
Two-Hand Push	Both hands pushing forward/apart	Bilateral orientation + velocity	10/50
Two-Hand Rotate	Both hands rotating together	Bilateral rotation tracking	6/50

Gesture Classification Quality

Classifier (`classifier.ts`, 873 lines):

- Hybrid angle + distance curl measurement
- Orientation-adaptive weights (palm-facing = angle reliable; edge-on = distance robust)
- Per-finger ROM normalization (ring/pinky mechanically coupled)
- Thumb decomposed: 60% opposition + 40% flexion
- Priority order: Fist, Pinch, LShape, Point, FlatDrag, OpenPalm (most to least specific)
- Hysteresis margins prevent boundary flickering

State Machine (`state.ts`, 580 lines):

- 2D pre-allocated grid [2 hands x 10 gesture types]
- Phase transitions: Idle, Onset, Hold, Release
- Per-gesture timing thresholds

Identified Gaps for 50 Use Cases

Missing Capability	How to Add	Use Cases Benefiting	Priority
Swipe (4 directions)	Track velocity vector during FlatDrag	Navigation, timeline scrub, next/prev	HIGH
Continuous pinch distance	Expose raw thumb-index distance as float	Zoom, scaling, continuous control	HIGH
Hand orientation (palm/yaw/roll)	Expose palm normal as continuous value	3D slice plane, object rotation	HIGH
Grab/grasp detection	Full-hand closure + position lock	Object manipulation, move-and-hold	MEDIUM

Missing Capability	How to Add	Use Cases Benefiting	Priority
Thumbs-up	Thumb extended upward, others curled	Confirmation, approval	LOW
OK sign	Thumb-index circle (variant of pinch)	Start/stop toggle	LOW
Finger tapping	Single-finger rapid on/off	Rhythm input, discrete triggers	LOW

Adding the 3 HIGH-priority gaps would cover an estimated 25–35% more interaction patterns without adding new gesture types — they are continuous data exposures from existing classification.

Part 6: Data Format Mapping by Domain

Input Formats to Rendering Primitives

Domain	Input Formats	Conversion	Target Primitive
XAI / ML	NumPy arrays (JSON/binary), ONNX activations	Python UMAP/t-SNE to JSON	Point Clouds, Heightmaps
Knowledge Graphs	GraphML, RDF/Turtle, JSON-LD, GEXF	graphology parse to nodes/edges	Force-Directed Graphs
Trading	CSV (OHLCV), WebSocket JSON (ticks)	Parse, aggregate, position buffers	Point Clouds, Heightmaps, Particles
Medical Imaging	DICOM (.dcm), NIfTI (.nii), NRRD	AMI Toolkit (browser)	Volume Rendering
Anatomy/CAD	GLTF 2.0 (.glb), STL, OBJ, FBX	GLTFLoader / STLLoader (Three.js)	Surface Meshes
Molecules	PDB, mmCIF, SDF, MOL	Mol* parse to ball-and-stick geometry	Instanced Meshes + Lines
Data Science	CSV, Parquet, JSON arrays	Parse to typed arrays to BufferGeometry	Point Clouds, Heightmaps
Geospatial	GeoJSON, CityGML, WMS raster, shapefiles	earcut.js triangulation / tile fetch	Surface Meshes, Heightmaps
Simulation (CFD/FEA)	VTK, HDF5 (.h5), OpenFOAM	Server-side convert to binary buffers	Volume, Heightmaps, Particles
Graphs (generic)	DOT, CSV (edge list), adjacency matrix	graphology parse	Force-Directed Graphs

Graph Format Comparison

Format	Structure	Web Parser	Size Efficiency	Metadata Support	Recommendation
GraphML	XML	xml2js + custom	Poor (verbose XML)	Excellent (typed attrs)	Standard interchange
GEXF	XML	graphology plugin	Poor (verbose)	Good (dynamics support)	Temporal graphs

Format	Structure	Web Parser	Size Efficiency	Metadata Support	Recommendation
JSON (custom)	JSON	Native	Good	Flexible	**Internal default**
DOT	Text	graphology plugin	Good (compact)	Basic (labels, styles)	Graphviz compat
CSV edge list	CSV	csvtojson	Excellent	Minimal	Simple imports
Adjacency matrix	Array	Native	OK	None	Mathematical analysis

Library choice: graphology — universal in-memory graph with import/export plugins for all formats above.

Part 7: Existing Code Reuse Across Projects

Visualization Components Already Built

Component	Location	Reusable?	Adaptation Needed
InstancedMesh renderer	`renderer/graph/NodesInstanced.tsx`	**Yes**	Generalize geometry type
Line edge renderer	`renderer/graph/EdgesLines.tsx`	**Yes**	Parameterize color scheme
Point cloud viewer	`renderer/manifold/PointCloud.tsx`	**Yes**	Add domain-specific hover
Force layout engine	`renderer/graph/forceLayout.ts`	**Yes**	Already generic
Raycaster interaction	`renderer/manifold/PointCloud.tsx`	**Yes**	Extract as hook
LOD system	`renderer/graph/NodesInstanced.tsx`	**Yes**	Make configurable
Memory visualization	`t4dm/src/components/MemoryNodes.tsx`	**Partial**	kappa-coloring is domain-specific
Memory edges	`t4dm/src/components/MemoryEdges.tsx`	**Partial**	Weight encoding is generic
2D graphs (D3)	`xai/src/components/N3Graph.tsx`	**No**	2D only, different paradigm
Time-series charts	`xai/src/components/Recharts.tsx`	**No**	2D only

Shared Performance Patterns (Already Validated)

Pattern	Implementation	Measured Benefit
Dirty-flag GPU upload	`if (version === prev) return`	30–50% frame time saved
Object pooling	`_dummy = new Object3D()` pre-allocated	Eliminates GC pressure
Raycaster throttle	33ms interval	10x frame stability
InstancedMesh count	`mesh.count = N` vs re-create	O(1) visibility change
LOD geometry swap	3 detail levels, camera-distance trigger	60–80% triangle savings
One-Euro filtering	Per-joint adaptive smoothing	Usable gesture from noisy signal

Gestalt Performance Benchmarks (Achieved)

Metric	Value
End-to-end latency	~50ms (camera 16ms + MediaPipe ~15ms + gesture ~32ms)

Metric	Value
Gesture throughput	778K frames/sec (25,930x headroom at 30fps)
Node rendering	10K+ instances at 60fps
Point cloud	5K+ points with raycasting at 60fps
Test coverage	1461 tests, 90%+ coverage
AppImage size	71MB (bundled)

Part 8: Summary Statistics & Coverage Analysis

Readiness Distribution

Tier	Count	%	Description
NOW	22	44%	Buildable today with existing tech
NEAR	25	50%	1–2 years, needs integration work
FUTURE	3	6%	3–5 years, needs research

Aaron's Projects Grounded: 19 of 50

Project	Use Cases
XAI thesis	1, 2, 38
T4DW / T4DV	3, 4
Survivorship	5, 14
Kymera memory	6
T4D platform	8
Mean-reversion	9
Forecast-go	10
Screener/Goblin Forge	22
Factorio/AgentForge	23
Gestalt manifold	25
Blender-MCP	32
OSINT context	21, 37
Gestalt overlay	41, 43
All projects	50

Gesture Frequency (All 50 Use Cases)

Gesture	Count	Coverage
Pinch	49/50	98%
FlatDrag	39/50	78%
Twist	36/50	72%
Point	32/50	64%
2H-Pinch	28/50	56%
Fist	18/50	36%
L-Shape	14/50	28%
OpenPalm	12/50	24%
2H-Push	10/50	20%
2H-Rotate	6/50	12%

Maximum Utility: What to Build First

If you build these 4 rendering primitives + the existing 4, you cover 80%+ of use cases:

```
ALREADY BUILT (Gestalt)          MUST ADD (Tier 2)
  Point Clouds (P1)                Surface Meshes (P4) - GLTF loader
  Force Graphs (P2)                Heightmaps (P6) - displacement shader
  Instanced Meshes (P5)            3D UI Panels (P10) - @react-three/uikit
  Lines & Tubes (P8)
```

If you add these 3 gesture capabilities, you cover 25–35% more interaction patterns:

```
ALREADY BUILT (10 types)         MUST ADD (continuous data)
  Pinch (binary)             ->    Pinch distance (continuous float)
  FlatDrag                   ->    Swipe direction (4-way velocity)
  OpenPalm                   ->    Hand orientation (palm normal vector)
```

Part 9: Critical Files

File	Role
`src/shared/protocol.ts`	10 GestureTypes + shared types
`src/renderer/controller/dispatcher.ts`	Gesture to action mapping
`src/renderer/gestures/classifier.ts`	873-line gesture classification engine
`src/renderer/gestures/state.ts`	580-line state machine
`src/renderer/tracker/HandTracker.ts`	649-line MediaPipe wrapper + filtering
`src/renderer/tracker/stereo-fuser.ts`	Dual-camera triangulation
`src/renderer/graph/Nodes.tsx`	InstancedMesh + LOD (reusable pattern)
`src/renderer/graph/Edges.tsx`	LineSegments + dirty-flag (reusable pattern)
`src/renderer/manifold/PointCloud.tsx`	Point cloud + raycaster (reusable pattern)
`src/main/connectors/CONNECTORS.md`	WebSocket bus protocol
`PRD.md`	Original PRD

Part 10: Next Steps

1. **Prioritize hero use cases** — Select 3–5 from NOW tier that span multiple rendering primitives and demonstrate universality.
2. **Add Tier 2 primitives** — Surface Meshes (GLTF), Heightmaps (displacement), 3D UI Panels (uikit).
3. **Expose continuous gesture data** — Pinch distance, swipe direction, hand orientation.
4. **Design plugin/adapter pattern** — Abstract the domain-specific data loading and gesture mapping so each use case is a thin adapter.
5. **Architect agent swarm layer** — RedDebate pattern, Constitutional AI constraints for the governance layer (use case 50).
6. **Prototype** — Build one hero use case end-to-end to validate the architecture.