

MID 36-60KTL3-X3

- Maximum string input current 20A
- 150% DC/AC ratio
- 4/5 MPPT, max. efficiency 98.8%
- Intelligent string monitoring, smart I-V curve scan
- AFCI function ready



P O W E R
- I N G
T O M O R R O W

Datasheet	MID 36KTL3-X3	MID 40KTL3-X3	MID 50KTL3-X3	MID 60KTL3-X3
Input Data (DC)				
Max. recommended PV power	54000W	60000W	75000W	90000W
Max. DC input voltage	1100V			
Start voltage	200V			
Nominal input voltage	600V			
MPP voltage range	160-1000V			
Full-load MPPT voltage range (certification)	350-850V		420-850V	
No. of MPPTs	4			5
Max. input strings per MPPT	2/2/2/2			2/2/2/1
Max. input currentper MPPT	40A/40A/40A/40A			40A/40A/40A/40A/20A
Max. short-circuit current per MPPT	50A/50A/50A/50A			50A/50A/50A/50A/25A
Output Data (AC)				
Rated AC output power	36000W	40000W	50000W	60000W
Max. AC apparent power	40000VA	44400VA	55500VA	66600VA
Nominal AC voltage / range	220V/380V; 230V/400V; 340-440V			
AC grid frequency / range	50/60 Hz 45~55Hz/55-65 Hz			
Max. output current	60.6A	67.3A	84.1A	100.9A
Power factor(at rated power)	>0.99			
Adjustable power factor range	0.8 leading ... 0.8 lagging			
Total harmonic distortion (THD)	<3%			
AC grid connection type	3W+N+PE			
Efficiency				
Max. efficiency	98.8%			
European efficiency	98.5%			
Protection				
DC reverse-polarity protection	Yes			
DC switch	Yes			
DC surge protection	Type II			
Insulation-resistance monitoring	Yes			
AC surge protection	Type II			
AC short-circuit protection	Yes			
Ground-fault monitoring	Yes			
Grid monitoring	Yes			
Anti-islanding protection	Yes			
Residual-current monitoring	Yes			
PID detection and recovery	No			
String monitoring	Optional			
Arc-fault circuit interrupter (AFCI)	Optional			
General Data				
Dimensions (W/H/D)	580*435*230mm			
Weight	28.6kg		29.6 kg	30.2 kg
Operating temperature range	-25°C ... +60°C			
Noise emission	≤55dB(A)			
Max. operating altitude	4000m(derating above 2000 m)			
Topology	Transformerless			
Cooling method	Forced air cooling			
Ingress protection rating	IP66			
Relative humidity	0~100%			
DC terminal type	H4/MC4 (optional)			
AC terminal type	Waterproof PG gland + OT terminal			
Display	LED indicator + OLED WiFi + APP			
USB/RS485	Yes			
WiFi/GPRS/4G/LAN	Optional			
Monitor	ShineWlan-X2 (for single device), ShineMaster4G-X or SEM-XA-R (for parallel devices)			
Warranty	5 years / 10 years(Optional)			
CE,IEC 61683/60068,IEC 62116/61727,RD 1699,INMETRO				