

ASTRAQ

ASTRAQ Electric Light Truck

4x2 Battery-Electric Urban Logistics Truck



Key Configuration

Model positioning	4x2 battery-electric light-duty box truck for urban and metro distribution
Overall dimensions (mm)	5,995 x 2,200 x 3,150 (box-body configuration)
Wheelbase (mm)	3,400
GVM	4,495 kg
Body type	Dry van / box body; refrigerated body available
Traction battery	LFP / blade battery, liquid-cooled pack
Battery capacity (kWh)	100 kWh standard; 132 kWh long-range option
Motor power	70 kW rated / 150 kW peak
Driving range	220-300 km typical urban operation, depending on load and body type
Charging method	CCS2; AC 11 kW, DC fast charge up to 70 kW

Vehicle & Chassis

Drive configuration	4x2
Vehicle category	4.5t electric light-duty truck
Cab	Forward-control EV cab, white exterior, aerodynamic front styling
Body	Integrated box body for city delivery applications
Frame	Ladder frame with box-body mounting provision
Front axle capacity	2,600 kg
Rear axle capacity	4,500 kg
Suspension	Front independent / coil spring; rear leaf spring with shock absorbers
Tyres	17.5-inch commercial tyres; 205/75R17.5 reference size
Turning circle	Approx. 12.8 m for 3,400 mm wheelbase configuration

Electric Drive, Battery & Charging

Motor	Permanent-magnet synchronous motor
Peak torque	430 Nm peak / 250 Nm continuous
Transmission	Single-speed reduction gearbox; no gear changes
Battery chemistry	LFP / blade battery
Battery capacity	100 kWh standard; 132 kWh option
Battery cooling	Liquid-cooled battery thermal management
Charging standard	CCS2
AC charging	Up to 11 kW
DC fast charging	Up to 70 kW
Auxiliary power	12V / 24V electrical system with body-builder support

Safety, Intelligence & Comfort

Active safety	AEB / Active Brake Assist, LDWS, ESP/ESC, ABS + EBD
Urban safety	Acoustic Vehicle Alerting System (AVAS), reverse warning buzzer
Lighting	LED headlamps, LED taillamps and daytime running lamps
Braking	Hydraulic dual-circuit disc brakes with regenerative braking
Parking brake	Electric park brake
Cab safety	ECE-R29 cab strength concept; driver and passenger SRS airbags
Driver interface	Digital display with speed, battery percentage, range and temperature
Comfort	Air conditioning / heater / demister; electric windows; central locking

Designed for zero-emission urban logistics, quiet delivery operation and practical city access.