

## ACID Transaction

A type of database transaction that has four important properties:

- **Atomicity:** The operations that constitute the transaction will either all succeed or all fail. There is no in-between state.
- **Consistency:** The transaction cannot bring the database to an invalid state. After the transaction is committed or rolled back, the rules for each record will still apply, and all future transactions will see the effect of the transaction. Also named **Strong Consistency**.
- **Isolation:** The execution of multiple transactions concurrently will have the same effect as if they had been executed sequentially.
- **Durability:** Any committed transaction is written to non-volatile storage. It will not be undone by a crash, power loss, or network partition.

## ACL

Short for **Access-Control List**. This term is often used to refer to a permissioning model: which users in a system can perform which operations. For instance, APIs often come with ACLs defining which users can delete, edit, or view certain entities.

## AES

Stands for **Advanced Encryption Standard**. AES is a widely used encryption standard that has three symmetric-key algorithms (AES-128, AES-192, and AES-256).

Of note, AES is considered to be the "gold standard" in encryption and is even used by the U.S. National Security Agency to encrypt top secret information.

## Alerting

The process through which system administrators get notified when critical system issues occur. Alerting can be set up by defining specific thresholds on monitoring charts, past which alerts are sent to a communication channel like Slack.

## Apache Kafka ⚡

A distributed messaging system created by LinkedIn. Very useful when using the **streaming** paradigm as opposed to **polling**.

Learn more: <https://kafka.apache.org/>

## Asymmetric Encryption

Also known as public-key encryption, asymmetric encryption relies on two keys—a public key and a private key—to encrypt and decrypt data. The keys are generated using cryptographic algorithms and are mathematically connected such that data encrypted with the public key can only be decrypted with the private key.

While the private key must be kept secure to maintain the fidelity of this encryption paradigm, the public key can be openly shared.

Asymmetric-key algorithms tend to be slower than their symmetric counterparts.

## | Availability

The odds of a particular server or service being up and running at any point in time, usually measured in percentages. A server that has 99% availability will be operational 99% of the time (this would be described as having two **nines** of availability).

## | Availability Zone

Sometimes referred to as an **AZ**, an availability zone designates a group of machines that share one or more central system components (e.g., power source, network connectivity, machine-cooling system). Availability zones are typically located far away from each other such that no natural disaster can realistically bring down two of them at once. This ensures that if you have redundant storage, for instance, with data stored in two availability zones, losing one **AZ** still leaves you with an operational system that abides by any **SLA** that it might have.

## | Blob Storage

Widely used kind of storage, in small and large scale systems. They don't really count as databases per se, partially because they only allow the user to store and retrieve data based on the name of the blob. This is sort of like a key-value store but usually blob stores have different guarantees. They might be slower than KV stores but values can be megabytes large (or sometimes gigabytes large). Usually people use this to store things like **large binaries, database snapshots, or images** and other static assets that a website might have.

Blob storage is rather complicated to have on premise, and only giant companies like Google and Amazon have infrastructure that supports it. So usually in the context of System Design interviews you can assume that you will be able to use **GCS** or **S3**. These are blob storage services hosted by Google and Amazon respectively, that cost money depending on how much storage you use and how often you store and retrieve blobs from that storage.

## | Cache

A piece of hardware or software that stores data, typically meant to retrieve that data faster than otherwise.

Caches are often used to store responses to network requests as well as results of computationally-long operations.

Note that data in a cache can become **stale** if the main source of truth for that data (i.e., the main database behind the cache) gets updated and the cache doesn't.

## | Cache Eviction Policy

The policy by which values get evicted or removed from a cache. Popular cache eviction policies include **LRU** (least-recently used), **FIFO** (first in first out), and **LFU** (least-frequently used).

## | Cache Hit

When requested data is found in a cache.

## | Cache Miss

When requested data could have been found in a cache but isn't. This is typically used to refer to a negative consequence of a system failure or of a poor design choice. For example:

*If a server goes down, our load balancer will have to forward requests to a new server, which will result in cache misses.*

## ■ CAP Theorem

Stands for **Consistency, Availability, Partition tolerance**. In a nutshell, this theorem states that any distributed system can only achieve 2 of these 3 properties. Furthermore, since almost all useful systems do have network-partition tolerance, it's generally boiled down to: *Consistency vs. Availability; pick one.*

One thing to keep in mind is that some levels of consistency are still achievable with high availability, but *strong* consistency is much harder.

## ■ Certificate Authority

A trusted entity that signs digital certificates—namely, SSL certificates that are relied on in **HTTPS** connections.

## ■ Client

A machine or process that requests data or service from a server.

Note that a single machine or piece of software can be both a client and a server at the same time. For instance, a single machine could act as a server for end users and as a client for a database.

## ■ Client—Server Model

The paradigm by which modern systems are designed, which consists of clients requesting data or service from servers and servers providing data or service to clients.

## ■ Cloud Pub/Sub ⚡

A highly-scalable Pub/Sub messaging service created by Google. Guarantees **at-least-once delivery** of messages and supports "rewinding" in order to reprocess messages.

Learn more: <https://cloud.google.com/pubsub/>

## ■ Configuration

A set of parameters or constants that are critical to a system. Configuration is typically written in **JSON** or **YAML** and can be either **static**, meaning that it's hard-coded in and shipped with your system's application code (like frontend code, for instance), or **dynamic**, meaning that it lives outside of your system's application code.

## ■ Consensus Algorithm

A type of complex algorithms used to have multiple entities agree on a single data value, like who the "leader" is amongst a group of machines. Two popular consensus algorithms are **Paxos** and **Raft**.

## ■ Consistent Hashing

A type of hashing that minimizes the number of keys that need to be remapped when a hash table gets resized. It's often used by load balancers to distribute traffic to servers; it minimizes the number of requests that get forwarded to different servers when new servers are added or when existing servers are brought down.

## Content Delivery Network

A **CDN** is a third-party service that acts like a cache for your servers. Sometimes, web applications can be slow for users in a particular region if your servers are located only in another region. A CDN has servers all around the world, meaning that the latency to a CDN's servers will almost always be far better than the latency to your servers. A CDN's servers are often referred to as **PoPs** (Points of Presence). Two of the most popular CDNs are **Cloudflare** and **Google Cloud CDN**.

## CRUD Operations

Stands for **Create, Read, Update, Delete** Operations. These four operations often serve as the bedrock of a functioning system and therefore find themselves at the core of many APIs. The term **CRUD** is very likely to come up during an API-design interview.

## Cypher

A **graph query language** that was originally developed for the Neo4j graph database, but that has since been standardized to be used with other graph databases in an effort to make it the "SQL for graphs."

Cypher queries are often much simpler than their SQL counterparts. Example Cypher query to find data in **Neo4j**, a popular graph database:

```
MATCH (some_node:SomeLabel)-[:SOME_RELATIONSHIP]->(some_other_node:SomeLabel
{some_property:'value'})
```

## Database Index

A special auxiliary data structure that allows your database to perform certain queries much faster. Indexes can typically only exist to reference structured data, like data stored in relational databases. In practice, you create an index on one or multiple columns in your database to greatly speed up **read** queries that you run very often, with the downside of slightly longer **writes** to your database, since writes have to also take place in the relevant index.

## Database Lock

In a relational database that provides ACID transactions, updating rows inside a table will cause a **lock** to be held on that table or on the rows you are updating. If a second transaction tries to update the same rows, it will block before the update until the first transaction releases that lock. This is one of the core mechanisms behind the **Atomicity** of ACID transactions.

## Databases

Databases are programs that either use disk or memory to do 2 core things: **record** data and **query** data. In general, they are themselves servers that are long lived and interact with the rest of your

application through network calls, with protocols on top of TCP or even HTTP.

Some databases only keep records in memory, and the users of such databases are aware of the fact that those records may be lost forever if the machine or process dies.

For the most part though, databases need persistence of those records, and thus cannot use memory. This means that you have to write your data to disk. Anything written to disk will remain through power loss or network partitions, so that's what is used to keep permanent records.

Since machines die often in a large scale system, special disk partitions or volumes are used by the database processes, and those volumes can get recovered even if the machine were to go down permanently.

## **DDoS Attack**

Short for "distributed denial-of-service attack", a DDoS attack is a DoS attack in which the traffic flooding the target system comes from many different sources (like thousands of machines), making it much harder to defend against.

## **Disk**

Usually refers to either **HDD (hard-disk drive)** or **SSD (solid-state drive)**. Data written to disk will persist through power failures and general machine crashes. Disk is also referred to as **non-volatile storage**.

SSD is far faster than HDD (see latencies of accessing data from SSD and HDD) but also far more expensive from a financial point of view. Because of that, HDD will typically be used for data that's rarely accessed or updated, but that's stored for a long time, and SSD will be used for data that's frequently accessed and updated.

## **Distributed File System**

A Distributed File System is an abstraction over a (usually large) cluster of machines that allows them to act like one large file system. The two most popular implementations of a DFS are the **Google File System** (GFS) and the **Hadoop Distributed File System** (HDFS).

Typically, DFSs take care of the classic **availability** and **replication** guarantees that can be tricky to obtain in a distributed-system setting. The overarching idea is that files are split into chunks of a certain size (4MB or 64MB, for instance), and those chunks are sharded across a large cluster of machines. A central control plane is in charge of deciding where each chunk resides, routing reads to the right nodes, and handling communication between machines.

Different DFS implementations have slightly different APIs and semantics, but they achieve the same common goal: extremely large-scale persistent storage.

## **DNS**

Short for Domain Name System, it describes the entities and protocols involved in the translation from domain names to IP Addresses. Typically, machines make a DNS query to a well known entity which is responsible for returning the IP address (or multiple ones) of the requested domain name in the response.

## **DoS Attack**

Short for "denial-of-service attack", a DoS attack is an attack in which a malicious user tries to bring down or damage a system in order to render it unavailable to users. Much of the time, it consists of flooding it with traffic. Some DoS attacks are easily preventable with rate limiting, while others can be far trickier to defend against.

## **Estimation Cheat Sheet**

### **Units Cheat Sheet**

These values are defined by the International System of Units.

- 1kB = 1000 bytes
- 1MB = 1000kB
- 1GB = 1000MB
- 1TB = 1000GB
- 1PB = 1000TB

### **Storage Scale Cheat Sheet**

- A character  
=> 1 byte
- Typical metadata for a "thing," excluding images (name, description, other attributes, etc.)  
=> ~1-10KB
- A high-quality 1920x1080p image  
=> ~2MB (realistically can be lossy-compressed by ~10-20x)
- 20 minutes of HD video  
=> ~1GB

### **Storage Capacity Cheat Sheet**

How much storage can a single industry-grade machine have?

- ~10TB disk space
- ~256GB-1TB of RAM (1TB for really large/optimized machines)

### **Latency Cheat Sheet**

How long does it take for a regular HTTP request to make a round trip, not bound by bandwidth?

- Intra-continental  
=> ~50-150ms
- Cross-continental  
=> ~200-500ms

### **Bandwidth Cheat Sheet**

- Mobile phone (4G)  
=> ~1-3MB/s

- Public internet (home WiFi)  
=> ~50-100MB/s
- Within a data center  
=> ~5GB/s

## Etcd ⚡

Etcd is a strongly consistent and highly available key-value store that's often used to implement leader election in a system.

Learn more: <https://etcd.io/>

## Eventual Consistency

A consistency model which is unlike **Strong Consistency**. In this model, reads might return a view of the system that is stale. An eventually consistent datastore will give guarantees that the state of the database will eventually reflect writes within a time period (could be 10 seconds, or minutes).

## File System

An abstraction over a storage medium that defines how to manage data. While there exist many different types of file systems, most follow a hierarchical structure that consists of directories and files, like the **Unix file system**'s structure.

## Forward Proxy

A server that sits between a client and servers and acts on behalf of the client, typically used to mask the client's identity (IP address). Note that forward proxies are often referred to as just proxies.

## Google Cloud Storage ⚡

GCS is a blob storage service provided by Google.

Learn more: <https://cloud.google.com/storage>

## Gossip Protocol

When a set of machines talk to each other in an uncoordinated manner in a cluster to spread information through a system without requiring a central source of data.

## Graph Database

A type of database that stores data following the graph data model. Data entries in a graph database can have explicitly defined relationships, much like nodes in a graph can have edges.

Graph databases take advantage of their underlying graph structure to perform complex queries on deeply connected data very fast.

Graph databases are thus often preferred to relational databases when dealing with systems where data points naturally form a graph and have multiple levels of relationships—for example, social networks.

## Hadoop ⚡

A popular, open-source framework that supports MapReduce jobs and many other kinds of data-processing pipelines. Its central component is **HDFS** (Hadoop Distributed File System), on top of which other technologies have been developed.

Learn more: <https://hadoop.apache.org/>

## ■ Hashing Function

A function that takes in a specific data type (such as a string or an identifier) and outputs a number. Different inputs *may* have the same output, but a good hashing function attempts to minimize those **hashing collisions** (which is equivalent to maximizing **uniformity**).

## ■ High Availability

Used to describe systems that have particularly high levels of availability, typically 5 nines or more; sometimes abbreviated "HA".

## ■ Horizontal Scaling

Scaling a system horizontally means adding more machines to perform the same task, resulting in increased throughput for the system. Typically, horizontal scaling increases a system's throughput roughly linearly with the number of machines performing a given task.

## ■ Hot Spot

When distributing a workload across a set of servers, that workload might be spread unevenly. This can happen if your **sharding key** or your **hashing function** are suboptimal, or if your workload is naturally skewed: some servers will receive a lot more traffic than others, thus creating a "hot spot".

## ■ HTTP

The **HyperText Transfer Protocol** is a very common network protocol implemented on top of TCP. Clients make HTTP requests, and servers respond with a response.

Requests typically have the following schema:

```
host: string (example: algoexpert.io)
port: integer (example: 80 or 443)
method: string (example: GET, PUT, POST, DELETE, OPTIONS or PATCH)
headers: pair list (example: "Content-Type" => "application/json")
body: opaque sequence of bytes
```

Responses typically have the following schema:

```
status code: integer (example: 200, 401)
headers: pair list (example: "Content-Length" => 1238)
body: opaque sequence of bytes
```

## ■ HTTPS

The **HyperText Transfer Protocol Secure** is an extension of **HTTP** that's used for secure communication online. It requires servers to have trusted certificates (usually **SSL certificates**) and uses the Transport



Layer Security (**TLS**), a security protocol built on top of **TCP**, to encrypt data communicated between a client and a server.

## Idempotent Operation

An operation that has the same ultimate outcome regardless of how many times it's performed. If an operation can be performed multiple times without changing its overall effect, it's idempotent.

Operations performed through a **Pub/Sub** messaging system typically have to be idempotent, since Pub/Sub systems tend to allow the same messages to be consumed multiple times.

For example, increasing an integer value in a database is *not* an idempotent operation, since repeating this operation will not have the same effect as if it had been performed only once. Conversely, setting a value to "COMPLETE" *is* an idempotent operation, since repeating this operation will always yield the same result: the value will be "COMPLETE".

## InfluxDB ⚡

A popular open-source time series database.

Learn more: <https://www.influxdata.com/>

## IP

Stands for **Internet Protocol**. This network protocol outlines how almost all machine-to-machine communications should happen in the world. Other protocols like **TCP**, **UDP** and **HTTP** are built on top of IP.

## IP Address

An address given to each machine connected to the public internet. IPv4 addresses consist of four numbers separated by dots: **a.b.c.d** where all four numbers are between 0 and 255. Special values include:

- **127.0.0.1**: Your own local machine. Also referred to as **localhost**.
- **192.168.x.y**: Your private network. For instance, your machine and all machines on your private wifi network will usually have the **192.168** prefix.

## IP Packet

Sometimes more broadly referred to as just a (network) **packet**, an IP packet is effectively the smallest unit used to describe data being sent over **IP**, aside from bytes. An IP packet consists of:

- an **IP header**, which contains the source and destination **IP addresses** as well as other information related to the network
- a **payload**, which is just the data being sent over the network

## JSON

A file format heavily used in APIs and configuration. Stands for **JavaScript Object Notation**. Example:

```
{  
  "version": 1.0,  
}
```

```
"name": "AlgoExpert Configuration"
}
```

## I Key-Value Store

A Key-Value Store is a flexible NoSQL database that's often used for caching and dynamic configuration. Popular options include DynamoDB, Etcd, Redis, and ZooKeeper.

## I Latency

The time it takes for a certain operation to complete in a system. Most often this measure is a time duration, like milliseconds or seconds. You should know these orders of magnitude:

- **Reading 1 MB from RAM:** 250  $\mu$ s (0.25 ms)
- **Reading 1 MB from SSD:** 1,000  $\mu$ s (1 ms)
- **Transfer 1 MB over Network:** 10,000  $\mu$ s (10 ms)
- **Reading 1MB from HDD:** 20,000  $\mu$ s (20 ms)
- **Inter-Continental Round Trip:** 150,000  $\mu$ s (150 ms)

## I Leader Election

The process by which nodes in a cluster (for instance, servers in a set of servers) elect a so-called "leader" amongst them, responsible for the primary operations of the service that these nodes support. When correctly implemented, leader election guarantees that all nodes in the cluster know which one is the leader at any given time and can elect a new leader if the leader dies for whatever reason.

## I Load Balancer

A type of **reverse proxy** that distributes traffic across servers. Load balancers can be found in many parts of a system, from the DNS layer all the way to the database layer.

## I Logging

The act of collecting and storing logs--useful information about events in your system. Typically your programs will output log messages to its STDOUT or STDERR pipes, which will automatically get aggregated into a **centralized logging solution**.

## I Man-In-The-Middle Attack

An attack in which the attacker intercepts a line of communication that is thought to be private by its two communicating parties.

If a malicious actor intercepted and mutated an IP packet on its way from a client to a server, that would be a man-in-the-middle attack.

MITM attacks are the primary threat that encryption and **HTTPS** aim to defend against.

## I MapReduce

A popular framework for processing very large datasets in a distributed setting efficiently, quickly, and in a fault-tolerant manner. A MapReduce job is comprised of 3 main steps:

- the **Map** step, which runs a **map function** on the various chunks of the dataset and transforms these chunks into intermediate **key-value pairs**.
- the **Shuffle** step, which reorganizes the intermediate **key-value pairs** such that pairs of the same key are routed to the same machine in the final step.
- the **Reduce** step, which runs a **reduce function** on the newly shuffled **key-value pairs** and transforms them into more meaningful data.

The canonical example of a MapReduce use case is counting the number of occurrences of words in a large text file.

When dealing with a MapReduce library, engineers and/or systems administrators only need to worry about the map and reduce functions, as well as their inputs and outputs. All other concerns, including the parallelization of tasks and the fault-tolerance of the MapReduce job, are abstracted away and taken care of by the MapReduce implementation.

## Memory

Short for **Random Access Memory (RAM)**. Data stored in memory will be lost when the process that has written that data dies.

## Microservice Architecture

When a system is made up of many small web services that can be compiled and deployed independently. This is usually thought of as a counterpart of **monoliths**.

## MongoDB ⚡

A NoSQL database with powerful querying through a JavaScript-like language. Consistency guarantees depend on the settings that the database is setup with.

Learn more: <https://www.mongodb.com/>

## Monitoring

The process of having visibility into a system's key metrics, monitoring is typically implemented by collecting important events in a system and aggregating them in human-readable charts.

## Monolith Architecture

When a system is primarily made up of a single large web application that is compiled and rolled out as a unit. Typically a counterpart of **microservices**. Companies sometimes try to split up this monolith into microservices once it reaches a very large size in an attempt to increase **developer productivity**.

## MySQL ⚡

A relational database that provides ACID transactions and supports a SQL dialect.

Learn more: <https://www.mysql.com/>

## Neo4j ⚡

A popular graph database that consists of **nodes**, **relationships**, **properties**, and **labels**.

Learn more: <https://neo4j.com/>

## ■ Nginx ⚡

Pronounced "engine X"—not "N jinx", Nginx is a very popular webserver that's often used as a **reverse proxy** and **load balancer**.

Learn more: <https://www.nginx.com/>

## ■ Nines

Typically refers to percentages of uptime. For example, 5 nines of availability means an uptime of 99.999% of the time. Below are the downtimes expected per year depending on those 9s:

- 99% (two 9s): 87.7 hours
- 99.9% (three 9s): 8.8 hours
- 99.99%: 52.6 minutes
- 99.999%: 5.3 minutes

## ■ Node/Instance/Host

These three terms refer to the same thing most of the time: a virtual or physical machine on which the developer runs processes. Sometimes the word **server** also refers to this same concept.

## ■ Non-Relational Database

In contrast with relational database (SQL databases), a type of database that is free of imposed, tabular-like structure. Non-relational databases are often referred to as NoSQL databases.

## ■ NoSQL Database

Any database that is not SQL-compatible is called NoSQL.

## ■ Pagination

When a network request potentially warrants a really large response, the relevant API might be designed to return only a single **page** of that response (i.e., a limited portion of the response), accompanied by an identifier or token for the client to request the next page if desired.

Pagination is often used when designing **List** endpoints. For instance, an endpoint to list videos on the YouTube Trending page could return a huge list of videos. This wouldn't perform very well on mobile devices due to the lower network speeds and simply wouldn't be optimal, since most users will only ever scroll through the first ten or twenty videos. So, the API could be designed to respond with only the first few videos of that list; in this case, we would say that the API response is **paginated**.

## ■ Paxos & Raft

Two consensus algorithms that, when implemented correctly, allow for the synchronization of certain operations, even in a distributed setting.

## ■ Peer-To-Peer Network

A collection of machines referred to as peers that divide a workload between themselves to presumably complete the workload faster than would otherwise be possible. Peer-to-peer networks are often used in file-distribution systems.

## Percentiles

Most often used when describing a **latency distribution**. If your **X**th percentile is 100 milliseconds, it means that **X**% of the requests have latencies of 100ms or less. Sometimes, SLAs describe their guarantees using these percentiles.

## Persistent Storage

Usually refers to disk, but in general it is any form of storage that persists if the process in charge of managing it dies.

## Polling

The act of fetching a resource or piece of data regularly at an interval to make sure your data is not too stale.

## Port

In order for multiple programs to listen for new network connections on the same machine without colliding, they pick a **port** to listen on. A port is an integer between 0 and 65,535 ( $2^{16}$  ports total).

Typically, ports 0-1023 are reserved for *system ports* (also called *well-known* ports) and shouldn't be used by user-level processes. Certain ports have pre-defined uses, and although you usually won't be required to have them memorized, they can sometimes come in handy. Below are some examples:

- 22: Secure Shell
- 53: DNS lookup
- 80: HTTP
- 443: HTTPS

## Postgres ⚡

A relational database that uses a dialect of SQL called PostgreSQL. Provides ACID transactions.

Learn more: <https://www.postgresql.org/>

## Process

A program that is currently running on a machine. You should always assume that any process may get terminated at any time in a sufficiently large system.

## Prometheus ⚡

A popular open-source time series database, typically used for monitoring purposes.

Learn more: <https://prometheus.io/>

## Publish/Subscribe Pattern

Often shortened as **Pub/Sub**, the Publish/Subscribe pattern is a popular messaging model that consists of **publishers** and **subscribers**. Publishers publish messages to special **topics** (sometimes called **channels**) without caring about or even knowing who will read those messages, and subscribers subscribe to topics and read messages coming through those topics.

Pub/Sub systems often come with very powerful guarantees like **at-least-once delivery**, **persistent storage**, **ordering** of messages, and **replayability** of messages.

## I Quadtree

A tree data structure most commonly used to index two-dimensional spatial data. Each node in a quadtree has either zero children nodes (and is therefore a leaf node) or exactly four children nodes.

Typically, quadtree nodes contain some form of spatial data—for example, locations on a map—with a maximum capacity of some specified number **n**. So long as nodes aren't at capacity, they remain leaf nodes; once they reach capacity, they're given four children nodes, and their data entries are split across the four children nodes.

A quadtree lends itself well to storing spatial data because it can be represented as a grid filled with rectangles that are recursively subdivided into four sub-rectangles, where each quadtree node is represented by a rectangle and each rectangle represents a spatial region. Assuming we're storing locations in the world, we can imagine a quadtree with a maximum node-capacity **n** as follows:

- The root node, which represents the entire world, is the outermost rectangle.
- If the entire world has more than **n** locations, the outermost rectangle is divided into four quadrants, each representing a region of the world.
- So long as a region has more than **n** locations, its corresponding rectangle is subdivided into four quadrants (the corresponding node in the quadtree is given four children nodes).
- Regions that have fewer than **n** locations are undivided rectangles (leaf nodes).
- The parts of the grid that have many subdivided rectangles represent densely populated areas (like cities), while the parts of the grid that have few subdivided rectangles represent sparsely populated areas (like rural areas).

Finding a given location in a perfect quadtree is an extremely fast operation that runs in **log<sub>4</sub>(x)** time (where **x** is the total number of locations), since quadtree nodes have four children nodes.

## I Rate Limiting

The act of limiting the number of requests sent to or from a system. Rate limiting is most often used to limit the number of incoming requests in order to prevent **DoS attacks** and can be enforced at the IP-address level, at the user-account level, or at the region level, for example. Rate limiting can also be implemented in tiers; for instance, a type of network request could be limited to 1 per second, 5 per 10 seconds, and 10 per minute.

## I Redis ⚡

An in-memory key-value store. Does offer some persistent storage options but is typically used as a really fast, best-effort caching solution. Redis is also often used to implement **rate limiting**.

Learn more: <https://redis.io/>

## I Redundancy

The process of replicating parts of a system in an effort to make it more reliable.

## I Relational Database

A type of structured database in which data is stored following a tabular format; often supports powerful querying using SQL.

## I Rendezvous Hashing

A type of hashing also coined **highest random weight** hashing. Allows for minimal re-distribution of mappings when a server goes down.

## I Replication

The act of duplicating the data from one database server to others. This is sometimes used to increase the redundancy of your system and tolerate regional failures for instance. Other times you can use replication to move data closer to your clients, thus decreasing the latency of accessing specific data.

## I Reverse Proxy

A server that sits between clients and servers and acts on behalf of the servers, typically used for logging, load balancing, or caching.

## I S3 ⚡

S3 is a blob storage service provided by Amazon through **Amazon Web Services (AWS)**.

Learn more: <https://aws.amazon.com/s3/>

## I Server

A machine or process that provides data or service for a client, usually by listening for incoming network calls.

Note that a single machine or piece of software can be both a client and a server at the same time. For instance, a single machine could act as a server for end users and as a client for a database.

## I Server-Selection Strategy

How a **load balancer** chooses servers when distributing traffic amongst multiple servers. Commonly used strategies include round-robin, random selection, performance-based selection (choosing the server with the best performance metrics, like the fastest response time or the least amount of traffic), and IP-based routing.

## I SHA

Short for "Secure Hash Algorithms", the SHA is a collection of cryptographic hash functions used in the industry. These days, SHA-3 is a popular choice to use in a system.

## I Sharding

Sometimes called **data partitioning**, sharding is the act of splitting a database into two or more pieces called **shards** and is typically done to increase the throughput of your database. Popular sharding strategies include:

- Sharding based on a client's region
- Sharding based on the type of data being stored (e.g: user data gets stored in one shard, payments data gets stored in another shard)
- Sharding based on the hash of a column (only for structured data)

## I SLA

Short for "service-level agreement", an SLA is a collection of guarantees given to a customer by a service provider. SLAs typically make guarantees on a system's availability, amongst other things. SLAs are made up of one or multiple SLOs.

## I SLO

Short for "service-level objective", an SLO is a guarantee given to a customer by a service provider. SLOs typically make guarantees on a system's availability, amongst other things. SLOs constitute an SLA.

## I Socket

A kind of file that acts like a stream. Processes can read and write to sockets and communicate in this manner. Most of the time the sockets are fronts for TCP connection.

## I Spatial Database

A type of database optimized for storing and querying spatial data like locations on a map. Spatial databases rely on spatial indexes like **quadtrees** to quickly perform spatial queries like finding all locations in the vicinity of a region.

## I SQL

Structured Query Language. Relational databases can be used using a derivative of SQL such as PostgreSQL in the case of Postgres.

## I SQL Database

Any database that supports SQL. This term is often used synonymously with "Relational Database", though in practice, not *every* relational database supports SQL.

## I SSL Certificate

A digital certificate granted to a server by a **certificate authority**. Contains the server's public key, to be used as part of the **TLS handshake** process in an **HTTPS** connection.

An SSL certificate effectively confirms that a public key belongs to the server claiming it belongs to them. SSL certificates are a crucial defense against **man-in-the-middle attacks**.

## I Stateful

A server or process is called "stateful" when it derives its functionality from storing and retrieving things from disk. Databases are primary case studies for stateful servers. Because of this persistence



requirement, it's much more difficult to run and manage stateful servers compared to **Stateless** servers because they can't be stopped and restarted on any physical machine.

## ■ Stateless

A server is usually called "stateless" if it does not *require* state to be persisted to disk in order to run successfully. Although many server process typically hold some state in memory including caching layers for instance, this typically means that we can run the server process the same way on any machine, and move it around whenever we want. This contrasts with **Stateful** processes.

## ■ Streaming

In networking, it usually refers to the act of continuously getting a feed of information from a server by keeping an open connection between the two machines or processes.

## ■ Strong Consistency

Strong Consistency usually refers to the consistency of ACID transactions, as opposed to **Eventual Consistency**.

## ■ Symmetric Encryption

A type of encryption that relies on only a single key to both encrypt and decrypt data. The key must be known to all parties involved in communication and must therefore typically be shared between the parties at one point or another.

Symmetric-key algorithms tend to be faster than their asymmetric counterparts.

The most widely used symmetric-key algorithms are part of the Advanced Encryption Standard (**AES**).

## ■ TCP

Network protocol built on top of the Internet Protocol (IP). Allows for ordered, reliable data delivery between machines over the public internet by creating a **connection**.

TCP is usually implemented in the kernel, which exposes **sockets** to applications that they can use to stream data through an open connection.

## ■ Throughput

The number of operations that a system can handle properly per time unit. For instance the throughput of a server can often be measured in requests per second (RPS or QPS).

## ■ Time Series Database

A **TSDB** is a special kind of database optimized for storing and analyzing time-indexed data: data points that specifically occur at a given moment in time. Examples of TSDBs are InfluxDB, Prometheus, and Graphite.

## ■ TLS

The **Transport Layer Security** is a security protocol over which **HTTP** runs in order to achieve secure communication online. "HTTP over TLS" is also known as **HTTPS**.

■

## TLS Handshake

The process through which a client and a server communicating over **HTTPS** exchange encryption-related information and establish a secure communication. The typical steps in a TLS handshake are roughly as follows:

- The client sends a **client hello**—a string of random bytes—to the server.
- The server responds with a **server hello**—another string of random bytes—as well as its **SSL certificate**, which contains its **public key**.
- The client verifies that the certificate was issued by a **certificate authority** and sends a **premaster secret**—yet another string of random bytes, this time encrypted with the server's public key—to the server.
- The client and the server use the client hello, the server hello, and the premaster secret to then generate the same **symmetric-encryption** session keys, to be used to encrypt and decrypt all data communicated during the remainder of the connection.

## Vertical Scaling

Scaling a system vertically means increasing the resources (CPU / Memory) available to a certain task on a single machine, so that your throughput may increase.

## Virtual Machine

A **VM** is a form of computer inside of a computer. It is a program that you run on a machine that completely emulates a new kernel and operating system. Very useful when isolating programs from one another while having them share the same physical machine.

## Worker Pool Pattern

Similar to the **Task Queue Pattern**. In this design, a pool of workers, usually themselves servers, take tasks off of a single shared queue and process those tasks independently. In order to ensure that every task gets done at least once despite potential partitions between queue and workers, the workers *must* confirm the status of the task after it is done (usually **success** or **failure**).

## YAML

A file format mostly used in configuration. Example:

```
version: 1.0
name: AlgoExpert Configuration
```

## ZooKeeper ⚡

ZooKeeper is a strongly consistent, highly available key-value store. It's often used to store important configuration or to perform leader election.

Learn more: <https://zookeeper.apache.org/>