

Lecture 09/30/16

Lecturer: Xiaodi Wu

Reading: Chapter 1.3, Note on loop invariants.

Loop Invariant: Framework to analyze loops

Notations for Loop Invariant

State of computation : (**boolean predicate**) a "snap-shot" of the computation; inter-relations of values of variables.

Program Statement : (**predicate transformers**) a program statement S causes state $\langle P \rangle$ to state $\langle Q \rangle$. (denoted $\langle P \rangle S \langle Q \rangle$).

Loop Invariant: Framework to analyze loops

Notations for Loop Invariant

State of computation : (**boolean predicate**) a "snap-shot" of the computation; inter-relations of values of variables.

Program Statement : (**predicate transformers**) a program statement S causes state $\langle P \rangle$ to state $\langle Q \rangle$. (denoted $\langle P \rangle S \langle Q \rangle$).

- ▶ State: $\langle x = 0; y = 1 \rangle$, $\langle x = y^2 \rangle$,
- ▶ Program Statement: $x \leftarrow x + 1$, $x \leftarrow x \times y$,

Loop Invariant: Framework to analyze loops

Notations for Loop Invariant

State of computation : (**boolean predicate**) a "snap-shot" of the computation; inter-relations of values of variables.

Program Statement : (**predicate transformers**) a program statement S causes state $\langle P \rangle$ to state $\langle Q \rangle$. (denoted $\langle P \rangle S \langle Q \rangle$).

- ▶ State: $\langle x = 0; y = 1 \rangle$, $\langle x = y^2 \rangle$,
- ▶ Program Statement: $x \leftarrow x + 1$, $x \leftarrow x \times y$,

Thus, any line in the program can be expressed as a statement that causes the state (before-line) to the state (after-line).

Loop Invariant

$\langle P \rangle$, the state before the loop
while Condition (C) **do** Body (B)
end while
 $\langle Q \rangle$, the state after the loop

A **loop invariant** I is a boolean predicate that does not change during the execution of the loop.

- ▶ $P \rightarrow I$ before the loop.
- ▶ $\langle I \text{ and } C \rangle B \langle I \rangle$ in the loop.
- ▶ $(I \text{ and } \neg C) \rightarrow Q$ after the loop.

Loop Invariant: Example 1

Code 1

```
 $s \leftarrow 0, k \leftarrow 0$   
while  $k < n + 1$  do  
     $s \leftarrow s + k, k \leftarrow k + 1$   
end while
```

Loop Invariant: Example 1

Code 1

```
 $s \leftarrow 0, k \leftarrow 0$   
while  $k < n + 1$  do  
     $s \leftarrow s + k, k \leftarrow k + 1$   
end while
```

- Invariant I : $s = k(k - 1)/2 \wedge (0 \leq k \leq n + 1)$.

Loop Invariant: Example 1

Code 1

```
 $s \leftarrow 0, k \leftarrow 0$   
while  $k < n + 1$  do  
     $s \leftarrow s + k, k \leftarrow k + 1$   
end while
```

- ▶ Invariant I : $s = k(k - 1)/2 \wedge (0 \leq k \leq n + 1)$.
- ▶ P is $s = 0, k = 0$ and $P \rightarrow I$.

Loop Invariant: Example 1

Code 1

```
 $s \leftarrow 0, k \leftarrow 0$   
while  $k < n + 1$  do  
     $s \leftarrow s + k, k \leftarrow k + 1$   
end while
```

- ▶ Invariant I : $s = k(k - 1)/2 \wedge (0 \leq k \leq n + 1)$.
- ▶ P is $s = 0, k = 0$ and $P \rightarrow I$.
- ▶ C is $k < n + 1$ and B is $s \leftarrow s + k, k \leftarrow k + 1$.

Loop Invariant: Example 1

Code 1

```
 $s \leftarrow 0, k \leftarrow 0$   
while  $k < n + 1$  do  
     $s \leftarrow s + k, k \leftarrow k + 1$   
end while
```

- ▶ Invariant I : $s = k(k - 1)/2 \wedge (0 \leq k \leq n + 1)$.
- ▶ P is $s = 0, k = 0$ and $P \rightarrow I$.
- ▶ C is $k < n + 1$ and B is $s \leftarrow s + k, k \leftarrow k + 1$.
- ▶ $\langle I \text{ and } C \rangle B \langle I \rangle$ in the loop.

Loop Invariant: Example 1

Code 1

```
 $s \leftarrow 0, k \leftarrow 0$   
while  $k < n + 1$  do  
     $s \leftarrow s + k, k \leftarrow k + 1$   
end while
```

- ▶ Invariant I : $s = k(k - 1)/2 \wedge (0 \leq k \leq n + 1)$.
- ▶ P is $s = 0, k = 0$ and $P \rightarrow I$.
- ▶ C is $k < n + 1$ and B is $s \leftarrow s + k, k \leftarrow k + 1$.
- ▶ $\langle I \text{ and } C \rangle B \langle I \rangle$ in the loop.
- ▶ Q is $s = s(n) = n(n + 1)/2$. $(I \text{ and } \neg C) \rightarrow Q$ after the loop.