Conjoint Survey Design Tool: Software Manual*

Anton Strezhnev, Jens Hainmueller, Daniel J. Hopkins, Teppei Yamamoto

Version 3.2

October 21, 2026

*Designed as a companion to Hainmueller, Jens, Daniel J. Hopkins, and Teppei Yamamoto. "Causal inference in conjoint analysis: Understanding multidimensional choices via stated preference experiments." Political Analysis 22, no. 1 (2014): 1-30

Contents

1 Introduction **2**

2 A Brief Overview of Conjoint Analysis **2**

3 Installation **3**

4 Using the SDT **3**

4.1 Main Window 3

4.2 Settings 5

4.3 Profile Restrictions 6

4.4 Weighted Randomization 8

4.5 Attribute Order Constraints 9

5 Export Qualtrics Survey (.qsf) **10**

6 Export to JavaScript **12**

6.1 How to embed your design into a Qualtrics question 12

7 Export to R **14**

8 Contact **14**

9 License **14**

1 Introduction

The Conjoint Survey Design Tool assists researchers in creating multi-dimensional choice experiments that can be readily incorporated into any pre-existing survey software (such as Qualtrics). Conjoint analysis is a type of survey experiment often used by market researchers to measure consumer preferences over a variety of product attributes. Hainmueller, Hopkins, and Yamamoto (2014) demonstrate the value of this design for political science applications. Conjoint experiments present respondents with a choice among set of profiles composed of multiple randomly assigned attributes. This approach permits researchers to estimate the effect of each individual component on the probability that the respondent will prefer a profile. This software tool is designed as a companion to Hainmueller et al. (2014) and provides a graphical user interface for generating conjoint experiments.

2 A Brief Overview of Conjoint Analysis

Conjoint survey experiments are made up of a set of **choice tasks** or **trials** performed by the respondent. Each **task** presents the respondent with a number of **profiles** and the respondent selects their most preferred alternative. **Profiles** are comprise of some number of **attributes** corresponding to particular characteristics of the profiles. Profiles might be candidates for office and attributes could include age, education, and prior experience (as in the choice experiment described by Hainmueller et al. (2014)). Each **attribute** can take on one of a set of discrete and pre-defined **levels**. For example, an "age" attribute might have the levels "young," "middle-aged," and "old." In each profile, a level is randomly selected for each attribute from the set of possible levels. Hainmueller et al. (2014) show that under this randomization, along with a simple set of consistency assumptions, the average marginal effect of each level is non-parametrically identified. Most importantly, the respondents need not be shown every potential combination of profiles/attributes to identify these component-specific effects. The conjoint experiment thus allows researchers to efficiently run multiple-treatment choice experiments without needing a sample size large enough to present respondents with every possible comparison. For a more detailed explanation of the design, see Hainmueller et al. (2014).

3 Installation

The Conjoint Survey Design Tool (SDT) runs from the Python source on Windows, Mac OSX and Linux. It is written for Python 3 and requires Python 3.6 or greater. To obtain the most recent release of Python 3, visit https://www.python.org/downloads/

Windows users should install Python using the installer from python.org and leave the "tcl/tk and IDLE" option checked (it is on by default), as the SDT's interface requires the TCL/TK library.

Mac OSX users should make sure that they have the most recent version of the TCL/TK library installed. Consult https://www.python.org/download/mac/tcltk/ for more information.

To run the Conjoint SDT from Python source, download the `conjointSDT.py` to the desired directory and run the file through the Python interpreter (this can be done through the command line by calling `python conjointSDT.py`).

A sample survey file, `immigrant_demo.sdt`, is included in the Demos folder.

4 Using the SDT

4.1 Main Window

The main window consists of two panels. The right panel displays the list of attributes in the design. The left panel displays the list of levels that correspond to a chosen attribute. By default, the program opens a blank file with no attributes and levels.

Above the panels are two action menus. The `File` menu contains the following commands

- `New`: Begins a new design project. Prompts the user to save any existing work.
- `Open`: Opens an existing project. Project filenames all must end in sdt. Note that files with these extensions will not automatically open when clicked on in a file browser.
- `Save`: Saves current project. Project filenames must end in .sdt.
- `Save As`: Saves current project to a new file.




Figure 1: Main Window

- `Import from CSV`: Imports a set of pre-defined attributes and levels from a Comma Separated Values file. CSV files must contain one line per attribute. The first element of each line defines the name of the attribute. The subsequent elements are the names of the corresponding levels.

The `Edit` menu contains the following commands

- `Settings`: Opens the settings menu (see Section 4.2 for details).
- `Restrictions`: Opens the profile restrictions menu. Here you can set the attribute/level pairs that should be prevented from appearing in profiles (see Section 4.3 for details).
- `Randomization Weights`: Opens the randomization weights menu. Here you can set the probability that each level will be chosen in a randomly generated profile (see Section 4.4

for details).

- `Attribute Order Constraints`: Opens the attribute order constraint menu. One option in the Settings menu is to randomize the order of the attributes in the profiles for each respondent. This helps minimize the influence of possible ordering effects. In this panel, you may set constraints on this randomization such that particular sets of attributes are always grouped together in the same block.

- `Export Qualtrics Survey (.qsf)`: Exports the current design as a complete Qualtrics survey file, including the randomization script, the embedded data fields and one question per task. This is the easiest way to get a design into Qualtrics. See Section 5 for details.

- `Export to JavaScript`: Exports the current design to a .js file that carries out task and profile generation for each respondent. This file can be integrated directly into Qualtrics. See Section 6 for details.

- `Create Qualtrics Question Templates`: Generates HTML question templates for Qualtrics that have the correct embedded data identifiers for each attribute and level.

- `Export design to R`: Exports the design (level probabilities and randomization constraints) to be used by the R package `cjoint`.

The `About` menu contains the following command

- `License`: View the GPL 3 license information.

Below the panels are the Add/Remove/Edit buttons for attributes and levels. To add an attribute to the design or a level to the current active attribute, use the corresponding Add button. To remove an attribute or level, select it in the panel and press the corresponding Remove button. To edit an attribute or level name, select it in the panel and press Edit.

4.2 Settings

The settings window contains options related to the exported JavaScript randomizer. **Note:** These settings, aside from the number of tasks and profiles per task are *not* saved as part of the `.sdt` file.




Figure 2: Settings Window

- `Randomize order of attributes for each respondent`: Turns on/off attribute order randomization in the exported JavaScript. Select if you want the order in which attributes are presented in a conjoint profile to vary for each respondent. Default True.

- `Use weighted randomization`: Enables weighted randomization of levels. Select if you have defined non-uniform randomization weights and want the randomization script to use them. Default False.

- `Prevent identical profiles`: Ensures that no task can have two profiles that have exactly the same levels for all attributes. With sufficiently many attributes/levels, the chances of getting a task with identical profiles is already very low and the presence of cross-profile restrictions creates additional complications for interpreting the AMCE estimand. Default False.

- `Number of Tasks per Respondent`: Sets the number of tasks assigned to a single respondent. Default 5

- `Number of Profiles per Task`: Sets the number of profiles presented in a single task. Default 2.

4.3 Profile Restrictions

This panel allows you to restrict the appearance of certain attribute/level combinations in profiles presented to respondents. By default, every possible level combination has the possibility of being

shown to a respondent. For some designs, certain combinations may be nonsensical, impossible or confusing to respondents. You may want to prohibit these combinations from being displayed in profiles. For example, in the immigration conjoint experiment in Hainmueller et al. (2014), profiles could not indicate that the prospective immigrant did not have at least a college education and worked in a high-skill occupation (e.g. research scientist, computer programmer). These combinations were a priori excluded because of their implausibility.




Figure 3: Profile Restrictions Window

Best practices in the conjoint literature suggest that these types of prohibitions should be used sparingly as they represent deviations from a fully randomized design. As Orme (2002) notes

> "Too many prohibitions, in the best case, can lead to imprecise utility estimation and, in the worst case, confounded effects and the complete inability to calculate stable utilities."

In this screen, restrictions are specified individually. Each restriction represents a unique combination of attribute-levels that are prohibited from being displayed. Note, that if three or more levels are specified in a restriction, only the combination of *all* of those levels is prevented from being displayed. For example, if a restriction prevents a profile from containing attribute-levels 1-A, 2-B and 3-C, absent additional restrictions, the profile could still contain 1-A, 2-B and 3-D or 1-E, 2-B, and 3-C.

To create a new restriction, click on `New Restriction`. To delete an existing restriction, click on that restriction in the panel and then press `Delete Restriction`. To add a particular level to a restriction, select that restriction in the panel, choose your desired attribute and level from the drop-down menus and click `Add Selected Level to Restriction`.

Note: In the current version of the Conjoint SDT, restrictions must be deleted manually. If a particular attribute or level is subsequently removed in the main panel, it is not automatically removed from any previously specified restrictions.

4.4 Weighted Randomization

By default, each attribute level has an equal probability of being drawn. That is, for a given attribute, each defined level has the same probability of appearing in a profile. However, you may want to define a non-uniform randomization scheme such that some levels are more likely to appear in a profile than others.

This window allows you to assign selection probabilities for each level within an attribute. By default, each level within an attribute has an equal probability of selection into the profile. To change a weight, select a level from the panel and click `Edit Weight`. Standard probability constraints apply. Probabilities must be between 0 and 1 and must sum to 1 across all levels within an attribute. The sum across weights within an attribute is displayed above the levels panel. To save the weights, click `Save Weights`. To reset the weights to the default uniform randomization scheme, click `Reset Weights to Default`.

Warning: In order for these weights to be properly exported to the randomization scripts, you also need to make sure to check the `Use Weighted Randomization` option in the **Settings** menu. This setting is **not saved** when you save the .sdt file, so be sure to enable it before using `Export to JavaScript`.

Note: If attributes and levels are subsequently added to the design, the weighted probabilities will reset to the default (uniform randomization). It is recommended that you define all of the attributes and levels that you wish to include in your design and then alter the randomization weights.




Figure 4: Weighted Randomization Window

4.5 Attribute Order Constraints

If you choose to randomize the order in which attributes are displayed for each respondent, you may still want to keep some attributes in a pre-defined order to ease comprehension and improve readability. For example, you may want to group thematically related attributes together.

This window allows you to define blocks of attributes that will always be presented to respondents in the same order. To create a new block click `New Constraint`. To delete an existing block click `Delete Constraint`. To add an attribute to a constraint, select the constraint from the panel, choose an attribute from the drop-down menu and press `Add Selected Attribute to Constraint`. The order of the attributes within the block will match the constraint list. So in the above figure, the "Profession" attribute will always be followed by the "Job experience" and "Job plans" attributes (in that order).

Note that if you define multiple blocks, only the attributes *within* each block will be ordered.




Figure 5: Attribute Order Constraint Window

The blocks themselves are *not* constrained such that block one always follows block two.

Note: As with the profile restrictions, if you choose to delete an attribute you will have to manually remove any corresponding order randomization constraint

5 Export Qualtrics Survey (.qsf)

The `Export Qualtrics Survey (.qsf)` command saves your design as a Qualtrics survey file that can be imported directly into Qualtrics. This creates a working conjoint survey without any manual setup. To import it, open a survey in Qualtrics, navigate to the Survey tab, click `Tools`, select `Import/Export`, choose `Import survey` and select the .qsf file. Select "Research Core" as the project category. Importing creates a new survey in your account.

The imported survey contains the following:

1. An "Embedded Data" element at the top of the Survey Flow that declares every embedded data field used by the design.

2. A "Conjoint Introduction" block with a single page of introductory text. The randomization script (the same code produced by `Export to JavaScript`) is attached to this question and

generates the respondent's tasks when the page loads. You may edit the text, but do not remove the question.

3. A second "Embedded Data" element that copies the randomized attributes and levels into the fields `F-[task number]-[attribute number]` and `F-[task number]-[profile number]-[attribute number]` described in Section 6.

4. A "Conjoint Tasks" block containing one Multiple Choice question per task, each on its own page. Each question displays the profiles in a table using the same layout as the `Create Qualtrics Question Templates` command, and has one choice per profile ("Choice 1", "Choice 2", ...). The questions have the export tags `task1`, `task2`, ...

You can then edit the question wording, add other blocks to the survey (for example, a consent form before the conjoint and demographic questions after it), and change the response format of the task questions. Keep the introduction block before the Conjoint Tasks block, and keep the second Embedded Data element between them.

Qualtrics' New Survey Taking Experience (formerly the Simple layout), which is the default for new surveys, only saves embedded data set from JavaScript if the field name begins with `__js_`. The randomization script in the .qsf therefore saves each field with this prefix (e.g. `__js_F-1-1-1`), and the second Embedded Data element copies these into the unprefixed fields. Your results will contain both sets of columns. The `F-` columns are the ones read by the `cjoint` R package, and the `__js_` columns can be ignored.

The survey is exported with the back button disabled. We recommend keeping it disabled, as returning to the introduction page would run the randomization script again and assign the respondent new profiles. As always, preview the survey and check a test response before fielding it.

If you want to add the conjoint to an existing survey rather than build the survey around it, use `Export to JavaScript` (Section 6) instead.

6 Export to JavaScript

To incorporate your conjoint design into Qualtrics, you can generate a snippet of javascript code that will randomly generate a full set of tasks for a respondent according to your specified settings. The snippet can be added to the custom javascript of any survey question that appears prior to your conjoint question block (typically the survey consent page if you have one).

The script will assign embedded data fields in Qualtrics for each randomized attribute and level. These fields all have the following structure:

`F-[task number]-[attribute number]` matches the attribute name corresponding to Task `[task number]`, Attribute `[attribute number]`. `F-[task number]-[profile number]-[attribute number]` matches the selected level corresponding to Task `[task number]`, Profile `[profile number]`, Attribute `[attribute number]`. For example, the embedded data field `F-1-3-2` will contain the level corresponding to Task 1, Profile 3, Attribute 2. Likewise, the embedded data field `F-3-3` will contain the attribute name corresponding to Task 3, Attribute 3.

6.1 How to embed your design into a Qualtrics question

If you are using the Qualtrics survey software, it is very easy to integrate the .js file you have exported with your survey flow. The following instructions will walk you through the process of incorporating your conjoint design into a Qualtrics question.

1. Select the first question in your survey (i.e. the consent page) (Really, any question that appears on a page prior to the conjoint block should work.)

2. Open the question's custom JavaScript (this appears under Edit Question - Question Behavior - JavaScript).

3. Copy the source code from your generated .js file below the commented line `/*Place your JavaScript here to run when the page loads*/` (this is inside the `addOnload` function). The code snippet will update the embedded data fields assigned to the respondent when the respondent loads the page.

4. If you have already created the question designs within Qualtrics, you can pipe the embedded

data fields into any question element within the survey. [1]

5. If you have not created the questions, a basic set of templates for the conjoint tasks can be generated using the `Create Qualtrics Question Templates` command in the `Edit` menu. This command will create an .html file for every task in your design.

6. To add a question to your design, create a new item in your Qualtrics survey and select the "Multiple Choice" item type. Edit the question in HTML view, open the source code from one of the .html files in a text editor (such as Notepad), and copy the source into the HTML view. Repeat for each task.

7. You may then edit the question text, labels and responses to match your design. Note that references to the embedded data fields have the format `${e://Field/F-[TASK]-[ATTRIBUTE]}` (for attribute names) and `${e://Field/F-[TASK]-[PROFILE]-[ATTRIBUTE]}` (for attribute levels)

In addition to pasting in the JavaScript code, you will also need to manually initialize each embedded data field in the Survey Flow in order for Qualtrics to correctly export these fields to the results CSV. To do this

1. In your Qualtrics control panel, navigate to the Survey Flow.

2. Add a new "Embedded Data" element to the top of your survey flow. Make sure that this element is above your conjoint question blocks **and above to the question that contains the JavaScript snippet** in the survey flow.

3. Add a unique field for each attribute and each level embedded data field in your survey (e.g. F-1-1, F-2-1, F-1-3-2). The total number of fields will depend on the number of tasks, profiles and attributes. You can consult the generated HTML Question Templates (see above) for a list of all attribute and level identifiers used in your survey. You may leave the assigned value in this element to "Value will be set from Panel or URL" as it will be subsequently modified by the JS code.

[1] For more information on piping text from embedded data fields, see http://www.qualtrics.com/university/researchsuite/basic-building/editing-questions/piped-text/.

Note that if you skip this step and field the survey without initializing the fields in the Survey Flow, the questions do seem to correctly appear and the assigned attributes and levels for each respondent *are* saved but will not be part of the CSV export. If you are having trouble getting the assigned attributes and levels to appear in your exported CSV results and you have already fielded your survey, make sure you add the embedded data field to your Survey Flow as above and re-export the CSV.

If you can come up with a faster way of doing this, please let me know! Unfortunately, Qualtrics appears to need all exported embedded data fields to be defined in the Survey Flow.

7 Export to R

If you would like to use the design tool to specify a conjoint design for use in the `cjoint` package, use the "Export Design to R" menu option. This will ask you to save a `.dat` file which will contain the design's attributes, levels and level assignment probabilities.

This file can be passed to the `makeDesign()` function in the `cjoint` R package. Please consult the documentation for the `cjoint` R package located on CRAN for more information on where to pass the design file and for general instruction on how to perform the analysis.

8 Contact

If you have further questions about using the Conjoint SDT or wish to report a bug, please do not hesitate to contact Anton Strezhnev at strezhnev@wisc.edu.

9 License

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see ⟨http://www.gnu.org/licenses/⟩.

References

Hainmueller, J., D. J. Hopkins, and T. Yamamoto (2014). Causal inference in conjoint analysis: Understanding multi-dimensional choices via stated preference experiments. *Political Analysis 22*(1), 1–30.

Orme, B. (2002). Formulating attributes and levels in conjoint analysis. Sawtooth Software Research Paper Series. http://www.sawtoothsoftware.com/download/techpap/formatt.pdf.