

Introduction to ggplot2

Karen Mazidi

There are 7 grammatical elements in ggplot2, the first 3 of these are essential to getting something plotted:

- data - the data being plotted should be the first argument, or specify data=...
- aesthetics - the scales onto which we plot; use aes() to specify at least x= and y= if needed as well as other parameters for customization
- geometries - visual elements such as points, lines, etc.
- facets - for plotting multiples
- statistics - representations to aid understanding
- coordinates - space on which data will be plotted
- themes - you can customize your own theme to use over and over

load tidyverse and some data

Loading the diabetes data set from package mlbench.

```
library(tidyverse)
library(mlbench)
data("PimaIndiansDiabetes2")

tb <- tbl_df(PimaIndiansDiabetes2)
```


Explore ggplot2

Hadley Wickham developed ggplot2 in 2005, inspired by a grammar of graphics developed by Leland Wilkinson in 1999. The ggplot2 functions are much more powerful than standard R graphs but also slower.

We have a short example below showing important components of building a ggplot. First we specify the data, then the aesthetics which are how the data is represented, followed by the geometry and finally labels.

```
ggplot(tb, aes(x=mass, y=glucose)) +
  geom_point() +
  labs(title="Glucose and BMI", x="BMI", y="Glucose")
```

```
## Warning: Removed 16 rows containing missing values (geom_point).
```




Next we add some color and a smoothing line which helps us see a trend in the data. By default the smoothing line to highlight the trend in the data

```
ggplot(tb, aes(x=mass, y=glucose)) +  
  geom_point(pch=20, color='blue', size=1.5) +  
  geom_smooth(method='lm', color='red', linetype=2) +  
  labs(title="Glucose and BMI", x="BMI", y="Glucose")
```

```
## `geom_smooth()` using formula 'y ~ x'
```

```
## Warning: Removed 16 rows containing non-finite values (stat_smooth).
```

```
## Warning: Removed 16 rows containing missing values (geom_point).
```




informative graph

```
ggplot(tb,
  aes(x=tb$mass, y=tb$age, shape=diabetes, col=pregnant)) +
  geom_point(size=2) +
  labs(x="BMI", y="Age")
```

Warning: Use of `tb\$mass` is discouraged. Use `mass` instead.

Warning: Use of `tb\$age` is discouraged. Use `age` instead.

Warning: Removed 11 rows containing missing values (geom_point).



facet_grid

- filter out rows with NAs in glucose or insulin
- create 2 new factor columns, glucose_high and insulin_high
- plot


The facet grid for 2 binary variables has 4 windows for all combinations.

```
tb <- filter(tb, !is.na(glucose), !is.na(insulin))

tb <- mutate(tb, glucose_high = factor(ifelse(tb$glucose > mean(tb$glucose), 1, 0)))
tb <- mutate(tb, insulin_high = factor(ifelse(tb$insulin > mean(tb$insulin), 1, 0)))

ggplot(tb,
  aes(x=mass, y=age, shape=diabetes, col=pregnant)) +
  geom_point(size=2) +
  facet_grid(glucose_high~insulin_high)
```

Warning: Removed 1 rows containing missing values (geom_point).




histogram

```
ggplot(tb, aes(x=mass)) +  
  geom_histogram(fill="cornsilk4")
```

`stat_bin()` using `bins = 30`. Pick better value with `binwidth`.

Warning: Removed 1 rows containing non-finite values (stat_bin).




boxplot and rug

```
ggplot(tb, aes(x=diabetes, y=mass)) +  
  geom_boxplot(notch=TRUE) +  
  geom_point(position="jitter", color="cornflowerblue", alpha=.5) +  
  geom_rug(color="cornflowerblue")
```

```
## Warning: Removed 1 rows containing non-finite values (stat_boxplot).
```


```
## Warning: Removed 1 rows containing missing values (geom_point).
```



density plot

```
ggplot(tb, aes(x=mass, fill=diabetes)) +  
  geom_density(alpha=0.5)
```


```
## Warning: Removed 1 rows containing non-finite values (stat_density).
```



bubble chart

```
ggplot(tb,  
  aes(x=mass, y=glucose, size=pregnant)) +  
  geom_point(shape=21, fill="cornflowerblue")
```

Warning: Removed 1 rows containing missing values (geom_point).



grid

```
library(gridExtra)
```

```
##
```

```
## Attaching package: 'gridExtra'
```

```
## The following object is masked from 'package:dplyr':
```

```
##
```

```
## combine
```

```
p1 <- ggplot(tb, aes(x=insulin_high)) + geom_bar(fill="cornflowerblue")
```

```
p2 <- ggplot(tb, aes(x=glucose_high)) + geom_bar(fill="cornflowerblue")
```

```
grid.arrange(p1, p2, ncol=2)
```

