

# Clustering

Karen Mazidi

Modified from Kabacoff, “R in Action”, 2nd ed

## K-means

Apply k-means to the wine data set, which contains 13 chemical measurements on 178 Italian wines.

The first column, Type, indicates 1 or 3 win varieties. We will drop this variable for the clustering.

```
data(wine, package="rattle")
names(wine)
```

```
## [1] "Type"          "Alcohol"        "Malic"          "Ash"
## [5] "Alcalinity"     "Magnesium"      "Phenols"        "Flavanoids"
## [9] "Nonflavanoids" "Proanthocyanins" "Color"          "Hue"
## [13] "Dilution"      "Proline"
```

```
head(wine)
```

```
##   Type Alcohol Malic  Ash Alcalinity Magnesium Phenols Flavanoids Nonflavanoids
## 1    1  14.23  1.71 2.43      15.6      127    2.80      3.06      0.28
## 2    1  13.20  1.78 2.14      11.2      100    2.65      2.76      0.26
## 3    1  13.16  2.36 2.67      18.6      101    2.80      3.24      0.30
## 4    1  14.37  1.95 2.50      16.8      113    3.85      3.49      0.24
## 5    1  13.24  2.59 2.87      21.0      118    2.80      2.69      0.39
## 6    1  14.20  1.76 2.45      15.2      112    3.27      3.39      0.34
##   Proanthocyanins Color  Hue Dilution Proline
## 1              2.29 5.64 1.04      3.92   1065
## 2              1.28 4.38 1.05      3.40   1050
## 3              2.81 5.68 1.03      3.17   1185
## 4              2.18 7.80 0.86      3.45   1480
## 5              1.82 4.32 1.04      2.93    735
## 6              1.97 6.75 1.05      2.85   1450
```


```
df <- scale(wine[,-1])
head(df)
```

```
##           Alcohol      Malic      Ash Alcalinity Magnesium Phenols
## [1,] 1.5143408 -0.56066822  0.2313998 -1.1663032 1.90852151 0.8067217
## [2,] 0.2455968 -0.49800856 -0.8256672 -2.4838405 0.01809398 0.5670481
## [3,] 0.1963252  0.02117152  1.1062139 -0.2679823 0.08810981 0.8067217
## [4,] 1.6867914 -0.34583508  0.4865539 -0.8069748 0.92829983 2.4844372
## [5,] 0.2948684  0.22705328  1.8352256  0.4506745 1.27837900 0.8067217
## [6,] 1.4773871 -0.51591132  0.3043010 -1.2860793 0.85828399 1.5576991
##           Flavanoids Nonflavanoids Proanthocyanins      Color      Hue Dilution
## [1,] 1.0319081 -0.6577078      1.2214385  0.2510088 0.3611585 1.8427215
## [2,] 0.7315653 -0.8184106     -0.5431887 -0.2924962 0.4049085 1.1103172
## [3,] 1.2121137 -0.4970050      2.1299594  0.2682629 0.3174085 0.7863692
## [4,] 1.4623994 -0.9791134      1.0292513  1.1827317 -0.4263410 1.1807407
## [5,] 0.6614853  0.2261576      0.4002753 -0.3183774 0.3611585 0.4483365
## [6,] 1.3622851 -0.1755994      0.6623487  0.7298108 0.4049085 0.3356589
##           Proline
## [1,] 1.01015939
## [2,] 0.96252635
## [3,] 1.39122370
```

```
## [4,] 2.32800680
## [5,] -0.03776747
## [6,] 2.23274072
```

Write a function to plot the within-groups sums of squares vs. the number of clusters.



```
wsplot <- function(data, nc=15, seed=1234){
  wss <- (nrow(data)-1)*sum(apply(data,2,var))
  for (i in 2:nc){
    set.seed(seed)
    wss[i] <- sum(kmeans(data,centers=i)$withinss)
  }
  plot(1:nc, wss, type="b", xlab="Number of Clusters",
       ylab="Within groups sum of squares")
}
wsplot(df)
```





Use the NbClust() function to help determine the best number of clusters.

In the within-groups plot, we see an “elbow” around 3, suggesting that 3 clusters is a good choice.

```
library(NbClust)
set.seed(1234)
nc <- NbClust(df, min.nc=2, max.nc=15, method="kmeans")
```



```
## *** : The Hubert index is a graphical method of determining the number of clusters.
##       In the plot of Hubert index, we seek a significant knee that corresponds to a
##       significant increase of the value of the measure i.e the significant peak in Hubert
##       index second differences plot.
##
```




```
## *** : The D index is a graphical method of determining the number of clusters.
##       In the plot of D index, we seek a significant knee (the significant peak in Dindex
##       second differences plot) that corresponds to a significant increase of the value of
##       the measure.
##
```

```
## *****
## * Among all indices:
## * 2 proposed 2 as the best number of clusters
## * 19 proposed 3 as the best number of clusters
## * 1 proposed 14 as the best number of clusters
## * 1 proposed 15 as the best number of clusters
##
##          ***** Conclusion *****
##
## * According to the majority rule, the best number of clusters is  3
##
## *****
table(nc$Best.n[1,])

##
##  0  1  2  3 14 15
##  2  1  2 19  1  1

barplot(table(nc$Best.n[1,]),
        xlab="Number of Clusters", ylab="Number of Criteria",
        main="Number of Clusters Chosen by 26 Criteria")
```

## Number of Clusters Chosen by 26 Criteria



## KMeans

Fit the model using the `kmeans()` function. We set a seed first so we get reproducible results.

The centroids are found in `fit.km$centers` and we display those.

```
set.seed(1234)
fit.km <- kmeans(df, 3, nstart=25)
```

```
fit.km$size
```

```
## [1] 62 65 51
```

```
fit.km$centers
```

```
##      Alcohol      Malic      Ash Alcalinity  Magnesium      Phenols
## 1  0.8328826 -0.3029551  0.3636801 -0.6084749  0.57596208  0.88274724
## 2 -0.9234669 -0.3929331 -0.4931257  0.1701220 -0.49032869 -0.07576891
## 3  0.1644436  0.8690954  0.1863726  0.5228924 -0.07526047 -0.97657548
##      Flavanoids Nonflavanoids Proanthocyanins      Color      Hue      Dilution
## 1  0.97506900  -0.56050853      0.57865427  0.1705823  0.4726504  0.7770551
## 2  0.02075402  -0.03343924      0.05810161 -0.8993770  0.4605046  0.2700025
## 3 -1.21182921  0.72402116     -0.77751312  0.9388902 -1.1615122 -1.2887761
##      Proline
## 1  1.1220202
## 2 -0.7517257
## 3 -0.4059428
```

The centroids were calculated based on the scaled data. Next we use the `aggregate()` function along with the cluster membership to get variable means for each cluster in units of the original, unscaled, data.

```
aggregate(wine[-1], by=list(cluster=fit.km$cluster), mean)
```

```
##   cluster Alcohol      Malic      Ash Alcalinity Magnesium      Phenols Flavanoids
## 1      1 13.67677 1.997903 2.466290      17.46290 107.96774 2.847581 3.0032258
## 2      2 12.25092 1.897385 2.231231      20.06308  92.73846 2.247692 2.0500000
## 3      3 13.13412 3.307255 2.417647      21.24118  98.66667 1.683922 0.8188235
##   Nonflavanoids Proanthocyanins      Color      Hue Dilution      Proline
## 1      0.2920968      1.922097 5.453548 1.0654839 3.163387 1100.2258
## 2      0.3576923      1.624154 2.973077 1.0627077 2.803385  510.1692
## 3      0.4519608      1.145882 7.234706 0.6919608 1.696667  619.0588
```

## Model Analysis

If we cross-tabulate the Type in column 1 of the wine data with cluster membership, we see that the clusters are strongly correlated with the wine type.

```
ct.km <- table(wine$Type, fit.km$cluster)
ct.km
```

```
##
##      1  2  3
## 1 59  0  0
## 2  3 65  3
## 3  0  0 48
```

We can quantify the agreement between the type and the cluster using an adjusted Rand index. The adjusted Rand index provides a measure of the agreement between two partitions, adjusted for chance. The range of the index is from -1 (no agreement) to +1 (perfect agreement).

The results below show very good agreement!

```
library(flexclust)
```

```
## Loading required package: grid
```

```
## Loading required package: lattice
```

```
## Loading required package: modeltools
```

```
## Loading required package: stats4
```

```
randIndex(ct.km)
```

```
##      ARI
```

```
## 0.897495
```