Outdoor LED Video Wall — Plain-English Summary

Model CW-20260501 | Design: Jerry | 31 May 2026 | Version 1.0 | Source: 3-page manufacturer drawing set

What it is

A large **outdoor LED video wall** — the kind mounted on a building, at a stadium, or roadside. It is built like LEGO out of 12 identical aluminium panels ("cabinets") tiled into a **4-wide × 3-tall** grid. The drawings cover one panel (page 1), the power wiring (page 2), and the video-signal wiring (page 3).

Key numbers at a glance

Size	1.28 m × 0.96 m (~13 cm deep)	5.12 m × 2.88 m (~16.8 × 9.4 ft), 16:9
Weight	44 kg (~97 lb)	528 kg (~1,160 lb)
Resolution	192 × 144 LEDs	768 × 432 px (~332,000 dots)
Power	1,040 W max / 360 W avg	12.48 kW max / 4.32 kW avg
Material	Aluminium	Aluminium frame + mounting structure
Pixel pitch	P6.667 mm (gap between LED dots)	Same — suited to viewing from a distance

How it is wired

Power: fed in groups — one 3-conductor 16 AWG cable feeds every 4 cabinets (one column of the grid), run from a power distribution box.

Video signal: laptop → "TB10plus" controller/sending box → the screen, connected by CAT5 network cable or WiFi. Panels are daisy-chained together.

■ **Check before installing — voltage inconsistency in the drawings:** Page 1 lists the single cabinet at **4.73 A @ AC 220 V**, while pages 2–3 list the full screen at **56.76 A @ AC 120 V**. The wattages are consistent, but the stated voltage jumps from 220 V to 120 V (the current only adds up at the lower voltage). Confirm the actual supply voltage with the manufacturer before wiring — it changes the cabling and breaker requirements significantly.

Plain-English summary generated from the original engineering drawing set (25ec718a-bb7b-451c-a951-e229e0c9c940.pdf). For construction, always work from the stamped manufacturer drawings.