

Pulse 3D

PROJECT OVERVIEW

Build a **single-screen, scroll-driven, custom-gesture landing page** called "Inner Circle".

There is **no native browser scrolling** — `document.body` and `html` both have `overflow: hidden`. A wheel/touch gesture controller drives a single `scrollProgress` numeric state from `0` to `3.5`. All animations (video scrubbing, text exits, rising panel, cylindrical drum) are derived from this single value.

Stack

- **Vite + React 19 + TypeScript**
- **Tailwind CSS v4** (via `@tailwindcss/vite`)
- **GSAP 3.15** for char-level split-text and parallax wiggle
- **lucide-react** for menu icons (`Menu` , `X`)
- `motion` , `@google/genai` , `express` , `dotenv` installed (the page itself only needs GSAP + Tailwind + React)

Fonts (loaded in `src/index.css`)

代码块

```
1  @import url('https://fonts.googleapis.com/css2?
    family=Manrope:wght@300;400;500;600;700;800&family=Michroma&display=swap');
2  @import "tailwindcss";
3
4  @theme {
5    --font-manrope: "Manrope", sans-serif;
6    --font-michroma: "Michroma", sans-serif;
7  }
```

- Use `font-manrope` for body, paragraph drum text, header subtitle, nav.
- Use `font-michroma` for the giant hero title and tile labels.

Global CSS (also in `index.css`)

代码块

```
1  ::-webkit-scrollbar { width: 8px; }
2  ::-webkit-scrollbar-track { background: #11010a; }
3  ::-webkit-scrollbar-thumb { background: #ea1f63; border-radius: 4px; }
4  ::-webkit-scrollbar-thumb:hover { background: #ff5c93; }
5
6  html, body {
7    background-color: #11010a;
8    color: #ffffff;
9    overflow-x: hidden;
10   font-family: var(--font-manrope);
11 }
12
13 @keyframes marquee-scroll {
14   from { transform: translateX(0); }
15   to   { transform: translateX(-50%); }
16 }
17 .marquee-container {
18   display: flex; overflow: hidden; width: 100%; position: relative;
19   mask-image: linear-gradient(to right, transparent, white 20%, white 80%,
transparent);
20   -webkit-mask-image: linear-gradient(to right, transparent, white 20%, white
80%, transparent);
21 }
22 .marquee-track {
23   display: flex; width: max-content; flex-wrap: nowrap;
24   animation: marquee-scroll linear infinite;
25   will-change: transform;
26 }
```

Color palette

- Hero background magenta: `#FF005E`
- Second screen near-black/wine: `#11010a`
- Loader accents: `#ea1f63`, `pink-500` (`#ec4899`), `#ff5c93`
- Text: white (`#ffffff`) and `text-white/60` for low-emphasis drum copy
- **No purple/indigo anywhere.**

Data files

`src/types.ts`:

代码块

```
1 export interface NavigationItem { id: string; label: string; scrollRatio:
  number; }
2 export interface Project { title: string; category: string; description:
  string; tags: string[]; }
3 export interface ExpertiseItem { title: string; percentage: number;
  description: string; }
```

`src/data.ts`:

代码块

```
1 export const NAVIGATION_ITEMS: NavigationItem[] = [
2   { id: "projects", label: "Projects", scrollRatio: 0.25 },
3   { id: "expertise", label: "Expertise", scrollRatio: 0.50 },
4   { id: "about", label: "About", scrollRatio: 0.95 },
5   { id: "contact", label: "Manifesto", scrollRatio: 3.50 },
6 ];
```

(Keep `PROJECTS_DATA` and `EXPERTISE_DATA` as defined — unused on this page but kept for parity.)

ROOT LAYOUT (`src/App.tsx`)

State

- `scrollProgress: number` (0 → 3.5)

- `lerpedScrollProgress: number` — smoothed copy of `scrollProgress`, updated each rAF tick with `currentLerp += (target - currentLerp) * 0.08`. Threshold `0.0001`.
- `activeSectionId: string` — derived via `updateActiveSection(progress)`:
 - `< 0.18` → "hero"
 - `0.18-0.45` → "projects"
 - `0.45-0.68` → "expertise"
 - `0.68-1.15` → "about"
 - else → "contact"

Gesture controller (runs once on mount)

- Sets `document.body.style.overflow = "hidden"` and same on `document.documentElement`.
- `wheel` listener (passive: false, `preventDefault()`): `scaleFactor = 0.0006`, new value = `clamp(prev + deltaY * 0.0006, 0, 3.5)`.
- `touchstart` saves `lastTouchY`. `touchmove`: `deltaTouchY = lastTouchY - currentTouchY`, `scaleFactor = 0.0015`, clamp same range.
- If a programmatic nav animation is in flight, cancel it on any user input.

Programmatic navigation (`handleNavigateToSection`)

- Duration: `1200ms`, `easeInOutCubic`:

代码块

```
1 ease = p < 0.5 ? 4p3 : 1 - (-2p + 2)3 / 2
```

- Lerps `scrollProgress` from current to `item.scrollRatio` while calling `updateActiveSection` each frame.

Derived values

代码块

```
1 const secondScreenProgress = clamp01((lerped - 1.15) / 0.50);
2 const easedRisingProgress = 1 - Math.pow(1 - secondScreenProgress, 3);
```

```
3  const smoothBlurAmount = Math.sin(secondScreenProgress * Math.PI / 2) * 64;
```

Markup skeleton

代码块

```
1  <main className="relative w-screen h-screen overflow-hidden bg-[#FF005E] text-
  white">
2    <div className="relative w-full h-full overflow-hidden">
3
4      {/* FIRST SCREEN – gets blurred as second screen rises */}
5      <div
6        className="absolute inset-0 w-full h-full z-10 transition-transform
  duration-[100ms] ease-out"
7        style={{ filter: secondScreenProgress > 0 ?
  `blur(${smoothBlurAmount}px)` : "none" }}
8      >
9        <VideoScrubber scrollProgress={Math.min(1, lerpedScrollProgress)} />
10
11       {/* Hero title strip pinned to bottom */}
12       <div className="absolute bottom-[40px] left-[1%] right-[1%] w-[98%]
  pointer-events-none z-20 select-none flex justify-center items-center">
13         <ScrollExitSplitText
14           scrollProgress={Math.min(1, lerpedScrollProgress)}
15           containerClassName="w-full text-[10.4vw] leading-none font-michroma
  font-normal uppercase text-white whitespace-nowrap text-center transition-all
  duration-300 will-change-transform"
16           style={{ letterSpacing: "-0.07em" }}
17         >
18           INNER CIRCLE
19         </ScrollExitSplitText>
20       </div>
21
22       <SoapTiles scrollProgress={lerpedScrollProgress} />
23     </div>
24
25     <Header activeSectionId={activeSectionId} onNavigate=
  {handleNavigateToSection} />
26
27     {/* SECOND SCREEN – rises from below, rounded top */}
28     <div
29       className="absolute bottom-0 left-0 w-full h-full bg-[#11010a] rounded-t-
  [48px] overflow-hidden z-40"
30     style={{
```

```

31         transform: `translateY(${(1 - easedRisingProgress) * 100}%)`,
32         visibility: secondScreenProgress > 0 ? "visible" : "hidden",
33         willChange: "transform",
34     }}
35 >
36     <div className="absolute top-5 left-1/2 -translate-x-1/2 w-16 h-[5px] bg-
white rounded-full z-50 pointer-events-none" />
37     <SecondVideoScrubber scrollProgress={lerpedScrollProgress} />
38     <CylindricalTextDrum scrollProgress={lerpedScrollProgress} />
39
40     <div className="absolute bottom-8 sm:bottom-12 md:bottom-16 left-0 w-
full sm:w-[65%] md:w-[60%] pl-6 sm:pl-12 md:pl-20 pr-6 sm:pr-12 md:pr-16 z-50
pointer-events-auto">
41         <div className="w-full border-t border-white/[0.08] pt-6">
42             <Marquee gap="80px" speed={25} fade>
43                 <GoogleWordmark size={100} />
44                 <GithubWordmark size={100} />
45                 
46                 
47                 
48                 
49                 
50             </Marquee>
51         </div>
52     </div>
53 </div>
54 </div>
55 </main>

```

SECTION 1 — HERO (First Screen)

1a. Background video — VideoScrubber

- **Video URL (exact):**

https://res.cloudinary.com/daklr2whx/video/upload/v1780426426/202606021731-ezremove_einsc0.mp4

- `<video>` is `playsInline muted preload="auto", object-cover`, full size, `pointer-events-none`.
- Wrapped in a `style={{ scale: "1.05" }}` div with `will-change-transform`. Container background is `bg-[#FF005E]`.
- **Scrub algorithm:** On every rAF tick:
 - `targetTime = clamp(scrollProgress * duration, 0, duration)` (fallback duration `4.2`).
 - `current += (target - current) * 0.15` (lerp).
 - Seek only when `!video.seeking && Math.abs(video.currentTime - current) > 0.01` → `video.currentTime = current`.
- **GSAP mouse parallax** on the container: on `mousemove`, compute `mx = e.clientX/innerWidth - 0.5`, `my = ...`. Animate `x: -mx*40, y: -my*40, duration: 1.2, ease: "power2.out", overwrite: "auto"`.
- **Loader overlay** (while `!isLoading`): full-bleed `bg-[#FF005Ef4]`, centered: a 64×64 wrapper with `animate-ping pink-500/20 ring + a 40×40 spinner ring (border-4 border-[#ea1f63]/20 border-t-[#ea1f63] animate-spin)`, label "LOADING SCROLL STREAM..." in `font-manrope font-semibold text-[12px] uppercase tracking-[0.25em] text-pink-500 drop-shadow-[0_0_8px_rgba(234,31,99,0.4)]`.

1b. Hero title — ScrollExitSplitText

- Text: `INNER CIRCLE`
- Class on outer container (from App): `text-[10.4vw] leading-none font-michroma font-normal uppercase text-white whitespace-nowrap text-center, letterSpacing: -0.07em`.

- Positioned: `absolute bottom-[40px] left-[1%] right-[1%] w-[98%]`, `z-20`, `pointer-events-none`.
- **Split-text mechanic:** split into lines → words → characters. Each char is a `span.char` `inline-block will-change-transform`. Words separated by a literal ` `; `span`.
- **GSAP timeline** (paused, controlled by scroll):

代码块

```
1 tl.fromTo(chars,
2   { opacity: 1, yPercent: 0, y: 0, scaleY: 1, scaleX: 1, transformOrigin:
   "50% 0%" },
3   { opacity: 0, yPercent: 300, y: "25vh", scaleY: 1.2, scaleX: 0.9,
   stagger: 0.03, ease: "power2.inOut" }
4 );
```

- On every `scrollProgress` change: `gsap.to(timeline, { progress: scrollProgress, duration: 0.6, ease: "power1.out", overwrite: "auto" })`. This produces a smooth lag/scrub.

1c. Reveal tiles — SoapTiles

- Three white pill-cards stacked vertically on the left:
 - a. `Private Discord & Networking` — `baseXOffset 120`, `delay 0ms`
 - b. `Weekly Market Alpha Drops` — `baseXOffset 180`, `delay 100ms`
 - c. `Exclusive Web3 Tooling Access` — `baseXOffset 240`, `delay 200ms`
- Container: `absolute left-4 right-4 md:left-[64px] top-[38%] md:top-1/2 -translate-y-1/2 flex flex-col gap-2 md:gap-[10px] z-40 pointer-events-auto transition-all duration-[800ms] ease-out`. Hidden state: `opacity-0 -translate-x-6 md:-translate-x-12 pointer-events-none`. Visible when `scrollProgress > 0.75`.
- Each tile class: `group relative h-[52px] sm:h-[72px] md:h-[138px] text-black bg-white rounded-xl sm:rounded-2xl md:rounded-[34px] flex items-center justify-center px-4 sm:px-8 md:px-14 w-full md:w-auto md:self-start cursor-pointer origin-left transition-all duration-[400ms] cubic-bezier(0.16, 1, 0.3, 1) whitespace-nowrap`.
- **Entry animation:** `easeProgress = clamp01((scrollProgress - 0.75) / 0.22)`. Each tile:

- `translateX = (easeProgress - 1) * responsiveOffset` (on mobile, offset is `× 0.25`)
- `opacity = easeProgress`
- `filter = blur(${(1 - easeProgress) * 12}px)`
- **Hover behavior (desktop only):** hovered tile scales `1.2`. Non-hovered tiles shift vertically by `±13.8px` (`baseHeight * 0.1`, with `baseHeight` `138/52`) — up if above hovered, down if below. On mobile, hover scale stays `1.0`.
- Label inside each tile: `font-michroma font-medium text-[11px] sm:text-[14px] md:text-[23px] leading-[16px] sm:leading-[22px] md:leading-[34px] tracking-tight, letter-spacing: -0.03em`.

1d. Header — Header

- Container: `absolute top-4 left-4 right-4 sm:top-8 sm:left-8 sm:right-8 md:top-[64px] md:left-[64px] md:right-[64px] flex items-center justify-between z-40`.
- **Logo group (left):** clicking navigates to `scrollRatio 0`. Contains:
 - **Logo** — `48×48` SVG with this exact path: a stylized "M" mark (`viewBox="0 0 80 80"`, single `<path>`, see code snippet below).
 - Subtitle (hidden `<sm>`): three lines `Full Workflow Automation. / We Manage Everything. You / Unwind.` in `font-manrope font-normal tracking-wide text-[12px] leading-[16px] text-white`.
- **Desktop nav ($\geq$ md):** the 4 `NAVIGATION_ITEMS` as buttons: `font-manrope font-medium text-[12px] leading-[16px] tracking-wider text-white px-4 py-2 rounded-full hover:bg-white hover:text-black transition-all duration-300`
- **Mobile burger:** circular `w-10 h-10 rounded-full border border-white/10 bg-white/5`. Toggles a full-screen overlay `fixed inset-0 bg-[#11010a]/98 backdrop-blur-xl z-30` with each item in `font-michroma text-[16px] uppercase tracking-widest py-4 px-6 border-b border-white/5`; active item: `text-[#FF005E] font-semibold`.

Logo path (exact):

代码块

```
1 M40 80C17.9086 80 0 62.0914 0 40V0C15.0436 0 28.1476 8.30466 34.9776
20.5796C25.6529 22.8063 18.7198 31.1937 18.7198 41.2004V42.0962C18.7198
```

```
53.3099 27.8104 62.4004 39.0242 62.4004H39.9199L39.9197 41.2004C39.9197
52.9088 49.4113 62.4004 61.1198 62.4004L61.1198 41.2004C61.1198 29.5187
51.6717 20.0437 40 20.0005L40 0H41.6902C62.8481 0 80 17.1519 80 38.3099V40C80
62.0914 62.0914 80 40 80Z
```

SECTION 2 — SECOND SCREEN (Rising Panel)

Reveal mechanics

- Triggered when `lerpedScrollProgress > 1.15`. Becomes fully on-screen at `1.65`.
- Panel: `absolute bottom-0 left-0 w-full h-full bg-[#11010a] rounded-t-[48px] overflow-hidden z-40`.
- `transform: translateY((1 - easedRisingProgress) * 100%)` where `easedRisingProgress = 1 - (1 - secondScreenProgress)^3`.
- `visibility: hidden` when `secondScreenProgress === 0`.
- While rising, the **first screen blurs** up to `64px` via `Math.sin(p *  $\pi$ /2) * 64`.
- **iOS grab-handle pill:** `absolute top-5 left-1/2 -translate-x-1/2 w-16 h-[5px] bg-white rounded-full z-50 pointer-events-none`.

2a. Background video — `SecondVideoScrubber`

- **Video URL (exact):**

https://res.cloudinary.com/daklr2whx/video/upload/v1780430770/20260602182_x923bh.mp4

- Same component skeleton as `VideoScrubber` but with these differences:
 - Background color of the loader bg: `bg-[#11010af4]`.
 - `DRUM_START = 1.45`, `DRUM_END = 3.50`.
 - `drumProgress = clamp01((scrollProgress - 1.45) / (3.50 - 1.45))`,
`target = drumProgress * duration`.
 - Same lerp `0.15`, same `!video.seeking && diff > 0.01` guard.

- Same GSAP mouse parallax `x/y: ±40px, duration 1.2, ease "power2.out"`.
- Loader label: `LOADING DRUM STREAM...` with `border-pink-500/20 border-t-pink-500`.

2b. Cylindrical text drum — `CylindricalTextDrum`

- Container: `absolute inset-y-0 left-0 w-full sm:w-[65%] md:w-[60%] z-30 flex flex-col items-start justify-center pointer-events-none select-none text-left pl-6 sm:pl-12 md:pl-20 py-16`, with `perspective: 1000px; perspectiveOrigin: 25% 50%`.
- Inner: `relative w-full h-[85vh] flex flex-col justify-center items-start overflow-visible` with `transformStyle: "preserve-3d"`.
- **Geometry:** `R = 380`, `lineHeight = 32`.
- `targetIndex = clamp01((scrollProgress - 1.45) / 2.05) * (LINES.length - 1)`.
- For each line `idx`:
 - `indexDiff = idx - targetIndex`
 - `translateY = indexDiff * 32`
 - `angleRad = translateY / 380`, `angleDeg = angleRad * 180/π`
 - `translateZ = cos(angleRad) * 380 - 380`
 - `baseScale = 0.78 + cos(angleRad) * 0.22`
 - `opacity = max(0, (cos(angleRad) - 0.2) / 0.8)`
 - `depthBlur = min(8, max(0, (|indexDiff| - 1.5) * 0.75))`
 - Apply `transform: translateY(${ty}px) translateZ(${tz}px) rotateX(${angleDeg * 0.8}deg) scale(${baseScale})`, `transformOrigin: "left center"`, plus blur when `> 0.1`.
- Each line `<p>`: `font-manrope text-[18px] sm:text-[24px] md:text-[28px] lg:text-[32px] font-semibold leading-[0.90] tracking-tight whitespace-nowrap, letter-spacing: -0.035em`.
- Text segments: if `highlight === true` use `text-white font-bold opacity-100`; else `text-white/60`. Empty `""` line renders a sized spacer at `opacity * 0.3`.
- Use the exact `LINES` array below — 32 entries (one empty string at index 15):

```

1 代码块. Welcome to the [ultimate convergence]
2 2. of [digital rebels], [underground creators],
3 3. and [top-tier product builders] who
4 4. refuse to follow [guidelines].
5 5. This is where [high-end design principles]
6 6. meet [pure technical execution],
7 7. without the [corporate bureaucracy] and
8 8. meaningless [standard aesthetics].
9 9. We [gather in the shadows] to build
10 10. the [next generation] of [scalable interfaces],
11 11. [automated workflows], and [decentralized assets]
12 12. that move the [cultural needle forward].
13 13. Experience [zero-bullshit networking],
14 14. weekly [alpha allocations], and [unreleased]
15 15. [toolkits] to shape the [internet's landscape].
16 16. (empty line)
17 17. This is [not another social club]
18 18. for casual enthusiasts or [template consumers].
19 19. This is a [highly selective environment]
20 20. engineered for [hyper-productive creators],
21 21. [UI/UX visionaries], and [AI prompt architects]
22 22. who operate at the [absolute limits]
23 23. of [digital product creation].
24 24. Our [framework is simple]:
25 25. [eliminate intermediate noise],
26 26. [automate the execution layer],
27 27. and [deploy elite digital products]
28 28. while others are still [scheduling meetings].
29 29. We loop through [complex design systems],
30 30. [break conventional grids], and
31 31. [execute fluid interactions] that
32 32. [redefine digital environments].

```

(Words in `[brackets]` are `highlight: true`.)

2c. Logo marquee — Marquee

- Position: `absolute bottom-8 sm:bottom-12 md:bottom-16 left-0 w-full sm:w-[65%] md:w-[60%] pl-6 sm:pl-12 md:pl-20 pr-6 sm:pr-12 md:pr-16`
- `z-50` inside a wrapper `border-t border-white/[0.08] pt-6`.
- `<Marquee gap="80px" speed={25} fade>` produces two duplicated tracks animated infinitely with the keyframe `marquee-scroll` (0% → -50%) over `25s` linear infinite, masked with a left/right transparent fade at 15%/85%.

- Children in order: `<GoogleWordmark size={100} />`, `<GithubWordmark size={100} />`, then `<img>` tags for these exact URLs, each styled `h-6 w-auto object-brightness-0 invert opacity-80 hover:opacity-100 transition-opacity`, `referrerPolicy="no-referrer"`:
 - <https://raw.githubusercontent.com/dsMagnatov/Acreage-landing-assets/refs/heads/main/voiceflow-logo-svg-150px.svg>
 - `.../zendesk-logo-svg-150px.svg`
 - `.../pendo-logo-svg-150px.svg`
 - `.../glide-logo-svg-150px.svg`
 - `.../canva-logo-svg-150px.svg`
- `GoogleWordmark` and `GithubWordmark` are inline `<svg>` wordmarks at `viewBox="0 0 115 30"` / `0 0 110 30` — see file for exact text/paths.

INTERACTIONS — Summary table

Trigger	Effect
Mouse wheel	<code>scrollProgress += deltaY * 0.0006</code> , clamp <code>[0, 3.5]</code>
Touch drag	<code>scrollProgress += (lastY - currentY) * 0.0015</code>
Nav click	1200ms <code>easeInOutCubic</code> lerp to target ratio
<code>scrollProgress</code> <code>0 → 1</code>	Hero video scrubs forward, "INNER CIRCLE" chars fall (300% y, 25vh) with 0.03 stagger

<code>scrollProgress</code> > 0.75	Soap tiles fade/slide in (over a 0.22 range), with 12px → 0 blur
Hover tile (desktop)	Hovered tile scales 1.2, neighbors shift ±13.8px
<code>scrollProgress</code> > 1.15	Second screen rises (ease-out cubic), first screen blurs to 64px
<code>scrollProgress</code> 1.45 → 3.50	Second video scrubs; cylindrical drum rotates; line at center is at scale 1.0/opacity 1.0
Mouse move (anywhere)	Both videos parallax-translate ±40px via GSAP <code>power2.out</code> , 1.2s

DATA PERSISTENCE

Supabase is available. This page is presentational and does not persist user state, so no database tables are required for the recreation. If extending with capture forms, waitlist sign-ups, or analytics events, create a Supabase table with RLS enabled and `auth.uid()`-based policies (one INSERT policy for `authenticated`, restrictive SELECT).

FILE STRUCTURE

代码块

```
1  src/  
2  App.tsx
```

```
3   main.tsx
4   index.css
5   types.ts
6   data.ts
7   components/
8     Header.tsx
9     Logo.tsx
10    Logos.tsx                (GoogleWordmark, GithubWordmark exported)
11    Marquee.tsx
12    VideoScrubber.tsx
13    SecondVideoScrubber.tsx
14    ScrollExitSplitText.tsx
15    SoapTiles.tsx
16    CylindricalTextDrum.tsx
```