

Growth Marketing SaaS

Build a single landing page with only a fixed Navbar and a full-screen Hero section that contains a parallax dashboard mock and a foreground grass image. Use React + Vite + TypeScript + Tailwind + framer-motion + lucide-react. No backend.

1. Global setup

`index.html` — add fonts in `<head>`

代码块

```
1 <link rel="preconnect" href="https://fonts.googleapis.com" />
2 <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin />
3 <link href="https://fonts.googleapis.com/css2?
  family=Inter:wght@400;500;600;700;800&display=swap" rel="stylesheet" />
4 <link href="https://fonts.googleapis.com/css2?
  family=Instrument+Serif:ital@0;1&display=swap" rel="stylesheet" />
5 <link href="https://fonts.googleapis.com/css2?
  family=Material+Symbols+Outlined:opsz,wght,FILL,GRAD@20..48,400,0..1,0"
  rel="stylesheet" />
```

Body background must be `#08020e`.

`tailwind.config.ts` — extend

代码块

```
1 fontFamily: { inter: ['Inter', 'ui-sans-serif', 'system-ui', 'sans-serif'] },
2 colors: {
3   landing: {
4     surface: "rgba(255,255,255,0.10)",
5     "surface-hover": "rgba(255,255,255,0.16)",
6     border: "rgba(255,255,255,0.10)",
7     "border-strong": "rgba(255,255,255,0.20)",
8     text: "rgba(255,255,255,0.80)",
9     "text-muted": "rgba(255,255,255,0.60)",
10  },
```

```
11 }
```

src/index.css — add

代码块

```
1  body { background-color: #08020e; margin: 0; min-height: 100vh; color: white; }
2
3  .landing-root {
4    --background: 0 0% 0%;
5    --foreground: 0 0% 98%;
6    --radius: 0.75rem;
7    background-color: hsl(var(--background));
8    color: hsl(var(--foreground));
9  }
10
11  /* Liquid glass utility */
12  .liquid-glass {
13    background: rgba(255,255,255,0.01);
14    background-blend-mode: luminosity;
15    backdrop-filter: blur(4px);
16    -webkit-backdrop-filter: blur(4px);
17    border: none;
18    box-shadow: inset 0 1px 1px rgba(255,255,255,0.1);
19    position: relative;
20    overflow: hidden;
21  }
22  .liquid-glass::before {
23    content: ''; position: absolute; inset: 0;
24    border-radius: inherit; padding: 1.4px;
25    background: linear-gradient(180deg,
26      rgba(255,255,255,0.45) 0%, rgba(255,255,255,0.15) 20%,
27      rgba(255,255,255,0) 40%, rgba(255,255,255,0) 60%,
28      rgba(255,255,255,0.15) 80%, rgba(255,255,255,0.45) 100%);
29    -webkit-mask: linear-gradient(#fff 0 0) content-box, linear-gradient(#fff 0
30    0);
31    -webkit-mask-composite: xor; mask-composite: exclude;
32    pointer-events: none;
33  }
34  .scrollbar-hide { -ms-overflow-style: none; scrollbar-width: none; }
35  .scrollbar-hide::-webkit-scrollbar { display: none; }
```

Wrap the page in `<div className="landing-root font-inter min-h-screen relative overflow-x-hidden">`.

2. Asset URLs (all remote — no local files)

- Hero background video:

https://d8j0ntlcm91z4.cloudfront.net/user_38xzZboKViGWJOttwIXH07lWA1P/hf_20260521_014404_fadafdb1-4df6-4699-be9c-77d25f39a3d0.mp4

- Dashboard live-preview video:

https://d8j0ntlcm91z4.cloudfront.net/user_38xzZboKViGWJOttwIXH07lWA1P/hf_20260328_115001_bcdaa3b4-03de-47e7-ad63-ae3e392c32d4.mp4

- Foreground grass PNG:

<https://miptxtnhvjrkmnjgdhk.supabase.co/storage/v1/object/public/training-assets/landing%2Fhero-bottom-bg.png>

3. Components

`MIcon` (Google Material Symbols)

代码块

```
1  export const MIcon = ({ name, size = 16, className = '', filled = false,
  weight = 400, style }: {
2    name: string; size?: number; className?: string; filled?: boolean; weight?:
  number; style?: React.CSSProperties;
3  }) => (
4    <span aria-hidden className={`material-symbols-outlined select-none leading-
  none inline-flex items-center justify-center ${className}`}
5      style={{ fontSize: size, width: size, height: size,
6        fontVariationSettings: ` 'FILL' ${filled?1:0}, 'wght' ${weight}, 'GRAD'
7        0, 'opsz' ${Math.min(48,Math.max(20,size))}` ,
8        ...style }}>{name}</span>
9  );
```

`AnimatedText` — text slides up on hover, replacement slides in from below (40px, 0.2s easeInOut). Uses framer-motion `motion.div` parent (`overflow-hidden`) with two stacked `motion.span` children; rest variant `{y:0}` / `{y:40}` , hover variant `{y:-40}` / `{y:0}` .

`FadeUp` — framer-motion wrapper: `initial={{opacity:0, y:24}}, whileInView={{opacity:1, y:0}}, viewport={{once:true, amount:0.3}}, transition={{duration:0.6, delay, ease:[0.22,1,0.36,1] }}`. Honors `useReducedMotion`. Accepts `delay`, `duration`, `y` props.

`PrimaryButton` — white pill CTA

- Classes: `inline-flex items-center justify-center rounded-full bg-white/80 hover:bg-white text-black leading-none transition-colors h-12 px-9 text-sm font-medium`
- Wraps children in `<AnimatedText>`.

`SecondaryButton` — glass pill

- Classes: `inline-flex items-center justify-center rounded-full bg-landing-surface hover:bg-landing-surface-hover border border-landing-border text-foreground backdrop-blur-[2.5px] font-medium leading-none h-8 px-4 text-sm (size=sm)`
- Wraps children in `<AnimatedText>`.

`HeroBadge`

代码块

```
1 <div className="inline-flex items-center justify-center rounded-full bg-
  landing-surface border border-landing-border px-4 h-7 text-sm text-landing-
  text">
2   {children}
3 </div>
```

4. Navbar (fixed, transparent)

代码块

```
1 const navItems = [
2   { name: "About", href: "#about" },
3   { name: "Features", href: "#features" },
```

```

4   { name: "What you get", href: "#what-you-get" },
5   { name: "Pricing", href: "#pricing" },
6 ];

```

- `<nav className="fixed top-0 left-0 right-0 z-50 w-full bg-transparent">`
- Inner: `mx-auto flex h-16 max-w-[1080px] items-center justify-between px-6 lg:px-0`
- Left logo: `<a href="/" className="flex items-center gap-2 text-foreground">` with `<MIcon name="rocket_launch" size={20} />` + `<span className="text-base font-semibold tracking-tight">UI Rocket</span>`
- Center (lg only): `flex items-center gap-8`, each link `text-sm text-landing-text hover:text-foreground transition-colors`, wrap label in `<AnimatedText>`. Smooth-scroll on click via `document.getElementById(id)?.scrollIntoView({behavior:"smooth"})`.
- Right actions (lg only): `flex items-center gap-5` → "Login" link (same style as nav links, wrapped in `AnimatedText`) + `<SecondaryButton href="/auth" size="sm">Get started</SecondaryButton>`
- Mobile: menu button (`MIcon name="menu" size={24}`) opens a right-side sheet (use `shadcn Sheet`) with the same items stacked.

5. Hero section

代码块

```

1  const HERO_VIDEO =
    "https://d8j0ntlcm91z4.cloudfront.net/user_38xzZboKViGWJ0ttwIXH07lWA1P/hf_20260
    521_014404_fadafdb1-4df6-4699-be9c-77d25f39a3d0.mp4";
2  const GRASS_IMG =
    "https://miptxtnhvjrkmnjgdhk.supabase.co/storage/v1/object/public/training-
    assets/landing%2Fhero-bottom-bg.png";

```

Inside the Hero component, set up scroll-linked parallax:

代码块

```

1  const sectionRef = useRef<HTMLInputElement>(null);
2  const { scrollYProgress } = useScroll({ target: sectionRef, offset: ["start
start", "end start"] });
3  const dashboardY      = useTransform(scrollYProgress, [0, 1],  ["0%", "-25%"]);
4  const grassY          = useTransform(scrollYProgress, [0, 1],  ["0%", "20%"]);
5  const contentY        = useTransform(scrollYProgress, [0, 1],  ["0%", "-60%"]);
6  const contentOpacity = useTransform(scrollYProgress, [0, 0.6], [1, 0]);

```

Structure:

代码块

```

1  <section ref={sectionRef} id="hero" className="relative w-full min-h-screen">
2    {/* 1) Background video – full bleed, no overlay */}
3    <video src={HERO_VIDEO} autoPlay muted loop playsInline
4      className="absolute inset-0 w-full h-full object-cover z-0" />
5
6    {/* 2) Centered copy + CTA, with scroll fade/translate */}
7    <motion.div style={{ y: contentY, opacity: contentOpacity }}
8      className="relative z-20 flex flex-col items-center text-center px-4 sm:px-
6 pt-28 sm:pt-36 md:pt-44 max-w-[980px] mx-auto">
9      <FadeUp delay={0}>
10        <HeroBadge>Founder member sale special</HeroBadge>
11      </FadeUp>
12      <FadeUp delay={0.1}>
13        <h1 className="mt-8 text-foreground text-[38px] sm:text-[52px] md:text-
[64px] leading-[1.05] tracking-[-0.03em] max-w-[960px]">
14          Are you a designer or builder who wants to stay ahead of AI?
15        </h1>
16      </FadeUp>
17      <FadeUp delay={0.2}>
18        <p className="mt-6 text-landing-text text-base sm:text-lg leading-[1.5]
max-w-[520px]">
19          Learn to turn your ideas into stunning websites with AI
20        </p>
21      </FadeUp>
22      <FadeUp delay={0.3} className="mt-10">
23        <PrimaryButton as="button">Get course</PrimaryButton>
24      </FadeUp>
25    </motion.div>
26
27    {/* 3) Dashboard mock – slower parallax (-25%) */}
28    <motion.div style={{ y: dashboardY }}
29      className="relative z-10 mt-8 sm:mt-10 md:mt-12 px-4 sm:px-6">
30      <DashboardMock />

```

```

31     </motion.div>
32
33     {/* 4) Foreground grass – in front of dashboard, drifts down 20% */}
34     <motion.img src={GRASS_IMG} alt="" aria-hidden style={{ y: grassY }}
35     className="pointer-events-none select-none absolute left-0 right-0 bottom-
    [-40px] sm:bottom-[-100px] lg:bottom-[-220px] w-full z-30 object-cover" />
36 </section>

```

6. DashboardMock — liquid-glass wrapper with two-column grid

代码块

```

1  <div className="liquid-glass w-full max-w-[1100px] aspect-[3/4] sm:aspect-
    [16/10] lg:aspect-[16/9] rounded-2xl mx-auto overflow-hidden p-2 sm:p-3">
2    <div className="grid h-full grid-cols-1 sm:grid-cols-
    [minmax(220px,320px)_1fr] gap-2 sm:gap-3">
3      <div className="min-h-0 hidden sm:block"><ChatPanel animateMessagesIn />
    </div>
4      <div className="min-h-0"><LivePreviewHero /></div>
5    </div>
6  </div>

```

ChatPanel (left column)

- Container: `flex h-full flex-col overflow-hidden rounded-2xl border border-white/10, inline style background: rgba(8,8,10,0.6); backdropFilter: blur(24px); WebkitBackdropFilter: blur(24px);`
- Header: `flex items-center gap-2 px-4 py-3 border-b border-white/5`. Circle `w-7 h-7 rounded-full bg-white/5 flex items-center justify-center` with `<MIcon name="auto_awesome" size={14} className="text-white/80" />`. Text column: `Vibe Design course` (`text-sm font-medium text-white`) + subtitle `Learn how to build website with AI` (`text-[11px] text-white/40`).
- Messages list: `flex-1 overflow-y-auto scrollbar-hide px-4 py-5 space-y-4`. Each row wrapped in `<FadeUp delay={i*0.12} y={16}>`. Layout:
 - Row: `flex justify-end` (user) or `flex justify-start` (assistant).

- Bubble: `max-w-[85%] rounded-2xl px-4 py-2.5 text-sm leading-relaxed;user= bg-white/15 text-white/90;assistant= bg-white/5 text-white/70 border border-white/5`.
- Seed messages (exact text):
 - assistant — "Welcome to the Vibe Design course! I'll guide you through building stunning websites with AI. What would you like to learn first?"
 - user — "I want to learn how to build a hero section with a cinematic video background using AI."
 - assistant — "Great choice! In this course, you'll learn how to create full-screen looping videos, liquid glass nav bars, email signups, and manifesto buttons — all with AI assistance. Let's dive in!"
- Input: outer `p-3 border-t border-white/5`. Inner `liquid-glass rounded-2xl flex items-end gap-2 p-2` with a `<textarea rows={1}> (flex-1 resize-none bg-transparent px-3 py-2 text-sm text-white placeholder:text-white/40 focus:outline-none max-h-32`, placeholder "Ask about the course...") and a send button `bg-white text-black rounded-xl p-2 hover:bg-white/90` containing `<MIcon name="arrow_upward" size={16} className="text-black" />`. Enter (no shift) sends; appends a user message then a canned assistant reply. After updates, scroll list to bottom smoothly.

`LivePreviewHero` (right column)

Uses `lucide-react` icons `Globe, ArrowRight, Instagram, Twitter`.

- Outer: `relative w-full h-full min-h-[500px] overflow-hidden rounded-2xl bg-black`.
- Background video (with JS fade-in/out loop):

代码块

```
1 <video ref={videoRef} src={DASHBOARD_VIDEO} muted autoPlay playsInline
  preload="auto"
2   className="absolute inset-0 w-full h-full object-cover translate-y-[17%]"
3   style={{ opacity: 0 }} />
```

Behavior (in `useEffect`):

- On `loadeddata`: set opacity 0, `play()`, fade opacity to 1 over 500ms via `requestAnimationFrame` linear tween.

- On `timeupdate`: when `duration - currentTime < 0.55s` and not already fading out, fade opacity to 0 over 500ms.
 - On `ended`: snap opacity to 0, after 100ms reset `currentTime=0`, `play()`, reset `fadingOut` flag, fade back to 1.
 - Cleanup all listeners and cancel RAF on unmount.
- Inner content stack(`relative z-10 flex flex-col min-h-full h-full`):

Mini-nav `relative z-20 px-3 sm:px-4 py-3`, inside a `rounded-full px-2 sm:px-4 py-1.5 flex items-center justify-between max-w-5xl mx-auto`:

- Left group `flex items-center gap-3 sm:gap-5`: `Globe size={14} text-white` + `<span className="text-white font-semibold text-xs sm:text-sm">Asme</span>`. After it, `hidden md:flex items-center gap-5` of links `Features`, `Pricing`, `About` each `text-white/80 hover:text-white text-[11px] font-medium`.
- Right group `flex items-center gap-2 sm:gap-3`: "Sign Up" link (`text-white text-[11px] font-medium hidden sm:inline`) + glass pill `<a className="liquid-glass rounded-full px-3 sm:px-4 py-1 text-white text-[11px] font-medium">Login</a>`.

Hero block `relative z-10 flex-1 flex flex-col items-center justify-center px-4 sm:px-6 py-4 text-center -translate-y-[8%] sm:-translate-y-[15%]`:

- `<h1 className="text-2xl sm:text-3xl md:text-4xl lg:text-5xl text-white mb-4 sm:mb-5 tracking-tight whitespace-nowrap" style={{ fontFamily: "'Instrument Serif', serif" }}>Built for the`
- `curious</h1>`
- Inner column `max-w-sm w-full space-y-3`:
 - Email pill `liquid-glass rounded-full pl-4 pr-1.5 py-1.5 flex items-center gap-2`: `<input type="email" placeholder="Enter your email" className="flex-1 bg-transparent text-white placeholder:text-white/40 text-xs focus:outline-none" />` + circular submit `bg-white rounded-full p-1.5 text-black` with `<ArrowRight size={14} />`
 - Paragraph `text-white/80 text-[11px] leading-relaxed px-2`: "Stay updated with the latest news and insights. Subscribe to our newsletter today and never miss out on exciting updates."

- Centered glass pill button: `liquid-glass rounded-full px-5 py-1.5 text-white text-[11px] font-medium hover:bg-white/5 transition-colors` → label "Manifesto".

Socials row `relative z-10 flex justify-center gap-2 pb-4 sm:pb-6`
 — three glass round buttons (`liquid-glass rounded-full p-2 text-white/80 hover:text-white hover:bg-white/5 transition-all`)
 wrapping `Instagram`, `Twitter`, `Globe` icons at `size={14}`.

7. Page assembly

代码块

```
1  export default function Page() {
2    return (
3      <div className="landing-root font-inter min-h-screen relative overflow-x-hidden">
4        <Navbar />
5        <Hero />
6      </div>
7    );
8  }
```

8. Behavioral notes (must match)

- Hero video is autoplay/muted/loop/playsInline with no dark overlay.
- Z-index stack: video `z-0`, dashboard `z-10`, copy/CTA `z-20`, grass `z-30`, navbar `z-50`.
- Hero copy fades + translates up to `-60%` during scroll through the section, fully fading by 60% scroll progress.
- Dashboard parallaxes up (`-25%`); grass drifts down (`+20%`) — creates depth.
- All button labels animate with the "text slides up, replacement slides in from below" effect via `AnimatedText`.
- Inter is the global UI font; the dashboard hero `<h1>` "Built for the curious" uses Instrument Serif.

