

Contact Cybernetic

Build a modern, interactive hero section using React, Tailwind CSS, and Framer Motion (motion/react). Ensure you follow these precise architecture and styling instructions:

1. Fonts & Global Animations

Import the Inter font from Google Fonts.

In your CSS setup, configure Tailwind to use it by default (--font-sans: 'Inter', ...).

Create a keyframe animation in CSS named blink for the typewriter cursor:

code

CSS

```
@keyframes blink {  
  0%, 100% { opacity: 1; }  
  50% { opacity: 0; }  
}  
  
.animate-blink { animation: blink 1s step-end infinite; }
```

2. General Page Structure

Wrap the entire application in a container div with the following classes: relative bg-white text-neutral-900 font-sans selection:bg-[#EAECE9] selection:text-[#1C2E1E] antialiased overflow-x-hidden flex flex-col lg:block lg:min-h-screen.

3. Background Video Component (with Native Scrubbing)

Container element: Add a div containing the background video with classes: order-last lg:order-none relative lg:absolute lg:inset-0 lg:z-0 overflow-hidden pointer-events-none w-full aspect-square md:aspect-video lg:aspect-auto lg:h-full bg-neutral-50 lg:bg-transparent.

Video element: Use <video> with muted, playsInline, preload="auto".

Video Source URL:

https://d8j0ntlcm91z4.cloudfront.net/user_38xzZboKVIGWJOttwIXH07IWA1P/hf_20260601_110537_3a579fa0-7bbc-4d94-9d25-0e816c7840f5.mp4

Classes: w-full h-full object-cover object-right lg:object-right-bottom.

Scrubbing/Playback Logic via useEffect hooks:

Desktop Mouse Scrubbing Hook: Listen to the window mousemove event. If window.innerWidth < 1024, ignore (disable scrubbing). Store the mouse 'previous X' coordinate to calculate the

delta against 'current X'. Update the target scrub time based on $(\text{delta} / \text{window.innerWidth}) * 0.8 * \text{video.duration}$. Clamp the time between 0 and duration. Set `video.currentTime = targetTime`. Bind a seeked event listener to ensure smooth tracking frame to frame.

Mobile Autoplay Hook: Because scrubbing is disabled on mobile frames, trigger normal playback for screens < 1024 width: `video.autoplay = true` and `video.play()`.

4. Interactive Navbar

Header wrapper: Wrap the Navbar in `<header className="fixed top-0 inset-x-0 z-10 px-5 sm:px-8 py-4 sm:py-5 flex flex-row justify-between items-center bg-transparent">`

Logo (Left side): Flex row with gap-3.

Text: Mainframe® (using the ® symbol). Classes: `text-[21px] sm:text-[26px] tracking-tight text-black font-medium select-none`.

Icon block right beside it: An asterisk ✱. Classes: `text-[25px] sm:text-[30px] text-black select-none tracking-[-0.02em] font-medium leading-none mb-1`.

Desktop Nav Links (Center): Flex row, hidden md:flex, `text-[23px] text-black`. Links are "Labs", "Studio", "Openings", "Shop" separated by `<span className="opacity-40">, </span>` dividers. Hover states should use `hover:opacity-60 transition-opacity`.

Desktop CTA (Right): Hidden on mobile. A link reading "Get in touch" mapped with `text-[23px] text-black underline underline-offset-2 hover:opacity-60 transition-opacity`.

Mobile Menu Logic:

Hamburger `<button>` visible below md. Has three `w-6 h-[2px] bg-black` spans.

Hook it to a local state `isMobileMenuOpen`. When open, animate the burger into an 'X' (top bar `rotate-45 translate-y-[7px]`, middle bar `opacity-0`, bottom bar `-rotate-45 -translate-y-[7px]`). All spans need `transition-all duration-300`.

Create a full screen Mobile Navigation Overlay div hidden on Desktop. Fixed `inset-0 z-[9]` with `bg-white/95 backdrop-blur-sm`. Apply `opacity-100 pointer-events-auto` when `isMobileMenuOpen` is true; otherwise, `opacity-0 pointer-events-none`.

5. Content Layout Container

Below the background video and relative to it, add a content grouping layer: `<div className="relative z-10 flex flex-col order-first lg:order-none w-full bg-white lg:bg-transparent pb-8 lg:pb-0 lg:min-h-screen">`

Inside that, the overarching layout engine: `<main id="spade-hero" className="w-full max-w-7xl mx-auto px-6 py-12 flex-1 flex flex-col justify-center">`

6. Typewriter Hook and Headline

Implement a custom `useTypewriter(text, speed = 38, startDelay = 600)` React hook. It uses `setTimeout` and `setInterval` to iteratively build a string slice by slice. It must return an object: {

displayed: string, done: boolean }.

Run the hook with the string "we'd love to\nhear from you!".

Wrap the headline securely in a motion.div configured to drop-in (initial: opacity: 0, y: 20, animate: opacity: 1, y: 0, transition duration 0.6).

Render your hook text inside <h1 className="text-5xl md:text-6xl lg:text-[76px] font-normal tracking-tight text-black leading-[1.08] mb-8 select-none w-full whitespace-pre-wrap">.

While typing (!done), output a cursor at the end of the displayed text string.

7. Secondary Description Text

Another motion.div (delay 0.1s from the headline).

Content: <p> tag that reads: Whether you have questions, feedback,
 drop us a message and we'll get back to you as soon as possible.

Classes: text-lg md:text-xl text-[#5A635A] leading-relaxed font-normal mb-14 max-w-2xl.

8. Interactive Multi-Select Service Pills

Using setServices track an array ["Brand", "Digital", "Campaign", "Other"].

The prompt Title: "What sort of service?" (text-2xl font-medium tracking-tight mb-2). Subtitle: "Select all that apply" (opacity-85 text-[#738273] mb-8).

Iterate over the options natively outputting motion.button wrapper tags allowing multiple selections inside a flex wrap container.

Pill active traits classes: bg-[#1C2E1E] text-white shadow-md shadow-emerald-950/5 transform. Show a check icon (lucide-react) dropping in using type: "spring", stiffness: 300, damping: 20.

Pill inactive traits classes: bg-white text-[#1C2E1E] border border-[#F1F3F1] hover:bg-[#F1F3F1]/55.

Contingent Feedback Status Banner: Underneath your service pills, write an <AnimatePresence mode="wait"> that tracks user state array length:

Empty: Show a generic placeholder indicating "Please click to select services above." at fifty percent opacity (opacity: 0.5, italic, text-xs).

Active Selection: Swap cleanly into a container <motion.div> that springs height gracefully (height: "auto"). Inside, display an acknowledgment banner reading "Ready to inquire about: [array.join(", ")]" combined with an arrow call-to-action button "Let's Go" (text-[#4D6D47] uppercase text-xs). Style the banner with bg-[#FAFBF9] border rounded-2xl.