

Scroll Landing Page

Create a React + Vite + Tailwind CSS v4 landing page for "WISA" -- a premium football/soccer organization website. The page has a scroll-driven video background, 3 content sections, and a glassmorphism footer. Use ONLY these dependencies: react 19, motion (framer-motion v12+), gsap, lucide-react, tailwindcss v4 with @tailwindcss/vite plugin. The design is dark, cinematic, minimal, with Manrope (sans) and JetBrains Mono (mono) fonts.

GLOBAL SETUP

package.json dependencies (exact):

代码块

```
1  react, react-dom ^19.0.0
2  motion ^12.23.24
3  gsap ^3.14.2
4  lucide-react ^0.546.0
5  tailwindcss ^4.1.14
6  @tailwindcss/vite ^4.1.14
7  @vitejs/plugin-react ^5.0.4
8  vite ^6.2.0
```

vite.config.ts: Use `@tailwindcss/vite` plugin + `@vitejs/plugin-react`. Alias `@` to project root.

index.html: Standard HTML5. Include `<script type="module" src="https://ajax.googleapis.com/ajax/libs/model-viewer/3.4.0/model-viewer.min.js"></script>` in head.

src/index.css -- EXACT:

代码块

```
1  @import url('https://fonts.googleapis.com/css2?
    family=JetBrainsMono:wght@400;500;600;700&family=Manrope:wght@300;400;500;600;
    700&display=swap');
2  @import "tailwindcss";
3
4  @theme {
5      --font-sans: "Manrope", ui-sans-serif, system-ui, sans-serif;
6      --font-mono: "JetBrains Mono", ui-monospace, SFMono-Regular, monospace;
7  }
8
9  @keyframes flyOutRight {
10     0% { transform: translateX(0); }
11     100% { transform: translateX(250%); }
12 }
13
14 @keyframes flyInLeft {
15     0% { transform: translateX(-250%); }
16     100% { transform: translateX(0); }
17 }
18
19 .animate-fly-out {
20     animation: flyOutRight 0.5s cubic-bezier(0.4, 0, 0.2, 1) forwards;
21 }
22
23 .animate-fly-in {
24     animation: flyInLeft 0.5s cubic-bezier(0.4, 0, 0.2, 1) forwards;
25 }
26
27 @keyframes flyOutUp {
28     0% { transform: translateY(0); }
29     100% { transform: translateY(-150%); }
30 }
31
32 @keyframes flyInUp {
33     0% { transform: translateY(150%); }
34     100% { transform: translateY(0); }
35 }
36
37 .animate-fly-out-up {
38     animation: flyOutUp 0.4s cubic-bezier(0.4, 0, 0.2, 1) forwards;
39 }
40
41 .animate-fly-in-up {
42     animation: flyInUp 0.4s cubic-bezier(0.4, 0, 0.2, 1) forwards;
```

These define 4 keyframe animations:

- `flyOutRight / flyInLeft` (250% translateX, 0.5s) -- for the arrow button hover
- `flyOutUp / flyInUp` (150% translateY, 0.4s) -- for nav text hover
- All use `cubic-bezier(0.4, 0, 0.2, 1)` easing with `forwards` fill mode

COMPONENT: ScrollReveal (`src/components/ScrollReveal.tsx` + `ScrollReveal.css`)

ScrollReveal.css:

代码块

```
1 .scroll-reveal { margin: 0; }
2 .scroll-reveal-text { display: flex; flex-wrap: wrap; margin: 0; }
3 .word { display: inline-block; white-space: pre; }
```

ScrollReveal.tsx: A GSAP-powered word-by-word scroll reveal component.

- Props: `children` (string), `scrollContainerRef?`, `enableBlur` (default true), `baseOpacity` (default 0.1), `baseRotation` (default 3), `blurStrength` (default 4), `containerClassName`, `textClassName`, `rotationEnd` (default "bottom bottom"), `wordAnimationEnd` (default "bottom bottom")
- Splits children text by whitespace into `<span className="word">` elements using `useMemo`
- Three GSAP ScrollTrigger animations:
 - Rotation:** Container rotates from `baseRotation` degrees to 0, origin "0% 50%", scrub true, trigger start "top bottom", end = `rotationEnd`
 - Opacity:** Each `.word` fades from `baseOpacity` to 1, stagger 0.05, scrub true, trigger start "top bottom-=20%", end = `wordAnimationEnd`

- c. **Blur** (if `enableBlur`): Each `.word` goes from `blur(blurStrength px)` to `blur(0px)`, same stagger/trigger as opacity
 - Renders: `<h2 ref={containerRef} className="scroll-reveal {containerClassName}"><p className="scroll-reveal-text {textClassName}">{splitText}</p></h2>`
 - Cleanup: kills all ScrollTrigger instances on unmount
-

COMPONENT: Reveal (inline in App.tsx)

A motion.div wrapper for viewport-triggered fade-in:

代码块

```
1  function Reveal({ children, delay = 0, className = "" }) {
2    return (
3      <motion.div
4        initial={{ opacity: 0, y: 30 }}
5        whileInView={{ opacity: 1, y: 0 }}
6        viewport={{ once: true, margin: "-50px" }}
7        transition={{ duration: 0.8, ease: [0.16, 1, 0.3, 1], delay }}
8        className={className}
9      >
10     {children}
11   </motion.div>
12 );
13 }
```

Easing is `[0.16, 1, 0.3, 1]` (ease-out-expo style).

COMPONENT: NavItem (inline in App.tsx)

A hover-animated navigation link with vertical text fly animation:

- Uses a `cycle` counter state (`useState(0)`)
 - On `mouseenter` and `mouseleave`: increment cycle
 - When `cycle === 0` (initial, no hover yet): render single `<span>` with `text-white/64` and `group-hover:text-white transition-colors duration-300`
 - When `cycle > 0`: render TWO spans keyed by cycle -- one with `.animate-fly-out-up` (exits upward), one absolute-positioned with `.animate-fly-in-up` (enters from below)
 - Container: `<a>` with `relative overflow-hidden group flex items-center justify-center py-1`
-

MAIN APP (src/App.tsx) - ARCHITECTURE

Video URL constant:

代码块

```
1  const VIDEO_URL =  
    'https://d8j0ntlcm91z4.cloudfront.net/user_38xzZboKViGWJ0ttwIXH07lWA1P/hf_20260521_064421_279656fd-e76f-40a0-8fed-7456d4f7715a.mp4';
```

State & Refs:

- `arrowCycle` (`useState(0)`) -- for arrow button hover animation, same pattern as `NavItem`
 - `videoRef` (`useRef HTMLVideoElement`)
 - `videoContainerRef` (`useRef HTMLDivElement`)
 - `isLoading` (`useState false`) -- tracks when video is ready
 - `screen3Ref` (`useRef HTMLDivElement`) -- reference to footer section for scroll calculation
 - `scroLly` from motion's `useScroll()`
 - `headerY = useTransform(scroLly, [0, 500, 800], [0, 0, -150])` -- header slides up and out after scrolling past 500px
-

SCROLL-DRIVEN VIDEO - CRITICAL IMPLEMENTATION

Effect 1: Video Loading

代码块

```
1  useEffect(() => {
2    const video = videoRef.current;
3    if (!video) return;
4    const handleCanPlay = () => setIsLoaded(true);
5    video.addEventListener('canplaythrough', handleCanPlay);
6    video.load();
7    return () => video.removeEventListener('canplaythrough', handleCanPlay);
8  }, []);
```

Effect 2: Scroll-to-Video-Scrub (with the `video.seeking` guard)

代码块

```
1  useEffect(() => {
2    if (!isLoaded) return;
3    const video = videoRef.current;
4    if (!video || !video.duration) return;
5
6    const handleScroll = () => {
7      if (!screen3Ref.current || video.seeking) return;
8      // ^^ CRITICAL: "video.seeking" check tells the browser: "Only update the
video
9      // frame when you've completely finished rendering the previous one."
10     // Without this guard, rapid scroll events queue up competing .currentTime
assignments,
11     // causing visible frame tearing, flickering, and dropped frames. The
browser's
12     // internal seek operation is asynchronous -- setting .currentTime while a
previous
13     // seek is still in progress gets silently ignored or causes visual
glitches.
14     // By checking video.seeking, we skip scroll events that arrive before the
prior
15     // frame has been decoded and painted, resulting in smooth, tear-free
scrubbing.
16  }
```

```

17     const rect = screen3Ref.current.getBoundingClientRect();
18     const absoluteTop = window.scrollY + rect.top;
19     const stopScroll = Math.max(1, absoluteTop - (window.innerHeight * 0.2));
20     const scrollFraction = Math.max(0, Math.min(1, window.scrollY /
    stopScroll));
21     video.currentTime = scrollFraction * video.duration;
22   };
23
24   window.addEventListener('scroll', handleScroll, { passive: true });
25   handleScroll();
26   return () => window.removeEventListener('scroll', handleScroll);
27 }, [isLoading]);

```

The scroll fraction maps from 0 (top of page) to 1 (when the footer section is 20% of viewport height from top). This means the video plays through its full duration as the user scrolls from top to the footer.

SECTION 0: LOADING SCREEN

Shown when `!isLoading`. Fixed fullscreen, z-50, black bg, centered:

- "LOADING" text: `text-[10px] font-mono tracking-widest mb-4 text-white/50`
- Progress bar below: `w-64 h-[1px] bg-white/10 mt-8 overflow-hidden` with inner `h-full bg-white w-1/3 animate-pulse`

LAYER STRUCTURE

The entire page is layered:

1. **Fixed video background** (`fixed inset-0 z-0 bg-black`) -- video is absolutely centered with cover behavior using `transform: translate(-50%, -50%),` `minWidth/minHeight: 100%,` `objectFit: cover`

2. **Fixed header** (z-20) -- animated with motion, slides out via `headerY` transform
 3. **Scrollable content** (`relative z-10 pointer-events-none`) -- all sections flow here, with `pointer-events-auto` on interactive areas
-

SECTION 1: HERO (Screen 1)

Container: `w-[90%] mx-auto h-screen flex flex-col py-8 md:py-12 lg:py-16 pb-12`

Inner main: `flex-1 w-full pointer-events-auto flex flex-col md:grid md:grid-cols-12 md:grid-rows-[1fr_auto] gap-y-8 md:gap-y-0 md:gap-x-8`

Grid layout (desktop 12-col, 2-row):

1. **Heading** (bottom-left): `md:row-start-2 md:col-start-1 md:col-span-8 flex items-end`
 - H1: `text-[clamp(2.5rem,6vw,5rem)] leading-[1.05] font-medium tracking-tight text-white whitespace-nowrap`
 - Text: "Championing" `<br/>` "The Pitch Of Legends"
 - Wrapped in `<Reveal delay={0.2}>`
2. **Description paragraph** (center-right): `md:row-start-1 md:col-start-8 md:col-span-5 flex flex-col justify-center items-start md:items-end text-left md:text-right`
 - Paragraph: `text-[clamp(1rem,1.6vw,1.375rem)] text-white/64 leading-[1.3] font-normal max-w-[460px] relative -top-[90px]`
 - Text: "Advanced preparation and training of world-class football teams for leagues, tournaments, and trophies. **We bring the trophy closer to your cabinet.**" (bold part is `font-semibold text-white`)
 - Wrapped in `<Reveal delay={0.3}>`

3. **CTA Button** (bottom-right): `md:row-start-2 md:col-start-8 md:col-span-5 flex items-end justify-start md:justify-end`
- Two-part button with 1px gap (`flex items-stretch gap-1 group cursor-pointer`)
 - **Text part:** `px-8 py-5 bg-white/8 backdrop-blur-[80px]` -> on group-hover: `bg-white` .Text: "EXPLORE OUR STADIUMS" in `font-mono text-[12px] tracking-[-0.01em] text-white/90` -> hover: `text-black`
 - **Arrow part:** `px-6 bg-white/8 backdrop-blur-[80px]` -> hover: `bg-white` . Contains `<ArrowRight>` (lucide, w-5 h-5) with the same fly-out/fly-in animation pattern as NavItem but horizontal (`.animate-fly-out` / `.animate-fly-in`)
 - `arrowCycle` state drives the animation, same increment pattern on `mouseenter/mouseleave`
 - Wrapped in `<Reveal delay={0.4}>`
-

SECTION 1.5: SPACER

```
<div className="h-[200px] w-full"></div> -- 200px empty gap
```

SECTION 2: SCROLL-REVEAL TEXT + 3-COLUMN GRID

Container: `w-[90%] mx-auto min-h-screen flex flex-col justify-center py-8 md:py-12 lg:py-16 pointer-events-auto`

Inner: `max-w-[1200px] w-full`

ScrollReveal component usage:

```

1  <ScrollReveal
2    baseOpacity={0.1}
3    enableBlur={true}
4    baseRotation={3}
5    blurStrength={4}
6    textClassName="text-[clamp(2rem,4.5vw,4rem)] leading-[1.1] font-medium
   tracking-tight text-white w-full"
7  >
8    Complete Football Programs For Professional Player Development. We Build The
   Foundations For Next-Generation Strikers, Midfielders, And Star Defenders.
9  </ScrollReveal>

```

3-Column Grid below (`mt-24 grid grid-cols-1 md:grid-cols-12 gap-12 md:gap-8`):

- Col 1 (md:col-span-4):** Globe SVG (71x43 wireframe globe) + WISA logo SVG (157x25, scaled to `h-[18px] w-auto`) side by side with `gap-4`. Below: tagline "Winning the future on pitch" in `text-[11px] font-mono tracking-widest text-white/60 uppercase leading-relaxed`. Wrapped in `<Reveal delay={0.1}>`
- Col 2 (md:col-span-4):** H3 "Performance Analytics / Facilities" (`text-xl font-medium text-white`), paragraph below (`text-[15px] text-white/80 leading-relaxed`). Wrapped in `<Reveal delay={0.2}>`
- Col 3 (md:col-span-4):** H3 "Matchday Premium / Fan Experiences!" same styling, paragraph same styling. Wrapped in `<Reveal delay={0.3}>`

SECTION 2.5: SPACER

Another `h-[200px]` spacer

SECTION 3: FOOTER (ref={screen3Ref})

This is the scroll endpoint for the video scrub calculation. Wrapped in `pointer-events-auto`.

Footer container: `width: 90%, margin: 0 auto, paddingBottom: 64px` (inline styles)

Inner card (glassmorphism): `backgroundColor: rgba(26, 26, 26, 0.6), backdropFilter: blur(80px), WebkitBackdropFilter: blur(80px), border: 1px solid rgba(255, 255, 255, 0.1), padding: clamp(32px, 4vw, 64px)` -- all inline styles

CTA Section (top of footer card):

- Flexbox wrap, `alignItems: flex-end, justifyContent: space-between, gap: 40px`
- Bottom border: `1px solid rgba(255, 255, 255, 0.1), paddingBottom: clamp(48px, 4vw, 80px)`
- H2: "Ready To Score / Your Winning Season?" -- `fontSize: clamp(2rem, 4.5vw, 3.5rem), fontWeight: 500, letterSpacing: -0.02em, lineHeight: 1.05`
- Button: Same two-part pattern (text + arrow) but with white bg / black text, `padding: 20px 32px` and `20px 24px`. Text: "START YOUR SEASONS" in `font-mono, 12px, -0.01em tracking, bold 700`

Footer Links Grid (`paddingTop: clamp(48px, 4vw, 64px)`):

- CSS Grid: `repeat(auto-fit, minmax(160px, 1fr)), gap: clamp(32px, 3vw, 48px)`
- 4 columns:
 - Brand:** WISA logo SVG (h:14px) + tagline paragraph (13px, rgba white 0.4, maxWidth 220)
 - Company:** Header "COMPANY" (10px mono, 0.1em tracking, rgba white 0.3) + links: About, Rosters, Press, Contact (14px, rgba white 0.6)
 - Services:** Header "SERVICES" same style + links: Coaching, Training Camp, Fitness, Tryout

- d. **Connect:** Header "CONNECT" same style + links: LinkedIn, X / Twitter, YouTube, Newsletter

Copyright Bar (`marginTop: 56, paddingTop: 32, borderTop: 1px solid rgba white 0.1`):

- Flex wrap space-between
 - Left: "2026 WISA. ALL RIGHTS RESERVED." (11px mono, rgba white 0.25, 0.1em tracking)
 - Right: PRIVACY | TERMS links (same styling, gap-24px)
-

FIXED HEADER

`<motion.header>` with:

- `style={{ y: headerY }}` -- slides out after scroll 500-800px
- `initial={{ opacity: 0, y: 20 }}`, `animate={{ opacity: 1 }}`, easing `[0.16, 1, 0.3, 1]`, duration 0.8
- Classes: `fixed top-0 left-1/2 -translate-x-1/2 z-20 w-[90%] flex items-center justify-between pointer-events-auto py-4 md:py-6 lg:py-8`

Left: WISA Logo SVG (157x25, white, 4 paths spelling "WISA")

Right: Navigation bar (`hidden lg:flex items-stretch bg-[#1A1A1A]/40 backdrop-blur-[80px]`):

- Nav links container: `flex items-center justify-between px-6 font-mono text-xs tracking-[-0.01em] w-[480px]`
 - 5 NavItem components: LEAGUES, STADIUMS, TRAINING, COMPETITIONS, TICKETS
 - CTA button: `bg-white text-black px-6 py-5 font-mono text-xs leading-4 font-bold tracking-[-0.01em] hover:bg-gray-200 transition-colors w-[148px]` -- text "BUY MATCH PASS"
-

SVG ASSETS

WISA Logo (used 3 times -- header, section 2, footer): 157x25 viewBox, 4 white paths. The paths spell "W I S A" in a custom typeface.

Globe icon (used in section 2 col 1): 71x43 viewBox, wireframe globe with horizontal/vertical/meridian lines, stroke white, no fill.

Both SVGs are inlined directly. They are too detailed to describe -- copy the exact path data from the source code above.

KEY DESIGN TOKENS SUMMARY

Token	Value
Font sans	Manrope 300-700
Font mono	JetBrains Mono 400-700
Background	Pure black (#000)
Text primary	white
Text secondary	white/64 (rgba 255,255,255,0.64)
Text muted	white/60, white/50, white/40, white/25
Glass bg	#1A1A1A at 40% opacity
Glass blur	80px
Glass border	rgba(255,255,255,0.1)

Button bg	white/8 -> white on hover
Spacing rhythm	90% viewport width container, clamp-based responsive values
Easing (motion)	[0.16, 1, 0.3, 1]
Easing (CSS)	cubic-bezier(0.4, 0, 0.2, 1)