

AI Workflow Hero

Stack

- **Vite + React 18 + TypeScript**
 - **Tailwind CSS 3.4**
 - **lucide-react** for icons (`LogIn` , `UserPlus` , `Play` , `Sparkles` , `Menu` , `X`)
 - No Framer Motion -- all animations are CSS `transition-*` classes
-

Fonts (loaded in `index.html`)

代码块

```
1 <link rel="preconnect" href="https://fonts.googleapis.com" />
2 <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin />
3 <link href="https://fonts.googleapis.com/css2?
  family=Inter:wght@300;400;500;600;700&display=swap" rel="stylesheet" />
4 <link href="https://db.onlinewebfonts.com/c/6e47ef470dd19698c911332a9b4d1cf4?
  family=Neue+Haas+Grotesk+Text+Pro" rel="stylesheet" />
5 <link href="https://db.onlinewebfonts.com/c/dec0d9b4e22ca588dc20e1e2e09a59b5?
  family=Neue+Haas+Grotesk+Display+Pro+55+Roman" rel="stylesheet" />
```

Body/root font stack (in `index.css`):

代码块

```
1 html, body, #root {
2   height: 100%;
3   margin: 0;
4   font-family: 'Neue Haas Grotesk Display Pro 55 Roman', 'Neue Haas Grotesk
  Text Pro', 'Helvetica Neue', Helvetica, Arial, sans-serif;
```

```
5  -webkit-font-smoothing: antialiased;
6  }
```

Video URL (CloudFront)

代码块

```
1  https://d8j0ntlcm91z4.cloudfront.net/user_38xzZboKViGWJ0ttwIXH07lWA1P/hf_20260511_131941_d136af49-e243-493a-be14-6ff3f24e09e6.mp4
```

Color Palette

Token	Hex
Dark green (text, buttons)	#1f2a1d
Medium dark green	#2d3a2a
Button hover	#2a3827
Body text green	#4b5b47
Heading primary	#336443
Heading accent	#85AB8B
Bottom-left text	#3d5638
Bottom-left button bg	#3d5638 , hover #2d4228

Architecture

Two files:

1. **BoomerangVideoBg.tsx** -- captures video frames into canvas, then plays them forward/backward in a seamless boomerang loop at 30fps (960px max capture width).
 2. **App.tsx** -- the full hero section.
-

BoomerangVideoBg.tsx (exact)

代码块

```
1  import { useEffect, useRef, useState } from 'react';
2
3  type Props = {
4    src: string;
5    className?: string;
6  };
7
8  export default function BoomerangVideoBg({ src, className }: Props) {
9    const videoRef = useRef<HTMLVideoElement>(null);
10   const displayCanvasRef = useRef<HTMLCanvasElement>(null);
11   const [framesReady, setFramesReady] = useState(false);
12   const framesRef = useRef<HTMLCanvasElement[]>([]);
13
14   useEffect(() => {
15     const video = videoRef.current;
16     if (!video) return;
17
18     const frames: HTMLCanvasElement[] = [];
19     let capturing = true;
20     let lastTime = -1;
21     const MAX_WIDTH = 960;
22
```

```

23     const captureFrame = () => {
24         if (!capturing || video.readyState < 2) return;
25         if (video.currentTime === lastTime) return;
26         lastTime = video.currentTime;
27
28         const vw = video.videoWidth;
29         const vh = video.videoHeight;
30         if (!vw || !vh) return;
31
32         const scale = Math.min(1, MAX_WIDTH / vw);
33         const w = Math.round(vw * scale);
34         const h = Math.round(vh * scale);
35
36         const canvas = document.createElement('canvas');
37         canvas.width = w;
38         canvas.height = h;
39         const ctx = canvas.getContext('2d');
40         if (!ctx) return;
41         ctx.drawImage(video, 0, 0, w, h);
42         frames.push(canvas);
43     };
44
45     type VFCVideo = HTMLVideoElement & {
46         requestVideoFrameCallback?: (cb: () => void) => number;
47     };
48     const vfcVideo = video as VFCVideo;
49     const hasVFC = typeof vfcVideo.requestVideoFrameCallback === 'function';
50
51     let rafId = 0;
52     const rafLoop = () => {
53         captureFrame();
54         if (capturing) rafId = requestAnimationFrame(rafLoop);
55     };
56
57     const vfcLoop = () => {
58         captureFrame();
59         if (capturing && vfcVideo.requestVideoFrameCallback) {
60             vfcVideo.requestVideoFrameCallback(vfcLoop);
61         }
62     };
63
64     const onEnded = () => {
65         capturing = false;
66         if (frames.length > 0) {
67             framesRef.current = frames;
68             setFramesReady(true);
69         }

```

```

70     };
71
72     const onLoaded = () => {
73         video.play().catch(() => {});
74         if (hasVFC) {
75             vfcVideo.requestVideoFrameCallback!(vfcLoop);
76         } else {
77             rafId = requestAnimationFrame(rafLoop);
78         }
79     };
80
81     video.addEventListener('loadedmetadata', onLoaded);
82     video.addEventListener('ended', onEnded);
83     if (video.readyState >= 1) onLoaded();
84
85     return () => {
86         capturing = false;
87         cancelAnimationFrame(rafId);
88         video.removeEventListener('loadedmetadata', onLoaded);
89         video.removeEventListener('ended', onEnded);
90     };
91 }, [src]);
92
93 useEffect(() => {
94     if (!framesReady) return;
95     const canvas = displayCanvasRef.current;
96     if (!canvas) return;
97     const ctx = canvas.getContext('2d');
98     if (!ctx) return;
99     const frames = framesRef.current;
100    if (frames.length === 0) return;
101
102    const first = frames[0];
103    canvas.width = first.width;
104    canvas.height = first.height;
105
106    let index = 0;
107    let direction = 1;
108    let last = performance.now();
109    const interval = 1000 / 30;
110    let rafId = 0;
111
112    const render = (now: number) => {
113        if (now - last >= interval) {
114            last = now;
115            ctx.drawImage(frames[index], 0, 0);
116            index += direction;

```

```

117         if (index >= frames.length - 1) {
118             index = frames.length - 1;
119             direction = -1;
120         } else if (index <= 0) {
121             index = 0;
122             direction = 1;
123         }
124     }
125     rafId = requestAnimationFrame(render);
126 };
127 rafId = requestAnimationFrame(render);
128 return () => cancelAnimationFrame(rafId);
129 }, [framesReady]);
130
131 return (
132     <div className={className ?? 'absolute inset-0 w-full h-full'}>
133         <video
134             ref={videoRef}
135             src={src}
136             className="w-full h-full object-cover"
137             style={{ display: framesReady ? 'none' : 'block' }}
138             muted
139             playsInline
140             preload="auto"
141             crossOrigin="anonymous"
142         />
143         <canvas
144             ref={displayCanvasRef}
145             className="w-full h-full object-cover"
146             style={{ display: framesReady ? 'block' : 'none' }}
147         />
148     </div>
149 );
150 }

```

App.tsx (exact)

代码块

```
1 import { useState, useEffect } from 'react';
```

```

2  import { LogIn, UserPlus, Play, Sparkles, Menu, X } from 'lucide-react';
3  import BoomerangVideoBg from './BoomerangVideoBg';
4
5  const BG_VIDEO =
6
7    'https://d8j0ntlcm91z4.cloudfront.net/user_38xzZboKViGWJOttwIXH07lWA1P/hf_20260
8    511_131941_d136af49-e243-493a-be14-6ff3f24e09e6.mp4';
9
10
11  function App() {
12    const [menuOpen, setMenuOpen] = useState(false);
13
14    useEffect(() => {
15      if (menuOpen) {
16        document.body.style.overflow = 'hidden';
17      } else {
18        document.body.style.overflow = '';
19      }
20      return () => {
21        document.body.style.overflow = '';
22      };
23    }, [menuOpen]);
24
25    const navLinks = [
26      { href: '#mission', label: 'Purpose' },
27      { href: '#how', label: 'The Process' },
28      { href: '#pricing', label: 'Tariffs' },
29    ];
30
31    return (
32      <section className="relative w-full min-h-screen sm:h-screen overflow-
33      hidden">
34        <BoomerangVideoBg src={BG_VIDEO} className="absolute inset-0 w-full h-
35        full" />
36        <nav className="absolute top-0 left-0 right-0 z-30 flex items-center
37        justify-between px-4 sm:px-6 md:px-10 py-4 sm:py-6">
38          <div className="flex items-center gap-2 text-[#2d3a2a]">
39            <span className="text-lg sm:text-xl md:text-2xl font-semibold
40            tracking-tight">
41              LinkFlow<sup className="text-[10px] sm:text-xs font-
42              medium">TM</sup>
43            </span>
44          </div>
45
46          <div className="hidden lg:flex items-center gap-1 bg-white/70 backdrop-
47          blur-md rounded-full pl-6 pr-1 py-1 shadow-sm border border-white/60">
48            {navLinks.map((link, i) => (
49              <a

```

```

41         key={link.href}
42         href={link.href}
43         className={`text-sm px-3 py-2 transition-colors ${
44             i === 0 ? 'font-semibold text-[#1f2a1d]' : 'font-medium text-
[#4b5b47] hover:text-[#1f2a1d]'
45         }}
46     >
47         {link.label}
48     </a>
49 ))}
50 <button className="ml-2 bg-[#1f2a1d] hover:bg-[#2a3827] text-white
text-sm font-medium px-5 py-2.5 rounded-full transition-colors">
51     Try it Live
52 </button>
53 </div>
54
55 <div className="flex items-center gap-3 sm:gap-6 text-[#2d3a2a]">
56     <a href="#signup" className="hidden sm:flex items-center gap-2 text-
sm font-medium hover:opacity-80 transition-opacity">
57         <UserPlus className="w-4 h-4" />
58         Sign Me Up!
59     </a>
60     <a href="#login" className="hidden sm:flex items-center gap-2 text-
sm font-medium hover:opacity-80 transition-opacity">
61         <LogIn className="w-4 h-4" />
62         Enter
63     </a>
64     <button
65         onClick={() => setMenuOpen((v) => !v)}
66         className="lg:hidden relative flex items-center justify-center w-
10 h-10 rounded-full bg-white/70 backdrop-blur-md border border-white/60 text-
[#1f2a1d] transition-all duration-300 hover:bg-white/90"
67         aria-label={menuOpen ? 'Close menu' : 'Open menu'}
68         aria-expanded={menuOpen}
69     >
70         <Menu
71             className={`w-5 h-5 absolute transition-all duration-300 ${
72                 menuOpen ? 'opacity-0 rotate-90 scale-50' : 'opacity-100
rotate-0 scale-100'
73             }`}
74         />
75         <X
76             className={`w-5 h-5 absolute transition-all duration-300 ${
77                 menuOpen ? 'opacity-100 rotate-0 scale-100' : 'opacity-0 -
rotate-90 scale-50'
78             }`}
79         />

```



```

80         </button>
81     </div>
82 </nav>
83
84 {/* Mobile menu overlay */}
85 <div
86     className={`lg:hidden fixed inset-0 z-20 transition-opacity duration-
300 ${
87         menuOpen ? 'opacity-100 pointer-events-auto' : 'opacity-0 pointer-
events-none'
88     }}
89     onClick={() => setMenuOpen(false)}
90     >
91         <div className="absolute inset-0 bg-[#1f2a1d]/40 backdrop-blur-sm" />
92     </div>
93
94 {/* Mobile menu drawer */}
95 <div
96     className={`lg:hidden fixed top-0 right-0 bottom-0 z-20 w-[85%] max-w-
sm bg-white/95 backdrop-blur-xl shadow-2xl transition-transform duration-500
ease-[cubic-bezier(0.22,1,0.36,1)] ${
97         menuOpen ? 'translate-x-0' : 'translate-x-full'
98     }}
99     >
100     <div className="flex flex-col h-full pt-24 px-8 pb-8">
101         <div className="flex flex-col gap-1">
102             {navLinks.map((link, i) => (
103                 <a
104                     key={link.href}
105                     href={link.href}
106                     onClick={() => setMenuOpen(false)}
107                     className={`text-2xl font-semibold text-[#1f2a1d] py-4 border-
b border-[#1f2a1d]/10 transition-all duration-500 ${
108                         menuOpen ? 'translate-x-0 opacity-100' : 'translate-x-8
opacity-0'
109                     }}
110                     style={{ transitionDelay: menuOpen ? `${150 + i * 70}ms` :
'0ms' }}
111                 >
112                     {link.label}
113                 </a>
114             ))}
115         </div>
116
117         <div
118             className={`mt-8 flex flex-col gap-4 transition-all duration-500 ${

```

```

119         menuOpen ? 'translate-x-0 opacity-100' : 'translate-x-8 opacity-
0'
120     }`}
121     style={{ transitionDelay: menuOpen ? '400ms' : '0ms' }}
122 >
123     <a href="#signup" className="flex items-center gap-2 text-sm font-
medium text-[#2d3a2a] sm:hidden">
124         <UserPlus className="w-4 h-4" />
125         Sign Me Up!
126     </a>
127     <a href="#login" className="flex items-center gap-2 text-sm font-
medium text-[#2d3a2a] sm:hidden">
128         <LogIn className="w-4 h-4" />
129         Enter
130     </a>
131     <button className="mt-2 bg-[#1f2a1d] hover:bg-[#2a3827] text-white
text-sm font-semibold px-5 py-3 rounded-full transition-colors">
132         Try it Live
133     </button>
134 </div>
135 </div>
136 </div>
137
138 {/* Hero copy */}
139 <div className="relative z-10 flex flex-col items-center text-center pt-
24 sm:pt-28 md:pt-32 px-4 sm:px-6">
140     <h1
141         className="font-normal leading-[0.95] text-[#336443] text-[2rem]
sm:text-4xl md:text-5xl lg:text-[4.75rem] xl:text-[5.25rem] max-w-5xl"
142         style={{ fontFamily: '"Neue Haas Grotesk Display Pro 55 Roman",
"Neue Haas Grotesk Text Pro", "Helvetica Neue", Helvetica, Arial, sans-serif',
letterSpacing: '-0.035em' }}
143     >
144         Close the rift{' '}
145         <span className="text-[#85AB8B]">
146             linking
147             <br className="hidden sm:block" /> signals and action
148         </span>
149     </h1>
150     <p className="mt-6 sm:mt-8 text-[#4b5b47] text-sm sm:text-base md:text-
lg leading-relaxed max-w-md px-2">
151         Shape scattered signals into meaningful outcomes via AI-driven
workflows.
152     </p>
153 </div>
154
155 {/* Bottom-left CTA block */}

```

```

156     <div className="absolute left-4 right-4 sm:right-auto sm:left-6 md:left-
10 bottom-6 sm:bottom-8 md:bottom-10 z-10 max-w-sm">
157     <div className="flex items-center gap-2 text-[#3d5638] sm:text-
white/95 mb-3">
158         <Sparkles className="w-4 h-4" />
159         <span className="text-sm font-semibold sm:font-medium">
160             FluxEngine<sup className="text-[10px]">TM</sup>
161         </span>
162     </div>
163     <p className="text-[#3d5638]/90 sm:text-white/85 text-xs leading-
relaxed mb-6 max-w-xs font-medium sm:font-normal">
164         LinkFlow smoothly unites your company systems, streamlining data
paths between services without having to write custom scripts.
165     </p>
166     <div className="flex items-center gap-4 flex-wrap">
167         <button className="bg-[#3d5638] sm:bg-white hover:bg-[#2d4228]
sm:hover:bg-white/90 text-white sm:text-[#1f2a1d] text-sm font-semibold px-5
sm:px-6 py-2.5 sm:py-3 rounded-full transition-colors shadow-sm">
168             Try it Live
169         </button>
170         <button className="text-[#3d5638] sm:text-white text-sm font-
semibold sm:font-medium hover:opacity-80 transition-opacity">
171             Know More.
172         </button>
173     </div>
174 </div>
175
176 {/* Bottom-right video link */}
177 <div className="hidden sm:flex absolute right-6 md:right-10 bottom-8
md:bottom-10 z-10 items-center gap-2 text-white/90 text-sm">
178     <button className="flex items-center justify-center w-6 h-6 rounded-
full bg-white/20 backdrop-blur-sm hover:bg-white/30 transition-colors">
179         <Play className="w-3 h-3 fill-white text-white ml-0.5" />
180     </button>
181     <span className="font-medium">How we build?</span>
182     <span className="text-white/60">1:35</span>
183 </div>
184 </section>
185 );
186 }
187
188 export default App;

```

Animation Details (all CSS, no Framer Motion)

Element	Property	Values
Hamburger Menu/X icon swap	transition-all duration-300	Open: Menu gets opacity-0 rotate-90 scale-50 , X gets opacity-100 rotate-0 scale-100 . Closed: reverse.
Mobile overlay backdrop	transition-opacity duration-300	Open: opacity-100 pointer-events-auto . Closed: opacity-0 pointer-events-none .
Mobile drawer slide	transition-transform duration-500 ease-cubic-bezier(0.22,1,0.36,1)]	Open: translate-x-0 . Closed: translate-x-full .
Mobile nav links stagger	transition-all duration-500	Open: translate-x-0 opacity-100 , delay per item: 150ms + i * 70ms . Closed: translate-x-8 opacity-0 , delay 0ms .
Mobile CTA group	transition-all duration-500	Open: translate-x-0 opacity-100 , delay 400ms . Closed: translate-x-8 opacity-0 , delay 0ms .
Nav buttons	transition-colors	Default Tailwind duration (150ms).
Opacity links	transition-opacity	hover:opacity-80 .

Key Layout/Spacing Notes

- Root section: `relative w-full min-h-screen sm:h-screen overflow-hidden`
 - Navbar padding: `px-4 sm:px-6 md:px-10 py-4 sm:py-6`
 - Desktop pill nav: `bg-white/70 backdrop-blur-md rounded-full pl-6 pr-1 py-1 shadow-sm border border-white/60`
 - Hero heading: `pt-24 sm:pt-28 md:pt-32`, font sizes `text-[2rem] sm:text-4xl md:text-5xl lg:text-[4.75rem] xl:text-[5.25rem]`, `leading-[0.95]`, `letterSpacing: '-0.035em'`
 - Bottom-left block: `absolute left-4 right-4 sm:right-auto sm:left-6 md:left-10 bottom-6 sm:bottom-8 md:bottom-10`
 - Bottom-right video: `absolute right-6 md:right-10 bottom-8 md:bottom-10`
-

Dependencies (package.json)

代码块

```
1  {
2    "dependencies": {
3      "lucide-react": "^0.344.0",
4      "react": "^18.3.1",
5      "react-dom": "^18.3.1"
6    },
7    "devDependencies": {
8      "@vitejs/plugin-react": "^4.3.1",
9      "autoprefixer": "^10.4.18",
10     "postcss": "^8.4.35",
11     "tailwindcss": "^3.4.1",
12     "typescript": "^5.5.3",
13     "vite": "^5.4.2"
14   }
15 }
```