


EEE 304, HW 5

Problem 1:

For the feedback system shown below, compute the transfer functions u/r , u/d , y/r , y/d .



$$\frac{u(s)}{r(s)} = \frac{C}{1+CP}, \quad \frac{u(s)}{d(s)} = \frac{-CP}{1+CP}, \quad \frac{y(s)}{r(s)} = \frac{PC}{1+PC}, \quad \frac{y(s)}{d(s)} = \frac{P}{1+PC}$$

Problem 2: (Low Bandwidth Controller)

For the feedback system of Problem 1, suppose $P(s) = 10/(0.3s + 1)$.

- When $C(s) = K$, design K so that the loop crossover frequency (i.e., ω : $|P(j\omega)C(j\omega)| = 1$) is 0.8rad/s. What is the contribution of a constant unit disturbance to the output?
- When $C(s) = K(Ts + 1)/s$, design K, T so that the crossover frequency is 0.8rad/s and the phase margin (i.e., the difference between the loop angle and -180 at the crossover frequency, $\angle P(j\omega_c)C(j\omega_c) + 180$) is at least 60° . What is the contribution of a constant unit disturbance to the output?

Verify in MATLAB, using `step(feedback(P,K),feedback(P,C))`

$$a. \quad \omega_c = 0.8: |P(j\omega_c)C(j\omega_c)| = 1 \Rightarrow \left| \frac{10K}{\sqrt{1 + (0.3\omega_c)^2}} \right| = 1 \Rightarrow |K| = 0.103$$

$K > 0$ for stability ($\angle C + \angle P > -180$)

$$y_d(s) = \frac{P}{1+PC} d(s) = \frac{10}{0.3s + 10K + 1} \frac{1}{s} = \frac{-4.93}{s + 6.77} + \frac{4.93}{s} \Rightarrow y_d(t) = 4.93(1 - e^{-6.77t})U(t)$$

$$\Rightarrow y_{d,ss} = \lim_{t \rightarrow \infty} y_d(t) = \left. \frac{P}{1+PC} \right|_{s=0} = 4.93$$

b. $\omega_c = 0.8: \angle(1/s) + \angle P = -103.5^\circ > -120^\circ$

$\Rightarrow T = 0$ (no zero is needed, the controller is an integrator)


$$\omega_c = 0.8: |P(j\omega_c)C(j\omega_c)| = 1 \Rightarrow \left| \frac{10K}{\omega_c \sqrt{1 + (0.3\omega_c)^2}} \right| = 1 \Rightarrow |K| = 0.082$$

$K > 0$ for stability ($\angle C + \angle P > -180$)

$$C = \frac{0.082}{s}$$

$$y_d(s) = \frac{P}{1+PC} d(s) = \frac{10s}{0.3s^2 + s + 10K} \frac{1}{s} = \frac{10}{0.3s^2 + s + 0.82} = \frac{-7.29}{s + 1.85} + \frac{7.29}{s + 1.48}$$

$$\Rightarrow y_d(t) = \left\{ -7.29e^{-1.85t} + 7.29e^{-1.48t} \right\} U(t) \Rightarrow y_{d,ss} = \lim_{t \rightarrow \infty} y_d(t) = \left. \frac{P}{1+PC} \right|_{s=0} = 0$$



Problem 3: (High Bandwidth Controller)

For the feedback system of Problem 1, suppose $P(s) = 1/(0.3s + 1)$.

- When $C(s) = K$, design K so that the loop crossover frequency (i.e., $w: |P(jw)C(jw)| = 1$) is 18rad/s. What is the contribution of a constant unit disturbance to the output?
- When $C(s) = K(Ts + 1)/s$, design K, T so that the crossover frequency is 18rad/s and the phase margin (i.e., the difference between the loop angle and -180 at the crossover frequency, $\angle P(jw_c)C(jw_c) + 180$) is at least 60° . What is the contribution of a constant unit disturbance to the output?

Verify in MATLAB, using `step(feedback(P,K),feedback(P,C))`

$$\text{a. } \omega_c = 18: |P(j\omega_c)C(j\omega_c)| = 1 \Rightarrow \left| \frac{K}{\sqrt{1 + (0.3 \cdot 18)^2}} \right| = 1 \Rightarrow |K| = 5.49$$

$K > 0$ for stability ($\angle C + \angle P > -180$)

$$y_d(s) = \frac{P}{1+PC} d(s) = \frac{1}{0.3s + 6.49} \frac{1}{s} = \frac{-0.154}{s + 2.16} + \frac{0.154}{s} \Rightarrow y_d(t) = 0.154(1 - e^{-2.16t})U(t)$$

$$\Rightarrow y_{d,ss} = \lim_{t \rightarrow \infty} y_d(t) = \left. \frac{P}{1+PC} \right|_{s=0} = 0.154$$

$$\text{b. } \omega_c = 18: \angle C + \angle P = -170^\circ + \angle(Ts + 1) = -180 + PM = -120^\circ$$

$$\Rightarrow T = \tan(50^\circ) / 18 = 0.066$$

$$\omega_c = 1: |P(j\omega_c)C(j\omega_c)| = 1 \Rightarrow \left| \frac{K(\sqrt{1 + (0.066\omega_c)^2})}{\omega_c \sqrt{1 + (0.3\omega_c)^2}} \right| = 1 \Rightarrow |K| = 1/0.016 = 63$$

$K > 0$ for stability ($\angle C + \angle P > -180$)

$$C = \frac{4.2s + 63}{s}$$

$$y_d(s) = \frac{P}{1+PC} d(s) = \frac{s}{0.3s^2 + 5.2s + 63} \frac{1}{s} = \frac{-0.14j}{s + 8.67 - 11.7j} + \frac{0.14j}{s + 8.67 + 11.7j}$$

$$\Rightarrow y_d(t) = 2\text{Re}\{-0.14je^{-8.67t} e^{11.7jt}\}U(t) \Rightarrow y_{d,ss} = \lim_{t \rightarrow \infty} y_d(t) = \left. \frac{P}{1+PC} \right|_{s=0} = 0$$

