

Doubly Linked List

C Program to delete node from Doubly Linked List

```
#include <stdio.h>

#include <stdlib.h>

struct node {
    int data;
    struct node * prev;
    struct node * next;
}*head, *last;

void createList(int n);
void displayList();
void deleteFromBeginning();
void deleteFromEnd();
void deleteFromN(int position);
void main()
{
    int n, data, choice=1;

    head = NULL;
    last = NULL;

    while(choice != 0)
    {

        printf("DOUBLY LINKED LIST PROGRAM\n");
```

```
printf("1. Create List\n");
printf("2. Delete node - from beginning\n");
printf("3. Delete node - from end\n");
printf("4. Delete node - from N\n");
printf("5. Display list\n");
printf("0. Exit\n");
printf("Enter your choice : ");

scanf("%d", &choice);

switch(choice)
{
    case 1:
        printf("Enter the total number of nodes in list: ");
        scanf("%d", &n);
        createList(n);
        break;
    case 2:
        deleteFromBeginning();
        break;
    case 3:
        deleteFromEnd();
        break;
    case 4:
```

```
        printf("Enter the node position which you want to delete: ");
        scanf("%d", &n);
        deleteFromN(n);
        break;
    case 5:
        displayList();
        break;
    case 0:
        break;
    default:
        printf("Error! Invalid choice. Please choose between 0-5");
}
```

```
    printf("\n\n\n\n\n");
}
```

```
getch();
}
```

```
void createList(int n)
```

```
{
    int i, data;
    struct node *newNode;
```

```
    if(n >= 1)
    {
```

```
head = (struct node *)malloc(sizeof(struct node));
```

```
printf("Enter data of 1 node: ");
```

```
scanf("%d", &data);
```

```
head->data = data;
```

```
head->prev = NULL;
```

```
head->next = NULL;
```

```
last = head;
```

```
for(i=2; i<=n; i++)
```

```
{
```

```
    newNode = (struct node *)malloc(sizeof(struct node));
```

```
    printf("Enter data of %d node: ", i);
```

```
    scanf("%d", &data);
```

```
    newNode->data = data;
```

```
    newNode->prev = last;
```

```
    newNode->next = NULL;
```

```
    last->next = newNode;
```

```
    last = newNode;    }
```

```

        printf("\nDOUBLY LINKED LIST CREATED SUCCESSFULLY\n");
    }
}

void deleteFromBeginning()
{
    struct node * toDelete;

    if(head == NULL)
    {
        printf("Unable to delete. List is empty.\n");
    }
    else
    {
        toDelete = head;

        head = head->next;
        if (head != NULL)
            head->prev = NULL;

        free(toDelete);

        printf("SUCCESSFULLY DELETED NODE FROM BEGINNING OF THE LIST.\n");
    }
}

void deleteFromEnd()
{
    struct node * toDelete;

```

```

if(last == NULL)
{
    printf("Unable to delete. List is empty.\n");
}
else
{
    toDelete = last;

    last = last->prev;
    if (last != NULL)
        last->next = NULL;

    free(toDelete);
    printf("SUCCESSFULLY DELETED NODE FROM END OF THE LIST.\n");
}
}

void deleteFromN(int position)
{
    struct node *current;
    int i;

    current = head;
    for(i=1; i<position && current!=NULL; i++)
    {
        current = current->next;
    }
}

```

```

    }

    if(position == 1)
    {
        deleteFromBeginning();
    }
    else if(current == last)
    {
        deleteFromEnd();
    }
    else if(current != NULL)
    {
        current->prev->next = current->next;
        current->next->prev = current->prev;

        free(current);

        printf("SUCCESSFULLY DELETED NODE FROM %d POSITION.\n", position);
    }
    else
    {
        printf("Invalid position!\n");
    }
}

void displayList()
{

```

```
struct node * temp;

int n = 1;

if(head == NULL)
{
    printf("List is empty.\n");
}
else
{
    temp = head;
    printf("DATA IN THE LIST:\n");

    while(temp != NULL)
    {
        printf("DATA of %d node = %d\n", n, temp->data);

        n++;
        temp = temp->next;
    }
}
```