Definition of Done

Confluence page version 5 · Copy for release v1.0.0 · October 24, 2026

A Jira story is finished only when it meets all items on this list. Move the story to "Done" only after the product owner checks the list.

> This list applies to the user stories for the tool. Sprint 0 tasks (Confluence pages, the Miro board, and Jira stories) are plan tasks. A plan task is done when the product owner reviews it and agrees with it.

Checklist for all stories

☐ The work is on its own branch. The branch name starts with the Jira key (for example, SRG-7-read-tickets).
☐ Each commit message starts with the Jira key, and each commit holds only the work of that ticket (D39).
☐ The code is merged into the main branch by a pull request **before** the ticket moves to Done (D39).
☐ All CI checks pass (tests, style check, and secret scan).
☐ All unit tests pass.
☐ The product owner checked the acceptance criteria.
☐ The repository has no secrets (API keys, tokens, or webhook links).
☐ The README is correct for the new function.
☐ If the ticket changes a rule, its rule page (RAG Rules or AI Guardrails) is updated in the same ticket (D39).
☐ The pull request lists its decisions, and each one is in the Decision Log (D39).
☐ New risks or issues are in the RAID Log.
☐ Each Jira status move is checked in Jira before the work goes on (L13).

Extra item for AI stories

An AI story changes the prompt, the data that goes to Claude, the API call, or the summary output.

☐ The AI evaluation set passes before the ticket goes to Review, not after the merge (L14).
☐ The AI runs once on real data in the same sprint, and its answer passes all checks (L15).
☐ Each API feature in the call is checked against the current documentation for the model in config.yaml (L16).
☐ Each warning states its reason, so a failure can be seen without a new run (L14, L16).

Extra items for each output format

☐ All text from Jira is escaped in the output (Lessons Learned L03).
☐ The tests check the form of the output (for example, the cells in each table row), not only that it exists (L02).
☐ A test uses a large week (40 or more tickets) (L04).

Sprint review checklist (D39)

☐ Each ticket is merged and Done, with its approval comment.
☐ The Decision Log has each decision of the sprint.
☐ The RAID Log is reviewed.
☐ The RAG Rules and AI Guardrails pages match the code.
☐ The README matches the tool.

☐ The Lessons Learned Log has each new finding.

Why each item is necessary

Item	Reason
Own branch with the Jira key	Jira shows the branch on the ticket. Each change links to its reason.
Jira key in each commit	Jira shows the commits on the ticket. A reviewer can trace the code to the story.
Pull request	The pull request is the review step. Nobody changes the main branch directly.
CI checks pass	The checks run automatically. They stop errors and secrets before the merge.
Unit tests pass	The tests show that the new code works and that old functions still work.
Product owner checked	The product owner sees each part of the tool before it is done. This gives the product owner real knowledge of the tool.
No secrets	The repository is public. A secret in a public repository is a security risk.
README is correct	A reviewer reads the README first. It must agree with the tool.
Decision Log is complete	The log keeps the reasons for each decision, for reviews and interviews.
RAID Log is complete	New risks and issues are visible at the next sprint review.
AI evaluation set passes	Unit tests do not check the quality of the AI summary. The evaluation set does.

Related pages

- Definition of Ready
- Decision Log
- Project Charter