

MULTIMEDIA NETWORK:

The screenshot displays a network simulation environment. On the left, a physical network diagram shows a '2960-24T Switch0' connected to an 'ISR4131 Router0'. The main window is titled 'Switch0' and shows the 'CLI' (Command Line Interface) tab. The CLI output displays the following information:

```
IOS Command Line Interface

Power supply serial number : A2S1007032H
Model revision number      : B0
Motherboard revision number : B0
Model number               : WS-C2960-24TT-L
System serial number       : FOC1010K104
Top Assembly Part Number   : 800-27221-02
Top Assembly Revision Number : A0
Version ID                 : V02
CLEI Code Number           : COM3100BBA
Hardware Board Revision Number : 0X01

Switch Ports Model          SW Version        SW Image
-----
*  1 24 WS-C2960-24TT-L    15.0(2)SE4       C2960-LANBASEK9-M

Cisco IOS Software, C2960 Software (C2960-LANBASEK9-M), Version 15.0(2)SE4, RELEASE SOFTWARE (fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2013 by Cisco Systems, Inc.
Compiled Wed 24-Jun-13 02:49 by mmguyen

Press RETURN to get started!

%ALINK-5-CHANGED: Interface FastEthernet0/1, changed state to up
%ALINKPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up
%ALINK-5-CHANGED: Interface FastEthernet0/2, changed state to up
%ALINKPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/2, changed state to up

Switch#
Switch#show cdp neigh
Capability Codes: R - Router, T - Trans Bridge, B - Source Route Bridge
                  S - Switch, H - Host, I - ISM, r - Repeater, P - Phone
Device ID    Local Intrfce    Holdtime   Capability   Platform    Port ID
Switch  Fas 0/1      145        S            2960        Fas 0/1
Router  Fas 0/2      132        R            ISR4131     Gig 0/0/0
Switch#
```

The bottom of the interface shows a 'Realtime' status bar and a 'Simulate' button.