

DBMS – WEEK 4

MEESHO WOMEN'S FASHION DATABASE MANAGEMENT SYSTEM

Orders and Order_Details Management

1. Objective

1. To design the Orders and Order_Details tables.
2. To manage customer product orders.
3. To store order date, quantity, unit price and total amount.
4. To perform order insertion and modification operations.
5. To generate customer order history and customer-wise order summary reports.

2. Database Design

2.1 Orders Table

Attribute	Data Type	Constraint
Order_ID	INT	Primary Key
Customer_ID	INT	-
Order_Date	DATE	NOT NULL
Total_Amount	NUMBER(10,2)	NOT NULL

2.2 Order_Details Table

Attribute	Data Type	Constraint
Order_Detail_ID	INT	Primary Key
Order_ID	INT	-
Product_ID	INT	-
Quantity	INT	NOT NULL
Unit_Price	NUMBER(10,2)	NOT NULL
Subtotal	NUMBER(10,2)	NOT NULL

3. Create Orders Table

```
SQL> CREATE TABLE Meesho_Orders (  
2     Order_ID INT PRIMARY KEY,  
3     Customer_ID INT,  
4     Order_Date DATE NOT NULL,  
5     Total_Amount NUMBER(10,2) NOT NULL  
6 );
```

Table created.

4. Create Order_Details Table

```
SQL> CREATE TABLE Meesho_Order_Details (  
2     Order_Detail_ID INT PRIMARY KEY,  
3     Order_ID INT,  
4     Product_ID INT,  
5     Quantity INT NOT NULL,  
6     Unit_Price NUMBER(10,2) NOT NULL,  
7     Subtotal NUMBER(10,2) NOT NULL  
8 );
```

Table created.

5. Order Data Insertion

```
SQL> DESC Meesho_Order_Details;
```

Name	Null?	Type
ORDER_DETAIL_ID	NOT NULL	NUMBER(38)
ORDER_ID		NUMBER(38)
PRODUCT_ID		NUMBER(38)
QUANTITY	NOT NULL	NUMBER(38)
UNIT_PRICE	NOT NULL	NUMBER(10,2)
SUBTOTAL	NOT NULL	NUMBER(10,2)

```
SQL> INSERT INTO Meesho_Orders  
2 (Order_ID, Customer_ID, Order_Date, Total_Amount)  
3 VALUES  
4 (1001, 1, '20-SEP-2026', 999.00);
```

1 row created.

```
SQL>  
SQL> INSERT INTO Meesho_Orders  
2 (Order_ID, Customer_ID, Order_Date, Total_Amount)  
3 VALUES  
4 (1002, 2, '21-SEP-2026', 1499.00);
```

1 row created.

```
SQL>  
SQL> INSERT INTO Meesho_Orders  
2 (Order_ID, Customer_ID, Order_Date, Total_Amount)  
3 VALUES
```

6. Order_Details Data Insertion

```
SQL> INSERT INTO Meesho_Order_Details
  2 (Order_Detail_ID, Order_ID, Product_ID, Quantity, Unit_Price, Subtotal)
  3 VALUES
  4 (1, 1001, 101, 1, 999.00, 999.00);

1 row created.

SQL>
SQL> INSERT INTO Meesho_Order_Details
  2 (Order_Detail_ID, Order_ID, Product_ID, Quantity, Unit_Price, Subtotal)
  3 VALUES
  4 (2, 1002, 102, 1, 1499.00, 1499.00);

1 row created.

SQL>
SQL> INSERT INTO Meesho_Order_Details
  2 (Order_Detail_ID, Order_ID, Product_ID, Quantity, Unit_Price, Subtotal)
  3 VALUES
  4 (3, 1003, 103, 1, 799.00, 799.00);

1 row created.

SQL>
SQL> INSERT INTO Meesho_Order_Details
  2 (Order_Detail_ID, Order_ID, Product_ID, Quantity, Unit_Price, Subtotal)
  3 VALUES
  4 (4, 1004, 104, 1, 1299.00, 1299.00);

1 row created.

SQL>
```

```
SQL>
SQL> COMMIT;

Commit complete.

SQL> SELECT * FROM Meesho_Orders;

ORDER_ID CUSTOMER_ID ORDER_DAT TOTAL_AMOUNT
-----
1001      1 20-SEP-26      999
1002      2 21-SEP-26     1499
1003      3 22-SEP-26      799
1004      1 23-SEP-26     1299
1005      2 24-SEP-26      899

SQL> SELECT * FROM Meesho_Order_Details;

ORDER_DETAIL_ID  ORDER_ID  PRODUCT_ID  QUANTITY  UNIT_PRICE  SUBTOTAL
-----
1              1001      101         1         999        999
2              1002      102         1        1499       1499
3              1003      103         1         799        799
4              1004      104         1        1299       1299
5              1005      105         1         899        899
```

7. Order Modification Operations

```
SQL> UPDATE Meesho_Orders
  2 SET Total_Amount = 1099.00
  3 WHERE Order_ID = 1001;

1 row updated.

SQL>
SQL> COMMIT;

Commit complete.

SQL> SELECT * FROM Meesho_Orders
  2 WHERE Order_ID = 1001;

  ORDER_ID CUSTOMER_ID ORDER_DAT TOTAL_AMOUNT
-----
      1001           1 20-SEP-26          1099

SQL> UPDATE Meesho_Orders
  2 SET Order_Date = '23-SEP-2026'
  3 WHERE Order_ID = 1002;

1 row updated.

SQL>
SQL> COMMIT;

Commit complete.
```

8. Order_Details Modification

```
SQL> UPDATE Meesho_Order_Details
  2 SET Quantity = 2,
  3     Subtotal = 1998.00
  4 WHERE Order_Detail_ID = 1;

1 row updated.

SQL>
SQL> COMMIT;

Commit complete.
```

9. Customer Order History Report

```
SQL> SELECT
2     o.Order_ID,
3     o.Customer_ID,
4     o.Order_Date,
5     o.Total_Amount,
6     od.Product_ID,
7     od.Quantity,
8     od.Unit_Price,
9     od.Subtotal
10  FROM Meesho_Orders o
11  JOIN Meesho_Order_Details od
12  ON o.Order_ID = od.Order_ID
13  ORDER BY o.Order_Date;
```

ORDER_ID	CUSTOMER_ID	ORDER_DAT	TOTAL_AMOUNT	PRODUCT_ID	QUANTITY	UNIT_PRICE
SUBTOTAL						
1001 1998	1	20-SEP-26	1099	101	2	999
1003 799	3	22-SEP-26	799	103	1	799
1004 1299	1	23-SEP-26	1299	104	1	1299

ORDER_ID	CUSTOMER_ID	ORDER_DAT	TOTAL_AMOUNT	PRODUCT_ID	QUANTITY	UNIT_PRICE
SUBTOTAL						
1002 1499	2	23-SEP-26	1499	102	1	1499
1005 899	2	24-SEP-26	899	105	1	899

10. Customer-wise Order Summary

```
SQL> SELECT
2     Customer_ID,
3     COUNT(Order_ID) AS Total_Orders,
4     SUM(Total_Amount) AS Total_Amount
5  FROM Meesho_Orders
6  GROUP BY Customer_ID
7  ORDER BY Customer_ID;
```

CUSTOMER_ID	TOTAL_ORDERS	TOTAL_AMOUNT
1	2	2398
2	2	2398
3	1	799

11. Conclusion

The Orders and Order_Details tables were successfully designed and implemented for the Meesho Women's Fashion Database Management System. Order records were inserted and modified successfully. Customer order history and customer-wise order summary reports were also generated using SQL queries.