Week-14

Roll No: 241701007

Question 1
Correct
Flag question

You are transporting some boxes through a tunnel, where each box is a parallelepiped, and is characterized by its length, width and height.

The height of the tunnel 41 feet and the width can be assumed to be infinite. A box can be carried through the tunnel only if its height is strictly less than the tunnel's height. Find the volume of each box that can be successfully transported to the other end of the tunnel. Note: Boxes cannot be rotated.

the other end of the tunnel. Note: Boxes cannot be rotated.

Input Format

The first line contains a single integer n, denoting the number of boxes.
In lines follow with three integers on each separated by single spaces - length; width; and helght; which are length, width and height in feet of the i-th box.

Constraints

1

In 100

1

I length; width, height;

100

Output Format

For every box from the input which has a height lesser than 41 feet, print its volume in a separate line.

Sample Input 0

4

555

12 40

105 41

72 42

Sample Output 0

--

Explanation 0

The first box is really low, only 5 feet tall, so it can pass through the tunnel and its volume is $5 \times 5 \times 5 = 125$.

The second box is sufficiently low, its volume is $1 \times 2 \times 4 = 80$.

The third box is exactly 41 feet tall so it cannot park. The same can be said about the fourth it

```
#include<stdio.h>
 1
    int main()
 2
 3 . {
 4
        int t, i=0;
 5
         scanf("%d",&t);
 6
        while(i<t)
 7 .
         {
 8
            int h,l,w,vol;
             scanf("%d %d %d",&1,&w,&h);
 9
             if(h<41)
10
             {
11 .
                 vol=h*l*w;
12
                 printf("%d\n",vol);
13
14
             i++;
15
16
17
```

	Input	Expected	Got	
~	4	125	125	~
	5 5 5	80	80	
	1 2 40			
	10 5 41			
	7 2 42			

Question 2
orrect
Elan quartin

You are given n triangles, specifically, their sides a_i , b_i and c_i . Print them in the same style but sorted by their areas from the smallest one to the largest one. It is guaranteed that all the areas are different

The best way to calculate a volume of the triangle with sides a, b and c is Heron's formula:

```
S = \vec{O} p * (p-a) * (p-b) * (p-c) where p = (a+b+c)/2.
```

Input Format

First line of each test file contains a single integer n. n lines follow with a_i , b_i and c_i on each separated by single spaces.

Constraints

1 ≤ n ≤ 100

1 ± 0 ; b; c; ± 70

 $a_i + b_i > c_b$ $a_i + c_i > b_i$ and $b_i + c_i > a_i$

Output Format

Print exactly n lines. On each line print 3 integers separated by single spaces, which are a_i b_i and c_i of the corresponding triangle.

Sample Input 0

3

7 24 25

5 12 13

345

Sample Output 0

345

5 12 13

7 24 25

Explanation 0

The square of the first triangle is 84. The square of the second triangle is 30. The square of the third triangle is 6. So the sorted order is the reverse one.

```
1 #include<stdio.h>
 2
    #include<math.h>
 3
    typedef struct
 4 . {
 5
        int a;
        int b;
 6
        int c;
 7
 8
        int area;
 9
    }Triangle;
    int area(int a,int b, int c)
10
11 . {
12
        int p=(a+b+c)/3;
13
        return sqrt(p*(p-a)*(p-b)*(p-c));
14
15
    void sort(Triangle triangles[],int n)
16 . {
17
        for(int i=0;i<n-1;i++)
18 .
        {
19
             for(int j=0;j<n-i-1;j++)
20 .
             {
21
                 if(triangles[j].area>triangles[j+1].area)
22 .
                 {
23
                     Triangle temp=triangles[j];
24
                     triangles[j]=triangles[j+1];
25
                     triangles[j+1]=temp;
26
                 }
27
28
        }
29
30
    int main()
31 . {
32
        int n;
33
        scanf("%d",&n);
34
        Triangle triangles[n];
        for(int i=0;i<n;i++)
35
36 .
        {
37
             int a,b,c;
             scanf("%d %d %d",&a,&b,&c);
38
39
            triangles[i].a=a;
            triangles[i].b=b;
40
            triangles[i].c=c;
41
            triangles[i].area=area(a,b,c);
42
43
        }
44
        sort(triangles,n);
        for(int i=0;i<n;i++)
45
46 .
        {
47
             printf("%d %d %d\n",triangles[i].a,triangles[i].b,triangles[i].c);
48
        }
49
        return 0;
50
   }
```

	Input	Expected	Got	
~	3	3 4 5	3 4 5	~
	7 24 25	5 12 13	5 12 13	
	5 12 13	7 24 25	7 24 25	
	3 4 5			

Passed all tests! <