



Linux : Get your feet wet

Bridge Course '19

EE Dept IITB

24 July 2019

Outline

1 Introduction

- What is Linux
- Why Linux

2 Linux Basics

- Linux File System

3 Standard out and IO redirection

4 Git Basics

- Git - What Why?
- Git - Getting Started

5 Facilities Provided by EE Dept

Linux is a family of open source Unix-like operating systems based on the Linux kernel,
Typically packaged in a Linux distribution



Why Linux




Why Linux

- 1 Access to hardware - almost no restrictions


Why Linux

- 1 Access to hardware - almost no restrictions
- 2 Opensource - view code , modify , learn create

Why Linux

- 
- 1 Access to hardware - almost no restrictions
 - 2 Opensource - view code , modify , learn create
 - 3 Tailor Made - servers , fedora scientific

Why Linux

- 
- 1 Access to hardware - almost no restrictions
 - 2 Opensource - view code , modify , learn create
 - 3 Tailor Made - servers , fedora scientific
 - 4 Top 100 fastest supercomputers run linux

Why Linux

- 
- 1 Access to hardware - almost no restrictions
 - 2 Opensource - view code , modify , learn create
 - 3 Tailor Made - servers , fedora scientific
 - 4 Top 100 fastest supercomputers run linux
 - 5 Almost all tech giants funds linux development

Why Linux ctd..




Why Linux ctd..

1 Free


Why Linux ctd..

- 1 Free
- 2 Sabko Cadence chalana he


Why Linux ctd..

- 
- 1 Free
 - 2 Sabko Cadence chalana he
 - 3 Friends urge friends to use linux

Why Linux ctd..

- 
- 1 Free
 - 2 Sabko Cadence chalana he
 - 3 Friends urge friends to use linux
 - 4 Microsoft gives you windows. Linux gives you whole house

File System Hierarchy



Linux File System: Basic commands



Note

use : `man <command>` - to get the full details regarding any command

Linux File System: Basic commands

1 `ls` - list the files the current directory

Note

use : `man <command>` - to get the full details regarding any command

Linux File System: Basic commands

- 1 `ls` - list the files the current directory
- 2 `pwd` - print the working directory

Note

use : `man <command>` - to get the full details regarding any command

Linux File System: Basic commands

- 1 `ls` - list the files the current directory
- 2 `pwd` - print the working directory
- 3 `touch <file_name>` - create an empty file

Note

use : `man <command>` - to get the full details regarding any command

Linux File System: Basic commands

- 1 `ls` - list the files the current directory
- 2 `pwd` - print the working directory
- 3 `touch <file_name>` - create an empty file
- 4 `mkdir <dir_name>` - create a directory

Note

use : `man <command>` - to get the full details regarding any command

Linux File System: Basic commands

- 1 `ls` - list the files the current directory
- 2 `pwd` - print the working directory
- 3 `touch <file_name>` - create an empty file
- 4 `mkdir <dir_name>` - create a directory
- 5 `cd` - change directory

Note

use : `man <command>` - to get the full details regarding any command

Users, Group and Permissions

As we saw, everything can be treated as a file in linux.



Users, Group and Permissions

As we saw, everything can be treated as a file in linux.

Who has permissions to edit these files???



Users, Group and Permissions

As we saw, everything can be treated as a file in linux.

Who has permissions to edit these files???

For each file, linux assigns a set of attributes , some of these decides which users can Read , Write and (if possible)Execute the file. These attributes are called the file permissions.

Users, Group and Permissions

As we saw, everything can be treated as a file in linux.


Who has permissions to edit these files???

For each file, linux assigns a set of attributes , some of these decides which users can Read , Write and (if possible)Execute the file. These attributes are called the file permissions.

For each file, permissions are given in three categories.

Users, Group and Permissions

Owners assign permission on every file and directory



TODO

hint

OWNER|GROUP|ALL.

RWX-RWX-RWX

1 use `ls -l` command to find out permission of files given to you.


TODO


hint

OWNER|GROUP|ALL.

RWX-RWX-RWX

- 1 use `ls -l` command to find out permission of files given to you.
- 2 try executing
- 3 `./hello_perm.sh`
- 4 what do you see

- 
- 5 change permission the file using
 - 6 `chmod 111 hello_perm.sh`
 - 7 try executing now .



5 change permission the file using

6 `chmod 111 hello_perm.sh`

7 try executing now .

8 try to read file using

9 `cat hello_perm.sh`

10 `chmod 755 hello_perm.sh`

11 `cat hello_perm.sh`

Echo and output redirection

1 `echo "test"`

Echo and output redirection

- 1 `echo "test"`
- 2 `output redirection (w+), echo "to file" > test-file`

Echo and output redirection

- 1 `echo "test"`
- 2 `output redirection (w+), echo "to file" > test-file`
- 3 `appending (a+), echo "added new line" » test-file`

Echo and output redirection

- 1 `echo "test"`
- 2 output redirection (`w+`), `echo "to file" > test-file`
- 3 appending (`a+`), `echo "added new line" » test-file`
- 4 substitutions, `echo `pwd``

Echo and output redirection

- 1 `echo "test"`
- 2 output redirection (`w+`), `echo "to file" > test-file`
- 3 appending (`a+`), `echo "added new line" » test-file`
- 4 substitutions, `echo `pwd``
- 5 substitutions , `echo `cat test-file``
- 6 `echo "current directory is `pwd`"`

cut command

Cut command is used to extract one or more fields from a file with fields separated by a delimiter

use cat to view the contents of `examples/cut-input`



cut command

Cut command is used to extract one or more fields from a file with fields separated by a delimiter

use cat to view the contents of examples/cut-input

cut syntax - `cut -d '<delimiter>' -f<number> <filename>`

try printing out only the names

cut command

Cut command is used to extract one or more fields from a file with fields separated by a delimiter

use cat to view the contents of examples/cut-input

cut syntax - `cut -d '<delimiter>' -f<number> <filename>`

try printing out only the names

ans : `cut -d ',' -f1 cut-input`

what is the command to get only specialisation ?

cut command

Cut command is used to extract one or more fields from a file with fields separated by a delimiter

use cat to view the contents of examples/cut-input

cut syntax - `cut -d '<delimiter>' -f<number> <filename>`

try printing out only the names

ans : `cut -d ',' -f1 cut-input`

what is the command to get only specialisation ?

sort command

sort can be applied on any of the fields

sort command

sort can be applied on any of the fields

sort syntax - `sort -t '<delimiter>' -k<number> <filename>`

try sorting based the names

sort command

sort can be applied on any of the fields

sort syntax - `sort -t '<delimiter>' -k<number> <filename>`

try sorting based the names

ans : `sort -t ',' -k1`

what is the command to get only specialisation ?

sort command

sort can be applied on any of the fields

sort syntax - `sort -t '<delimiter>' -k<number> <filename>`

try sorting based the names

ans : `sort -t ',' -k1`

what is the command to get only specialisation ?

grep command

grep is used for finding occurrences

grep command

grep is used for finding occurrences

- 1 `grep <find> <filename>`
- 2 `grep pclab cut-input1`

grep command

grep is used for finding occurrences

- 1 `grep <find> <filename>`
- 2 `grep pclab cut-input1`
- 3 `grep -i variant`

grep command

grep is used for finding occurrences

❶ `grep <find> <filename>`

❷ `grep pclab cut-input1`

❸ `grep -i variant`

❹ `grep -i ee5 cut-input2 -c`

grep command

grep is used for finding occurrences

- 1 `grep <find> <filename>`
- 2 `grep pclab cut-input1`
- 3 `grep -i variant`
- 4 `grep -i ee5 cut-input2 -c`
- 5 `grep with regexes`

pipes(|) and the Unix philosophy

Pipe allows us to redirect the output of one command as the input of another command

common syntax - `command1 input-file | command2`

eg: `cat test-file | sort`

Q: write the command to get only the sorted names from file `cut-input2`
use `cat cut-input2` to inspect the file

pipes(|) and the Unix philosophy

Pipe allows us to redirect the output of one command as the input of another command

common syntax - `command1 input-file | command2`

eg: `cat test-file | sort`

Q: write the command to get only the sorted names from file `cut-input2`

use `cat cut-input2` to inspect the file

ans: `cut -d ',' -f1 cut-input2 | sort`

what is the command to sort all lines based on names for `EE1`?

pipes(|) and the Unix philosophy

Pipe allows us to redirect the output of one command as the input of another command

common syntax - `command1 input-file | command2`

eg: `cat test-file | sort`

Q: write the command to get only the sorted names from file `cut-input2`

use `cat cut-input2` to inspect the file

ans: `cut -d ',' -f1 cut-input2 | sort`

what is the command to sort all lines based on names for `EE1`?

`grep -i ee1 | sort -t ',' -k1`


Git - What Why?




Git - What Why?

- 1 Version control system
- 2 Manages source code history
- 3 Git is local

Git - What Why?


- 
- 1 Version control system
 - 2 Manages source code history
 - 3 Git is local
 - 4 Free and open source
 - 5 Fast and small



GitHub

- 1 Git-based repository hosting platform with over 26 million users

GitHub

- 
- 1 Git-based repository hosting platform with over 26 million users
 - 2 GitHub projects can be made public and every publicly shared code is freely open to everyone

GitHub

- 
- 1 Git-based repository hosting platform with over 26 million users
 - 2 GitHub projects can be made public and every publicly shared code is freely open to everyone
 - 3 You can have private projects as well

GitHub

- 
- 1 Git-based repository hosting platform with over 26 million users
 - 2 GitHub projects can be made public and every publicly shared code is freely open to everyone
 - 3 You can have private projects as well
 - 4 Can be used for issue tracking, documentation, and wikis

Other Git repo hosting platforms

- 1 AWS codecommit
- 2 Gitlab - you can also create your own git server using gitlab
- 3 Bitbucket
- 4 Sourceforge
- 5 ...
- 6 git.ee.iitb.ac.in

Getting Started




Getting Started

- 1 Install git
- 2 `sudo apt install git-all`

Getting Started

- 1 Install git
- 2 `sudo apt install git-all`
- 3 Check installation
- 4 `git --version`

Getting Started



Getting Started

- 1 Cloning a repository
- 2 `git clone repo-address`
- 3 Eg. `git clone`

`https://github.com/aswinpajayan/linux-workshop.git`

Getting Started

- 1 Cloning a repository
- 2 `git clone repo-address`

- 3 Eg. `git clone`

`https://github.com/aswinpajayan/linux-workshop.git`

- 4 Adding the changes
- 5 `git add updated-filename`

Getting Started



Getting Started

6 Committing changes

7 `git commit -m "Commit message" <3->`

Pushing changes to remote repository

Getting Started

6 Committing changes

7 `git commit -m "Commit message" <3->`

Pushing changes to remote repository

8 `git push origin branch-name`

Getting Started

6 Committing changes

7 `git commit -m "Commit message" <3->`

Pushing changes to remote repository

8 `git push origin branch-name`

9 Pulling latest changes from remote repository

10 `git pul origin branch-name`

Getting Started



Getting Started

11 Other useful commands

12 `git branch`

13 `git status`

14 `git diff filename`