VIKASITA KERALAM · ADMIN PLATFORM · WORKING BRIEF

Role Control and Designation

Workflows and requirements as implemented

A five-page summary of how roles, permissions, data access and designations actually work in the Vikasita Keralam repository today. It records what is built, where it lives, which rules the code enforces, and what must still be decided. It is not a proposal for new functionality and it changes nothing in the application.

DOCUMENT	EVIDENCE BASE	VERSION	SCOPE
5-page workflow brief	Source-code inspection	v1.0 · 13 Nov 2026	Roles, access, designations only

WHAT THIS DOCUMENT COVERS

01	02	03	04	05
Role control	**Assignment**	**Designation**	**Organisation**	**Requirements**
Create, edit and govern roles across seven permission modules.	Users, status, role selection and the access-evaluation chain.	Catalogue, parent rank and organisation-level filtering.	Levels, location and the data-scope vocabulary.	Requirement status, confirmed gaps and open decisions.

HOW STATUS IS RECORDED

Implemented in code	Prototype persistence	Not verified
Workflow and validation verified in the client source.	Logic is real, but records live in browser localStorage only.	No server-side API, query guard or database constraint was found.

VERIFIED SYSTEM MAP



Tabs are addressable by query string: ?tab=roles | users | designations | location. The mobile settings mirror reuses the same data model and storage keys.

Figure 1 — Where role and designation management lives

KEY FIGURES AT A GLANCE

7 permission modules	**29** module actions	**6** organisation levels
32 seeded designations	**6** built-in roles	**3** admin permissions

Scope boundary

This brief covers the Settings area only: Roles and Control, Designations, Users, Location, Organisational Charts and the mobile settings mirror. It does not document schemes, applications, applicant profiles or any other module except where a permission touches it.

01 · ROLE CONTROL

Roles: create, edit and govern access

Roles are the functional permission layer. Every role carries a name, a status, one or more allowed assignment levels, a module-by-action permission matrix and a separate set of administrative permissions. Data access is configured per module on the same record.




Figure 2 — Role lifecycle with validation gates

Verified workflow

#	Step and screen	What happens	Rule enforced
1	Roles list /admin/settings?tab=roles	Default tab of Role and Access Settings. Shows role count, filters, bulk selection, import and export.	Admin shell access required.
2	Create New Role /admin/settings_/new-role	Full-page editor. Edit mode is the same route with ?editRoleId=.	Role name is required.
3	Identity Name, Description, Status	Captures the role label, purpose and Active or Inactive state. Allowed assignment levels are selected here.	Duplicate names are rejected case-insensitively.
4	Module permissions 7 modules, 29 actions	Create, view, edit and delete per module; Schemes adds View List and View Details; Users adds View Teams; Request adds Assign and Respond.	At least one module permission. View is auto-added before Create, Edit or Delete.
5	Data access per module	Own, Below and Peers can be combined for each module; All selects the three levels.	Selections are stored in canonical order.
6	Administrative permissions	Role management, Access assignment and Access delegation are granted independently of module rights.	Optional; used for role authoring and delegation.
7	Save and assign Assign Users sheet	Saving writes the role, then opens user assignment with search, filters and multi-select.	Skip is allowed; the role still becomes assignable.

Source: src/components/admin/RoleAccessSettings.tsx, src/routes/admin.settings_.new-role.tsx, src/data/role-management.ts

Module permission catalogue

Module	Actions	Permission key
Applicant Profile	create · edit · view · delete	applicant_profile.view
Applications	view · create · edit · delete	applications.edit
Schemes	view_list · view_details · create · edit · delete	schemes.view_details
Roles	view · create · edit · delete	roles.manage
Designations	view · create · edit · delete	designations.edit
Users (party_workers)	view · create · edit · delete · view_teams	party_workers.view_teams
Request (help_desk)	view · assign_team_member · respond_reply	help_desk.assign_team_member

Source: permissionModules and permissionPrerequisites in src/data/party-workers.ts

Business rules the code enforces

- **Prerequisites cascade.** A role cannot hold Create, Edit or Delete without View; Schemes View Details requires View List. Removing View strips the dependants.
- **Built-in roles are protected.** State Admin, District Admin, Constituency Admin, Local Body Admin, Booth Admin and Party Worker are marked system and cannot be deleted; custom roles can be deactivated or deleted.
- **Deactivation is a guard, not a delete.** The role record and its users stay; the confirmation states that new assignments are blocked.
- **One role per user today.** The user record stores a single assignedRole string; there is no role-membership table.

02 · ASSIGNMENT AND EVALUATION

Assigning roles and evaluating access

Assignment connects a person to a role. Evaluation is the chain that should decide whether a request is allowed. In the repository the assignment side is complete in the client; the evaluation side is rendered and stored but was not verified as a server-enforced gate.



Steps A1-A3 and B1-B3 exist in the client. The module, action and data-scope gates (B4-B7) are rendered and stored, but no server-side enforcement was found in the repository.

Figure 3 — Assignment path and the access-evaluation chain

Data access vocabulary

Scope	Intended meaning	Today
Own records	Records created by or explicitly assigned to the signed-in user.	Default for every module.
Below my level	Records belonging to subordinate organisation units.	Selectable; not enforced in a query found.
Same level — peers	Records belonging to peer units at the same organisation level.	Selectable; not enforced in a query found.
Above my level	Records belonging to superior units.	Defined in the type; hidden from the desktop create-role grid.

Source: dataAccessOptions and RoleDataAccess in src/data/role-management.ts

Assignment rules

- **Single role.** The Assign Role screen writes one role per user; the picker also offers None, which leaves the user unassigned.
- **Per-user overrides.** The same screen carries a permission grid so an individual can be adjusted without creating a new role.
- **Status change is reviewed.** Moving a user between Active, Pending and Inactive opens an acknowledgement dialog before the record is written.
- **Bulk assignment.** Selecting several users applies one role to all of them; the users tab also exposes role and status filters.
- **Separate option list.** /admin/settings_/assign-role uses its own ROLE_OPTIONS labels (Admin, Sub Admin, Support Admin, Specific Role) rather than the permissionModules action ids. This is a consistency risk, not a verified runtime failure.

Confirmed limitation

Role, user and designation records are written to browser localStorage keys (vk-managed-roles, vikasita_managed_designations_v1, managed users). No backend API, database constraint or query-level data filter was found for these records. Access must therefore be treated as a client prototype until server enforcement is implemented.

03 · DESIGNATION MANAGEMENT

Designations: organisational identity

A designation describes where a person sits in the party structure. It is deliberately separate from the role: a designation does not grant module permissions unless a role does. The Designations tab maintains the catalogue and the rank order used when a user is created.




Figure 4 — Designation lifecycle and rank derivation

Seeded designation catalogue

Organisation level	Seeded	Designations
State	7	President, Vice President, General Secretary, General Secretary (Organisation), Secretary, Treasurer, Executive Member
Region	4	President, In-charge, Coordinator, Cluster In-charge
Organisational District	7	President, Vice President, General Secretary, General Secretary (Organisation), Secretary, Treasurer, Executive Member
Mandalam	6	President, Vice President, General Secretary, Secretary, Treasurer, Committee Member
Area	4	Kendra Convener, Area Coordinator, Area In-charge, Area Committee Member
Booth	4	President, Secretary, Committee Member, Worker

Source: DEFAULT_DESIGNATIONS_BY_LEVEL in src/components/admin/RoleAccessSettings.tsx. A second seeded list, partyDesignations, exists in src/data/party-workers.ts with slightly different labels and counts.

Designation compared with role

Dimension	Role	Designation
Purpose	Functional system access	Organisational identity
Grants module permissions	Yes, by design	No, unless a role is also assigned
Linked to organisation level	Allowed assignment levels	One level per designation
Drives data visibility	Through per-module data scope	Only by placing the user in a unit
Deactivation effect	Blocks new assignments	Hides the option for new users

Designation rules

- **Parent sets rank.** Rank is derived from the parent designation (parent rank + 1); reorder actions move a record up or down the list.
- **Level filters the picker.** Creating a user shows only designations for the selected organisation level; changing the level resets the designation.
- **Validation is explicit.** Saving a user with a designation from another level is rejected with the message that the designation does not belong to the selected organisation level.
- **Status is controlled.** Designations are Active or Disabled and can be bulk enabled, disabled or deleted.

Storage today

Designations are written to browser localStorage (vikasita_managed_designations_v1); custom organisation levels use vk-custom-organisation-levels. No server-side designation table was found.

04 · REQUIREMENTS AND GAPS

Requirements catalogue and confirmed gaps

The table records the requirement, its priority, what the repository actually implements and the file that evidences it. Status words are used strictly: implemented means verified in the client; stored means the value is written but not enforced; not verified means no implementation was found.

Requirements

ID	Requirement	Priority	Status	Evidence
FR-01	View the role catalogue with search, filters and counts	High	Implemented	RoleAccessSettings, Roles tab
FR-02	Create a custom role from a full-page editor	High	Implemented	admin.settings_.new-role.tsx
FR-03	Edit an existing role and its permission matrix	High	Implemented	RoleEditorDialog
FR-04	Activate, deactivate, duplicate or delete a role	Medium	Implemented	RoleAccessSettings handlers
FR-05	Assign 7 modules and 29 actions to a role	High	Implemented	permissionModules
FR-06	Enforce permission prerequisites automatically	High	Implemented	withPrerequisites, togglePermission
FR-07	Configure data access per module	High	Stored	dataAccess on ManagedRole
FR-08	Grant administrative permissions separately	Medium	Implemented	administrativePermissionOptions
FR-09	Assign one role to one or many users	High	Implemented	admin.settings_.assign-role.tsx
FR-10	Maintain the designation catalogue	High	Implemented	managed designations, localStorage
FR-11	Derive and reorder designation rank	Medium	Implemented	RoleAccessSettings handlers
FR-12	Filter designations by organisation level	High	Implemented	admin.settings_.new-user.tsx
FR-13	Enforce permissions on the server	Critical	Not verified	no API or route guard found
FR-14	Record an access audit trail	High	Not implemented	no audit store in the codebase

Confirmed gaps

Gap	Impact	Priority	Recommendation
No server-side RBAC	Client controls can be bypassed	Critical	Enforce module and action checks in the API
Data scope not applied to queries	Visibility rules are advisory	Critical	Apply own, below and peer filters in data access
No audit log	Access changes cannot be traced	High	Record actor, target, before and after values
Single role per user	Combined duties need overrides	Medium	Decide whether multi-role is required
Two designation seed lists	Labels and counts differ by screen	Medium	Consolidate on one catalogue

Decisions required before build

- Should a user hold multiple roles, or is one role plus per-user overrides the intended model?
- Does “Below my level” include every descendant unit or only direct children, and does “peers” mean one unit or the whole level?
- Should a designation ever imply a default role, or must the two remain strictly independent?
- Which persistence target replaces localStorage, and who owns migration of existing role and designation records?

Prepared from direct inspection of the repository. No application code, role, designation, mapping, API or database record was modified by this document.