

Lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem
 ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
 lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem
 ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
 lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem
 ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum

lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum

Lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum

Lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum

Lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum lorem ipsum lorem ipsum
lorem ipsum lorem ipsum lorem ipsum

3. PROPOSED APPROACH

To retrieve a list of human and bot Twitter accounts, we compiled a list of 113 users with an approximately even split between humans and bots. We then retrieved data for their followers, and their followers' followers, leaving us with 9,025 Twitter users, which we then classified.

After discovering a number of inconsistencies with the overall BotOrNot score, we determined that more information was required for automated analysis of Twitter accounts. Using unsupervised machine learning to cluster accounts let us successfully organize a large number of accounts into separate categories, which we manually classified and verified. As described by Bessi and Ferrera[2], we retrieved the most important descriptors of bots: whether they're using the default appearance, their retweet-to-tweet ratio, and others, in addition to the *BotOrNot* score and category scores. However, our best results were found when simply clustering based on the *BotOrNot* category scores.

To classify each cluster, we set up a basic Python script using Selenium that displayed a sample set of Twitter feeds, and allowed a user to submit a category for the user[TODO: What categories?]. Based on the categories reported for the cluster, we could determine what type of Twitter account a user was likely to be. We then examined the average *BotOrNot* scores for these categories.

4. RESULTS & DISCUSSION

5. CONCLUSION

While some spambots use hashtags to make their tweets more visible, the vast majority of bots don't directly interact with human users. Instead, they're more likely to simply follow a large number of users, and either pass as human or hope that the user follows them back.

5.1 Further Work

Although we were able to manually identify advertising links, when we retrieved data on individual Tweets we did not expand Twitter's shortened URL format. This made media, such as photos, appear identical to other links, since Twitter represents media as URLs. In addition, the sample size for manual classification was small by necessity; setting up a web service such as Mechanical Turk to crowdsource this account classification would improve analysis and clustering.

6. REFERENCES

- [1] S. Aral and D. Walker. Creating social contagion through viral product design: A randomized trial of peer influence in networks. *Management Science*, 57(9):1623–1639, 2011.
- [2] A. Bessi and E. Ferrara. Social bots distort the 2016 U.S. Presidential election online discussion. *First Monday*, 21(11), 2016.
- [3] Z. Chu, S. Gianvecchio, H. Wang, and S. Jajodia. Detecting automation of twitter accounts: Are you a human, bot, or cyborg? *IEEE Trans. Dependable Secur. Comput.*, 9(6):811–824, Nov. 2012.
- [4] C. A. Davis, O. Varol, E. Ferrara, A. Flammini, and F. Menczer. Botornot: A system to evaluate social bots. *CoRR*, abs/1602.00975, 2016.
- [5] J. P. Dickerson, V. Kagan, and V. S. Subrahmanian. Using sentiment to detect bots on twitter: Are humans more opinionated than bots? In *2014 IEEE/ACM International Conference on Advances in Social Networks Analysis and Mining (ASONAM 2014)*, pages 620–627, Aug 2014.
- [6] J. Ratkiewicz, M. Conover, M. Meiss, B. Goncalves, A. Flammini, and F. Menczer. Detecting and tracking political abuse in social media, 2011.
- [7] G. Stringhini, C. Kruegel, and G. Vigna. Detecting spammers on social networks. In *Proceedings of the 26th Annual Computer Security Applications Conference, ACSAC '10*, pages 1–9, New York, NY, USA, 2010. ACM.
- [8] C. Xiao, D. M. Freeman, and T. Hwa. Detecting clusters of fake accounts in online social networks. In *Proceedings of the 8th ACM Workshop on Artificial Intelligence and Security, AISec '15*, pages 91–101, New York, NY, USA, 2015. ACM.

APPENDIX

A. CONTRIBUTIONS

Alic Szecsei provided data retrieval methods for Twitter accounts, programmed the machine learning clustering, and wrote the data analysis.

Willem DeJong programmed BotOrNot score retrieval methods, retrieved data for Twitter accounts to store in SQL databases, and created many of the graphs and charts.