

# Exploring the Impact of Decision Tree Depth

Alic Szecsei  
University of Iowa  
alic-szecsei@uiowa.edu

Diego Castaneda  
University of Iowa  
diego-castaneda@uiowa.edu

Willem DeJong  
University of Iowa  
willem-dejong@uiowa.edu

## ABSTRACT

Lobortis scelerisque fermentum dui faucibus in ornare quam viverra orci sagittis eu volutpat odio facilisis mauris sit amet massa vitae tortor condimentum lacinia quis vel eros donec ac odio tempor orci dapibus ultrices in iaculis nunc sed augue lacus viverra vitae congue eu consequat ac felis donec et odio pellentesque diam volutpat commodo sed egestas egestas fringilla phasellus faucibus scelerisque eleifend donec pretium vulputate sapien nec sagittis aliquam malesuada bibendum arcu vitae elementum curabitur vitae nunc sed velit dignissim sodales ut eu sem integer vitae justo eget magna fermentum iaculis eu non diam phasellus vestibulum lorem sed risus ultricies tristique nulla aliquet enim tortor at auctor urna nunc id cursus metus aliquam eleifend mi in nulla posuere sollicitudin aliquam ultrices sagittis orci a scelerisque purus semper eget duis at tellus at urna condimentum mattis pellentesque id nibh tortor id aliquet lectus proin nibh nisl condimentum id venenatis a condimentum vitae sapien pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas sed tempus urna et pharetra pharetra massa massa ultricies mi quis hendrerit dolor magna eget est lorem ipsum dolor sit amet consectetur adipiscing elit pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas integer eget aliquet nibh praesent tristique magna sit amet purus gravida quis blandit turpis cursus in hac habitasse platea dictumst quisque sagittis purus sit amet volutpat consequat mauris nunc congue nisi vitae suscipit tellus mauris a diam maecenas sed enim ut sem viverra aliquet eget sit amet tellus cras.

## CCS CONCEPTS

• **Computing methodologies** → **Machine learning**; *Supervised learning by classification*; *Classification and regression trees*; Cross-validation.

## KEYWORDS

decision trees, model selection

## 1 BACKGROUND AND MOTIVATION

Machine learning algorithms fall into one of two categories: classification and regression. In regression, input data is consumed and transformed by a function which can produce values along a numeric range; in classification, data is categorized into a finite number of possible values, and machine learning algorithms seek only to label data sets. These classification problems can use both numeric and categorical data attributes. For purely categorical data, decision trees are a way to build machine learning algorithms that are understandable by both humans and machines. Rather than a sort of “black box” in which numbers are passed in and answers are returned, there is a logical tree hierarchy that is familiar to anyone who has played the game Twenty Questions.

Decision trees require both a way to construct them, and a way to use them to categorize data. This categorization is a trivial tree traversal, and so many of the innovations regarding decision trees has to do with their construction. Most decision tree construction algorithms use a two-phase approach: first a *growing* phase, followed by a *pruning* phase. In the growing phase, the decision tree is built out, trying to fit the provided training data as closely as possible. To combat over-fitting, the pruning phase determines which branches of the tree are too “noisy” using  $\chi^2$  tests and removes them.

Additionally, decision tree models can be constrained by size to combat overfitting. Russell and Norvig [6] showcase an implementation of restricting a decision tree to be beneath a maximum size by generating the tree in breadth-first fashion, and stopping when the maximum number of nodes has been reached. As stated in Garofalakis, Hyun, Rastogi, and Shim [3], there is no point in creating a branch when it is guaranteed to be pruned later.

The amount of pruning which occurs is heavily dependent on the data set chosen. As such, the exact values which optimize our trained decision trees are relatively unimportant. However, our goal was to examine how impactful depth-based pruning was, and how much it assisted with reducing overfitting.

## 2 METHODS

Our first step was selecting datasets to use as the foundation for our programs. We used four UCI data sets [2]:

- (1) MUSHROOMS, a dataset to classify mushrooms as edible or inedible
- (2) BALANCE, a dataset to classify whether or not a scale with objects of varying weights and distances was balanced
- (3) CARS, a dataset of car evaluations
- (4) TICTACTOE, a dataset of Tic-Tac-Toe board states.

The foundation of our decision tree algorithm was the one provided by Russell and Norvig [6] which, in turn, is based on the ID3 algorithm [5].

A two-program approach was used: first, a decision tree generator was developed, called dt1. This program would take in a flag to determine which of our data sets was represented by the input. As the ordering of attributes and classes was inconsistent between datasets, this allowed us to significantly simplify the process of importing data.

A second program, classify, was used to classify data using a decision tree generated from dt1. To communicate a decision tree between these two programs, a JSON representation of the decision tree was used. This data format allowed us to produce human-readable representations of the decision trees, which we could use as a sanity check during development.

---

**Function** DecisionTreeLearning(*examples*, *attributes*, *parent\_examples*, *depth*)

---

```

1 if examples is empty then
2   return Plurality-Value(parent_examples)
3 else if depth = 0 then
4   return Plurality-Value(examples)
5 else if all examples have the same classification c then
6   return a leaf node c
7 else if attributes is empty then
8   return Plurality-Value(examples)
9 end
10  $A \leftarrow \operatorname{argmax}_{a \in \text{attributes}} \text{Importance}(a, \text{examples})$ ;
11 tree  $\leftarrow$  a new decision tree with root test A;
12 foreach value  $v_k$  of A do
13   exs  $\leftarrow \{e : e \in \text{examples and } e.A = v_k\}$ ;
14   subtree  $\leftarrow$ 
      DecisionTreeLearning(exs, attributes - A, examples, depth - 1);
15   add a branch to tree with label (A =  $v_k$ ) and subtree
      subtree;
16 end
17 return tree;

```

---

Finally, we used Python to generate data for  $k$ -fold cross-validation for both our decision tree program as well as the decision tree algorithm provided by scikit-learn [4]. This provided a simple baseline for our experimentation.

We then ran each of our datasets through the **DecisionTree-Learning** algorithm with maximum depths ranging from 1 to 10 and performed  $k$ -fold cross-validation to determine error rates, with  $k = 4$ . As we noticed that subsequent experiments could obtain dramatically varying error rates, we repeated each of these experiments for 100 trials, to determine both average error rates and the variance of these error rates.

### 3 RESULTS

The results of our experimentation varied quite a bit between datasets. For MUSHROOMS in particular, our algorithm was able to achieve significantly greater accuracy than scikit-learn for smaller maximum depth constraints. However, for other datasets, such as TICTACTOE, our algorithm produced consistently more error-prone results at all depth values, as seen in Figure 1.

### 4 DISCUSSION

We were surprised at the discrepancies between our algorithm and the one provided by scikit-learn, as we expected both decision tree algorithms to produce similar results. While an effort was made to produce similar constraints on both algorithms (scikit-learn was used with the “entropy” heuristic, as well as the same tree depth constraint), there were a few differences that we were unable to resolve. First, scikit-learn uses “an optimised version of the CART [1] algorithm.” Additionally, scikit-learn cannot be used with categorical data. To get around this restriction, we used one-hot encoding for the scikit-learn algorithm.




Figure 1: Error for our algorithm versus scikit-learn on the Tic-Tac-Toe dataset




Figure 2: The error on training and validation data for the MUSHROOMS data set

### ACKNOWLEDGMENTS


This work was supported in part by the University of Iowa.

### REFERENCES


- [1] Leo Breiman, J. H. Friedman, R. A. Olshen, and C. J. Stone. 1984. *Classification and Regression Trees*. Wadsworth.
- [2] Dheeru Dua and Casey Graff. 2017. UCI Machine Learning Repository. <http://archive.ics.uci.edu/ml>
- [3] Minos Garofalakis, Dongjoon Hyun, Rajeev Rastogi, and Kyuseok Shim. 2000. Efficient Algorithms for Constructing Decision Trees with Constraints. In *Proceedings of the Sixth ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD '00)*. ACM, New York, NY, USA, 335–339. <https://doi.org/10.1145/347090.347163>
- [4] F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. 2011. Scikit-learn: Machine Learning in Python. *Journal of Machine Learning Research* 12 (2011), 2825–2830.
- [5] J. R. Quinlan. 1986. Induction of decision trees. *Machine Learning* 1, 1 (01 Mar 1986), 81–106. <https://doi.org/10.1007/BF00116251>
- [6] Stuart J. Russell and Peter Norvig. 2010. *Artificial intelligence: a modern approach* (3rd ed.). Prentice Hall.

### A ERRATA


## Exploring the Impact of Decision Tree Depth



**Figure 3: The error on training and validation data for the BALANCE data set**



**Figure 5: The error on training and validation data for the TICTACTOE data set**



**Figure 4: The error on training and validation data for the CARS data set**