

Modular responsive web design

Allowing responsive web modules to respond to custom criterias instead of only viewport size by implementing *element queries*

LUCAS WIENER lwiener@kth.se

Master's Thesis task specification

Supervisors at EVRY AB: Tomas Ekholm & Stefan Sennerö Supervisor at CSC: Philipp Haller Examiner: Mads Dam

Problem definition

By using CSS media queries developers can specify different rules for different viewport sizes. This is fundamental to create responsive web applications. If developers want to build modular applications by composing the application by smaller components (elements, scripts, styles, etc.) the media queries are no longer applicable. Modular components should be able to react and change style depending on the given size that the component has been given by the application, not the viewport size. The problem can be formulated as: Elements can not specify conditional style rules depending on their own size, or the size of any other element.

W3C¹ has unofficially stated that such feature would be infeasible to implement. Some problems with implementing element queries in CSS are:

- Circularity: The styling of elements depend on many factors (theoretically on all other elements in the layout tree). If elements can apply styles by criterias of other elements, it will be possible to create infinite loops of styling. The simplest example of this would be an element to set its width to 200 pixels if it is under 100 pixels wide. If the element is under 100 pixels wide, the new style will be applied to the element which would make the width of the element 200 pixels. If this element would have another rule that set its width to 50 pixels if it is wider than 150 pixels, there is an infinite loop of styling. Problems like this can probably be catched during CSS parsing, but there are so many combinations of style properties that could result in similar loops that it will add a lot of complexity to the language, both for implementers and users.
- **Performance:** Rendering engines typically perform selector matching and layout computations in parallel to achieve good performance. If element queries would be implemented, the rendering engines would need to first compute the layout of all elements in order to decide which selectors would conform to the element query conditions and then do a new layout computation, and so on until a stable state has been reached. Far worse, since selectors now depend on layout style, this cannot be done in parallel which impacts performance heavily.

Because of the problems, it is stated that such feature will not be implemented in the near future. So it is now up to the developers to implement this feature as a third-party solution. Efforts have been made by big players to create a robust implementation, with moderate success. Since all implementations have shortcomings, there is still no de facto solution that developers use and the problem remains unsolved.

¹World Wide Web Consortium (abbreviated W₃C) is the main international standards organization for the World Wide Web.

Objective

The main objective of my master's thesis is to develop a third-party implementation of element queries (or equivalent to solve the problem of modular responsive elements). To do this, I will need to research and understand all existing attempts and analyze the advantages and shortcomings of each approach. I will also need to be aware of the premises, such as browser limitations and specifications that need to be conformed. In addition, I will research the problems of implementing element queries natively to get a deeper understanding of how an official API would look like. There are many challenges along the way that will need to be researched and worked around. Examples of such subproblems that would need to be investigated are:

- How should circularity be handled? Should it be detected at runtime or parse time, and what should happen on detection?
- How can one listen to element dimension changes with without any native support?
- Can custom viewport elements such as *object* or *svg* be utilized to make regular media queries perform with respect to the elements?
- How can a custom API be crafted that will enable element queries and still conform to the CSS specification?
- If a custom API is developed, how would one make third-party modules (that uses media queries) work without demanding a rewrite of all third-party modules?

The scientific question to be answered is if it is possible to solve the problem without extending the current web standard. The hypothesis is that the problem can be solved in a reliable and performant way by crafting a third-party implementation. A reliable implementation should also enable existing responsive components to react to a specified criteria (parent container size for example) with no modifications to the components. The goal of the thesis should be considered fulfilled if a solution was successfully implemented or described, or if the problems hindering a solution are thoroughly documented.

Significance

Web developers are today limited to writing big applications in an entagled mess. In almost all other programming environments it is possible and encouraged to write applications in smaller parts (or modules). By creating modules that can be used in any context with well defined responsibilites and dependencies, developing applications is reduced to the task of simply configuring modules (to some extent). It is today possible to write the web client logic in a modular way in javascript. The desire of writing modular code can be shown by the popularity of frameworks that helps dividing up the client code into modules. The ever so popular frameworks Angular, Backbone, Ember, Web Components, requirejs, Browserify, Polymer, React and many more all have in common

that they embrace coding modular components. Many of these frameworks also help with dividing the HTML up into modules, creating small packages of style, markup and code. One of the biggest issues keeping the modules from being truly modular is that they cannot adapt to given sizes. This makes the modules either force the client to style them properly depending on viewport size, or not being responsive. Both options are undesirable for developing larger applications. A third option would be to make the modules context aware and style themselves according to the viewport, which defeats the purpose of modules (making them not reusable).

The last couple of years a lot of articles have been written about the problem and how badly we need element queries. As already stated, third-party implementation efforts have been made by small and big players, with moderate success. W3C keep getting requests and questions about it, but the answer seems to lean towards no. An organization called Responsive Issues Community Group (abbreviated RICG) have started an initial planning regarding element queries. However, things are moving slow and a draft about element queries use cases are still being made.

Solving this problem would push to web forward a big leap, enabling developers to create truly modular components. By studying the problem, identifying approaches and providing a third-party solution the community can take a step closer to solve the problem. If the hypothesis holds, developers will be able to use element queries in the near future, while waiting for W3C to make their verdict. The outcome of this thesis can also be helpful for W3C and others to get an overview of the problem and possibly get ideas how subproblems can be handled.

Literature study

Since the problem is relatively new and unique for the web, my main literature will be web articles and W3C mailing lists. There are many experienced individuals writing good articles about the problem and mostly discusses how an API can look like. The W3C mailing lists are a good resource to get insight into how the browser vendors view the problem. To investigate third-party implementation approaches, I will read the implementation attempts that I can find. To understand the issues with implementing the problem better, I will read books, scientific papers and articles covering how rendering engines work. To solve the circular problems of the third-part implementation I will read scientific papers and articles how other languages have solved similar problems. To make sure I fully understand responsive web development I will read books about the subject. To support my claims that modular development is a good thing, I will research scientific papers and books.

Current literature

This is the literature that I have so far.

Books

- Tim Kadlec. Implementing Responsive Design: Building sites for an anywhere, everywhere web. New Riders, 2012.
- Frain, Ben. Responsive Web Design with HTML5 and CSS3. Packt Publishing, 2012.

Scientific papers and reports

- Jerjas, Allan. Building Blocks of Responsive Web Design. KTH, 2013. http://kth.diva-portal.org/smash/get/diva2:699709/FULLTEXT01.pdf
- Tobias Sundqvist, Christoffer WÃ¥hlander. Applikationsutveckling i Responsive Web Design. LIU, 2013. http://liu.diva-portal.org/smash/get/diva2:628224/FULLTEXT01.pdf
- Christopher Grant Jones, Rose Liu, Leo Meyerovich, Krste Asanovic, Rastislav BodÃk. Parallelizing the Web Browser. Department of Computer Science, University of California, Berkeley, 2009. https://www.usenix.org/legacy/event/hotpar09/tech/full_papers/jones/jones_html/
- Calin Cas¸caval Seth Fowler Pablo Montesinos Ortego Wayne Piekarski Mehrdad Reshadi Behnam Robatmili Michael Weber Vrajesh Bhavsar. ZOOMM: A Parallel Web Browser Engine for Multicore Mobile Devices. Qualcomm Research Silicon Valley, 2013. http://instartlogic.com/resources/research_papers/mreshadi-zoomm-sigplan2013.pdf
- Alan Grosskurth, Michael W. Godfrey. Architecture and evolution of the modern web browser. David R. Cheriton School of Computer Science, University of Waterloo, Waterloo, ON N2L 3G1, Canada, 2006. http://plg.uwaterloo.ca/~migod/papers/2006/jss-browserRefArch.pdf
- Helen J. Wang, Chris Grier, Alexander Moshchuk, Samuel T. King, Piali Choudhury, Herman Venter. Microsoft Research, University of Illinois at Urbana-Champaign, University of Washington, 2009. https://www.usenix.org/legacy/event/sec09/tech/full papers/wang.pdf
- Lingjun Fan, Weisong Shi, Shibin Tang, Chenggang Yan2 Dongrui Fan. Chinese Academy of Sciences, Wayne State University, 2011. http://ieeexplore.ieee.org.focus.lib.kth.se/stamp/stamp.jsp?tp=&arnumber=6118943&tag=1

Articels

• Christopher Grant Jones, Rose Liu, Leo Meyerovich, Krste Asanovic, Rastislav Bodik. The Berkeley Par Lab: Progress in the Parallel Computing Landscape. Chapter 2, Parallelizing the Web Browser. Microsoft Research, The Berkeley

Par Lab, 2009. http://research.microsoft.com/en-us/um/redmond/about/collaboration/par-lab-book/chapter-2.pdf

- Carmen Badea, Mohammad R. Haghighat, Alexandru Nicolau, Alexander V. Veidenbaum. Towards Parallelizing the Layout Engine of Firefox. UC Irvine, Intel Corporation, 2010. https://www.usenix.org/legacy/event/hotpar10/tech/full_papers/Badea.pdf
- Tali Garsiel, Paul Irish. How Browsers Work: Behind the scenes of modern web browsers. html5rocks, 2011. http://www.html5rocks.com/en/tutorials/internals/howbrowserswork/
- Dave Hyatt. Layout and Rendering. The WebKit Open Source Project, 2007. http://www.webkit.org/projects/layout/index.html

Other

- Francois Remy. The :min-width/:max-width pseudo-classes. W3C mailing list, 2013. https://lists.w3.org/Archives/Public/www-style/2013Mar/0368.html
- Kevin Mack. Element Query and Selector Media Query Types. W3C mailing list, 2014. https://lists.w3.org/Archives/Public/public-resping/20140ct/0005.html
- Responsive Issues Community Group element queries use discussion repository. https://github.com/ResponsiveImagesCG/eq-usecases. Creating the use cases draft: https://responsiveimagescg.github.io/eq-usecases/

In addition to the listed literature, I have found numerous web articles regarding element queries. There are around 10 unique open source implementation attempts of element queries to examine. I am still searching for good literature regarding render engines and why element queries are hard to implement natively.

TODO: Write how the literature study will be examined.

Methodology

A theoretical study of the problem and render engines will be performed in order to understand the premises and limitations of implementing element queries in browsers. When a deep understanding of the problem has been acquired, a third-party framework shall be developed. A study of implementation attempts will be made and a comparison of approaches will be presented. Then the API will be designed and implemented. Studies of the subproblems that may arise during the implementation will be studied in parallel to the implementation.

Boundaries

The focus of the thesis lays on developing a third-party framework that realizes element queries. All theoretical studies and work will be performed to support the development of the framework.

What will be done

- A third-party implementation of element queries will be developed.
- The problems of implementing element queries natively will be addressed.
- Theory about rendering engines, CSS, HTML and responsive web design will be given to fully understand the problem.

What will not be done

- No efforts will be made to solve the problems accompanied with a native solution.
- No API or similar will be designed for a native solution.
- UI and UX design will not be addressed, other than necessary for understanding the problem.
- No complete history of browsers, the Internet or responsive web design will be given other than necessary.

Timetable

The work can be divided into 4 stages:

- Literature study: Search for suitable literature and sources will be performed in 2 weeks (a big part of the literature study has already been done before the writing of this document). Total time of literature study is estimated to 4 weeks.
- Background: The background of the problem will be investigated by reading the literature. The background will mainly address responsive web design and modular development.
- Theory: In this part the theory will be addressed. Here I will find out what element queries really are and how they relate to CSS and HTML. The most time will be spent investigating how rendering engines work and why element queries are hard to implement.
- Third-party framework: Here an analyse will be done of different implementation approaches and other implementation attempts will be investigated. The biggest time of this stage will be dedicated to designing an API and implementing the actual framework.

Report writing will occur in parallel to all the stages, as shown in figure 0.1.



Figure 0.1. Box plot of number of positions sent per iteration using this scheme