

MITx 6.86x

Machine Learning with Python-From Linear Models to Deep Learning

Discussion Course **Progress** Dates Resources

Course / Unit 5. Reinforcement Learning (2 we... / Lecture 17. Reinforcement



7. Value Iteration

 \square Bookmark this page

Exercises due May 3, 2023 08:59 -03 Past due

Value Iteration



Video

▲ Download video file

Transcripts

▲ Download SubRip (.srt) file

▲ Download Text (.txt) file

Recall from lecture the value iteration update rule :

$$V_{k+1}^{st}\left(s
ight)=\max_{a}\left[\sum_{s^{\prime}}T\left(s,a,s^{\prime}
ight)\left(R\left(s,a,s^{\prime}
ight)+\gamma V_{k}^{st}\left(s^{\prime}
ight)
ight)
ight],$$

where $V_{k}^{st}\left(s
ight)$ is the expected reward from state s after acting optimally for k steps.

Recall the example discussed in the lecture.

A cont's		
Agent's starting state		+1

Complexity of Value Iteration

Another Example of Value Iteration (Software Implementation)

3 points possible (graded)

Consider the same one-dimensional grid with reward values as in the first few problem However, consider the following change to the transition probabilities: At any given gric choose to either stay at the location or move to an adjacent grid location. If the agent clocation, such an action is successful with probability and

- if the agent is at the leftmost or rightmost grid location it ends up at its neighboring probability ,
- if the agent is at any of the inner grid locations it has a probability each of end neighboring locations.

If the agent chooses to move (either left or right) at any of the inner grid locations, such with probability and with probability it fails to move, and

- if the agent chooses to move left at the leftmost grid location, then the action ends choosing to stay, i.e., staying at the leftmost grid location with probability , and neighboring grid location with probability ,
- if the agent chooses to move right at the rightmost grid location, then the action er
 as choosing to stay, i.e., staying at the rightmost grid location with probability
 neighboring grid location with probability

Note in this setting, we assume that the game does not halt after reaching the rightmost Let .

Run the value iteration algorithm for 100 iterations. Use any computational software of

Enter the value of as an array

(For example, type [0,2,0,3,4] for the array . Type at least 4 decimal

Are the values different if we iterate 200 times? Consider only the first three decimal diquestion.

Yes

) No

Discussion

Topic: Unit 5. Reinforcement Learning (2 weeks): Lecture 17. Reinforcement Learning 1 / 7. Value Iteration

> Previous Next >

Show all posts



edX

About

Affiliates

edX for Business

Open edX

Careers

News

Legal

Terms of Service & Honor Code

Privacy Policy

Accessibility Policy

Trademark Policy

Sitemap

Cookie Policy

Do Not Sell My Personal Information

Connect

Blog

Contact Us

Help Center

Security

Media Kit









