



MITx 6.86x

Machine Learning with Python-From Linear Models to Deep Learning

[Course](#)

[Progress](#)

[Dates](#)

[Discussion](#)

[Resources](#)



[Course](#) / [Unit 2. Nonlinear Classification, Linear regression, ...](#) / [Project 2: Dig](#)

< Previous



7. Classification Using Manually Crafted Features

Bookmark this page



Performance of most learning algorithms depends heavily on the representation of the data. In this section, we will try representing each image using different features in place of the raw pixel values. Subsequently, we will investigate how well our regression model from the previous section performs on different representations of the data.



About Dimensionality Reduction via PCA

Affiliates

edx for Business

Open edX

Careers

News

Legal

Terms of Service & Honor Code

Privacy Policy

Accessibility Policy

Trademark Policy

Sitemap

Cookie Policy

Do Not Sell My Personal Information

Cubic Features

In this section, we will also work with a **cubic feature** mapping which maps an input vector $x \in \mathbb{R}^d$ into a new feature vector $\phi(x)$, defined so that for any $x, x' \in \mathbb{R}^d$:

$$\phi(x)^T \phi(x') = (x^T x' + 1)^3$$

Blog

Contact Us

Help Center

Security

Media Kit

Discussion

Topic: Unit 2. Nonlinear Classification, Linear regression, Collaborative Filtering (2 weeks): Project 2: Digit recognition (Part 1) / 7. Classification Using Manually Crafted Features



There are no posts in this topic yet.