

503_report_knn

13 April 2018

Problem of Interest

Images have played a great part of our life after data storage became cheaper and convenient in the 21st century. In 2001, Google enabled users to search images with a 250 million image database, and the database has grown exponentially ever since its launch. Within a decade, Reverse image search [content-based image retrieval (CBIR)] was introduced. The importance of image recognition and automated image classification has become popular over time. Even though the concept of neural networks was first introduced back in the 1940s, computers were not available nor able to undertake massive calculations when it was first introduced, but nowadays we are able to compute complicated models and algorithms such as Convolutional Neural Networks (CNN), Deep Neural Networks (DNN), ... etc. Popular algorithms were introduced to solve the image classification problems.

Data Exploration Challenge with Image data/ Difference with tabular data

Color digital images are made of pixels, and pixels are made of combinations of primary colors represented by a series of codes. A channel in this context is the grayscale image of the same size as a color image, made of just one of these primary colors. For instance, an image from a standard digital camera will have a red, green and blue channel.

Data Structure

A color digital image can be decomposed into a 3-dimensional array with each a n by m matrix (or a nm length vector), which each matrix (vector) corresponds to a specific channel **R**, **G**, and **B**.

Properties

- Ordered/ Not exchangeable

Even the data storage is tabular, but the columns are not exchangeable, and pixels are highly correlated with each other.

- Scale
- Rotation
- Noise

Naïve Classifier - Nearest Neighbor Classifier

Introduction

First, we start with a naïve classifier which only considers the distance of the two matrices, the prediction of the test data is solely decided by the closest neighbor it can find among the training data space, we picked **L-1 norm** and **L-2 norm** for the distance calculation process.

-

$$||M||_1 = \max_{1 \leq j \leq m} \sum_{i=1}^m |m_{ij}|$$

Which is the maximum absolute column sum of the matrix.

•

$$\|M\|_2 = \sigma_{max}(M) \leq \left(\sum_{i=1}^n \sum_{j=1}^m |m_{ij}|^2 \right)^{1/2}$$

where $\sigma_{max}(M)$ is the maximum singular value of matrix M .

Algorithm

Suppose we have a test image, say M_{test} and set of training images $M_{train_1}, M_{train_2}, \dots, M_{train_n}$ with known class labels

- First calculate the matrix difference of the test image M_{test} with **ALL** training images $M_{train_1}, M_{train_2}, \dots, M_{train_n}$, the difference of any two matrices is defined as the element-wise subtraction, i.e.

$$\begin{aligned} A_{m \times n} - B_{m \times n} &= \begin{bmatrix} a_{11} & \cdots & a_{1n} \\ \vdots & \ddots & \vdots \\ a_{m1} & \cdots & a_{mn} \end{bmatrix} - \begin{bmatrix} b_{11} & \cdots & b_{1n} \\ \vdots & \ddots & \vdots \\ b_{m1} & \cdots & b_{mn} \end{bmatrix} \\ &= \begin{bmatrix} a_{11} - b_{11} & \cdots & a_{1n} - b_{1n} \\ \vdots & \ddots & \vdots \\ a_{m1} - b_{m1} & \cdots & a_{mn} - b_{mn} \end{bmatrix} = M_{m \times n} \end{aligned}$$

- Second, we calculate the choose of $L-1$ norm/ $L-2$ norm distance of the matrix from previous step.
- The prediction is made by comparing all $L-1/L-2$ distances of the target test data to be classified, such that the predicted class is the one with minimum distance, i.e

$$Y_{Test}^{\hat{}} = \left\{ N \in \{Class\ of\ ||M_i||_p\}; ||M_i||_p = \min\{||M_1||_p, \dots, ||M_m||_p\} \right\}, \text{ where } p \text{ denotes } L_p \text{ distance}$$


Pseudo Code

Data experiment

From the MNIST hand writing data set, we selected: + Training Set: First 100 observations per class (0-9), total of 1000 observations. + Test Set: First 10 observations per class (0-9), total of 100 observations.

The result from the test data (consist of 100 observations per class):

Heatmap of classification matrix with *Low-resolution* images



Notes: Err denotes the misclassified count frequency.

L1 vs. L2.

Introducing Feature Descriptors

TODO: Describe what a feature detector is.

Histogram of Gradient (HOG)

TODO: Explain histogram of gradient TODO: Discuss HOG on low- and high- resolution data set.

PCA of Histogram of gradient(HOG)

TODO: Explain model TODO: pseudo code TODO: low/high res classification matrix TODO: Interpret result

Bag of Feature

TODO: Flow chart

Image credit (BOF Flow Chart): Image adapted from Arénaire project, Laboratoire de l'Informatique du Parallélisme(LIP)




Figure 1: Bag Of Features: Flow Chart

TODO: Explain model using flow chart

- Step (A):
- Step (B):
- Step (C):
- Step (D):

TODO: Pseudo code

BoF with HOG

TODO: Explain BoF with HOG

TODO: BoF with HOG, high-/low- classification matrix

TODO: Bof with HOG interpret result

SIFT

TODO: Introduce SIFT

BoF with SIFT

TODO: Explain BoF with SIFT

TODO: BoF with SIFT, high-/low- classification matrix

TODO: Bof with SIFT interpret result

Feature Descriptors + SVM

TODO: flow chart

TODO: HOG + SVM

TODO: HOG + SVM, high-/low- classification matrix

TODO: HOG + SVM interpret result

Appendix

```
#####
# Course : STAT 503
# File: Final Project
# Author: Yung-Chun LEE, Aman Taxali
#####

#####
# settings #
#####
library(tidyverse)
library(latex2exp)
library(ggplot2)
library(knitr)
library(MASS)
library(GGally)
library(grid)
library(gridExtra)
library(latex2exp)
setwd("C:/Users/user/Desktop/Umich Stat/2018 Winter/STAT 503/Project")
knitr::opts_chunk$set(echo = FALSE)
#source class_heatmap function
source('./class_heatmap.R')

#load plot data
load("./Data/nn_low_res.RData")

##description of figure
mnist_desc =substitute (paste(italic("Notes:") ,
                                "Err denotes the misclassified count frequency."))

#plot images

L1_mnist_plt = class_heatmap(L1_df,"Using L1-norm")
L2_mnist_plt = class_heatmap(L2_df,"Using L2-norm")
grid.arrange(L1_mnist_plt,L2_mnist_plt,ncol=2,
              top = textGrob(substitute(paste("Heatmap of classification matrix with ",
                                                italic('Low-resolution'), " images")),
                             x = 0, # starts far left
                             y = 0.5, # experiment with
                                   # vertical placement
                             just = "left", # left-aligned,
                             gp = gpar(fontsize = 16)),
              bottom = textGrob( mnist_desc,
                                x = 0, # starts far left
                                y = 0.5, # experiment with
                                    # vertical placement
                                just = "left", # left-aligned,
                                gp = gpar(fontsize = 10)))
```