

Atbash Configuration

Rudy De Busscher

Version 0.9.1, ??/??/2018

Table of Contents

| | |
|---|---|
| Release Notes | 1 |
| 0.9.1 | 1 |
| 0.9. | 1 |
| Introduction | 1 |
| Ported to Java 7 | 1 |
| Getting started | 2 |
| MP Configuration running on Java 7 | 2 |
| Atbash configuration extension | 2 |
| Atbash configuration features | 3 |
| Define the file containing the properties | 3 |
| Support for multiple <i>stages</i> | 4 |
| Logging of configuration entries | 5 |
| Specify the configuration name | 6 |
| Flexible Date format | 7 |
| YAML support | 8 |
| AbstractConfiguration (0.9.1) | 8 |
| Java SE support | 8 |
| Roadmap before 1.0 | 9 |

User manual for Atbash configuration.

Release Notes

0.9.1

1. *AbstractConfiguration* containing some helper methods to retrieve optional values programmatically
2. Logging no longer contain class name with no *@ConfigEntry* values.

0.9

Initial release, based on some extensions written for DeltaSpike logging.

Introduction

MicroProfile (MP) has done a great job in standardizing the configuration for applications.

However, there are a few improvements which I need for my applications and let me create Atbash configuration:

- Should also run on Java 7.
- Configuration for multiple *stages* within the artifact.
- Logging of configuration entries belonging to a *module*.
- Flexible date format support
- And optionally using YAML layout for configuration values to indicate relations between configuration properties.

Atbash Config is compliant with MP Config 1.1 and can be used in Java SE and Java EE (only dependency on CDI) environments.

Ported to Java 7

MicroProfile is targeted to Java 8. So the Config API (the specification) and any implementations, like the general usable Geronimo config, are using features of Java 8.

So I took the code from the following repositories

- MicroProfile-config API: <https://github.com/eclipse/microprofile-config/tree/master/api>
- Apache Geronimo configuration: <https://github.com/apache/geronimo-config/tree/trunk/impl>

And updated the code to be compliant with Java 7.

The only feature which is removed is the mapping between optional configuration values and the

Java 8 Optional class.

I kept the original packages and class names but placed them under a different Maven artifact name. That way, upgrading to Java 8 and the *real* implementations should be very smooth and require no changes whatsoever.

Getting started

MP Configuration running on Java 7

If you just want to run an implementation of MP configuration on Java 7 (with the Atbash extensions), you can add the following dependency to your application.

Plain MP Config for Java 7

```
<dependency>
  <groupId>be.atbash.config</groupId>
  <artifactId>geronimo-config</artifactId>
  <version>${atbash.config.version}</version>
</dependency>
```

For the list of features and how to use them, I refer to the MicroProfile configuration documentation and examples.

Atbash configuration extension

By adding the Atbash configuration Maven artifact, you add some additional features as described in the *introduction* section.

This artifact can be used in combination with the Java 7 ported code but also works with any other MP Config 1.1 compliant implementation.

Atbash extension

```
<dependency>
  <groupId>be.atbash.config</groupId>
  <artifactId>atbash-config</artifactId>
  <version>${atbash.config.version}</version>
</dependency>
```

The list of features is described in the *Atbash configuration features* section.

When using The Atbash configuration extension with a 'real' implementation, it is advised to exclude the *be.atbash.config:microprofile-config-api* since these classes are already present (through the dependency on the MP API from the 'real' configuration implementation)

```
<dependency>
  <groupId>be.atbash.config</groupId>
  <artifactId>atbash-config</artifactId>
  <version>${atbash.config.version}</version>
  <exclusions>
    <exclusion>
      <groupId>be.atbash.config</groupId>
      <artifactId>microprofile-config-api</artifactId>
    </exclusion>
  </exclusions>
</dependency>
```

Atbash configuration features

Define the file containing the properties

In the MicroProfile Configuration, the file name which contains the configuration values is fixed and defined as **META-INF/microprofile-config.properties**.

However, Atbash configuration should also be available within applications which aren't categorized as micro-services, but general Java EE application (perhaps a Web application using JSF framework)

Therefore the *base* name of the configuration file is specified by implementing the **be.atbash.config.spi.BaseConfigurationName** interface and defining this class for usage with the ServiceLoader mechanism of Java.

Defining the base name of the configuration file

```
public class DemoBaseName implements BaseConfigurationName {
    @Override
    public String getBase() {
        return "demo";
    }
}
```

Define classname for ServiceLoader mechanism within src/main/resources/META-INF/services/be.atbash.config.spi.BaseConfigurationName

```
be.atbash.config.examples.se.DemoBaseName
```

In the above example, the file **demo.properties** (but also demo.yaml; see further on) on the classpath is used as configuration source.

Multiple classes implementing the interface (and specified within the ServiceLoader file) are supported.

Support for multiple *stages*

Everyone agrees that your artifact (thin war or fat jar) shouldn't be changed between the different stages like *Testing*, *Acceptance* and *Production*.

Most people achieve this by externalizing the configuration properties which changes in the different environment and specifies them as environment properties or System Properties.

But it is better that all configuration values of your application are also under version control, just as your code.

Therefore your artifact could contain the following files (on the classpath)

- demo.properties → Configuration properties which do not change between the different environments and/or default values for those properties that do change.
- demo-test.properties → Configuration property values for the test environment/stage
- demo-production.properties → Configuration property values for the production environment/stage

If the application is started with the stage *test*, the files *demo.properties* and *demo-test.properties*. When configuration properties are defined in both files, the one in the stage-specific file (*demo-test.properties* in the example) has priority.

In fact, Atbash adds 3 levels to the `_ConfigSource_s` defined with the Configuration spec.

| Priority | ConfigSource |
|----------|--|
| 400 | JVM System properties based ConfigSource (From geronimo Config) |
| 300 | System environment properties based ConfigSource (From geronimo Config) |
| 250 | Configuration file(see remark) to overrule application property, specified by -Ds JVM System Property. |
| 200 | Stage/environment specified file (classpath only), specified by -DS JVM System property. |
| 150 | 'Default' configuration file for application defined by <i>base</i> name. |
| 100 | microprofile-config.properties file based ConfigSource (From geronimo Config) |

Remark: There are 3 prefixes supported to specify the location type of the configuration file, **classpath:**, **file:** and **url:**.

This feature is modeled based on WildFly Swarm configuration principles.

Some examples

TODO

Logging of configuration entries

Atbash configuration will also be used in the rewrite of the Octopus security framework. There we have several modules which each have their separate configuration values and they are logged at startup of the application.

But also in general, it can be handy to have a list within the logs of all the configuration values which are used.

This can be achieved by using the **ModuleConfig** marker interface, as shown in the example.

_ModuleConfig_s which are logged during application startup.

```
@ApplicationScoped
public class ApplicationConfiguration implements ModuleConfig {

    @Inject
    private Config config;

    @Inject
    @ConfigProperty(name = "value1")
    private String value1;

    @ConfigEntry
    public String getValue1() {
        return config.getValue("value1", String.class);
    }

    @ConfigEntry
    public Integer getValue2() {
        return config.getValue("value2", Integer.class);
    }
}
```

```
INFO [be.atbash.config.logging.StartupLogging] (ServerService Thread Pool -- 22)
Config implementation: be.atbash.config.examples.ee.ApplicationConfiguration
  method:    getValue2
  value:     500

  method:    getValue1
  value:     Stage based Value
```

Of course, this feature only works in CDI based environment and is triggered by the initialization event linked to the CDI `@ApplicationScoped`.

Specify the configuration name

With the `@ModuleConfigName`, we can define the name which is showed above the config values within the log.

For this example, we have the following 2 classes

Parent class.

```
public class ParentConfig {  
  
    @ConfigEntry  
    public String defineParentValue() {  
        return "Parent Config Value";  
    }  
}
```

Child class.

```
@ApplicationScoped  
public class ChildConfig extends ParentConfig implements ModuleConfig {  
  
    @ConfigEntry  
    public String defineChildValue() {  
        return "Child Config Value";  
    }  
  
}
```

Depending on what we define on the ChildConfig class, we have a slightly different output.

```
@ModuleConfigName("Module Config Name example")  
  
INFO [be.atbash.config.logging.StartupLogging] (ServerService Thread Pool -- 66)  
Module Config Name example :  
    method: defineChildValue  
    value:  Child Config Value  
  
    method: defineParentValue  
    value:  Parent Config Value
```



```
@ModuleConfigName(value = "Module Config with classes", className = true)

INFO [be.atbash.config.logging.StartupLogging] (ServerService Thread Pool -- 24)
Config implementation: Module Config with classes (
be.atbash.config.examples.ee.configname.ChildConfig )
  method: defineChildValue
  value:   Child Config Value

Config implementation: Module Config with classes (
be.atbash.config.examples.ee.configname.ParentConfig )
  method: defineParentValue
  value:   Parent Config Value
```

```
without @ModuleConfigName

INFO [be.atbash.config.logging.StartupLogging] (ServerService Thread Pool -- 63)
Config implementation: be.atbash.config.examples.ee.configname.ChildConfig
  method: defineChildValue
  value:   Child Config Value

Config implementation: be.atbash.config.examples.ee.configname.ParentConfig
  method: defineParentValue
  value:   Parent Config Value
```

Advanced logging features

@ConfigEntry(noLogging)

@ConfigEntry(value)

Dynamic values

Flexible Date format

Now That the code is ported to Java 7, the converters for the *DateTime* and equivalent are removed. A general one for **Date.class** is added, but the default format is Locale dependent.

This means that when the application runs on multiple servers where, for whichever reason, the Locale information of the OS is not identical, the parsing of the dates can fail.

Therefore, support is foreseen to define the Date pattern within the configuration file itself, as a configuration value.

```
atbash.date.pattern:dd-MM-yyyy
```

or in YAML format

```
atbash :  
  date :  
    pattern : dd-MM-yyyy
```



This date format will be used for all Date values within all configuration files, not only the file where the pattern is defined.

Being global can have some nasty unwanted effects when you include artifacts from other developers containing also configuration files but specifying Date values in another format.

Therefore, the format can be specified for each Date value separately as follows

```
dateValue : 16-11-2017,dd-MM-yyyy
```

YAML support

TODO

AbstractConfiguration (0.9.1)

An abstract class which can be used to retrieve optional configuration values with or without a default value.

Using the CDI Qualifier `@ConfigProperty`, thus can already be achieved, but not in a programmatic way.

```
protected <T> T getOptionalValue(String propertyName, T defaultValue, Class<T>  
    propertyType) {
```

Java SE support

Since the core of MicroProfile Configuration is created around the *ServiceLoader* principal of Java SE, it can also be used within Command Line programs for example.

Using Configuration with plain Java SE programs

```
Config config = ConfigProvider.getConfig();  
config.getValue("value1", String.class);
```

Next to the basic functionality of MP Configuration (like converts), following Atbash extension features are also available

- Configuration for multiple *stages* within the artifact.

- Flexible date format support.
- YAML layout for configuration values.

Roadmap before 1.0

- More tests
- A parameter to completely disable logging during startup.
- Annotation to assign a name to the ModuleConfig so it can be used within the logging instead of the class name.
- Prefix-based configuration keys
- Investigate Startup logging in Java SE environments
- Various small improvements