

STANDARD ARRIVAL ROUTES

GENERAL: Maximum speed 250 KT IAS unless otherwise stated under “**RESTRICTIONS**” or instructed by ATC.

VECTORIZING: Vectoring may be used for sequencing.

RADIO COMMUNICATION FAILURE:

SQUAWK 7600

Follow cleared or expected STAR until IAF, then start approach to assigned runway without delay. If no specific runway for landing has been assigned, start visual approach for runway 36R without delay.

DESIGNATOR	ROUTE	RESTRICTIONS	DESCEND
CAMEL 1D (CAMEL ONE DELTA DEPARTURE)	From CAMEL to DUNKS, to ROSMO, right DCT ZO345, to MORRD.	Speed 250 KT IAS or less: BEANS. Speed 220 KT IAS or less: CRACK. Enter STAR at or below 5000 feet, not below 3000.	As cleared by ATC.
CHAIN 2D (CHAIN TWO DELTA DEPARTURE)	From DEATH to CRACK.	Speed 250 KT IAS or less: DEATH. Speed 220 KT IAS or less: CRACK. Enter STAR at or below 5000 feet, not below 3000.	As cleared by ATC.
DOGGO 2D (ENDER TWO DELTA DEPARTURE)	From ENDER to PARTS, to WAREZ, to HELPR, to CRACK.	Speed 250 KT IAS or less: ENDER, PARTS, WAREZ, HELPR. Speed 220 KT IAS or less: CRACK. Enter STAR at or below 5000 feet, not below 3000.	As cleared by ATC.
JUSTY 2D (FORIA TWO DELTA DEPARTURE)	From FORIA to SAVES.	Speed 250 KT IAS or less: FORIA. Speed 220 KT IAS or less: SAVES.	As cleared by ATC.