

model_GA_LM_ad.R

arman

Sun May 28 15:19:31 2017

```
library(MASS)
library(car)
library(DataCombine)    # Pair wise correlation
library(stargazer)
library(dplyr)          # Data aggregation
library(glmnet)
source('./atchircUtils.R')

data    <- read.csv('./intrim/eleckart.csv')

# KPI selection
# units, product_mrp, list_mrp, COD, Prepaid are factors
# Insig : Affiliates corr OnlineMarketing
# Insig : Radio corr Other
# Insig : Digital, ContentMarketing corr SEM
# delivery(b/c)days are corr, lets choose deliverydays
# will use marketing levers rather TotalInvestment

# Filter significant KPIs
model_data <- subset(data, product_analytic_sub_category=='GamingAccessory',
  select = -c(product_analytic_sub_category,product_mrp,
    units,COD,Prepaid,deliverybdays,
    TotalInvestment,Affiliates,Radio,Digital,
    ContentMarketing,sla,procurement_sla))

model_data_org <- model_data
model_data[,c(8:12)] <- model_data[,c(8:12)]*10000000

# # *****
# #           FEATURE ENGINEERING -PASS2 ----
# # *****
#
# # . . . . List Price Inflation ----
model_data$chnglist <- c(0,diff(model_data$list_mrp))
#
# # . . . . Discount Inflation ----
model_data$chngdisc <- c(0,diff(model_data$discount))
#
#
# # . . . . Ad Stock ----
model_data$adTV <- as.numeric(
  stats::filter(model_data$TV,filter=0.5,method='recursive'))
# model_data$adSponsorship <- as.numeric(
#   stats::filter(model_data$Sponsorship,filter=0.5,method='recursive'))
```

```

# model_data$adOnlineMarketing <- as.numeric(
#   stats::filter(model_data$OnlineMarketing,filter=0.5,method='recursive'))
# model_data$adSEM <- as.numeric(
#   stats::filter(model_data$SEM,filter=0.5,method='recursive'))
# model_data$adOther <- as.numeric(
#   stats::filter(model_data$Other,filter=0.5,method='recursive'))

# model_data <- subset(model_data,select = -c(TV,Sponsorship,
#   OnlineMarketing,
#   SEM,Other))

model_data <- subset(model_data,select = -c(TV))

# # *****
# #          TRAIN and TEST Data  ----
# # *****

test_data <- model_data[c(43:52),-2]
test_value <- model_data[c(43:52),2]

model_data <- model_data[-c(43:52),]

```

*

****PROCs:****

Linear, Ridge and Lasso Model are wrapped with abstract functions. This would facilitate readable code for model building and Model optimization. Set Class definitions

```
setOldClass('elnet')
setClass(Class = 'atcglmnet',
  representation (
    R2 = 'numeric',
    mdl = 'elnet',
    pred = 'matrix'
  )
)
```

```
setOldClass('lm')
setClass(Class = 'atclm',
  representation (
    R2 = 'numeric',
    mdl = 'lm',
    pred = 'matrix'
  )
)
```

Finding min lambda from 1000 iterations Function to find Min Lambda using bootstrap method. minlambda identified over 1000 cross validation trails. observed minlambda used for Ridge and Lasso regression.

```
findMinLambda <- function(x,y,alpha,folds) {
  lambda_list <- list()
  for (i in 1:1000) {
    cv.out <- cv.glmnet(as.matrix(x), as.vector(y), alpha=alpha,
                       nfolds=folds)
    lambda_list <- append(lambda_list, cv.out$lambda.min)
  }
  return(min(unlist(lambda_list)))
}
```

Linear Model with Regularization Wrapper function for Ridge and Lasso regression. functions performs Ridge/Lasso regression and returns R2, Model and Predicted values as `atcglmnet` object

```
atcLmReg <- function(x,y,l1l2,folds) {
  # l1l2 = 0 for L1, 1 for L2

  if (l1l2) { # Lasso/L2
    min_lambda <- findMinLambda(x,y,1,folds)
  } else { # Ridge/L1
    min_lambda <- findMinLambda(x,y,0,folds)
  }
  mdl <- glmnet(x,y,alpha=l1l2,lambda = min_lambda)
```

```

pred      <- predict(mdl,s= min_lambda,newx=x)

# MSE
mean((pred-y)^2)
R2 <- 1 - (sum((y-pred )^2)/sum((y-mean(pred))^2))
return(new('atcglmnet', R2 = R2, mdl=mdl, pred=pred))
}

```

*

MODELING

```
# Prune KPI as part of model optimization
model_data <- na.omit(model_data)
model_data <- subset(model_data,select=-c(discount,SEM,NPS,list_mrp))
```

Linear Model:

```
mdl <- lm(gmv~., data=model_data)
step_mdl <- stepAIC(mdl,direction = 'both',trace = FALSE)

stargazer(mdl,step_mdl, align = TRUE, type = 'text',
           title='Linear Regression Results', single.row=TRUE)
```

```
##
## Linear Regression Results
## =====
##                               Dependent variable:
##                               -----
##                               gmv
##                               (1)                (2)
## -----
## week                11,001.430 (25,981.860)
## deliverycdays       52,422.110 (236,382.400)
## n_saledays          74,698.490 (105,798.700)
## Sponsorship          0.010** (0.004)          0.008** (0.003)
## OnlineMarketing      0.034* (0.018)          0.031*** (0.011)
## Other                0.016 (0.012)          0.013 (0.010)
## chnglist            696.039 (769.670)
## chngdisc            40,391.840** (15,869.990)  40,221.130** (14,865.520)
## adTV               -263,528.300 (320,586.100)
## Constant            1,116,578.000** (413,404.400) 1,249,874.000*** (334,454.000)
## -----
## Observations                43                43
## R2                          0.592                0.565
## Adjusted R2                  0.481                0.519
## Residual Std. Error    1,073,635.000 (df = 33)    1,033,727.000 (df = 38)
## F Statistic              5.329*** (df = 9; 33)    12.334*** (df = 4; 38)
## =====
## Note:                                *p<0.1; **p<0.05; ***p<0.01
```

```
knitr::kable(viewModelSummaryVIF(step_mdl))
```

var	Estimate	Std.Error	t-value	Pr(> t)	Significance	vif
chngdisc	4.022e+04	1.487e+04	2.706	0.010149	*	1.020509
OnlineMarketing	3.133e-02	1.130e-02	2.773	0.008569	**	1.984230
Other	1.312e-02	9.719e-03	1.350	0.184888	NA	1.523019
Sponsorship	7.836e-03	3.416e-03	2.294	0.027419	*	1.859146

```
pred_lm <- predict(step_mdl, model_data)
```

Regularized Linear Model:

```
x = as.matrix(subset(model_data, select=-gmv))  
y = as.vector(model_data$gmv)  
  
ridge_out <- atcLmReg(x,y,0,3) # x, y, alpha, nfolds  
lasso_out <- atcLmReg(x,y,1,3) # x, y, alpha, nfolds
```

Model Accuracy

```
ypred <- predict(step_mdl,new=test_data)  
# MSE  
mean((ypred-test_value)^2)
```

```
## [1] 1.351174e+12
```


```
predR2 <- 1 - (sum((test_value-ypred )^2)/sum((test_value-mean(ypred))^2))
```

*

PLOTTING MODEL RESULTS

Plot Model prediction and base sales:

```
plot(model_data$gmv, main = 'GamingAccessory Linear Model with AdStock - Final',
     xlab='week', ylab='PredictGMV')
lines(model_data$gmv)
lines(pred_lm, col='red', lwd=2)
lines(ridge_out@pred, col='green', lwd=2)
lines(lasso_out@pred, col='blue', lwd=2)
lines(step_md1$coefficients['(Intercept)'] + step_md1$coefficients['week'] * model_data$week,
     lty=2, lwd=2, col='red')
lines(ridge_out@mdl$a0 + ridge_out@mdl$beta['week', 1] * model_data$week,
     lty=2, lwd=2, col='green')
lines(lasso_out@mdl$a0 + lasso_out@mdl$beta['week', 1] * model_data$week,
     lty=2, lwd=2, col='blue')
legend('topright', inset=0, legend=c('GMV', 'LM', 'LM+L1', 'LM+L2'), horiz = TRUE,
     lwd = 2, col=c(1:4), cex = 0.5)
```



*

*Model Coefficients:**

```
coeff_lm <- as.data.frame(as.matrix(coef(step_md1)))
coeff_l1 <- as.data.frame(as.matrix(coef(ridge_out@mdl)))
coeff_l2 <- as.data.frame(as.matrix(coef(lasso_out@mdl)))
```

```
lm_df=data.frame('x'=rownames(coeff_lm),'y'=coeff_lm)
colnames(lm_df) = c('coeff','lm')
l1_df=data.frame('x'=rownames(coeff_l1),'y'=coeff_l1)
colnames(l1_df)= c('coeff','l1')
l2_df=data.frame('x'=rownames(coeff_l2),'y'=coeff_l2)
colnames(l2_df) <- c('coeff','l2')
```

```
smry <- merge(lm_df,l1_df,all = TRUE)
smry <- merge(smry,l2_df,all=TRUE)
```

```
print(smry)
```

##		coeff	lm	l1	l2
## 1	(Intercept)	1.249874e+06	1.237663e+06	1.124572e+06	
## 2	adTV	NA	-8.189433e+04	-2.502575e+05	
## 3	chnngdisc	4.022113e+04	3.771310e+04	4.028413e+04	
## 4	chnnglist	NA	7.009542e+02	6.938502e+02	
## 5	deliverycdays	NA	-1.819145e+03	4.920311e+04	
## 6	n_saledays	NA	6.764275e+04	7.346759e+04	
## 7	OnlineMarketing	3.132878e-02	2.748578e-02	3.329897e-02	
## 8	Other	1.312435e-02	1.197516e-02	1.591923e-02	
## 9	Sponsorship	7.836374e-03	8.410581e-03	9.944514e-03	
## 10	week	NA	9.406841e+03	1.062579e+04	

```
print(paste0('Ridge regression R2 : ',ridge_out@R2))
```

```
## [1] "Ridge regression R2 : 0.586668344815821"
```

```
print(paste0('Lasso regression R2 : ',lasso_out@R2))
```

```
## [1] "Lasso regression R2 : 0.592384565292928"
```

```
print(paste0('Linear Mode R2 : ',getModelR2(step_md1)))
```

```
## [1] "Multiple R-squared: 0.5649,\tAdjusted R-squared: 0.5191 "
```

```
## [1] "Linear Mode R2 : Multiple R-squared: 0.5649,\tAdjusted R-squared: 0.5191 "
```

```
print(paste0('Predicted R2 : ',predR2))
```

```
## [1] "Predicted R2 : -0.0642339669657048"
```


*

Significant KPI

>